

# The **mathastext** package

JEAN-FRAN OIS BURNOL  
jfbu (at) free (dot) fr  
Package version: 1.4b (2024/07/27)

The **mathastext** package changes the fonts which are used in math mode for letters, digits and a few other punctuation and symbol signs to replace them with the font as used for the document text. Thus, the package makes it possible to use a quite arbitrary font without worrying too much that it does not have specially designed accompanying math fonts. Also, **mathastext** provides a simple mechanism in order to use more than one math-as-text font in the same document.

`mathastext' is a LaTeX package

```
\usepackage{mathastext}
```

The document will use in math mode the text font as configured at package loading time, for these characters:

```
abcdefghijklmnoprstuvwxyz
ABCDEFGHIJKLMNOPQRSTUVWXYZ
0123456789
!?,.:;+--()[]/#$%&<>|{}\'
```

The command `\MTsetmathskips` allows to set up extra spacings around each given letter.

Use multiple `\Mathastext[name]`'s to define in the preamble various math versions using each a given text font, to be later activated in the document body via the command `\MTversion{name}`.

With the subdued option, `mathastext` will be active only inside such math versions distinct from the normal and bold.

Main options: `italic`, `frenchmath`, `defaultmathsizes`, `subdued`, `asterisk`, `LGRgreek`.

## Contents

<b>What <code>mathastext</code> does . . . 1, p. 2</b>	
Aim of this package and basic usage . . . . .	with Greek letters via the LGRgreek+ option.
1.1, p. 2	
Examples . . . . . 1.2, p. 3	Advanced capacities . . . . . 1.8, p. 33
Main options . . . . . 1.3, p. 8	Extra spaces around letters–Background on italic corrections in math mode–Extra glue after \exists, \forall, and before the prime glyph–Extended scope of the math alphabets commands–Hacking letters (and even digits) for special tasks.
The italic option–The frenchmath option –The defaultmathsizes option–The subdued option–The LGRgreek option.	
Miscellanea . . . . . 1.4, p. 10	<b>Package commands . . . . . 2, p. 43</b>
Load <code>mathastext</code> always last–Avoid OT1 encoding–Derivative, minus, asterisk–Large symbols and delimiters–amsmath–hbar–Dotless i and j–fontspec–vec accent–math accents–Sans serif in math– <code>mathastext</code> with beamer– <code>mathastext</code> with frenchmath–Intervals and separators–Unicode engines–The unicodeminius option–Two examples with OpenType fonts–Compatibility with other packages.	Commands for regular usage 2.1, p. 43 Preamble-only commands–Commands for body or math.
Math alphabets . . . . . 1.5, p. 20	Commands for expert usage 2.2, p. 48 Expert commands which are preamble-only–Expert commands usable everywhere–Expert commands usable only outside of math mode–Expert commands usable only in math mode.
Math versions . . . . . 1.6, p. 23	
Greek letters . . . . . 1.7, p. 25	<b>Package options . . . . . 3, p. 57</b>
The Greek-related options–Shape of Greek letters–Control sequences to access directly upright or italic shape for Greek under LGRgreek option–\mathgreekupbold and \mathgreekitbold–Special behavior of \mathrm, \mathbf, \mathit	Summary of main options . . . 3.1, p. 57 Complete list of options . . . 3.2, p. 57
	<b>Change log . . . . . 4, p. 65</b>
	<b>Implementation . . . . . 5, p. 73</b>

## 1 What `mathastext` does

If you have used the package before please make sure to check first [section 4](#) where all changes across releases are recorded.

All blue colored words, such as `\Mathastext` or `italic`, are hyperlinked to their official descriptions located either in the [section 2](#) (Package commands) or [subsection 3.2](#) (Complete list of options).

### 1.1 Aim of this package and basic usage

The initial ideology of `mathastext` was to produce mathematical texts with a very uniform look, not separating math from text as strongly as is usually done.

`mathastext`'s basic aim is thus to have the same font for text and mathematics. With hundreds of free text fonts packaged for L<sup>A</sup>T<sub>E</sub>X and only a handful of math ones, chances are your favorite text font does not mix so well with the available math ones; `mathastext` may then help. Note that `mathastext` was initially developed for the traditional T<sub>E</sub>X fonts and engines, and that compatibility with Unicode engines and OpenType fonts is partial.

Here is a minimal example of what may go into the preamble:

```
\usepackage[T1]{fontenc}
\usepackage{times}
\usepackage[italic]{mathastext}
```

The package records which font is set up for text, at the time it is loaded, and then arranges things in order for this text font to be used in math mode as well. So, with the preamble as above all letters, digits, and punctuation signs inside math mode will then be typeset in Times.<sup>1</sup> The exact list of characters concerned by **mathastext** is a subset of the basic ASCII set:

abcdefghijklmnopqrstuvwxyz  
ABCDEFGHIJKLMNPQRSTUVWXYZ  
0123456789  
! ? \* , : ; + - = ( ) / # \$ % & < > | { } and \

As one can see, this is a very limited list! Some possibilities exist regarding Greek letters and will be described later.

## 1.2 Examples

Here is another simple example:

```
\usepackage{libertinus-type1}
\usepackage[italic,LGRgreek,defaultmathsizes]{mathastext}
```

The **LGRgreek** option is there to take advantage that the **libertinus-type1** package<sup>2</sup> also provides Greek letters in LGR encoding, which can thus be used by **mathastext** in math mode. And we do here as if we did not know about the existence of the **libertinust1math** package!<sup>3</sup> This would have been the obvious choice, but then one wouldn't need **mathastext** and I couldn't even start this documentation.

More sophisticated preambles will use multiple times the **\Mathastext** command in the preamble with its optional argument **[<math\_version>]** in order to define *math versions* corresponding to a given font configuration. These **mathastext**-enriched math versions are then activated in the document body via the **\MTversion{<math\_version>}** command, which modifies *both* the text font and the math font.

---

<sup>1</sup>let's do as if we did not know the excellent **txfonts** package which employs Times for text and has a very complete math support, including many additional mathematical glyphs in comparison to the CM fonts. *This was written many years ago, nowadays, newtx is the successor of txfonts.*

<sup>2</sup>Bob TENNENT, *Support for using Libertinus fonts with L<sup>A</sup>T<sub>E</sub>X/pdfL<sup>A</sup>T<sub>E</sub>X*, <https://ctan.org/pkg/libertinus-type1>.

<sup>3</sup>Michael SHARPE, *A Type 1 font and L<sup>A</sup>T<sub>E</sub>X support for Libertinus Math*, <https://ctan.org/pkg/libertinust1math>.

We now give some examples with a verbatim copy of the preamble code corresponding to them, as can be found in the source of this documentation. The detailed option and command descriptions will be given later.

First of all, the package was loaded using this:

```
\usepackage[subdued,%
            asterisk,%
            defaultmathsizes,%
            symbolmisc,symbolre,%
            LGRgreek]{mathastext}
```

In the definitions of the `mathastext`-enriched *math versions* we keep commands which may have been redundant in the original preamble, because they were issued earlier for a previous math version definition.

Let's start with Latin Modern typewriter proportional. Its usage was configured in the preamble using this:

```
\MTlettershape{n}
\MTupgreek
\MTgreekfont{cmtt}
\MTfamily{lmvtt}
\Mathastext{lmvtt}
```

Its usage is triggered using

```
\MTversion{lmvtt}
```

in the document. Here is an example:

Let  $(X, Y)$  be two functions of a variable  $a$ . If they obey the differential system  $(VI_{v,n})$ :

$$\begin{aligned} a \frac{d}{da} X &= vX - (1 - X^2) \frac{2na}{1 - a^2} \frac{aX + Y}{1 + aXY} \\ a \frac{d}{da} Y &= -(v + 1)Y + (1 - Y^2) \frac{2na}{1 - a^2} \frac{X + aY}{1 + aXY} \end{aligned}$$

then the quantity  $q = a \frac{aX + Y}{X + aY}$  satisfies as function of  $b = a^2$  the  $P_{VI}$  differential equation:

$$\begin{aligned} \frac{d^2q}{db^2} &= \frac{1}{2} \left\{ \frac{1}{q} + \frac{1}{q-1} + \frac{1}{q-b} \right\} \left( \frac{dq}{db} \right)^2 - \left\{ \frac{1}{b} + \frac{1}{b-1} + \frac{1}{q-b} \right\} \frac{dq}{db} \\ &\quad + \frac{q(q-1)(q-b)}{b^2(b-1)^2} \left\{ \alpha + \frac{\beta b}{q^2} + \frac{\gamma(b-1)}{(q-1)^2} + \frac{\delta b(b-1)}{(q-b)^2} \right\} \end{aligned}$$

with parameters  $(\alpha, \beta, \gamma, \delta) = (\frac{(v+n)^2}{2}, \frac{-(v+n+1)^2}{2}, \frac{n^2}{2}, \frac{1-n^2}{2})$ .

Test of uppercase Greek in math: ΑΒΓΔΞΩ.

Both the Latin and Greek letters are upright, in conformity to the way the `lmvtt` version was defined.

Now with the fonts from the `libertinus-type1` distribution<sup>4</sup>. The preamble code is:

```
\MTfamily{LibertinusSerif-TLF}
\MTlettershape{n}
\MTseries{m}
\MTgreekfont{LibertinusSerif-TLF}
\MTupgreek
\Mathastext[libertinus]
\MTseries{sb}
\Mathastext[libertinussemibold]
```

Its usage in the document body for the example below is triggered via

```
\MTversion[libertinus]{libertinussemibold}
```

This syntax modifies the text fonts to be those which were defined to hold for the `mathastext`-math version passed as optional argument, and sets the math fonts according to the mandatory argument. Hence the math mode uses semibold font but the text font uses the normal weight.

Let  $(X, Y)$  be two functions of a variable  $a$ . If they obey the differential system  $(VI_{v,n})$ :

$$\begin{aligned} a \frac{d}{da} X &= vX - (1 - X^2) \frac{2na}{1 - a^2} \frac{aX + Y}{1 + aXY} \\ a \frac{d}{da} Y &= -(v + 1)Y + (1 - Y^2) \frac{2na}{1 - a^2} \frac{X + aY}{1 + aXY} \end{aligned}$$

then the quantity  $q = a \frac{aX+Y}{X+aY}$  satisfies as function of  $b = a^2$  the  $P_{VI}$  differential equation:

$$\begin{aligned} \frac{d^2q}{db^2} &= \frac{1}{2} \left\{ \frac{1}{q} + \frac{1}{q-1} + \frac{1}{q-b} \right\} \left( \frac{dq}{db} \right)^2 - \left\{ \frac{1}{b} + \frac{1}{b-1} + \frac{1}{q-b} \right\} \frac{dq}{db} \\ &\quad + \frac{q(q-1)(q-b)}{b^2(b-1)^2} \left\{ \alpha + \frac{\beta b}{q^2} + \frac{\gamma(b-1)}{(q-1)^2} + \frac{\delta b(b-1)}{(q-b)^2} \right\} \end{aligned}$$

with parameters  $(\alpha, \beta, \gamma, \delta) = (\frac{(v+n)^2}{2}, \frac{-(v+n+1)^2}{2}, \frac{n^2}{2}, \frac{1-n^2}{2})$ .

Test of uppercase Greek in math:  $\text{ΑΒΓΔΞΩ}$ .

Now with a Times clone. We will configure Latin letters to be in italic shape, and Greek letters to be italic for lowercase and upright for uppercase:

```
\usepackage{times}% it modifies the \rm,\sf,\tt default's
\MTfamily{\rmdefault}
\MTlettershape{it}
\MTseries{m}
\MTgreekfont{txr}
```

---

<sup>4</sup>Bob TENNENT, *Support for using Libertinus fonts with L<sup>A</sup>T<sub>E</sub>X/pdfL<sup>A</sup>T<sub>E</sub>X*, <https://ctan.org/pkg/libertinus-type1>.

```
\MTitgreek\MTupGreek
\Mathastext[times]
% \MTversion{times} will change not only math but also text, so it
% will re-enact the \rmdefault, \sfdefault, \ttdefault from loading times.sty
```

We now use this in the document body via

```
\MTversion{times}
```

Let  $(X, Y)$  be two functions of a variable  $a$ . If they obey the differential system  $(VI_{v,n})$ :

$$\begin{aligned} a \frac{d}{da} X &= vX - (1 - X^2) \frac{2na}{1 - a^2} \frac{aX + Y}{1 + aXY} \\ a \frac{d}{da} Y &= -(v + 1)Y + (1 - Y^2) \frac{2na}{1 - a^2} \frac{X + aY}{1 + aXY} \end{aligned}$$

then the quantity  $q = a \frac{aX + Y}{X + aY}$  satisfies as function of  $b = a^2$  the  $P_{VI}$  differential equation:

$$\begin{aligned} \frac{d^2q}{db^2} &= \frac{1}{2} \left\{ \frac{1}{q} + \frac{1}{q-1} + \frac{1}{q-b} \right\} \left( \frac{dq}{db} \right)^2 - \left\{ \frac{1}{b} + \frac{1}{b-1} + \frac{1}{q-b} \right\} \frac{dq}{db} \\ &\quad + \frac{q(q-1)(q-b)}{b^2(b-1)^2} \left\{ \alpha + \frac{\beta b}{q^2} + \frac{\gamma(b-1)}{(q-1)^2} + \frac{\delta b(b-1)}{(q-b)^2} \right\} \end{aligned}$$

with parameters  $(\alpha, \beta, \gamma, \delta) = (\frac{(v+n)^2}{2}, \frac{-(v+n+1)^2}{2}, \frac{n^2}{2}, \frac{1-n^2}{2})$ .

Test of uppercase Greek in math:  $\text{ΑΒΓΔΞΩ}$ .

Let us be a bit more original and have our mathematics with italic letters from the sans serif font Helvetica, while the letters in text use New Century Schoolbook. Also we want Greek letters (both lowercase and uppercase) to be in italic shape. The preamble code was:

```
\usepackage[newcent]{newcent} % attention that it modifies all three of \rmdefault,
% \sfdefault and \ttdefault
\MTfamily{\rmdefault}
\MTlettershape{it}
% \MTitgreek\MTupGreek % our demo does not use newcent for math anyway
\Mathastext[newcent]

\usepackage[scaled]{helvet}
\MTfamily{\sfdefault}
\MTlettershape{it} % redundant here
\MTseries{m}
\MTitgreek % make both lowercase and uppercase Greek italic
\MTgreekfont{cmss}
\Mathastext[helvet]
```

And the next demo is configured in the document body via

```
\MTversion[newcent]{helvet}
```

Let  $(X, Y)$  be two functions of a variable  $a$ . If they obey the differential system  $(VI_{\nu,n})$ :

$$\begin{aligned} a \frac{d}{da} X &= \nu X - (1 - X^2) \frac{2na}{1 - a^2} \frac{aX + Y}{1 + aXY} \\ a \frac{d}{da} Y &= -(\nu + 1)Y + (1 - Y^2) \frac{2na}{1 - a^2} \frac{X + aY}{1 + aXY} \end{aligned}$$

then the quantity  $q = a \frac{aX + Y}{X + aY}$  satisfies as function of  $b = a^2$  the  $P_{VI}$  differential equation:

$$\begin{aligned} \frac{d^2q}{db^2} &= \frac{1}{2} \left\{ \frac{1}{q} + \frac{1}{q-1} + \frac{1}{q-b} \right\} \left( \frac{dq}{db} \right)^2 - \left\{ \frac{1}{b} + \frac{1}{b-1} + \frac{1}{q-b} \right\} \frac{dq}{db} \\ &\quad + \frac{q(q-1)(q-b)}{b^2(b-1)^2} \left\{ a + \frac{\beta b}{q^2} + \frac{\gamma(b-1)}{(q-1)^2} + \frac{\delta b(b-1)}{(q-b)^2} \right\} \end{aligned}$$

with parameters  $(\alpha, \beta, \gamma, \delta) = (\frac{(\nu+n)^2}{2}, \frac{-(\nu+n+1)^2}{2}, \frac{n^2}{2}, \frac{1-n^2}{2})$ .

Test of uppercase Greek in math:  $A\bar{B}\Gamma\Delta\Xi\Omega$ .

And after all that, we may wish to return to the default math typesetting (let's shorten the extract here in case the reader makes an indigestion ...). This is easy because all previous usages were enclosed in braces  $\{\dots\}$  so as to limit the scope. As `mathastext` was loaded with option `subdued` the default rendering (i.e. in the *normal* and *bold* math versions) is (almost) as if the package was not loaded at all, and it simply matches the document font configuration. Here it thus matches the

`\usepackage{mlmodern}`

which was included in the document preamble prior to loading `mathastext`.

Let  $(X, Y)$  be two functions of a variable  $a$ . If they obey the differential system  $(VI_{\nu,n})$ :

$$\begin{aligned} a \frac{d}{da} X &= \nu X - (1 - X^2) \frac{2na}{1 - a^2} \frac{aX + Y}{1 + aXY} \\ a \frac{d}{da} Y &= -(\nu + 1)Y + (1 - Y^2) \frac{2na}{1 - a^2} \frac{X + aY}{1 + aXY} \end{aligned}$$

then the quantity  $q = a \frac{aX + Y}{X + aY}$  satisfies as function of  $b = a^2$  the  $P_{VI}$  differential equation with parameters  $(\alpha, \beta, \gamma, \delta) = (\frac{(\nu+n)^2}{2}, \frac{-(\nu+n+1)^2}{2}, \frac{n^2}{2}, \frac{1-n^2}{2})$ .

Test of uppercase Greek in math:  $\Gamma\Delta\Xi\Omega$  (no `\Alpha`, no `\Beta`).

If the scope of our earlier examples using `mathastext`-enriched math versions had not been limited we would have issued

`\MTversion{normal}`

to return to the normal (almost not influenced by `mathastext`) math version.

The Greek letters varied across our examples thanks to the `LGRgreek` option which made the `\MTgreekfont` command active for configuration of the math versions.<sup>5</sup>

Since 1.3y this documentation uses globally the `mlmodern`<sup>6</sup> font package and has added an example using the *Libertinus* font in type-1 format<sup>7</sup> although there is an existing accompanying math font<sup>8</sup>.

## 1.3 Main options

### 1.3.1 The `italic` option

In the initial version 1.0, the Latin letters in mathematical mode assumed the exact same shape as in text mode, and this meant, generally speaking, that they would turn up upright. Doing this gives a very uniform look to the document, so that one has to make an effort and read it with attention, and this was one of the design goals of `mathastext`.

Nevertheless, soon after I posted the initial version of the package to CTAN, I was overwhelmed by numerous<sup>9</sup> questions<sup>10</sup> on how to have the letters be in italic shape.

The default is still, as in version 1.0, for everything to be in upright shape, but it suffices to pass to the package the option `italic` to let the Latin letters in math mode be in italic shape.<sup>11</sup>

### 1.3.2 The `frenchmath` option

It is a variant of the `italic` option which keeps the uppercase Latin letters in upright shape<sup>12</sup>. Also lets the Greek letters, if the latter are under `mathastext` influence, be all upright, lowercase as uppercase.

---

<sup>5</sup>The document used the `cmtt`, `cmss`, `txr`, as well as *LibertinusSerif-TLF* font families in LGR encoding. The first two are available (with no need to load explicitly any package in the document) if the  $\text{\LaTeX}$  installation provides the `cbfonts` (or `cbgreek-complete`) & `babel` packages, and the LGR encoded `txr` font (again no package loading is necessary) is part of the files of the `txfonts` package. For *LibertinusSerif-TLF*, the files of the `libertinus-type1` package must be present.

<sup>6</sup>Daniel Benjamin MILLER, *A blacker Type 1 version of Computer Modern, with multilingual support*, <https://ctan.org/pkg/mlmodern>. I have added to the preamble

```
\DeclareEncodingSubset{TS1}{mlmtt}{0}
```

to circumvent some  $\text{\LaTeX}$  complaints about `\textasciigrave` (this is a widespread problem when not using default fonts) related to occurrences of the backtick character in verbatim displays.

<sup>7</sup>Bob TENNENT, *Support for using Libertinus fonts with \TeX/pdf\TeX*, <https://ctan.org/pkg/libertinus-type1>.

<sup>8</sup>Michael SHARPE, *A Type 1 font and \TeX support for Libertinus Math*, <https://ctan.org/pkg/libertinust1math>. Note that it is then highly advantageous to use `latex+dvipdfmx` and not `pdflatex` for reasons of PDF file size.

<sup>9</sup>this means “more than one.”

<sup>10</sup>I thank in particular Tariq PERWEZ and Kevin KLEMENT for their kind remarks (chronological order).

<sup>11</sup>more precisely stated, the value of `\itdefault` is used.

<sup>12</sup>more precisely stated, the value of `\shadefont` is used.

### 1.3.3 The `defaultmathsizes` option

The default sizes give for subscripts of subscripts barely legible glyphs (author's opinion!). So `mathastext` makes more reasonable choices. It also redefines `\Huge` and defines a `\HUGE` size, copied from the `moresize` package. To cancel all of this use option `defaultmathsizes`.

### 1.3.4 The `subdued` option

This option was introduced in v1.15. It provides a manner to switch on the `mathastext`-ification only for limited portions of the document, with the help of the mechanism of math versions. Without the `subdued` option, the `mathastextification` applies by default to the whole of the document (and one may also define additional math versions in the preamble); with the `subdued` option the `mathastextification` is done only in *math versions* distinct from the standard and bold ones.

(1.15)

Despite some limitations I will now partially describe, the `subdued` option has its utility, as I think is illustrated enough by the examples given at the start of this document and it works reasonably well.

`mathastext` was not written initially in order to allow its action to be completely canceled. It does not store (all) mathcodes nor does it set them (all) when changing math versions; only that would allow a perfect subdued mode (and L<sup>A</sup>T<sub>E</sub>X is rather obstinate in making that tricky or at least uneasy if sticking to its official interface to math mode, as it is almost entirely preamble only).

Releases 1.3t and 1.3u do this kind of things to maintain usability across multiple `mathastext`-ified math versions of characters which are obviously font encoding dependent such as the minus sign as en-dash (or unicode minus), the dotless i, the `\hbar`, the text accents.

But this should be extended to all `mathastext`-ified characters which basically would amount to an extensive rewrite of large legacy portions of the code. Currently the support for the `subdued` mode and to multiple math versions amounts to some kind of a kludge, added to an initial design which handled a single unique text font.

To get the displayed math (almost) as if `mathastext` had not been loaded, one must also use the option `defaultmathsizes`. But this does not quite suffice, as, for example, the colon, the dot, and the minus sign belong in the default L<sup>A</sup>T<sub>E</sub>X math mode set-up to three distinct fonts whereas `mathastext` will pick (even subdued) the three of them in the same font,<sup>13</sup> and although it will make a reasonable choice of this font, this is not an exact re-installement of the previously prevailing situation.

<sup>13</sup>The minus sign is now perfectly subdued, because its original mathcode is stored and restored; this was only way to handle the case with Unicode engines where the math operator font is in a classic T<sub>E</sub>X encoding, but the minus sign is configured by `mathastext` to use a Unicode en-dash or minus character in non-subdued math versions.

(1.3t)

And then other packages could have done arbitrary things regarding character mathcodes, so to be on the safe side one needs the `basic` option which limits the `mathastextification` to letters and digits.<sup>14</sup> <sup>15</sup> <sup>16</sup> Even then, in some circumstances, this may not suffice: for example the `euler` package declares the digits to be picked from the same font as the Latin letters, but the subdued `mathastext` “normal” math version will pick them from the same font as used for operator names, which here with the `euler` package is the document body default text font.

The `frenchmath` option effect applies *also* to the subdued “normal” and “bold” math versions.

### 1.3.5 The `LGRgreek` option

There is the issue of Greek letters. Sometimes the text font has Greek glyphs, in LGR encoding<sup>17</sup> (this should be mentioned in the documentation of the font package). Then option `LGRgreek` tells `mathastext` to pick up these Greek letters.

It is naturally possible to leave the responsibility to set up Greek letters to some other packages loaded previously to `mathastext`. And even if `mathastext` has been loaded with one of its Greek related options the command `\MTstandardgreek` will locally cancel its customization of Greek letters. The command `\MTcustomgreek` reenables the customization done by `mathastext`, if it was loaded with the `LGRgreek` or one of the other Greek related options.

Release 1.3y has added important new aspects to the handling of Greek letters via the `LGRgreek` option. Make sure to read the subsubsection 1.7.3.

## 1.4 Miscellanea

Please note that most material to be found in this section was written many years ago (except the two subsections on `frenchmath` on one hand and intervals on the other hand). But it should still be valid!

Ultimately most information here should be moved into the reference sections [section 2](#) and [subsection 3.2](#), and only some generalities should be kept here.

<sup>14</sup>The subdued mode does extinguish in the normal and bold math versions the action of options `selfGreek`, `eulergreek`, and `symbolgreek` (previously only `LGRgreek` was subdue-able). (1.3d)

<sup>15</sup>The `\imath` and `\jmath` now obey the subdued regime. (1.3t)

<sup>16</sup>Also `\hbar` and the math accents (see `mathaccents` option) obey the subdued regime. (1.3u)

<sup>17</sup>For example the default CM and its replacement Latin Modern for european languages are (transparently to the user) extended with LGR encoded fonts from the cbfonts (`cbgreek-complete`) T<sub>E</sub>XLive package.

### 1.4.1 Load `mathastext` always last

The “large” math symbols are not modified in any way by `mathastext`. Only loading some math font packages such as `fourier`, `kpfonts`, `mathabx`, `mathdesign`, `txfonts`, `newtxmath`, `libertinust1math`, others... will change them. Think of loading these packages before `mathastext`, else they might undo what `mathastext` did.

More generally any package (such as `amsmath`) dealing with math mode should be loaded *before* `mathastext`.

### 1.4.2 Avoid OT1 encoding

The default OT1 does not have the `<>|{}>` and `\` glyphs. If `mathastext` detects OT1 as the default encoding it will leave these characters to their defaults from the math fonts.<sup>18</sup>

If `mathastext` detects the obsolete OT1 encoding it does not do anything with `<`, `>`, `|`, `{`, and `}` which (except for monospace fonts) are not available in that encoding. To fully benefit from `mathastext` it is recommended to use some other encoding having these glyphs such as T1 or LY1.

### 1.4.3 Derivative, minus, asterisk

The text characters ' and - are not used, and the asterisk is done only optionally:

- the derivative sign ' is left to its default as the text font glyph ' is not, as a rule, a satisfying alternative.<sup>19</sup>
- for the minus sign `mathastext` uses the endash character –, if available, and not the hyphen character -. With an OpenType font, `mathastext` uses per default the EN DASH U+2013 (see [unicodeminus](#)).
- the `asterisk` option is required for `mathastext` to use the text font for the binary infix math operator \* and the control sequence `\ast`. They will use then the text asterisk \* suitably lowered, and with the correct spaces around it as binary operator.

Attention that with this option, inputs such as `$R^*$` or `$R^\ast$` raise errors and *must* be replaced by `$R^{*}$`, respectively `$R^{\ast}$`.

<sup>18</sup>The `subdued` option, described next, acts a bit otherwise, it forces, contrarily to its usual low-key character, the replacement of OT1 by T1 for the fonts ultimately used with letters and digits in math mode.

<sup>19</sup>v1.2 adds a customizable tiny space before ' to separate it from the previous letter, this is really needed when using upright letters in math mode with the CM derivative glyph. Compare `f'` with `f'`.

#### 1.4.4 Large symbols and delimiters

Nothing is changed to the “large” math symbols, except for  $\prod$  and  $\sum$  in inline math which, like here:  $\prod\sum$ , will be taken from the Symbol Font if option `symbolmisc` was used.

The left and right delimiters are taken from the text font only for the base size: any one of `\big`, `\bigl`, `\bigr`, etc... will trigger the use of the original math symbols.

#### 1.4.5 amsmath

The behavior of the `\DeclareMathOperator` command of `amsmath` is modified by (1.3n) `mathastext` for it to use the correct font. Additionally, release 1.3n of `mathastext` at long last also handles an extra operation done by `amsmath` for `' .:/-*` to be used in operator names without the extra math spacing.<sup>20</sup> This customization is suppressed in `subdued` mode for the `normal` and `bold` math versions.

#### 1.4.6 hbar

The default L<sup>A</sup>T<sub>E</sub>X definition of `\hbar` would in our context make use of the `h` of the current math font (so for us, it is also the text font, perhaps in italic shape), but with a bar accross the `h` from the original default math font for letters (usually `cmmi`). We redefine `\hbar` to use the text font macron accent (`\=`) as a mock math accent (this takes into account the `italic` option and is compatible with subscripts and superscripts).

Since 1.12 `mathastext` when dealing with a Unicode font sets the `\hbar` to be the character from the font having hexadecimal codepoint U+0127.

Since 1.3u the general 8bits font encoding is supported (see discussion of the `mathaccents` option at end of this list for the shared limitations). Brief testing with various usual T<sub>E</sub>X fonts shows that the vertical positioning of the bar isn’t satisfying. It is planned to either add a parameter to adjust it or to modify altogether the mode of construction of the `\hbar`.

Use `nohbar` to tell `mathastext` not do provide its own `\hbar`.

#### 1.4.7 Dotless i and j

By default the package redefines `\imath` and `\jmath` to give (in math mode) the dotless i and j (if it exists at all) from the text font.

---

<sup>20</sup>To the experts: there is a long story here that `\newmcodes@` hardcodes the font, that it was not compatible with Unicode engines, that during some time (2013-2016) lualatex-math fixed that and very recently `amsopn.sty` 2016/03/08 v2.02 also, so now lualatex-math 1.6 does nothing as it is already fixed “upstream” in `amsopn.sty`, but anyhow in both cases, this still hardcoded the font, so finally `mathastext` does the right thing from its point of view. See the code comments for more, there is an issue here with L<sup>A</sup>T<sub>E</sub>X not applying the curly right quote contrarily to X<sup>A</sup>T<sub>E</sub>X.

### 1.4.8 fontspec

`fontspec` has to be loaded with the option `no-math`, and before `mathastext`.

### 1.4.9 vec accent

The default `\vec` accent is not appropriate for upright letters, so `mathastext` provides under option `fouriervec` a math accent control sequence `\fouriervec` which takes its glyph in a Fourier font. A poorman Ersatz `\pmvec` is always available ; it is reasonably good looking on upright letters and works with the `\rightarrow` glyph.

### 1.4.10 math accents

If option `mathaccents` is used then `mathastext` attempts to let the math accents `\acute{e}`, `\grave{e}`, etc... use the suitable glyphs from the text font.

The `\vec` math accent is not handled here, as it is not available in the usual 8bits font encodings. See the `fouriervec` option or the `\pmvec` command.

The math accents obey the `subdued` option and will change in sync with the `mathastext`-ified text font used in each non subdued math version. (1.3u)

(Very) brief testing during 1.3u development with XeTeX and LuaTeX let the author conclude that usage with the `\Umathaccent` primitive of an OpenType accent glyph slot (which in the text font is for usage as a postpended combining character) gives definitely bad horizontal placements for both engines (each in its own way). Thus, the redefinitions of accents for a `mathastext` declared math version with an OpenType font is by default canceled.<sup>21</sup> Use `unimathaccents` to force usage of the OpenType font text accents glyph slots with the `\Umathaccent` primitive. Expert users are invited to check out the code and to contribute suggestions if some extras can improve it.

### 1.4.11 Sans serif in math

The following set-up often gives esthetically pleasing results: it is to use the sans-serif member of the font family for math, and the serif for text.

```
\renewcommand\familydefault\sfdefault
\usepackage{mathastext}
\renewcommand\familydefault\rmdefault
\begin{document}
```

### 1.4.12 mathastext with beamer

Starting with release 3.34 of `beamer`<sup>22</sup>, `mathastext` is recognized as a “math font package”.

<sup>21</sup>I.e., the `\grave{e}` etc... control sequences will, in math versions with an OpenType `mathastext`-ified font, expand to macros holding their initial meanings, unmodified by `mathastext`, which was in force at the `\begin{document}`.

<sup>22</sup>Till TANTAU, Joseph WRIGHT, Vedran MILETIĆ, *A L<sup>A</sup>T<sub>E</sub>X class for producing presentations and slides*, <https://ctan.org/pkg/beamer>.

*Only with earlier beamer versions is it necessary to issue  
`\usefonttheme{professionalfonts}`*  
*in the preamble. Example:*

```
\documentclass{beamer}
%\usefonttheme{professionalfonts}% obsolete for mathastext since beamer 3.34
\usepackage{newcent}
\usepackage[scaled=.9]{helvet}
\renewcommand{\familydefault}{\rmdefault}
\usepackage[defaultmathsizes,symbolgreek]{mathastext}
\renewcommand{\familydefault}{\sfdefault}
\begin{document}
\begin{frame}
This is some text and next comes some math: $E=mc^2$\\
\[\\
E=mc^2=a^n+b^n-c^n=\alpha\beta\gamma\\
\]\\
\begin{aligned}
&E=mc^2\\
&E=h\nu
\end{aligned}\\
\end{frame}
And again some text.
\end{document}
```

#### 1.4.13 `mathastext` with `frenchmath`

To use `mathastext` concurrently with the `frenchmath` package<sup>23 24</sup> of Antoine MISSIER:

- load `frenchmath` with its option `capsit`,
- and load `mathastext` afterwards (with possibly some font packages loaded in-between), passing it the option `frenchmath*`.

Limited testing indicated that the combination of the two packages (using the options as indicated above) works satisfactorily. There may be some minor adjustments to do, as the `mathastext`-ified math font may cause issues to some of the `frenchmath` macros: for example `\Oijk` may not work well simply due to the font lacking a dotless j, but use then `defaultimath`.

You can either use the Greek related options of `frenchmath` or those of `mathastext`. Quite certainly better not to use both at same time, anyhow this has not been tested and is not supported.

---

<sup>23</sup>Antoine MISSIER, *Typesetting mathematics according to French rules*, <https://ctan.org/pkg/frenchmath>.

<sup>24</sup>The package `mismath` also by the Antoine MISSIER may probably be used with `mathastext`, but not in a fully inter-operative way, as the two packages conflict on some aspects. Reports welcome, we have not tested this.

### 1.4.14 Intervals and separators

For appropriate mark-up and typesetting of intervals with conventions about opening and closing delimiters which are not the default TeX ones, one may use the `mathtools`<sup>25</sup> provided `\DeclarePairedDelimiterX`. For example, here is how one can define an `\Ioo` macro (the letter “o” standing for “open”) for typesetting an open (in the mathematical meaning of the word) interval using square brackets:

```
\DeclarePairedDelimiterX\Ioo[2]{\!}{\!}{\{}{\!}{\!}{\#1;#2\!}\}
```

Use then `$I = \Ioo{A}{B}$` type mark-up in your source, and the derived variants `\Ioo*` or `\Ioo[\Big]` for example will also work.

Note for very advanced users: if employing `\MTnonlettersobeymathxx`, our `\Ioo` must be used as `\Ioo*` or `\Ioo[\Big]` (for example) else it raises an error. Alternatively, replace in the above `I` by `\{}{\!}` and `[` by `\{[{\!}` and then `\Ioo` works (and also `\Ioo[\Big]`). But `\Ioo*` is broken. This is a known limitation of the `\MTnonlettersobeymathxx` functionality, and is one reason why `mathastext` does not make it the default behavior.

We used in this example the semi-colon as separator. This is seen sometimes in contexts where the interval extremities are decimal numbers, and the language convention is to use the comma as decimal point. The `binarysemicolon` option tells `mathastext` to configure the ; character to use in math mode “binary infix operator” type spacing, matching observed practice in some mathematical contexts. The `binarysemicolon` option is executed automatically by `mathastext` on receiving either the `frenchmath*` or the `frenchmath+` options.

On the topic of the decimal point, it is recommended to use the `\np` macro from the `numprint`<sup>26</sup> package with its `autolanguage` and `np` options. This is the best choice if one may have to also use the same mathematical expression with numerical quantities in another language having different conventions.

For those languages such as French where the convention is to use as decimal separator a colon, you may alternatively pass to `mathastext` either the `decimalcomma` or the `ncccomma` options, to tell it to load the eponymous packages `decimalcomma`<sup>27</sup> or `ncccomma`<sup>28</sup> respectively, which make the comma (to some extent) ‘intelligent’, i.e. decide on the spacing type (ordinary or punctuation) depending on next token. Do not load directly the packages but simply use the corresponding option and `mathastext` will do the loading and take appropriate needed measures for compatibility. The `decimalcomma` option is included in the `frenchmath*` option, and the `ncccomma` option is included in the `frenchmath+` option.

(1.3zb)

(1.3zb)

Let’s give another example of usage of `mathtools` here to define a macro for integer ranges:

```
\DeclarePairedDelimiterX\Iffint[2]{\llbracket}{\rrbracket}{\#1,\#2}
```

<sup>25</sup>Morten HØGHOLM, Lars MADSEN and the L<sup>A</sup>T<sub>E</sub>X3 project, *Mathematical tools to use with amsmath*, <https://ctan.org/pkg/mathtools>. As explained elsewhere in this documentation always load `mathastext` after `mathtools`.

<sup>26</sup>Harald HARDERS, *Print numbers with separators and exponent if necessary*, <https://ctan.org/pkg/numprint>.

<sup>27</sup>Antoine MISSIER, *Comma for decimal numbers*, <https://ctan.org/pkg/decimalcomma>.

<sup>28</sup>Alexander I. ROZHENKO, *Use comma as decimal separator in mathematics*, <https://ctan.org/pkg/ncccomma>.

This used control sequences `\llbracket` and `\rrbracket` from the `fourier` package (and possibly others). A poorman definition might be:

```
\ifdefined\llbracket\else \def\llbracket{{[\! [}}\fi
\ifdefined\rrbracket\else \def\rrbracket{{]\! ]}}\fi
```

Regarding open intervals in the French notation such as `]a,b[`, an alternative avoiding usage of specific mark-up is provided by the `ibrackets`<sup>29</sup> package which makes the square brackets mathematically active, in the same spirit as for the (semi) ‘intelligent’ comma mentioned above. Brief testing indicates this package is compatible with `mathastext`, even when using multiple math versions. Read the fine print below for some limitations though.

Note for very advanced users: compatibility is only partial as the effect of `ibrackets` is canceled after `\MTnonlettersobeymathxx`. This is expected and a special compatibility layer would be needed, of the same type as has been done to support fully the `decimalcomma` and `ncccomma` packages via eponymous `mathastext` options. There is no plan at this time to add such a patch making the compatibility exhaustive.

It is possible to use the `noparenthesis` option to turn off completely the `mathastext` actions on square brackets (and parentheses).

#### 1.4.15 Unicode engines

`mathastext` is minimally Unicode aware since 1.12 and can be used with X<sub>E</sub>T<sub>E</sub>X or LuaT<sub>E</sub>X. Starting with release 1.3, it needs luatex to be at least as recent as the one which was provided with the TL2013 distribution.

However `mathastext` applies only to (a subset of) the 32–127 ascii range, and optionally to Greek letters, but for the latter only if provided via “T<sub>E</sub>X fonts” such as Euler, Symbol or LGR-encoded fonts. It does not know how to use a given Unicode font simultaneously for Latin and Greek letters.

Thus, first consider much better alternatives:

- Since 2018, the package `mathfont`<sup>30</sup> adapts Unicode text fonts to usage in math mode. It works with both X<sub>E</sub>T<sub>E</sub>X and LuaT<sub>E</sub>X.
- For X<sub>E</sub>T<sub>E</sub>X only, `mathspec`<sup>31</sup> also allows usage of arbitrary text fonts in mathematics.
- and of course `unicode-math`<sup>32</sup> is the standard package for using OpenType fonts which are equipped with the needed extra support being used in T<sub>E</sub>X math mode.

If using any one of the above you probably don’t need, don’t want, and should not use `mathastext`.

---

<sup>29</sup>Antoine MISSIER, *Intelligent brackets*, <https://ctan.org/pkg/ibrackets>.

<sup>30</sup>Conrad KOSOWSKY, *Use TrueType and OpenType fonts in math mode* <https://ctan.org/pkg/mathfont>.

<sup>31</sup>Andrew Gilbert MOSCHOU, *Specify arbitrary fonts for mathematics in X<sub>E</sub>T<sub>E</sub>X* <https://ctan.org/pkg/mathspec>.

<sup>32</sup>Will ROBERTSON, et al., *Unicode mathematics with support for XeTeX and LuaTeX* <https://ctan.org/pkg/unicode-math>.

Let me insist that **mathastext** has not been tested in any systematic manner under the Unicode engines; and that it is expected to be most definitely incompatible with **unicode-math**, although your mileage may vary and some features may appear to work.

When using **mathastext** with either X<sub>E</sub>T<sub>E</sub>X or LuaT<sub>E</sub>X it is recommended to use the **fontspec** package (see remark below on `\encodingdefault`). Furthermore, if using **fontspec** it is *necessary* to load it with its **no-math** option, and this *must* happen before loading **mathastext**.

- Use **fontspec** with its *no-math* option, and load it *prior* to **mathastext**. As some packages load **fontspec** themselves (for example **polyglossia**), a  
`\PassOptionsToPackage{no-math}{fontspec}`  
early in the preamble might be needed.
- The **amsmath** package, if used, *must* be loaded *prior* to **mathastext**.
- Under **lualatex** engine, it is recommended to also load the package **lualatex-math**.

I already mentioned in the [subsubsection 1.8.2](#) the fact that the italic corrections were not available for OpenType fonts under the X<sub>E</sub>T<sub>E</sub>X engine and only partially available for the LuaT<sub>E</sub>X engine, with the result that the spacings in math mode when using for the letters an upright text font will be less satisfying than with the standard PDFT<sub>E</sub>X engine (the OpenType fonts not being usable with the latter engine, this is not a criterion of choice anyhow).

To define math versions when using unicode fonts, use **fontspec**'s `\setmainfont` before the `\Mathastext[<version>]` command, or simply before loading **mathastext** for the default math versions.

It is possible to mix usage of Unicode fonts and classical T<sub>E</sub>X fonts. All used 8bits font encoding must have been passed as options to the **fontenc** package.

#### 1.4.16 The **unicodeminus** option

For legacy reason, **mathastext** uses by default the EN DASH U+2013 for the minus sign in math mode, if the font is determined to be a “Unicode” font.

There is now the **unicodeminus** to use rather MINUS SIGN U+2212.<sup>33</sup> Check [its \(1.3q\) documentation](#) on page 60.

#### 1.4.17 Two examples with OpenType fonts

I include here two examples which compiled successfully (a long time ago!) with X<sub>E</sub>T<sub>E</sub>X and LuaL<sub>A</sub>T<sub>E</sub>X, the first one on a Linux machine, the second one on a Mac

<sup>33</sup>Thanks to Tobias BRINK who asked for this feature.

OS X machine.

```
\documentclass{article}
\usepackage[hscale=0.8]{geometry}
\usepackage{multicol}
\usepackage[no-math]{fontspec}
\usepackage{lmodern}
\usepackage[subdued,italic]{mathastext}
\setmainfont[Color=999999]{Verdana}      \Mathastext[Verdana]
\setmainfont[Color=0000FF]{Arial}        \Mathastext[Arial]
\setmainfont[Color=00FF00]{DejaVu Serif} \Mathastext[DejaVu]
\MTDeclareVersion{times}{T1}{ptm}{m}{n}
\setmainfont[Color=FF0000]{Andale Mono} \Mathastext[Andale]
\begin{document}
\newcommand{\TEST}[1]{\MTversion{#1}%
\begin{multicols}{2}
\hbox to\columnwidth{\hbox to\columnwidth{\hfil
$abcdefghijklmnopqrstuvwxyz$\hfil}\kern-2.5em{#1}}%
\centerline{ $ABCDEFGHIJKLMNOPQRSTUVWXYZ$ }
\centerline{ \$0123456789$ }
\centerline{ !$\backslash,?\backslash,*\backslash,,\backslash,:$\backslash,;$\backslash,+$\backslash,-$\backslash,=$\backslash,($\backslash,)\backslash,[\backslash,]\backslash,/\\,\#\backslash,%
$\backslash,\%\backslash,\&\backslash,<\backslash,>\backslash,\backslash,\{[\backslash,]\backslash,\backslash\$char92 }%
\columnbreak
\centerline{ abcdefghijklmnopqrstuvwxyz }
\centerline{ ABCDEFGHIJKLMNOPQRSTUVWXYZ }%
\centerline{ 0123456789}%
\centerline{ !$\backslash,?\backslash,*\backslash,,\backslash,:$\backslash,;$\backslash,+$\backslash,-$\backslash,=$\backslash,($\backslash,)\backslash,[\backslash,]\backslash,/\\,\#\backslash,%
$\backslash,\%\backslash,\&\backslash,<\backslash,>\backslash,\backslash,\{[\backslash,]\backslash,\backslash\$char92 }%
\end{multicols}}
\begin{multicols}{2}
\centerline{\textbf{math mode}}
\columnbreak
\centerline{\textbf{text}}
\end{multicols}
\TEST{DejaVu}\TEST{Verdana}\TEST{times}\TEST{Andale}
\TEST{Arial}\TEST{bold}\TEST{normal}
\end{document}
```

And now the same thing with fonts available on Mac OS X:

```
\documentclass{article}
\usepackage[hscale=0.8]{geometry}
\usepackage{multicol}
\usepackage[no-math]{fontspec}
\usepackage{lmodern}
\usepackage[subdued,italic]{mathastext}
\setmainfont[Color=FF0000]{Hoefler Text} \Mathastext[Hoefler]
\setmainfont[Color=336633]{American Typewriter}\Mathastext[Typewriter]
\setmainfont[Color=0000FF]{Herculanum}    \Mathastext[Herculanum]
\setmainfont[Color=FF00FF]{Didot}         \Mathastext[Didot]
\setmainfont[Color=999999]{Comic Sans MS} \Mathastext[Comic]
\begin{document}
--- copy here the code from the previous example ---
\TEST{Didot}\TEST{Comic}\TEST{normal}\TEST{Herculanum}
```

```
\TEST{Hoefler}\TEST{Typewriter}\TEST{bold}
\end{document}
```

### 1.4.18 Compatibility with other packages

Regarding the namespace of the package: all internal macros use `\mst@` (or `\ifmst@` for TeX conditionals) as prefix. Almost all user commands have `\MT` prefix, the oldest ones may use `\Mathastext` or variants.<sup>34</sup>

Compatibility issues are often questions of who decides last. They are naturally to be expected with packages dealing with the math setting. The fix is simply to load `mathastext` last. In particular one should *always* load `mathastext` after `amsmath` (this is especially needed with Unicode engines but applies in general as well).

Any definition made in a package loaded before `mathastext` of the font to be used for letters or for the common characters in the ascii basic range will be overruled by the loading of `mathastext`. Conversely most of the set-up done by `mathastext` may well be overruled by packages loaded later which do math related things.

Starting with version 1.2, `mathastext` makes some characters ‘mathematically active’ to achieve certain effects: automatic insertion of the italic corrections when using an upright text font in math (subsubsection 1.8.2), extended scope of the math alphabet commands which now apply to non-letter symbols (subsubsection 1.8.4; and also to math operator names, but this is much easier to achieve). And the (already mathematically active) right quote is modified to have some extra space added before the derivative glyph ‘ (see `\MTprimeskip`).

This mathematical activation is compatible with the `\label` and `\ref` commands in and outside of math mode.

But a difficulty arises when some other package has made the character ‘catcode active’ everywhere in the document. If it is detected for such a character that `mathastext` wishes to make ‘mathematically active’ that it is already ‘catcode active’, `mathastext` then checks if it is handling a Babel shorthand. If yes, it then hacks into `babel` support macros for that character to let it do what it desires it to do in math mode. And it does not make the character mathematically active, to the contrary it makes sure that the character is *not* mathematically active.

This last paragraph applies to the characters `;,:!?=<>()[]*` mentioned in subsubsection 1.8.4 as ‘hard non-letters’. The right tick (which is already mathematically active per default) is also handled via a similar process, and in particular is tested for being a Babel shorthand (which happens in particular with the Spanish language `activeacute` option).

The reason for avoiding in general for a catcode active character to be at same time mathematically active is illustrated in next shaded box.

In the case of the Spanish active ‘, the advantage of `mathastext` intervention to reset its mathcode is that in case of a faulty input as a curly right tick U+8217 ‘, which L<sup>A</sup>T<sub>E</sub>X will map to

---

<sup>34</sup>It is only years after initial release that I became aware that package `mathtools` used `\MT_` prefix (with an underscore as shown) for most internal constructs, and sometimes `\MT@`, and those can not clash with our `\MT[a-z|A-Z]` for public commands and `\mst@` for internal macros. They do have however user commands `\MTflushSpaceAbove` and `\MTflushSpaceBelow`, but nothing else hence some retroactive relief.

`\textquoteright` which itself gives the catcode 12 ', it will show as curly quote in output not as prime glyph, as `mathastext` removes its mathematical activation. This complements the L<sup>A</sup>T<sub>E</sub>X warnings about `\textquoteright` being invalid in math mode.

The ascii letters can not have been made active by Babel interface (see code comments of `\mst@do@activecase`) so if an ascii letter is catcode active when `mathastext` examines it, nothing will change to its meaning.

**changed:** At 1.4 these actions are done for ascii letters at loading of the package or via `\MTmathactiveletters`, which is itself done by `\MTversion` when entering non-subdued math version. Check documentation of `\MTmathactiveletters` for some relevant details. (1.4)

On matters of *mathematical* versus *catcode* active character tokens, here is some code, not involving `mathastext`, that you should **not** try at home:

```
\documentclass{article}
\usepackage[french]{babel}
\usepackage{mathtools}\mathtoolsset{centercolon}
\begin{document}
$:$
\end{document}
```

**DO NOT DO THIS AT HOME**: it creates (with `pdflatex`) an infinite loop. This is due to the fact that the colon is simultaneously active (this is made by `babel-french` at begin document) and mathematically active (done by `mathtools` in the preamble). The interaction gives an infinite loop.

Regarding mathematical activation, an incompatibility of another type arose with `amsmath`. To fix it, `mathastext` now replaces an inner macro of `amsmath` (`\resetMathstrut@`) with its own version.

Always load `amsmath` before `mathastext`.

Actually this last commandment was already made necessary by the use of the text endash to represent the minus sign in math mode, and, especially for Unicode engines, some aspects of the `\DeclareMathOperator` macro from `amsmath`.

**New with 1.3i:** `mathastext` patches `\url` of packages `url` and `hyperref`, and also `\nolinkurl`, to force them to do automatically `\MTeverymathoff`. Indeed they use math mode, and it is better to turn `mathastext` off for their dealings.

See the `\MTeverymathoff` documentation.

## 1.5 Math alphabets

Let us first recall fundamental facts of life, in the world of traditional PDFT<sub>E</sub>X engine and T<sub>E</sub>X fonts, as background for understanding what `mathastext` does in this context. People familiar with using Unicode engines and `unicode-math`, please be aware that the semantics there of the L<sup>A</sup>T<sub>E</sub>X math alphabet commands are **significantly** modified!

- In the default L<sup>A</sup>T<sub>E</sub>X set-up all five of `\mathrm`, `\mathbf`, `\mathit`, `\mathsf` and `\mathtt` tell T<sub>E</sub>X to use for their arguments specific OT1-encoded fonts.
- If the document body uses, as will be the case probably with any language other than English or its variants, some other encoding such as T1 for its fonts, there is no change whatsoever to the math configuration, indeed most font packages ignore it completely.
- It is thus a priori wrong to think of these commands as switching to some body text font, although letters within their scopes will act as in a text font, and in particular obey ligatures (this also applies to operator names defined by `amsmath`'s `\DeclareMathOperator` which are, with some extras not mentioned here, as using `\mathrm`).
- These commands are completely different in spirit from the L<sup>A</sup>T<sub>E</sub>X `\textrm`, `\textbf`, and others, which change only some font axis; indeed the math alphabet commands inherit from legacy Knuth's `\rm`, `\bf`, and others which are complete font specifiers.
- In particular when nesting, it is the inner-most which wins.
- Only mathematical characters (such as letters) which are declared to T<sub>E</sub>X as being of “variable family type” react to being in the argument of a math alphabet command.
- Lowercase Greek letters are by default in L<sup>A</sup>T<sub>E</sub>X immune to math alphabets (so `\mathrm{\pi}` induces no change in output), but the eleven uppercase Greek letters are of “variable family type” because they are picked in the OT1-encoded font also used for operator names (the one to which `\mathrm` maps), *and they occupy the exact same slots in the OML-encoding to which `\mathnormal` maps!* So in default T<sub>E</sub>X, `\mathnormal{\Gamma}` gives a slanted glyph. The slots occupied in OML-encoding by the lowercase Greek letters (to which encoding they are a priori assigned) give completely unrelated glyphs in the OT1-encoding, so it makes sense that the default L<sup>A</sup>T<sub>E</sub>X declares lowercase Greek to not react to math alphabets. Notice though, that if L<sup>A</sup>T<sub>E</sub>X had declared a `\mathnormalbold`, mapping to a bold OML-encoded font, it would have made sense to also have `\alpha`, `\beta`, etc... be of “variable family type”.
- But of course even if `\pi` is of such “variable family type” then `\mathbf{\pi}` will give garbage because the default `\mathbf` selects an OT1-encoded font, where there is no pi glyph whatsoever and in particular not at the slot (which is 25) of  $\pi$  in the OML encoding!

- Please keep all the above in mind when trying to understand what `mathastext` does with math alphabets. The most significant point described next naturally is that `mathastext` will sync `\mathnormal`, `\mathrm`, `\mathbf`, `\mathit`, `\mathsf` and `\mathtt` to map to the `mathastext`-ified body text fonts.
- changed:**
- `\mathnormal`, `\mathrm`, `\mathbf`, `\mathit`, `\mathsf` and `\mathtt` are modified to use the `mathastext`-ified text fonts; this can be disabled via `defaultalphabets` and related individual options, but the package always provides `\Mathnormal`, `\Mathrm`, etc..., to match the `mathastext` font configuration (prior to 1.3za `defaultalphabets` and related options also caused the `mathastext` alphabet commands not to be defined). Recall that there may arise a “too many math alphabets” error if too many of these commands are *used* in the document: *declaring* them is not by itself the cause of the error. See the L<sup>A</sup>T<sub>E</sub>X news entry of its 2021-11-15 release for the counter `local-mathalphabets` (with default value 2) which can be now be used if one hits such a difficulty. (1.3za)
  - We define a new math alphabet command `\mathnormalbold` which gives direct access to the bold version of the `\mathnormal` alphabet (rather than using either the `\bm` command from the `bm` package or the `\boldsymbol` command from the `amsbsy` package). As it does not exist in the default L<sup>A</sup>T<sub>E</sub>X math font set-up, this alphabet is *not* subjected to the subdued option action.
  - Version 1.2 of `mathastext` has extended the scope of the math alphabets to apply to non-alphabetical characters and to operator names. This respects the automatic white spaces added by T<sub>E</sub>X around math symbols. See the devoted subsubsection 1.8.4. (1.2)
  - The optional extra skips around letters (see subsubsection 1.8.1 and subsubsection 1.8.2) are removed in the scope of the math alphabets. (1.3i)
  - Depending on options, further math alphabet commands are defined by the package: `\MathEulerBold`, `\MathEuler`, `\MathPSymbol`, and since 1.3y under the `LGRgreek` family of options also `\mathgreekup` and `\mathgreekit`. See subsubsection 1.7.3. And also `\mathgreekupbold` and `\mathgreekitbold` under the `LGRgreek` family of options. (1.3y)  
(1.3za)
  - With the `LGRgreek+` option which enhances Greek letters with a specific behavior when in the arguments of the `\mathrm`, `\mathbf`, etc..., math alphabet commands, this special behavior is not triggered by the `\Mathrm`, `\Mathbf`, et al., which are genuine unmodified math alphabet commands. See subsubsection 1.7.5. (1.3za)

## 1.6 Math versions

L<sup>A</sup>T<sub>E</sub>X has the concept of *math versions*<sup>35</sup>, but most font packages do not define any such version beyond the default normal and bold (the package `unicode-math` for unicode engines does use this concept).

`mathastext` extends the concept of math versions in order to allow the math mode fonts (for letters, digits, punctuation and a few other ascii symbols) used in the different parts of the document to be kept in sync with the text fonts.

Most math symbols (sums, products, integrals, logical signs, etc...) are kept the same throughout the document though as it is not in `mathastext` power to modify them.

For examples see the earlier subsection 1.2. The interface to define a `math version` includes the commands `\Mathastext` and `\MTDeclareVersion`.

Once such a `math versions` has been defined in the preamble, `\MTversion{name_of_version}`, or equivalently `\Mathastextversion{name_of_version}`, enacts the font switches when encountered in the body of the document. As is usual with L<sup>A</sup>T<sub>E</sub>X one can limit the scope to inside a group, or also switch back to the main set-up via `\Mathastextversion{normal}`.

When `\Mathastext` is used in the preamble, it records the current text font defaults (`\familydefault` et al. or what has been configured by `\MTfamily` and similar commands) and (except for the `normal` and `bold` versions if in `subdued` regime) sets up *both* the math font and the text font in the defined `mathastext`-math version to be this text font. It is still possible to switch on via `\MTversion` in the document body distinct fonts for text and math: an optional argument (the name of another `mathastext`-declared math version) to `\MTversion` is allowed (such as for example `\MTversion[newcent]{helvet}` for one of the examples of the subsection 1.2). It instructs to use as text font the font which was configured to be used in this second `mathastext`-math version.<sup>36</sup>

The native L<sup>A</sup>T<sub>E</sub>X command `\mathversion{<version_name>}` would change only the fonts for the math mode, not the text mode fonts. It is important to use rather the package command `\MTversion` (or one of its synonyms `\mathastextversion`, `\Mathastextversion`, `\MTVersion`), with its mandatory argument `{<version_name>}`, as it does additional actions:

- it sets the font for math mode (letters, math operator names, digits, punctuations, some other symbols) according to the version name given as mandatory

---

<sup>35</sup>math versions are discussed in the document `fntguide.pdf` from your T<sub>E</sub>X distribution.

<sup>36</sup>When not using math versions at all (so not using subdued mode either) another way to achieve distinct fonts in text and math is naturally to modify the document text font *after* having loaded `mathastext` (or after last usage of `\Mathastext` without optional argument). Another way is to use `\MTfamily`, `\MTencoding`, `\MTseries`, `\MTshape`, `\MTlettershape` in the preamble before a call to `\Mathastext` which will configure math fonts without having modified the document text fonts. However if one does `\MTversion{normal}` in the document then the text font will be reset to what was recorded as math font by the `\Mathastext` call in the preamble (as said above, when not using subdued option).

argument,

- it resets the text font of the document and the `\(family,rm,sf,\dots)` defaults to their values as registered at the time of definition of the version. *Use the starred variant in case this is not desired.* As explained above tt is possible to specify within brackets an extra optional version name, and the text font will be set according to it.

For all math versions if not using the `subdued` option, or only for the non-*normal* and non-*bold* math versions if using the `subdued` option, `\MTversion` does further additional tasks:

- it resets the `\hbar`, `\imath` (see `\inodot`), `\jmath`, math accents (see option [mathaccents](#)) and minus sign as en dash according to the used font encoding for the `mathastext`-ified text font, [\(1.3u\)](#)
- (see [subsubsection 1.8.1](#) and [subsubsection 1.8.2](#)) it re-issues the command `\MTmathactiveletters` to let a to z, A to Z, be mathematically active in order to automatically insert the skips as defined by the user with `\MTsetmathskips`, and the italic corrections (if the font is not italic or slanted),
- (see [subsubsection 1.8.3](#)) it resets the extra spaces after the symbols  $\exists$ ,  $\forall$  and before the derivative ' to the values as decided by the user in the preamble on a *per version* basis,
- (see [subsubsection 1.8.4](#)) it re-issues the commands `\MTmathoperatorsobeymathxx` and `\MTeasynonlettersobeymathxx` to let the math operator names and ('easy') non letter characters obey the math alphabets,
- in case of option `asterisk`, it re-issues `\MTactiveasterisk`,
- it does the additional set-up for Greek letters in case of the package received one of the Greek related options.

The scope is limited to the current L<sup>A</sup>T<sub>E</sub>X environment or group.

It is sometimes not compatible with `mathastext` to load a font package after it, as the font package may contain instructions which will modify the math set-up. This may be a bit hidden to the user: for example the `epigrafica` package loads `pxfonts`. Hence it will interfere with `mathastext` if it is loaded after it.<sup>37</sup> But one can use instead `\renewcommand{\rmdefault}{epigrafica}`,<sup>38</sup> followed with

---

<sup>37</sup>may typically give a 'too many math alphabets' error message.

<sup>38</sup>sometimes one needs to look in the .sty file of the font package to figure out the font name (it is rarely as here with `epigrafica`, the same as the package name), and, if one does not know the arcanae of finding .fd files in one's T<sub>E</sub>X distribution, one should look at the log file of a test document to see if for example T1 is available for that font; for `epigrafica` it is not, only OT1 and LGR are possible.

`\Mathastext`, or also `\MTfamily{epigrafica}\Mathastext` which will only change the font in math.

To use `epigrafica` for Greek in math mode one can use the package option `LGRgreek` and the command `\MTgreekfont{epigrafica}\Mathastext`. Or `\usepackage{epigrafica}` followed with `\usepackage[LGRgreek]{mathastext}`.

## 1.7 Greek letters

### 1.7.1 The Greek-related options

The Computer Modern fonts are very light and thin in comparison to many text fonts, and as a result rarely mix well with them (particularly if the Latin letters in math mode are upright). The following options are provided by `mathastext`:

**no option:** nothing is done by the package, Greek letters are the default Computer Modern ones or have been set-up by other packages; for example by the `fourier` package with option ‘upright’, which gives upright Greek letters or by the author `lgrmath` package.

**LGRgreek:** (this was substantially updated at [1.3y](#), make sure to read the new documentation at [subsubsection 1.7.3](#)) this option is for fonts which additionally to Latin letters also provide Greek letters in LGR encoding. Here is a list from a 2012 standard `TeX` installation: the Computer Modern, Latin Modern, and the CM-LGC fonts; the Greek Font Society fonts (such as GFS Didot), the `epigrafica` and `kerkis` packages, the `txfonts` package which extends the `txfonts` package with LGR-encoded Greek letters; the Droid fonts, the DejaVu fonts, the Comfortaa font, and the Open Sans font. The LGR encoded CM/LM fonts (in serif, sans-serif and typewriter family) give the nice Greek letters in upright shape from the `cbfonts` package. To get these letters in your `mathastext` math mode, you can do the following:

```
% instructions to load the document fonts:  
\usepackage{nice_font}  
% and then the following:  
\renewcommand{\familydefault}{\cmr} % or cmss or cmtt for sans resp. mono  
\usepackage[LGRgreek]{mathastext}  
\renewcommand{\familydefault}{\rmdefault}  
\Mathastext % this re-initializes mathastext with the nice_font,  
% without changing the LGR font cmr/cmss/cmtt used for Greek letters  
% in math mode.  
\begin{document}
```

If you use the `italic` option note that the italic Greek letters from the `cbfonts` are not the same glyphs as the default Greek letters from the OML encoded font `cmmi`.

**LGRgreek+:** extends `LGRgreek` to allow abusive usage of `\mathrm` and alike commands with Greek letters. This is very much not in the spirit (especially with [\(1.3za\)](#)

traditional “8bit” TeX fonts) of the L<sup>A</sup>T<sub>E</sub>X kernel concept of math alphabet commands. Check [subsubsection 1.7.5](#) for relevant information.

**eulergreek:** the Greek letters will be taken from the Euler font (the document does not have to load the eulervm package, **mathastext** directly uses some file included in this package, as it provides a mechanism to scale by an arbitrary factor the Euler font.) The letters are upright.

**symbolgreek:** the Greek letters will be taken from the (Adobe Postscript) Symbol font. A command is provided so that the user can scale the Symbol font to let it better fit with the text font. The letters are upright.

**selfGreek:** this option concerns only the eleven Greek capitals from the OT1-encoding. It does nothing for the lowercase Greek letters. The encoding used in the document does not have to be OT1.

There is also **LGRgreek** (and **LGRgreeks+**) which tells **mathastext** to pick up in each math version the letters from the LGR encoded font used in that version, and **selfGreeks** to tell **mathastext** to do as for **selfGreek** but separately in all math versions.

Under the **subdued** option the Greek letters in the normal and bold math versions are kept to their defaults as found at the time of loading the package.

The commands **\MTstandardgreek** allow at any point in the document to turn inactive any Greek related option passed to **mathastext**. And conversely **\MTCustomgreek** reactivates it.

### 1.7.2 Shape of Greek letters

Classic TeX uses in math mode italic lowercase and upright uppercase Greek letters. French typography uses upright shape for both lowercase and uppercase. And the ISO standard is to use italic shape for both lowercase and uppercase.

The Euler and Symbol fonts not being available in other than their default upright shape, this question of shapes for Greek letters raises issues only in the case of the options **LGRgreek** and **selfGreek**.

The options **frenchmath**, **itgreek**, **upgreek**, **itGreek** and **upGreek** modify the Greek letter shapes according to the following rules, listed from the lowest to the highest priority:

**no option:** the lowercase Greek letters are in the same shape as Latin letters, and the uppercase in the same shape as is applied to digits and operator names,

**frenchmath:** both lowercase and uppercase are in the same shape as the digits and operator names (most of the time this means “upright shape”, but it can be otherwise),

**itgreek** : says that Greek letters (both lowercase and uppercase) will be in ‘it’ shape. More precisely the expansion of `\MTgreekitdefault` is used. (1.3y)

This was changed at 1.3y, formerly the value of `\itdefault` which was in force at the time of using `\Mathastext` (or at time of loading the package if no use is made of `\Mathastext`) was used.

**upgreek** : says that Greek letters (both lowercase and uppercase) will be in ‘n’ shape. More precisely the expansion of `\MTgreekupdefault` is used. (1.3y)

This was changed at 1.3y, formerly the value of `\updefault` which was in force at the time of using `\Mathastext` (or at time of loading the package if no use is made of `\Mathastext`) was used. But since LATEX 2020-02-02 this caused many Font Warnings in the log because `\updefault` is now ‘up’, not ‘n’ as formerly.

**itGreek, upGreek:** same but they apply only to the uppercase Greek letters. Their effect is computed after having taken into account either **itgreek** or **upgreek** presence.

So, the default gives the classic T<sub>E</sub>X behavior when option **italic** was passed.

As mentioned already the package allows to define various “math versions”. There are commands to be used inside the preamble to influence the shapes, and even the font, used for Greek letters in each given **mathastext**-declared math version: `\MTitgreek`, `\MTupgreek`, `\MTitGreek`, `\MTupGreek` and `\MTgreekfont{name_of_font}`.

Their effect is as the options of the alike name, except that the effect applies only to **mathastext**-math versions declared *next* in the preamble (be it via `\Mathastext` or `\MTDeclareVersion`).

To use `\MTgreekfont` you need to know the name of a suitable font family available in LGR encoding: for example **lmr**, **txr** (needs **txfonts** package on your system), **DejaVuSerif-TLF** (needs **dejavu** package on your system), etc...

`\MTitgreek`, `\MTupgreek`, `\MTitGreek`, `\MTupGreek` have some effect only if one of the `LGRgreek`, `LGRgreeks`, `selfGreek` or `selfGreeks` options was passed to the package.

Once any of these commands has been made use of, changes in the shape configuration of the Latin letters will stop having any influence on the shape of the Greek letters.

`\MTgreekfont` has an effect only for `LGRgreek` and `selfGreek`. It is without any effect with `LGRgreeks` and `selfGreeks`.

### 1.7.3 Control sequences to access directly upright or italic shape for Greek under LGRgreek option

Some changes were made at 1.3y to enhance the `LGRgreek` (and `LGRgreeks`) options with new features. Everything which will be explained here applies only to these two options.

First of all the package now makes available control sequences to access either the upright or italic shape of the Greek letters: `\alphaup`, `\alphait`, etc...<sup>39</sup> Which shape is meant by ‘up’ or ‘it’ is configured via defining `\MTgreekupdefault` and `\MTgreekitdefault` respectively prior a `\Mathastext` command in the preamble (possibly with [`<version_name>`] optional argument). Their default definitions are to expand to ‘n’ and ‘it’ respectively. They can also be defined prior to loading `mathastext`.

See the [Table 1](#) and [Table 2](#) for illustrations (using here the Libertinus Serif font). (1.3y)

<code>\Alphaup A</code>	<code>\Xiup Ξ</code>	<code>\alphaup α</code>	<code>\xiup ξ</code>
<code>\Betaup B</code>	<code>\Omicronup O</code>	<code>\betaauup β</code>	<code>\omicronup o</code>
<code>\Gammaammaup Γ</code>	<code>\Piup Π</code>	<code>\gammaauup γ</code>	<code>\piup π</code>
<code>\Deltaup Δ</code>	<code>\Rhoup P</code>	<code>\deltaauup δ</code>	<code>\rhoup ρ</code>
<code>\Epsilonup E</code>	<code>\Sigmaup Σ</code>	<code>\epsilonauup ε</code>	<code>\sigmaauup σ</code>
<code>\Zetaup Z</code>	<code>\Tauup T</code>	<code>\zetaauup ζ</code>	<code>\tauauup τ</code>
<code>\Etaup H</code>	<code>\Upsilonup Y</code>	<code>\etaauup η</code>	<code>\upsilonauup υ</code>
<code>\Thetaetaup Θ</code>	<code>\Phiiuup Φ</code>	<code>\thetaetaup θ</code>	<code>\phiiuup φ</code>
<code>\Iotaup I</code>	<code>\Chiup X</code>	<code>\iotaauup ι</code>	<code>\chiiuup χ</code>
<code>\Kappaup K</code>	<code>\Psiiuup Ψ</code>	<code>\kappaauup κ</code>	<code>\psiiuup ψ</code>
<code>\Lambdaambdaup Λ</code>	<code>\Omegaegaup Ω</code>	<code>\lambdaambdaup λ</code>	<code>\omegaegaup ω</code>
<code>\Muup M</code>	<code>\Digammaup F</code>	<code>\muup μ</code>	<code>\digammaup ρ</code>
<code>\Nuup N</code>		<code>\nuup ν</code>	<code>\varsigmaauup ζ</code>

Table 1: Greek letters via ‘up’ control sequences (math mode only)

The regular control sequences without ‘up’ or ‘it’ postfix will map to either one of the two versions according to how the shapes were configured, i.e. in almost all cases via usage of either the `itgreek`, `upgreek`, etc... options or `\MTitgreek` et al. commands. This is on a per `mathastext`-enriched math version basis, depending only on how the options or commands were used in the preamble.

Furthermore two math alphabets are provided

`\mathgreekup`

<sup>39</sup>No check is done of pre-existing such math symbol, they will be replaced by the `mathastext` definition with no warning. If they happen to be pre-defined as  $\text{\LaTeX}$  commands, not as math symbols, errors will happen during the loading of `mathastext`.

\Alphait A	\Xiit Ξ	\alphait α	\xiit ξ
\Betalit B	\Omicronit O	\betait β	\omicronit o
\Gammait Γ	\Piit Π	\gammait γ	\piit π
\Deltait Δ	\Rhoit P	\deltait δ	\rhoit ρ
\Epsilononit E	\Sigmait Σ	\epsilonpsilononit ε	\sigmait σ
\Zetait Z	\Tauit T	\zetait ζ	\tauait τ
\Etait H	\Upsilononit Y	\etait η	\upsilononit ν
\Thetait Θ	\Phiit Φ	\thetaetait θ	\phiit φ
\Iotait I	\Chiit X	\iotait ι	\chiit χ
\Kappait K	\Psiit Ψ	\kappait κ	\psiit ψ
\Lambdait Λ	\Omegait Ω	\lambdait λ	\omegait ω
\Muit M	\Digammait F	\muit μ	\digammait ψ
\Nuit N		\nuit ν	\varsigmait ζ

Table 2: Greek letters via ‘it’ control sequences (math mode only)

### \mathgreekit

which can be used to map a letter to the corresponding Greek fonts:

```
$\mathgreekup{a}=\mathgreekup{\alpha}=\mathgreekup{\alphait}=\alphaup$  

    α = α = α = α  

$\mathgreekup{G}=\mathgreekup{\Gamma}=\mathgreekup{\Gammatit}=\Gammaup$  

    Γ = Γ = Γ = Γ  

$\mathgreekit{z}=\mathgreekit{\zeta}=\mathgreekit{\zetaup}=\zetait$  

    ζ = ζ = ζ = ζ  

$\mathgreekit{W}=\mathgreekit{\Omega}=\mathgreekit{\Omegaup}=\Omegait$  

    Ω = Ω = Ω = Ω
```

Some refactoring<sup>40</sup> was required to achieve this at 1.3y and it is not 100% backwards compatible: if none of the `itgreek` etc... things was used, the Greek letters formerly would follow the shape of Latin letters (for lowercase Greek) and of operator names (for uppercase Greek). Now, some check is made for each of these two shapes whether it is ‘it’ or ‘sl’ and then the ‘italic’ shape, i.e. `\MTgreekitdefault` which by default is ‘it’ (without the quotes) is used, else the ‘upright’ shape, i.e. `\MTgreekupdefault` which by default expands to ‘n’ (without the quotes) is used. Naturally these checks are done on a per `mathastext`-math version basis, if multiple math versions are used.

So for example those who used some adventurous ‘sc’ for the main shape (the one used per default for operator names) and used the option `LGRgreek` but none of the `itgreek` et al. options, and none of the `\MTitgreek` et al. commands, now will

<sup>40</sup>Technically, formerly two symbol fonts were declared, one for the lowercase Greek letters and one for the uppercase Greek letters; now those are dropped and replaced by two symbol fonts, one for ‘italic’ Greek letters, the other for ‘upright’ Greek letters.

need to adjust `\MTgreekupdefault` to expand to ‘sc’ prior to some `\Mathastext` or `\Mathastext[⟨version_name⟩]` or `\MTDeclareVersion` in the preamble depending on context.

It is hoped most documents, even those using multiple math versions, which made use of the `LGRgreek` (or `LGRgreeks`) option will simply produce unmodified output. Please report to the author unexpected results not fitting the above attempted description of the only partial backwards compatibility.

#### 1.7.4 `\mathgreekupbold` and `\mathgreekitbold`

Again this applies only to `LGRgreek` and `LGRgreeks` options (and the [1.3za](#) added `LGRgreek+` and `LGRgreeks+`).

See the [Table 3](#) and [Table 4](#) for illustration of usage (in math mode only) of code [\(1.3za\)](#) such as

```
\mathgreekupbold{\alpha}
or \mathgreekitbold{\alpha}
```

Note that all three of `\alpha`, `\alphaup` and `\alphait` would give the same output. These two tables again use the Libertinus Serif font via an `mathastext` math version which was configured in the preamble using this set-up (and the package `LGRgreek` option):

```
\MTfamily{LibertinusSerif-TLF}
\MTlettershape{n}
\MTseries{m}
\MTgreekfont{LibertinusSerif-TLF}
\MTupgreek
\Mathastext[libertinus]
```

Some examples here to illustrate the effect of the math alphabet commands on Latin letters also:

```
$\mathgreekupbold{a}=\mathgreekupbold{\alpha}$
α = α
$\mathgreekupbold{G}=\mathgreekupbold{\Gamma}$
Γ = Γ
$\mathgreekitbold{z}=\mathgreekitbold{\zeta}$
ζ = ζ
$\mathgreekitbold{W}=\mathgreekitbold{\Omega}$
Ω = Ω
```

#### 1.7.5 Special behavior of `\mathrm`, `\mathbf`, `\mathit` with Greek letters via the `LGRgreek+` option

With option `LGRgreek+` or `LGRgreeks+`, `mathastext` makes Greek letters control sequences `\alpha`, `\beta`, ... (but not `\alphaup` or `\betaait` and the others) react [\(1.3za\)](#)

\Alpha → <b>A</b>	\Xi → <b>Ξ</b>	\alpha → <b>α</b>	\xi → <b>ξ</b>
\Beta → <b>B</b>	\Omicron → <b>O</b>	\beta → <b>β</b>	\omicron → <b>ο</b>
\Gammaa → <b>Γ</b>	\Pi → <b>Π</b>	\gamma → <b>γ</b>	\pi → <b>π</b>
\Delta → <b>Δ</b>	\Rho → <b>P</b>	\delta → <b>δ</b>	\rho → <b>ρ</b>
\Epsilon → <b>E</b>	\Sigma → <b>Σ</b>	\epsilon → <b>ε</b>	\sigma → <b>σ</b>
\Zeta → <b>Z</b>	\Tau → <b>T</b>	\zeta → <b>ζ</b>	\tau → <b>τ</b>
\Eta → <b>H</b>	\Upsilon → <b>Y</b>	\eta → <b>η</b>	\upsilon → <b>v</b>
\Theta → <b>Θ</b>	\Phi → <b>Φ</b>	\theta → <b>θ</b>	\phi → <b>ϕ</b>
\Iota → <b>I</b>	\Chi → <b>X</b>	\iota → <b>ι</b>	\chi → <b>χ</b>
\Kappa → <b>K</b>	\Psi → <b>Ψ</b>	\kappa → <b>κ</b>	\psi → <b>ψ</b>
\Lambda → <b>Λ</b>	\Omega → <b>Ω</b>	\lambda → <b>λ</b>	\omega → <b>ω</b>
\Mu → <b>M</b>	\Digamma → <b>F</b>	\mu → <b>μ</b>	\digamma → <b>f</b>
\Nu → <b>N</b>		\nu → <b>ν</b>	\varsigma → <b>ς</b>

Table 3: Greek control sequences in the argument of `\mathgreekupbold`.

\Alpha → <b>A</b>	\Xi → <b>Ξ</b>	\alpha → <b>α</b>	\xi → <b>ξ</b>
\Beta → <b>B</b>	\Omicron → <b>O</b>	\beta → <b>β</b>	\omicron → <b>ο</b>
\Gammaa → <b>Γ</b>	\Pi → <b>Π</b>	\gamma → <b>γ</b>	\pi → <b>π</b>
\Delta → <b>Δ</b>	\Rho → <b>P</b>	\delta → <b>δ</b>	\rho → <b>ρ</b>
\Epsilon → <b>E</b>	\Sigma → <b>Σ</b>	\epsilon → <b>ε</b>	\sigma → <b>σ</b>
\Zeta → <b>Z</b>	\Tau → <b>T</b>	\zeta → <b>ζ</b>	\tau → <b>τ</b>
\Eta → <b>H</b>	\Upsilon → <b>Y</b>	\eta → <b>η</b>	\upsilon → <b>v</b>
\Theta → <b>Θ</b>	\Phi → <b>Φ</b>	\theta → <b>θ</b>	\phi → <b>ϕ</b>
\Iota → <b>I</b>	\Chi → <b>X</b>	\iota → <b>ι</b>	\chi → <b>χ</b>
\Kappa → <b>K</b>	\Psi → <b>Ψ</b>	\kappa → <b>κ</b>	\psi → <b>ψ</b>
\Lambda → <b>Λ</b>	\Omega → <b>Ω</b>	\lambda → <b>λ</b>	\omega → <b>ω</b>
\Mu → <b>M</b>	\Digamma → N/A	\mu → <b>μ</b>	\digamma → N/A
\Nu → <b>N</b>		\nu → <b>ν</b>	\varsigma → <b>ς</b>

Table 4: Greek control sequences in the argument of the `\mathgreekitbold` command.  
This font has no bold italic Digamma nor digamma (last tested 2023/12/19).

in a special manner within the scope of `\mathnormal`, `\mathrm`, `\mathit`, `\mathbf`, and `\mathnormalbold`, but not further math alphabet commands, and not when using the `mathastext` defined commands named with an uppercased initial.

Here is an example

	<i>abCDαπΔΓ</i>
<i>mathnormal</i>	<i>abCDαπΔΓ</i>
<i>mathrm</i>	<i>abCDαπΔΓ</i>
<i>mathit</i>	<i>abCDαπΔΓ</i>
<i>mathbf</i>	<b>abCDαπΔΓ</b>
<i>mathnormalbold</i>	<b>abCDαπΔΓ</b>
<i>mathgreekup</i>	<i>αβ“ΔαπΔΓ</i>
<i>mathgreekit</i>	<i>αβ“ΔαπΔΓ</i>
<i>mathgreekupbold</i>	<b>αβ“ΔαπΔΓ</b>
<i>mathgreekitbold</i>	<b>αβ“ΔαπΔΓ</b>

It used this source:

```
\[ \def\zzz{abCD\alpha\pi\Delta\Gamma}
\begin{array}{l}
&\&\zzz\\
&\mathnormal& \mathnormal{\zzz}\\
&\mathrm& \mathrm{\zzz} \% \mathrm on Greek is like \mathgreekup
&\mathit& \mathit{\zzz} \% \mathit on Greek is like \mathgreekit
&\mathbf& \mathbf{\zzz} \% \mathbf on Greek is like \mathgreekupbold
&\mathnormalbold& \mathnormalbold{\zzz}\\
&\mathgreekup& \mathgreekup{\zzz}\\
&\mathgreekit& \mathgreekit{\zzz}\\
&\mathgreekupbold& \mathgreekupbold{\zzz}\\
&\mathgreekitbold& \mathgreekitbold{\zzz}\\
\end{array}
\]
```

This was typeset here using a “libertinustexstyle” math version which (differently from the one used in an earlier section) has the default T<sub>E</sub>X settings for the shape of Latin and Greek letters: i.e. italic Latin and lowercase Greek, upright uppercase Greek. Its preamble definition was something like this:

```
\MTfamily{LibertinusSerif-TLF}
\MTgreekfont{LibertinusSerif-TLF}
\MTlettershape{it} \% not needed with italic option if nothing was changed prior
\MTitgreek\MTupGreek \% this is also the default configuration
\Mathastext[libertinustexstyle]
```

The difference with using only `LGRgreek` option is that with the latter the Latin math alphabets such as `\mathrm`, `\mathit`, `\mathbf` produce a Latin letter when acting on a Greek control sequence, as the latter are defined by `mathastext` under `LGRgreek` to be of “variable family type” for usage with `\mathgreekup` and

`\mathgreekit`. With `LGRgreek+`, the Greek control sequences are not mathchar tokens anymore but macros with conditionals detecting some flag set by custom `\mathnormal`, `\mathnormalbold`, `\mathrm`, `\mathit`, and `\mathbf`.

`mathastext` has no logical way to sync shape of Latin and Greek letters once usage has been made of Greek related commands. Hence `\mathnormal` is currently configured to do nothing on Greek letters. This may change, please consider this behavior unstable.

Remark: this `LGRgreek+` functionality is considered by its author an abuse of the concept of a math alphabet command and required accomodating a serious deviation from internal logical design of `mathastext`. I don't know if it is because L<sup>A</sup>T<sub>E</sub>X documentations are deficient or misleading on such matters but it appears many L<sup>A</sup>T<sub>E</sub>X users are surprised when `\mathrm{\pi}` does not give an upright pi letter but this is completely to be expected in a world with fonts having only 128 or 256 glyphs, and from the fact that `\mathrm` and `\mathbf` originate in Plain T<sub>E</sub>X `\rm` and `\bf` and are still quite akin to it, they are font switching commands nothing more or less.

## 1.8 Advanced capacities

Some such capacities are on per default (but if with `subdued` option will be turned off in the *normal* and *bold* math versions), others require an action from the user for activation.

### 1.8.1 Extra spaces around letters

This is a new feature<sup>41</sup> added with release 1.3: the command `\MTsetmathskips` allows the user to set up some spaces (more precisely, ‘mu glue’; but stretch and shrink are discarded) to be automatically inserted around the letters in math mode. Some (very) unrealistic uses:

```
% this may be anywhere in the document (also within a math group):
\MTsetmathskips{x}{20.33mu}{15.66mu}%
 20.33mu before all x's and 15.66mu after.
\MTsetmathskips{y}{\thickmuskip}{\thickmuskip}%
\MTsetmathskips{z}{10mu}{5mu}%
  stretch and shrink are anyhow without effect.
\MTsetmathskips{A}{\muexpr \thickmuskip*2}{\muexpr \medmuskip-\thinmuskip/2}%

```

Here is what `wxtytz^{\wxtytz}=BAC^{\BAC}` then gives using the Times font:  $w x t y t z^w x t y t z = B A C^B A C$ . Any T<sub>E</sub>X group or L<sup>A</sup>T<sub>E</sub>X environment limits as usual the scope of this command. Furthermore the command `\MTunsetmathskips` cancels previous use of `\MTsetmathskips` for a given letter.

The implementation relies on the ‘mathematical activation’ of letters, which is done by default by the package since release 1.2b. Should this cause compatibility problems, the command `\MTmathstandardletters` cancels it entirely. To reactivate it, there is `\MTmathactiveletters`. Note that `\MTmathactiveletters` is done

---

<sup>41</sup>It was new in 2013 indeed. Not so much new now, but it is never too late to try it out.

automatically (as part of `\MTicinmath`) by `mathastext` when loaded (if not with `subdued` option), and also each time the package enhanced math-version-switch command `\MTversion` is used, except for the normal and bold math versions under the `subdued` option.

The extra skips are set at natural width; they do not contribute to the overall stretchability or shrinkability of the math formula and do not create break points.

**Changed with 1.3i:** they are *not* applied within the scope of math alphabet commands.

### 1.8.2 Background on italic corrections in math mode

Note: this is somewhat technical discussion which may well be skipped in its entirety on first reading.

With the `italic` option the letters in math will be generally in italic shape (and, normally, upright in operator names).

For the built-in placement routines of TEX in math mode to work as well as they usually do, the characters from the math italic font obviously should have their bounding boxes wide enough for the glyphs not to collide with other symbols. A letter from a text italic font such as  $f$  extends way out of its declared bounding box; let us compare the bounding boxes<sup>42</sup> for the letter  $f$  in the math italic font to the one from the text italic font:  vs. .

This could make us think that attempting to use in math a text italic font will lead to disaster. Well, surprisingly the situation is not that bad. Sure  $f(x)$  is wider with the standard math italic  (21.31474pt) than it is with the text italic font used in math:<sup>43</sup>  (19.74986pt) but we should be surprised that our text italic  $f$  did not end up even closer to the opening parenthesis. Why is it so?

The explanation is that TEX uses in such a situation the *italic correction* for the letter  $f$ . The italic correction also exists and is used for the math italic font, it was inserted in  $f$  without us having to ask anything. Its value is 1.17865pt for the math italic  $f$  and 1.8919pt for the text italic  $f$ .<sup>44</sup> With the italic corrections included our bounding boxes are indeed more alike:  vs. .

Without the italic corrections<sup>45</sup> it is  vs. . I said that  $f$  included the italic correction automatically, but if we tell TEX to use the text italic in math, and typeset the alphabet, we obtain something exactly identical to typing the letters in text, hence without any italic correction:

<sup>42</sup>let's be honest, we are lying here about what exactly the first of these is bounding; this is explained later!

<sup>43</sup>we used simply `\mathit{f(x)}`.

<sup>44</sup>these values are for the Latin Modern fonts of course.

<sup>45</sup>here we give correctly the bounding box for the math italic  $f$ ... without its italic correction!

<i>abcdefghijklmnpqrstuvwxyz</i>	text italic in text
<i>abcdefghijklmnpqrstuvwxyz</i>	text italic in math
<i>abcdefghijklmnpqrstuvwxyz</i>	math italic in math
<i>abcdefghijklmnpqrstuvwxyz</i>	math italic in text

Where are our italic corrections gone? the last line was done with `\usefont{OML}{mlmm}{m}{it}` and the line before that using math mode is longer and confirms that italic corrections have been used for the math italic in math mode.

Turning to the *TeXbook* (and its Appendix G) we learn that in such circumstances, for the italic corrections to be put in from the font, one of its parameters, the interword space (aka `\fontdimen2`), should be zero. It is indeed zero for the math italic font, not for the text italic.

It is possible to make *TeX* believe it is. Doing so, we obtain in math mode with the text italic:

<i>abcdefghijklmnpqrstuvwxyz</i>	text italic in math
<i>abcdefghijklmnpqrstuvwxyz</i>	math italic in math

We saw that the italic correction was taken into account automatically (independently of the value of the interword space font parameter) in expressions such as `$f(x)$`. Another clever thing done by *TeX* is to use it for the placement of superscripts; the next examples systematically use the text italic in math. We see that  $f^j$  is very different from  $f^j\dots$  where the latter was coded with `\hbox{\itshape f}^j`. The inputs `\mathit{\hbox{\itshape f}\^{}j}` and `\mathit{f\^{}j}` give almost identical results:  $f^j$  vs.  $f^j$ . Close examination reveals that the horizontal spacing is exactly identical, however the exponent in the second case is a bit lower. Anyway, the point is that in the second case the italic correction for  $f$  was indeed used.

Subscripts are another matter: they do *not* take into account the italic correction. For example `\mathit{f_i}` gives the same horizontal positions as `\mathit{\hbox{\itshape f}_i}`:  $f_i$  vs.  $f_i$ . Printing them one on another gives  $f_i$  and reveals (use the zoom of your viewer!) that only the vertical placement was affected, not the horizontal placement.

We learn in Appendix G of the *TeXbook* that the italic correction is used for the horizontal shift of the superscript with respect to the position of the subscript:  $f_i^j$ , or, going back now to the standard math italics  $f_i^j$ . In the next paragraphs we use  $f_i^i$  for more accurate comparison of the positioning of the sub- and superscript.

If we try something like this: `{f\^{}i}_i^i` we obtain  $f_i^i$ . Our overlapping game with `\rlap{f_i^i}{f_i^i}` gives  $f_i^i$ . We discover that the effect of the explicit italic correction has mainly been to translate the subscript horizontally to be positioned exactly below the superscript!<sup>46</sup> We most probably do *not* want this to happen for our indices and exponents in math mode. So perhaps we can rejoice in how astute *TeX* has been in judiciously using the italic correction data, and there seems to be no need into fiddling with this algorithm which seems to work well even when applied to a text italic font. Actually we may even be of the opinion that the

---

<sup>46</sup>there are also some tiny vertical displacements of the sub- and superscripts.

text italic version  $f_i^i$  is a bit better-looking than the true math italic  $f_i^i \dots$

But wait... **mathastext** was initially developed to easily use in math mode the document text font not in its italic variant, but as is, so, usually, upright. And upright TeX fonts may also have italic correction data! And what I just said about the shift of the superscript with respect to the subscript apply equally well to such a font, if TeX has been told to use it. Let's try Latin Modern Upright for letters in math:  $\$f\_i^i\$$  now gives<sup>47</sup>  $f_i^i$ . We see the italic correction in action for the positioning of the superscript! Compare with  $\$\\mathrm{\\hbox{f}}\_i^i\$$ :  $f_i^i$ . Overlapping with  $\rlap{\\mathrm{f}_i^i} \\mathrm{\\hbox{f}}_i^i$  gives  $f_i^i$  and shows that the upright f has an italic correction which was used to shift the superscript to the right (and it is now in a slightly lower position). Let's now do  $\mathrm{{f}/}_i^i$ : this gives  $f_i^i$  and the subscript is shifted to the right, and is now on the same vertical axis as the superscript. There are also some slight vertical displacements,  $\rlap{\\mathrm{f}_i^i} \\mathrm{{f}/}_i^i$  gives  $f_i^i$ .

People will tell me crazy, but if we decide for using upright fonts in math, wouldn't it be satisfying to have the subscript and superscript positioned on the same vertical axis? the letter has no slant, why should the indices display one?

We end up in this strange situation that it is attractive to systematically incorporate the italic corrections after the upright Latin letters in math! But we don't want to do this inside the arguments to math alphabets as this would make impossible the formation of ligatures (the standard  $\mathrm{ff}$ ,  $\mathit{ff}$ ,  $\mathbf{ff}$ ,  $\mathsf{ff}$  all give ligatures ff, ff, ff, and ff and we would like to preserve this behavior).

Starting with version v1.2b, **mathastext** adds the italic correction automatically after each letter of the Latin alphabet in math mode, *except* when these letters are italic or slanted.<sup>48</sup>

These italic corrections are canceled inside the arguments to the math alphabet commands, to allow the formation of ligatures as is expected in the standard default TeX font set-up in math.

The feature-implementing commands `\MTicinmath`, `\MTnoicinmath`, `\MTicalsoinmathxx` are described in [subsubsection 2.2.2](#).

**Note:** from brief testing on 2012/12/28, XeTeX seems not to obey in math mode italic corrections for OpenType fonts. Hence the TeX placement algorithms for math mode described in this section do not work well when an OpenType (text) font is

<sup>47</sup>we just use  $\mathrm{f}_i^i$ .

<sup>48</sup>the situation is rather ironical! by the way, the warnings in [subsubsection 1.8.4](#) with  $x^?$  or similar are less of an issue here, because the letter is only followed by  $/$  and anyhow the whole is put by **mathastext** within group braces, so no surprises with  $x^y$  or  $\mathbin{x}$ . Nevertheless it is still true that (in math mode only) the letters a-z, A-Z, expand to composite objects, something which could surprise other packages. The command `\MTmathstandardletters` cancels this mechanism.

used for the letters in math mode, and the document is compiled with the *X<sub>E</sub>T<sub>E</sub>X* engine. On the other hand *L<sub>A</sub>T<sub>E</sub>X* seems to implement the italic corrections when using OpenType fonts, but only with italic fonts (as far as I could tell). Try the following (which will use the OpenType Latin Modern font) on a recent *T<sub>E</sub>X* installation and compare the output of both engines:

```
\documentclass{article}
\usepackage{fontspec}
\begin{document}
\Huge
$\mathit{f_i^i} \par \mathrm{f_i^i}$
\end{document}
```

Comment out the `fontspec` line and use *pdfL<sub>A</sub>T<sub>E</sub>X*. All three outputs are different on my *T<sub>E</sub>X* installation. *X<sub>E</sub>T<sub>E</sub>X* does not have the italic corrections. *L<sub>A</sub>T<sub>E</sub>X* does, but only for the italic font. *pdfL<sub>A</sub>T<sub>E</sub>X* has them for both the italic and the upright font.<sup>49</sup>

### 1.8.3 Extra glue after `\exists`, `\forall`, and before the prime glyph

`\MTforallskip`, `\MTexistsskip`, and `\MTprimeskip` are three commands with each a mandatory argument like for example `3mu plus 1mu minus 1mu` or just `2.5mu`. They are especially useful when using an upright font in math mode. The `mu` is a unit length used in math mode ('math unit', 1/18th of the 'quad' value of the symbol font in the current style). Its value is relative to the current math style. Its use is **mandatory** in the commands described here.

- compare  $\forall B$  with  $\forall B$ , typeset after `\MTforallskip{2mu}`,
- compare  $\exists N$  with  $\exists N$ , typeset after `\MTexistsskip{2mu}`,
- and finally compare  $f'$  with  $f'$ , typeset after `\MTprimeskip{2mu}`.

These three commands may be used throughout the document, or also in the preamble, in which case the declared math versions will record the then current values of the skips. `mathastext` applies the following (small) default skips: `0.6667mu` for the skip after  $\forall$ , `1mu` for the skip after  $\exists$ , and `0.5mu` for the skip before the prime. The examples above become  $\forall B$ ,  $\exists N$  and  $f'$ .<sup>50</sup>

With the `italic` option the defaults are set to zero. Indeed  $\forall B$ ,  $\exists N$  and  $f'$  look fine without additional skips. If the document decides then to declare in the preamble a math version with an upright font it is thus recommended to use the commands in the preamble before the `\Mathastext[<version_name>]` (or `\MTDeclareVersion`) command defining the version. They will be remembered when this

---

<sup>49</sup>2016/11/04: the situation hasn't changed, at least on current TL2016.

2022/10/29: no change with current TL2022.

<sup>50</sup>the derivative glyph from the `txfonts` math symbols adapts itself better to an upright letter, no skip seems to be needed then.

math version is entered in the document. The commands may also be used directly in the document body.

Under the `subdued` option, the *normal* math version (at the start of the document body, or after `\MTversion{normal}`) and the *bold* math version (either at the start of the document body after `\boldmath`, or after `\MTversion{bold}`) do not have any extra skip inserted (even one of zero width) after  $\forall$ ,  $\exists$ , or before the  $'$ .

#### 1.8.4 Extended scope of the math alphabets commands

Ever since the initial version of the package, some characters usually unaffected by the math alphabet commands `\mathbf`, `\mathtt`, `\mathsf...` are declared to be of ‘variable family type’, in order for them to obey these commands: for example the hash sign `#` gives `#` if input as `$\mathbf{\#}$` (`mathastext`, especially in its beginnings, wanted as many characters as possible to be picked up from the text font and to behave similarly to letters and digits).

So it was especially frustrating that mathematical characters such as `+`, or `<`, or `]` could not be declared of ‘variable family’ (in addition to being picked up in the text font) as this would, for reasons of the inner workings of  $\TeX$ , not be compatible with the automatically inserted spaces around them.

A revolutionary ;-) novelty is introduced with version 1.2 of the package: (1.2)

1. the pre-declared or user-declared (using the `amsmath \DeclareMathOperator` or equivalent) operator names obey the math alphabet commands,<sup>51</sup>
2. as well as all non alphabetical characters treated by `mathastext`.

The non-letters handled by `mathastext` (if not disabled by options) fall into two groups:

- Those to which  $\TeX$  associates some specific spacings:

`! ? , : ; + - = ( ) [ ] < > { } *`

We call them the “hard” ones.

- Those for which  $\TeX$  uses so-called ordinary spacings:

`. / | \ # $ % &`

We call them the “easy” ones.

The “easy” non-letters are handled *easily* by `mathastext`, simply by declaring them to be of “variable family type”. This will be done automatically.<sup>52</sup>

The “hard” non-letters require a more complex approach using a concept called “mathematical activation”. For reasons explained next, this is not done automati-

---

<sup>51</sup>contrarily to the next feature, this one is not likely to create incompatibilities with other packages, so it is activated by default.

<sup>52</sup>`# $ % &` obey the math alphabets since the initial version of `mathastext`; the dot `.`, the slash `/`, the vertical bar `|` and the backslash `\` do not have specific spacings inserted by  $\TeX$  around them, and the procedure is then activated by default since 1.2 for these characters as they are ‘easy non-letters’. But for `\mid` and `\setminus` which are `|` and `\` with special spacing (of type `\mathrel` and `\mathbin` resp.) the activation requires `\MTnonlettersobeymathxx`.

ically and requires the user to employ the command `\MTnonlettersobeymathxx` (or, for the specific case of the asterisk the option `asterisk`).

It is a fundamental feature that the spacing added by TeX before and after each such `mathastext`-ified non-letter is in no way modified.

Let us compare, for example, the new behavior of `\mathtt` and `\mathbf` when `\MTnonlettersobeymathxx` has been used

*new* :  $(\sin(n!) < \cos(m - p)?) \quad [\sin(x + y) = \cos(z - t)]$

with the traditional default behavior one observes without `mathastext` or in `subdued` normal or bold math version:

*standard* :  $(\sin(n!) < \cos(m - p)?) \quad [\sin(x + y) = \cos(z - t)]$

The commands for *deactivation* are:

`\MTmathoperatorsdonotobeymathxx`,  
`\MTeasydonotobeymathxx`,  
`\MTnonlettersdonotobeymathxx`,

and those for *activation*:

`\MTmathoperatorsobeymathxx` (done by default),  
`\MTeasydonotobeymathxx` (done by default),

`\MTnonlettersobeymathxx` is *not* done by default (see explanations why in the shaded box next) and applies to the “hard” non-letters mentioned above and also to `\mid` and `\setminus`. Furthermore, it applies to the braces `{}` only if `\MTexplicitbracesobeymathxx` is also used.

**Important:** the package does not execute on its own `\MTnonlettersobeymathxx`. The reason is that the mechanism in effect replaces the original “hard” characters such as ?, [, < by (in math mode only) a more complex structure, which ceases looking to TeX as only one token, and as a consequence `$x^?$, $R^+$` or `$\mathopen{<}A\mathclose{>}$` raise an error, the workaround being to employ additional braces: `$x^{?}$`, `$R^{+}$` and `$\mathopen{<}A\mathclose{>}$`.

Similarly `$R^*$` does not work anymore under option `asterisk`, the user is supposed to know that with this option `$R^{*}$` is the mark-up to use.

Thus, if one adds

`\usepackage{mathastext}\MTnonlettersobeymathxx`

to a pre-existing document, it is needed to check if the mark-up satisfies to the above guidelines. For this reason the mechanism is by default not activated and the user has to execute:

### `\MTnonlettersobeymathxx`

This can be done in the preamble and will trigger actual modifications only at time of `\begin{document}`.

Some TeXnical notes:<sup>53</sup>

- The asterisk \* is associated with its own option `asterisk`, because independently of the matter of its behavior in the scope of math alphabets commands, its handling by `mathastext` (via the `\MTlowerast` associated configuration) always requires it to be made mathematically active and to expand to a more complex structure. So once this option is received by the package, it goes full steam and also adds by default the responsiveness to math alphabet commands (in non-`subdued` math versions).
- The legacy situation which is a bit late to change is that the responsiveness of the asterisk to math alphabets being on by default under option `asterisk`, it was decided that this responsiveness would be turned off by `\MTeasy nonletters do not obey mathxx` and back on by `\MTeasy nonletters obey mathxx`, although the \* is part of the “hard” non-letters. One can use `\MTnormal asterisk` to stop the \* to obey math alphabet commands, but it also cancels the `\MTlowerast` mechanism.
- At 1.4 “easy” non-letters found out to be (at `\begin{document}`) or with `\MTversion` except for `subdued normal` or `bold`) mathematically active characters will not get overridden by `mathastext`. This applies for example with the dot “.” under `babel` with Spanish language. Its special behavior to transform into a comma “,” if before a digit is now kept. As an amusing side note, if `\MTnonlettersobeymathxx` is used, this comma does obey math alphabet commands.
- An “easy” non-letter which (at `\begin{document}`) or with `\MTversion` except for `subdued normal` or `bold`) is catcode active will still be set by `mathastext` to be of “variable family type”, if it is not mathematically active. The catcode status is not checked nor modified, only the mathcode as per previous item. Now whether the `mathastext`-ification has any effect depends on how the user has configured the catcode active character to behave if in math mode.
- When `mathastext` wants to employ mathematical activation for a non-letter character among the “hard” cases (inclusive of the asterisk), which is done at `\begin{document}` if not `subdued` or with every `\MTversion` except for `subdued normal` or `bold`, it first checks if this character is currently catcode active. If this is the case, it then checks if the character is a `babel` shorthand. If yes, it then hooks into `babel` internals to modify the way this shorthand acts in math mode, so that now the character will respond to math alphabet commands. If however the catcode active character does not appear to be a `babel` shorthand, then `mathastext` does not do anything at all (beyond its general business at package loading time to set-up the font used for the non-active token). In relation to this context `mathastext` should always be loaded *after* `babel`. And also *after* the `amsmath` package.
- The braces `\{` and `\}` remain unresponsive to the alphabet changing commands even after `\MTnonlettersobeymathxx`. The user must employ for this

### `\MTexplicitbracesobeymathxx`

This has the disadvantage that `\{` and `\}` become then unusable as variable-size delimiters: `\big\{` or `\big\}` create errors and one must make use of `\big\lbrace` and `\big\rbrcase`. But one can now enjoy `\{a, a > b\}`, `\{a, a > b\}`, `\{a, a > b\}`, or even `\{a, a > b\}`.<sup>54</sup>

<sup>53</sup>The complete truth is only to be found in source code. Here are some extra details:

The dollar sign and the curly braces are not tested for mathematical or catcode activation.

changed: The \* is tested as are the “hard” non-letters, except under option `everymath`. On the other hand `\last` will be modified independently of what is decided for \*. Comprene qui pourra.

<sup>54</sup>This last example uses the `\mathnormal bold` additional alphabet defined by `mathastext`.

<sup>55</sup>Let me recall that braces will anyhow not be handled at all by `mathastext` if the document font

- Even with `\MTnonlettersobeymathxx`, the parentheses-like symbols (, ), [ , ], < and > and the slashes /, \, if used as left/right delimiters (i.e. with `\left/\right`) will not respond to math alphabet commands. This is mainly explained by the fact that the text font will not contain suitable glyphs, hence no attempt was made by `mathastext` to make the delimiters pick up their glyphs there.  
But `mathastext` does try to pick up most of the ‘small variants’ of the delimiters from the text font: `\left<\right>` gives  $\langle x \rangle$  but `\left<\right>` gives  $\langle b \rangle$ . Notice that this differs from standard L<sup>A</sup>T<sub>E</sub>X for which `\left<\right>` gives  $\langle x \rangle$ . As it is perhaps a bit strange to have  $\langle x \rangle$  and  $\langle y \rangle$  not use the same bracketing glyphs, there is an option `nosmalldelims`: with this option the small-sized variants of the delimiters are not modified by `mathastext` (option `nosmalldelims` has the side effect that, for the non-delimiter uses of \{, \} to be `mathastext`-ified it is necessary to issue `\MTnonlettersobeymathxx` and `\MTexplicitbracesobeymathxx`.)
- At any rate, as said above, whether ‘small’ or not, delimiters will remain unresponsive to math alphabet commands, due to technical aspects of T<sub>E</sub>X, and the way `mathastext` handles these things. Examples:
  - `\mathbf{\langle a,b \rangle}` gives  $\langle a, b \rangle$ : no use of `\left/\right`, hence brackets do obey the math alphabets — as we issued `\MTnonlettersobeymathxx` a bit earlier,
  - `\mathbf{\langle\left< a,b\right>}` gives  $\langle a, b \rangle$ : delimiters used with `\left/\right` will not obey the math alphabets,
  - `\mathbf{\langle\mathopen{\langle} a,b \mathclose{\rangle}\rangle}` gives  $\langle a, b \rangle$ : no `\left/\right`, so the brackets do obey the math alphabets due to `\MTnonlettersobeymathxx`.
  - to compare, the L<sup>A</sup>T<sub>E</sub>X standard for `\mathbf{\langle\mathopen{\langle} a,b\mathclose{\rangle}\rangle}` is to produce  $\langle a, b \rangle$ : neither brackets nor the comma are responding to `\mathbf`.

### 1.8.5 Hacking letters (and even digits) for special tasks

For some ascii characters, i.e. the “hard” non-letters considered in the previous section, and even more spectacularly for all ascii letters, `mathastext` achieves the capabilities described in earlier sections via a T<sub>E</sub>Xnique known as “mathematically active characters”. For letters this is turned on by default, but for the non-letter characters it is the command `\MTnonlettersobeymathxx` which triggers this mathematical activation.

It is possible for daring L<sup>A</sup>T<sub>E</sub>X users to hook into this architecture. Release 1.4 has made this especially easy regarding ascii letters (and even for digits if using the package option `activedigits`).

Except if told otherwise, `mathastext` will make all Latin ascii letters mathematically active, and when T<sub>E</sub>X encounters e.g. ‘e’ in math mode it replaces it with the macro having name `\MTcommandlettere` (mind the ending `e`). Its default definition inserts `optional extra skips` and/or an `italic correction`.

You can redefine this `\MTcommandlettere`, or any `\MTcommandletter{ascii-letter}`, to achieve (globally or locally) custom goals.<sup>56</sup> Attention, this redefinition should not use ‘e’ itself as a “naked” character to typeset in math mode, else an infinite loop will arise at time of use. To access a symbol equivalent to the “naked” ‘e’, use

---

encoding is OT1, except under option `alldelims`.

changed: <sup>56</sup>Prior to 1.4, there was no equivalent to `\MTcommandletter{letter}`. An internal macro `\mst@{letter}` stood for what is denoted now `\MTmathcharletter{letter}`, but required a `\protected` if redefined as it was submitted to an `\edef` during processing. (1.4)

`\MTmathcharlettere` (again mind the ending `e`). For example:

```
\renewcommand\MTcommandlettere{\mathsf{\MTmathcharlettere}}% not \mathsf{e}!
```

In this case we could do the simpler approach with `\textsf`, which works as it will then typeset the `e` in text mode, not math mode.

```
\renewcommand\MTcommandlettere{\textsf{e}}% not \mathsf{e}!
```

This gives a priori the same result in our `mathastext` context, which picks the font for `\mathsf` from the one used by `\textsf`, assuming here default configuration in the preamble following the loading of `mathastext`.<sup>57</sup>

It is recommended in general to add an extra pair of braces to avoid problems when used with `_` and `^`. Let's give an other example and demonstrate its output:

```
\[
\renewcommand\MTcommandlettere{{\mathcolor{blue}{\mathsf{\MTmathcharlettere}}}}%
abcde^efgh
\]
```

`abcdeefgh`

As this document is in `subdued` mode, we had, to show the effect, to switch temporarily to some math version activating `mathastext`, and we used here a `times` math version with Times and Helvetica clones.


If you redefine `\MTcommandlettere` as described in this section the optional extra math skips added before or after via `\MTsetmathskips` will be lost, as well as the automatic italic correction `\/` added by `mathastext` for an upright font, and it is up to the redefinition of `\MTcommandlettere` to do the job.

The explanations above apply to any (ascii) Latin letters `<ascii-letter>` with associed macros `\MTcommandletter<ascii-letter>` and “naked” symbol command `\MTmathcharletter<ascii-letter>`.

With option `activedigits` you can even extend the game to digits. The “raw” digit symbol is kept as a math symbol control sequence `\MTmathchardigit<y>` where `<y>` stands for the Roman version of the digit: empty for 0, then `i`, `ii`, etc... until `ix`. The macro to redefine for special effect is `\MTcommanddigit<y>`. Example:

```
\[
\renewcommand\MTcommanddigit{{\MTmathchardigit^{\mathcolor{blue}{1}}%
_{\mathcolor{red}{2}}}}%
\renewcommand\MTcommanddigiti{{\boxed{\mathbf{\MTmathchardigiti}}}}%
0^0_0
\]
```

<sup>57</sup>This example simply reassigned `e` to another font, and one could use also the `\DeclarerMathSymbol` for this. But few `\LaTeX` users are familiar with its interface, and such an approach could cost adding an extra math symbol font, depending on what one wants to do. Besides `\DeclarerMathSymbol` is a preamble-only command, which limits considerably its usability, forcing basically the change to apply to the whole document. Using the `mathastext` interface via mathematically active characters opens up the possibility of arbitrary replacements, of local scope in the document body.



(\boxed is from `amsmath`) Let's hope you find better usage... recall that you can't use digit 0 in its redefinition but must use \MTcommanddigit. But you can of course use other digits... except if their definitions use the digit 0 rather than the non-active symbol control sequence \MTmathchardigit.

See also \MTmathactiveletters and \MTmathactivedigits.

## 2 Package commands

### 2.1 Commands for regular usage

#### 2.1.1 Preamble-only commands

These commands mainly facilitate the definition of math versions, in a `mathastext` extended sense. It is not necessary to use them to activate the package basic functionalities, as loading `mathastext` is enough (except with the `subdued` option).

- \Mathastext (or \mathastext) reinitializes `mathastext`: it sets the fonts used in math mode (in versions `normal` and `bold`) for letters, digits and a few ascii symbols to the *current* defaults of encoding, family, series and shape.<sup>58</sup> Both the normal and bold math version are modified by this action of \Mathastext.
- \Mathastext[*version\_name*] rather than redefining the fonts for math mode, \Mathastext declares a new *math version*, and it is this math version which will use the then current text font in math mode.<sup>59</sup>
- \Mathastext[*version\_name*][*parent\_name*] declares *version\_name* and configures it to inherit from *parent\_name* all which is not under the scope of `mathastext`, such as large symbols. The main use will be with `[bold]` in order for the symbols and large symbols to be typeset as in the `bold` math version. For example, this document has in its preamble:

```
\usepackage{newcent}% this package makes New Century the roman font
\Mathastext[newcent]% this math version will use New Century
\MTseries{b}          % next \Mathastext will use a bold font
\Mathastext[boldnewcent][bold] % large symbols, etc, will be bold too
```

We can check that it does work:

$$\text{\MTversion{newcent}: } abcde \oint \bigvee \bigcup \otimes \oplus$$

<sup>58</sup>\Mathastext updates also the font and shapes for the Greek letters (`LGRgreek` option), and the skips to be inserted after the symbols  $\forall$  and  $\exists$ , see *infra*.

<sup>59</sup>The allowed version names are as for the L<sup>A</sup>T<sub>E</sub>X \DeclareMathVersion macro. *Do not use \Mathastext[foo] with foo equal to “normal” or “bold”;* this is already taken care of by the initial loading of the package or a later command \Mathastext without any optional argument. And it will be rejected.

`\MTversion{boldnewcent}: abcde  $\oint \bigvee \biguplus \bigotimes \bigoplus$`

Naturally, for this one needs an initial math font setup with some nice bold fonts also for large symbols. This is the case with the excellent `txfonts` package of Young RYU. As the present document must use many fonts and declares many math alphabets, we did not load the full package and fonts but only the `largesymbols`:

```
\DeclareSymbolFont{largesymbols}{OMX}{txex}{m}{n}
\SetSymbolFont{largesymbols}{bold}{OMX}{txex}{bx}{n}
\DeclareFontSubstitution{OMX}{txex}{m}{n}
```

- `\MTencoding{<enc>}, \MTfamily{<fam>}, \MTseries{<ser>}, \MTshape{<sh>}, and \MTlettershape{<sh>}.`<sup>60</sup> For example valid respective arguments are, respectively,  $\langle T1 \rangle$ ,  $\langle phv \rangle$ ,  $\langle m \rangle$ ,  $\langle n \rangle$ , and  $\langle it \rangle$ : this is the Helvetica font in T1-encoding, regular (medium) series, upright shape, and the letters will be in italic shape. Once used their effect applies to all succeeding calls to `\Mathastext`, and can only be undone by using them again with other settings, again followed by a call to `\Mathastext`.

NOTE: *only* if `\Mathastext` is used next (possibly with a version name as optional argument) will these commands have any real effect.

- `\MTWillUse[<ltsh>]{<enc>}{<fam>}{<ser>}{<sh>}` tells `mathastext` to use the font with the specified encoding, family, series, and shape for the letters and digits (and all other afflicted characters) in math mode. The optional argument  $\langle ltsh \rangle$  specifies a shape for the letters, for example `\itdefault`, or directly  $\langle it \rangle$  or  $\langle sc \rangle$ .
- `\MTDeclareVersion[<ltsh>]{<name>}{<enc>}{<fam>}{<ser>}{<sh>} [<other_version>]`: declares that the document will have access to the font with the specified characteristics, under the math version name  $\langle name \rangle$ . For example:

```
\MTDeclareVersion[sc]{palatino}{T1}{pp1}{b}{s1}
```

declares under the name `palatino` a version where mathematics will be typeset using the Palatino font in T1-encoding, bold, slanted, and the letters will in fact be in caps and small caps (and bold).<sup>61</sup> When the initial optional argument is absent, and `mathastext` was loaded with the `italic` option, then the default letter shape will be `it`,<sup>62</sup> else letters will have the same shape as used for digits and operator-names.

Another optional argument may be used as last argument. Similarly as its use with `\Mathastext` this makes the declared math version inherit, for things not modified by `mathastext` like large symbols, the font set up of the math version whose name was passed as optional argument (typical use will be with `[bold]`).

---

<sup>60</sup>These commands exist also with long names: `\Mathastextencoding`, etc... The same applies to the other commands mentioned in this section.

<sup>61</sup>I do not especially recommend to use this in real life!

<sup>62</sup>more precisely, the shape is the latest value passed in one of the previously used package commands to specify the shape of letters, or the `\itdefault` of the time of loading the package.

- `\MTboldvariant{<var>}`: when used before `\Mathastext`, specifies which bold (`b`, `sb`, `bx`, ...) to be used by `\mathbf` (and `\boldmath`). Default is the `\bfdefault` at the time of loading `mathastext`. When used before the declaration of a version, decides the way `\mathbf` will act in this version.
- `\MTEulerScale{<factor>}`: scales the Euler font by `<factor>`.
- `\MTSymbolScale{<factor>}`: scales the Symbol font by `<factor>`.
- `\MTitgreek`, `\MTupgreek`, `\MTitGreek`, `\MTupGreek`: these commands are active in case the `LGRgreek` option was used; they act as the options of the similar names `itgreek`, `upgreek`, `itGreek`, `upGreek`, but only for the Greek letters in the versions yet to be defined. Their effect become recorded only when the version is declared via `\Mathastext` or `\MTDeclareVersion`.
- `\MTgreekfont{<fontfamily>}`: a command with a mandatory argument which specifies the font family for Greek letters in all `mathastext` math versions declared afterwards via `\Mathastext` or `\MTDeclareVersion`. Only effective if `LGRgreek` (or `LGRgreek+`) or `selfGreek` option was passed to the package.

Check the `LGRgreek` documentation for some relevant information.

### 2.1.2 Commands for body or math

- `\MTversion[<nametext>]{<namemath>}`, `\MTversion*{<namemath>}`, also known as `\Mathastextversion` (and as `\MTVersion`, and `\mathastextversion`):
  - the non-starred version changes *both* the document text fonts and the math fonts (for those characters treated by `mathastext`): the mandatory argument is the math version to be used for math; the optional argument is the name of (another) `mathastext`-declared math version, the font which was chosen during its declaration will be set as document text font (and `\familydefault` etc... also are redefined). In the absence of the optional argument, the mandatory one is used. The versions *must* be either `normal`, or `bold`, or previously declared ones via `\Mathastext` or `\MTDeclareVersion`.
  - the starred variant does the math set-up, but changes *nothing* to the text fonts (see [subsection 1.6](#) for a description of the math set-up, which summarizes what is done additionally to only using L<sup>A</sup>T<sub>E</sub>X's `\mathversion`). (1.3c)

`\MTversion[<nametext>]{<namemath>}` does `\MTeverymathdefault` (except for `\MTversion{normal}` and `\MTversion{bold}` under package option `subdued`), which in particular activates the insertion of skips around letters specified by `\MTsetmathskips` and also, if the font used is not oblique the insertion of italic corrections (for better positioning of subscripts; see the discussion in [subsubsection 1.8.2](#)). Under the `frenchmath` option the package checks separately the letter shape for lowercase and uppercase.

`\MTversion` also does `\MTexistsdoesskip`, `\MTforalldoesskip`, and also `\MTprimedoesskip`, `\MTmathoperatorsobeymathxxx`, except under the `subdued` option for *normal* and *bold*, in which case it does the opposite actions.

- `\hbar`: this macro is by default redefined (in a way compatible with the `italic` option) combining the `h` letter and the `~` accent from the `mathastext` font. Note that `\mathrm{\hbar}` and `\mathbf{\hbar}` will work and that `\hbar` does scale in subscripts and exponents. Since 1.3u, this is a priori compatible with all 8bits text font encodings supporting the `\=` text accent in the LaTeX way.<sup>63</sup> <sup>64</sup> (1.3u)
- `\fouriervec`: this is a `\vec` accent taken from the Fourier font; the `fourier` package need not be loaded. Active only if option `fouriervec`.
- `\pmvec`: this provides a poor man `\vec` accent command, for upright letters. It uses the right arrow. Does not change size in subscripts and exponents.

- new description:**
- `\Mathnormal`, `\Mathrm`, `\Mathbf`, `\Mathit`, `\Mathsf`, `\Mathtt`: they use the `mathastext`-ified fonts. By default, `\mathnormal`, `\mathrm`, `\mathbf`, `\mathit`, `\mathsf`, `\mathtt` are redefined to map to these new commands using the `mathastext` fonts. The option `defaultalphabets` tells to keep them with their original meanings. Alternatively the original commands can be saved under other names before loading `mathastext`: the underlying architecture is not deleted by the package, and aliases defined before loading `mathastext` will work as expected. (1.3za)
  - `\mathnormalbold`: a bold version of `\mathnormal`, i.e. picks up the math alphabet used for ascii letters as mathematical variables, but in a bold weight. When the package typesets such letters in the same shape as for operator names (i.e. neither `italic` option nor the `\MTlettershape` command have been used) the output is as the one of `\mathbf`.

This command is also made available under `subdued` option in the “normal” and “bold” math versions, as L<sup>A</sup>T<sub>E</sub>X does not define it a priori, contrarily to `\mathbf` and other math alphabet commands.

- `\mathgreekup`: math alphabet, only available under `LGRgreek` (or `LGRgreeks`) option, which gives access to ‘upright’ Greek letters (picked up from a font available in LGR-encoding). Note that the package also defines `\alphaup`, ..., `\piup`, ... mathematical character tokens, see [subsubsection 1.7.3](#). What “up” shape really means may be math version dependent. It is configurable in the preamble via re-defining `\MTgreekupdefault` and then declaring the math version via `\Mathastext` (with optional argument if for a math version other than the “normal” one), or `\MTDeclareVersion`. The font used is also math version dependent: it is the one which was similarly configured via usage of `\MTgreekfont` prior to the `\Mathastext` or `\MTDeclareVersion` step. In absence of any such configuration

<sup>63</sup>The horizontal skips for letter `h` from `\MTsetmathskips` are ignored for `\hbar`. (1.3u)

<sup>64</sup>The `\hbar` redefinition is canceled in normal and bold math versions under the `subdued` option. (1.3u)

in the preamble, it will be (in all math versions) the family default at time of loading the package (which thus has then to be available in LGR encoding; it is not a problem if the family default has no LGR support as long as suitable usage of `\MTgreekfont` later on configures a suitable font).

Also `\mathgreekupbold`.

(1.3za)

These math alphabets are also available under `subdued` option in the “normal” and “bold” math versions, as L<sup>A</sup>T<sub>E</sub>X does not (a priori) define analog ones, so `mathastext` has no reason not to leave them live. Note though that `\mathgreekup{\pi}` will work only if the original `\pi` is of “variable family type” which is not the case except if some math package handling Greek was used, but then why load `mathastext` with option `LGRgreek`?

But you can use `\mathgreekup{p}` as the slot number of p in the L<sup>A</sup>T<sub>E</sub>X font for mathematical letters is the same as the slot number of  $\pi$  in LGR encoding.

Or, use rather `\piup` because it is not undefined by `mathastext` in `subdued` normal mode, as L<sup>A</sup>T<sub>E</sub>X has no a priori definition for it. Or use (but why?) `\mathgreekup{\piit}`.

The LGR font family used will be the latest one configured by `\MTgreekfont` usage followed by `\Mathastext` (*without* optional argument) in the preamble which is what is needed to modify the non-subdued aspects of subdued “normal” math; if no such configuration was done, the font family will be the family default found at time of loading the package.

Worse:  $\Delta$  is per L<sup>A</sup>T<sub>E</sub>X default of variable family type but its slot number in its assigned font is not at all the one of the LGR encoding, so `\mathgreekupbold{\Delta}` will give some unrelated glyph. This is because `mathastext` restores the pristine `\Delta` in `subdued` normal mode to its original meaning. But it keeps its own defined `\Deltaup` and `\Deltait`, so you can use `\mathgreekupbold{\Deltaup}` for example. Or `\mathgreekupbold{D}` as the mathematical letter D slot number in L<sup>A</sup>T<sub>E</sub>X is also the one of  $\Delta$  in LGR encoding.

I am sorry for such lengthy explanations, but this is to comment on why `mathastext` keeps also in `subdued` normal math some of its Greek related functionality, if option `LGRgreek` was used. Most `mathastext` users will not use the `subdued` option anyhow.

- `\mathgreekit`: math alphabet, only available under `LGRgreek` (or `LGRgreeks`) option, which gives access to ‘italic’ Greek letters (picked up from a font available in LGR-encoding). The actual shape is configurable via re-defining `\MTgreekit-default` and then redeclaring the math version via `\Mathastext` (with optional argument if for a math version other than the “normal” one), or `\MTDeclare-Version`.

Also `\mathgreekitbold`.

(1.3za)

See the discussion of `\mathgreekup` for some T<sub>E</sub>X hacker level information on what happens with `subdued` option in the “normal” (or “bold”) math version.

- `\inodot`, `\jnodot`: the corresponding glyphs in the `mathastext`-ified font for use in math mode. By default, `\imath` and `\jmath` are redefined to use them. Since 1.3t, these macros obey the `subdued` regime.
- `\MathEuler`, `\MathEulerBold`: math alphabets to access all the glyphs of the Euler font, if option `eulergreek` (or `eulerdigits`) was passed to the package.
- `\MathPSymbol`: math alphabet to access the Symbol font.

- when one of the options `symbolgreek`, `eulergreek`, or `selfGreek` is passed to the package the capital Greek letters which look like their Latin counterparts acquire names: `\Digamma`, `\Alpha`, `\Beta`, `\Epsilon`, `\Zeta`, `\Eta`, `\Iota`, `\Kappa`, `\Mu`, `\Nu`, `\Omicron`, `\Rho`, `\Tau`, `\Chi` (no `\Digamma` for Symbol). Also an `\omicron` control sequence is provided.
- LGR Greek and ‘var’-letters: only the `\varsigma` is available in this encoding, so using for example `\varphi` will load the previous default math font. It might thus be suitable when recompiling already written L<sup>A</sup>T<sub>E</sub>X sources to add to the preamble `\let\varphi=\phi`, `\let\varepsilon=\epsilon`, etc..., in case only the ‘variant’ form of the letter was used in the documents.
- Miscellaneous mathematical symbols from the postscript Symbol font are made available (or replaced) by option `symbolmisc`.<sup>65</sup> They are `\prod`  $\prod$  `\sum`  $\sum$  `\implies`  $\Rightarrow$  `\impliesby`  $\Leftarrow$  `\iff`  $\Leftrightarrow$  `\shortiff`  $\leftrightarrow$  `\to`  $\rightarrow$  `\longto`  $\rightarrowtail$  `\mapsto`  $\mapsto$  `\longmapsto`  $\rightarrowtail$  `\aleph`  $\aleph$  `\infty`  $\infty$  `\emptyset`  $\emptyset$  `\surd`  $\sqrt$  `\nabla`  $\nabla$  `\angle`  $\angle$  `\forall`  $\forall$  `\exists`  $\exists$  `\neg`  $\neg$  `\clubsuit`  $\clubsuit$  `\diamondsuit`  $\diamondsuit$  `\heartsuit`  $\heartsuit$  `\spadesuit`  $\spadesuit$  `\smallint`  $\int$  `\wedge`  $\wedge$  `\vee`  $\vee$  `\cap`  $\cap$  `\cup`  $\cup$  `\bullet`  $\bullet$  `\div`  $\div$  `\otimes`  $\otimes$  `\oplus`  $\oplus$  `\pm`  $\pm$  `\ast`  $\ast$  `\times`  $\times$  `\propto`  $\propto$  `\mid`  $\mid$  `\leq`  $\leq$  `\geq`  $\geq$  `\approx`  $\approx$  `\supset`  $\supset$  `\subset`  $\subset$  `\supseteq`  $\supseteq$  `\subseteq`  $\subseteq$  `\in`  $\in$  `\sim`  $\sim$  `\cong`  $\cong$  `\perp`  $\perp$  `\equiv`  $\equiv$  `\notin`  $\notin$  `\langle`  $\langle$  `\rangle`  $\rangle$ . And a `\DotTriangle`  $\therefore$  is made available by option `symbolre` (which overwrites `\Re` and `\Im`:  $\Re, \Im$ ). The `\infty` and `\propto` have these names to leave up to the user the choice to replace (or no) the original (larger) `\infty` and `\propto`.

Regarding the `\prod` and `\sum` commands: they will use the Symbol glyphs  $\prod$   $\sum$  in inline math, and in display math the Computer Modern ones (or whatever is set up by other packages; here we have the symbols from `txfonts`):

$$\prod \sum$$

The package provides `\prodpsy` and `\sumpsy`: if one really wants in all situations the Symbol glyphs, one can do `\let\prod\prodpsy` and `\let\sum\sumpsy`. Also `\MToriginalprod` and `\MToriginalsum` will refer to the `\prod` and `\sum` before redefinition by the package: this is to allow constructs such as `$\displaystyle\MToriginalprod$` or `\textstyle\MToriginalprod`, because they would not work with the `\prod` and `\sum` as re-defined by the package.

## 2.2 Commands for expert usage

A few preliminary comments, mainly destined to advanced users aware of some T<sub>E</sub>X innards (more extensive explanations are to be found in the code comments).

<sup>65</sup>option `asterisk` is also required to treat the `*`. Recall from [subsubsection 1.8.4](#) that the asterisk in math mode (also when using the control sequence `\ast`) appears then to T<sub>E</sub>X to be a composite object.

The timing for actions of `mathastext` falls into three cases:

1. things done by `mathastext` itself during its loading (some are delayed to `\begin{document}`),
2. things done as the result of user commands, either in the preamble or in the body of the document, (but note that some commands if used in preamble have a real effect only at the time of `\begin{document}`),
3. things done everytime math mode is entered.

**changed:** At 1.4 a very significant change took place: the last category, the one of things done everytime math mode is entered, has become *empty*.<sup>66</sup> (1.4)

The `everymath` option added at 1.4 re-establishes the legacy behavior. Except for ascii letters: they will not even then be made mathematically active at each entrance in to math mode, but only once at time of package loading (if not `subdued`) and also when using `\MTversion` (for non-`subdued` math versions).

Under `everymath` option some commands described here as being usable everywhere have in fact an effect only if used externally of math mode. The documentation is only accurate for the default 1.4 configuration, not for the legacy one as re-enacted by `everymath`.

### 2.2.1 Expert commands which are preamble-only

- `\MTgreekupdefault`: a command with no argument whose expansion specifies, under `LGRgreek` regime, the shape for the ‘up’ Greek control sequences (and for the no-postfix Greek control sequences under `upgreek` option) in all `mathastext` math versions declared *afterwards* via `\Mathastext` or `\MTDeclareVersion`. The a priori default for this shape is ‘n’ (without the quotes). See [subsubsection 1.7.3](#). (1.3y)

This command can also be defined *prior* to loading the package, as the package itself only does:

```
\providecommand*\MTgreekupdefault{n}
```

- `\MTgreekitdefault`: a command with no argument whose expansion specifies, under `LGRgreek` regime, the shape for the ‘it’ Greek control sequences (and for the no-postfix Greek control sequences under `itgreek` option) in all `mathastext` math versions declared *afterwards* via `\Mathastext` or `\MTDeclareVersion`. The a priori default for this shape is ‘it’ (without the quotes). See [subsubsection 1.7.3](#). (1.3y)

This command can also be defined *prior* to loading the package, as the package itself only does:

```
\providecommand*\MTgreekitdefault{it}
```

<sup>66</sup>There ia always an exception to a good rule, and here it is: only with Lual<sup>A</sup>T<sub>E</sub>X engine, a certain command is executed as part of `\everymath`. For details see `\MTfixfonts`.

## 2.2.2 Expert commands usable everywhere

- `\MTcustomgreek`: in case `mathastext` has been loaded with one of its Greek related options, this activates the corresponding customization of Greek letters in math mode. It is issued automatically by the package in the preamble (except if loaded with `subdued` option) and at each switch of math version via `\MTversion` or `\MTversion*` (except for the normal and bold math versions in subdued mode). Also available as `\Mathastextcustomgreek`. May be used even inside of math mode. (1.3d)
- `\MTstandardgreek`: in case `mathastext` was loaded with one of the Greek related options this command reverts the customization, it resets the Greek letters to their definitions in force at package loading time. Can be used in the preamble, but is mainly for the document body (may even be used inside math mode ...). Done automatically under the `subdued` option when switching to the normal or bold math version. Also available as `\Mathastextstandardgreek`. (1.3d)
- `\MTsetmathskips{<a-z/A-Z>}{<muglue_before>}{<muglue_after>}`: is used to specify extra skips (or rather mu glue) to be inserted in math mode, before and after a letter. The rationale is that standard text fonts used in math mode may sometimes cause glyph (near-) collisions with math symbols, as TeX has some implicit expectations on the design of fonts for math letters. (1.3a)

These extra skips around letters are set at their natural width and do not add any stretchability or shrinkability to the math formula as a whole, nor do they result in extra potential break points.

Random (silly) examples:

```
\MTsetmathskips{x}{\medmuskip}{\thickmuskip}
\MTsetmathskips{A}{.5mu}{2.3mu}
```

and the effect:  $vw\,x\,yz\,A\,BC^{vw\,x\,yz\,A\,BC}$ . The effect obeys the usual L<sup>A</sup>T<sub>E</sub>X scoping rules.

The first argument of `\MTsetmathskips` may be any expandable code giving a letter; this facilitates use of `\MTsetmathskip` in `\@for` loops such as this one:

```
\makeatletter
\@for\@tempa:=a,b,c,d,e,f,g,h,i,j,k,l,m,n,o,p,q,r,s,t,u,v,w,x,y,z\do{%
  \MTsetmathskips{\@tempa}{2mu}{2mu}}%
\makeatother
```

**Starting with v1.3i:** the extra skips are *not* applied to the letters within the scope of math alphabet commands, or the letters from operator names (pre-defined or user declared).

Note that contrarily to the `\MTexistsskip`, `\MTforallskip`, and `\MTprimeskip` commands described next, these extra skips (which may be specified in the preamble) are not recorded in

the definition of the math version (as defined via `\Mathastext` with its optional argument or via `\MTDeclareVersion`). The declared skips hold throughout the document until modified or canceled, independently of math versions (of course, `mathastext` cancels the skips in the normal and bold math versions if package option `subdued` was used).

- `\MTunsetmathskips{<a-z/A-Z>}`: cancels the skips for that letter (they are not set to `0mu` but completely removed).

The argument may be a macro (or any expandable code) expanding to a letter.

- `\MTnormalexists`, `\MTexistsdoesskip`: the latter (done by default if not `subdued`, and also on each use of `\MTversion` in the body of the document) makes it so that  $\exists$  takes into account the math glue as specified by `\MTexistsskip`. The former is its opposite. (1.3j)
- `\MTexistsskip{<math glue>}`: specifies the amount of skip or more generally glue to put after each  $\exists$  math symbol. Indeed, upright letters (or digits for that matter) often appear to be positioned a bit too close to the quantifier:  $\exists B$ . The package default is to add a `1mu` skip (this default is set to zero in the case of `italic`):  $\exists B$ . One can change the default with the following syntax: `\MTexistsskip{2mu plus 1mu minus 1mu}`, which if used in the preamble and followed with a `\Mathastext` command (or `\MTDeclareVersion`), will be recorded in the definition of this math version (and subsequent ones). One may also use the command at any time in the document. In the case of the option `subdued`, the skip is canceled in the *normal* and *bold* math versions. In the case of the option `italic`, the default skip is set to zero.
- `\MTnormalforall`, `\MTforalldoesskip`: the latter (done by default if not `subdued`, and also on each use of `\MTversion` in the body of the document) makes it so that  $\forall$  takes into account the math glue as specified by `\MTforallskip`. The former is its opposite. (1.3j)
- `\MTforallskip{<math glue>}`: the default is to add a `.6667mu` math skip after each  $\forall$  (except with the option `italic` for which the default skip is set to zero). Compare  $\forall F$  (has the skip) with  $\forall F$  (has no skip). Use this command in the preamble to set up the skip or glue to be used in the *next to be declared* math versions. In the case of the option `subdued`, the skip is canceled in the *normal* and *bold* math versions. In the case of the option `italic`, the default skip is zero for all math versions. One may use the command at any location in the document.
- `\MTnormalprime`, `\MTprimedoesskip`: the latter (done by default if not `subdued`, and also on each use of `\MTversion` in the body of the document except for the `subdued` *normal* and *bold* math version) makes it so that  $'$  takes into account the math glue as specified by `\MTprimeskip`. The former is its opposite. In all cases the right quote  $'$  is a mathematically active character throughout the document. (1.3j)

producing ' as is the default in TeX, it is only its meaning which changes to include or not an extra skip.

Even though `\MTprimedoesskip` is not done in the `subdued` case, it is *not* a no-op even then in the preamble or in the *normal* and *bold* math versions.

- `\MTprimeskip{<math glue>}`: specifies the amount of math skip to add before the derivative glyph. The default initial value is `0.5mu`, except with the `italic` option where it is `0mu`. In the case of the option `subdued`, the skip is canceled in the *normal* and *bold* math versions.
- `\MTnormalasterisk`, `\MTactiveasterisk`: the latter will use for \* and `\ast` the text font asterisk, suitably lowered; the former if used in the preamble tells `mathastext` to not modify the non-`mathastext` situation, or if used in the body to revert to it. Both are no-op's in absence of option `asterisk`.

A legacy feature is that `\MTactiveasterisk` is *not* a no-op in `subdued normal` or `bold` math versions, and does let the asterisk obey the `\MTlowerast` configuration, if used explicitly by user (even in the preamble).

**changed:** At 1.4 `mathastext` checks at `\begin{document}` (or each time `\MTactiveasterisk` is made use of) if \* is a Babel shorthand (which I far as I know is the case of no language) or is already mathematically active. In the latter case the \* is not modified in math mode; and it is not modified either if found to be catcode active but not a `babel` shorthand. In contrast, the `\ast` will always be set to obey `\MTlowerast` configuration after `\MTactiveasterisk`. (1.4)

- `\MTlowerast{<dimen>}`: under option `asterisk` a `\raisebox` command is used to lower the text asterisk to produce a reasonable math asterisk. The package uses this command initially with argument `0.3\height`, this will have to be fine-tuned for each given text font but worked out ok with the fonts we tried. The dimension argument will be used also in sub-scripts and sub-sub-scripts, so it is best not to use an absolute dimension. The dimension specification is for text it can not be with `mu` unit.
- `\MTmathoperatorsobeymathxx`, `\MTmathoperatorsdonotobeymathxx`: the former is done by default, it makes operator names obey math alphabets. See also [subsubsection 1.8.4](#). This functionality *does not rely* on “math active characters”. Automatically issued by each `\MTversion`, except under option `subdued` when switching to *normal* or *bold*.
- `\MTmathactiveletters`: ‘math activation’ of all ascii Latin letters. This is done by the package automatically except under the `subdued` option. (1.3)

**changed:** At 1.4 its behavior was modified significantly: instead of setting some toggle obeyed only at entrance of math mode, it acts on the spot immediately. (1.4)

Formerly, this command was only a configuration toggle with no immediate impact (and was not usable from inside math mode). Indeed, the `mathastext` work

of mathematical activation was done (or not done) *each time* math mode was entered (if not in `subdued`), and the ascii letters kept standard mathcodes outside of math mode.

The command now does the mathematical activation on the spot and the meaning of the active shape of the ascii letters — a priori undefined because typesetting a document with an active ascii letter is near impossible, as no L<sup>A</sup>T<sub>E</sub>X command name used in the document can contain it — is modified here and then; but of course the catcodes are not modified only the mathcodes are. Except if `mathastext` is loaded with the `subdued` option, this mathematical activation is executed already at package loading time.

If with the `subdued` option, the command is inactive in the preamble, as well as in the *normal* and *bold* math versions. In all cases it gets (re-)executed automatically when `\MTversion` is used for activating a non-subdued math version.

The new situation may be dangerous if the document author makes a letter, say `A`, catcode active at some point, with a definition of the active state using `\string A`. As `mathastext` has (earlier, in the preamble) set `A` to be mathematically active as well, and as the `\string` changes nothing to that, an infinite loop will be triggered by such an `A` in math mode.

But, having an active ascii letter can only be in very localized portions of a document, and only be authored by experts. The experts should carefully make sure the mathcode of the letter is not active if they set the catcode to active and let the active meaning use `\string` on the letter itself, thus we can trust that the mathematical activation done earlier by `mathastext` is undone and there will be no problems.

This 1.4 change may thus need to be followed by some adjustments in some quite special circumstances caused by some expert interventions.

See [subsubsection 1.8.1](#) and [subsubsection 1.8.2](#) for the rationale of this mathematical activation, and [subsubsection 1.8.5](#) for ways to use it for other goals.

If you do want mathematically active letters also in subdued *normal* or *bold* math versions (to apply tricks such as those of [subsubsection 1.8.5](#)) there is `\mst@mathactivateletters` which does not check the `subdued` status.

- `\MTmathstandardletters`: turns off the mathematical active ascii letters, i.e. reverts their mathcodes to package font configuration. Here “standard” only means that the letters will not be mathematically active, but they are still under the influence of `mathastext` regarding the typeface they use, so they are only “standard” from `mathastext` point of view. (1.3)

**changed:** At 1.4 its behavior was modified: instead of setting some toggle obeyed only at entrance of math mode, it acts on the spot immediately. (1.4)

`\MTmathstandardletters` will not try to restore the meaning associated to the catcode active variant of the letter token which may have been in place at the time of `\MTmathactiveletters`. This meaning is not saved for later reset.

*Except* if the *letter* was an active Babel-shorthand at the time of `\MTmathactiveletters`, which is in fact almost impossible to achieve via the `babel` interface.

And if the letter was catcode-active due to user action, `\MTmathactiveletters` will not have made it mathematically active, nor will it have modified its active meaning. So the active meaning may get overwritten only for a letter having a normal catcode at time of `\MTmathactiveletters` but which for some reason has some meaning associated to its catcode active variant.

- new:** • `\MTmathactivedigits`: is a no-op except under option `activedigits`. It then makes all digits mathematically active and is executed during package loading, except if `subdued`. It is again executed when entering any non-`subdued` math version in the document body. See [subsubsection 1.8.5](#) for an example of use.

If you do want mathematically active digits also in subdued *normal* or *bold* math versions (to apply tricks such as those of [subsubsection 1.8.5](#)) there is `\mst@mathactivedigits` which does not check the `subdued` status.

- new:** • `\MTmathstandarddigits`: a no-op except under option `activedigits`. Under this option it resets the digits to their normal mathcodes as configured by the package.
- `\MTicinmath`: this command is executed by default by `mathastext` except in case of option `subdued` or if the user chosen letter shape is oblique (`it` or `s1`). It tells `mathastext` to add italic corrections after all letters in math mode, except within the scope of math alphabets.

**changed:** This command and the next ones in this item can be used anywhere in the document and even from inside math mode. In case of `subdued` option, using the command from within the preamble remains without effect, as the document body will start in the subdued normal math version anyhow. Each `\MTversion` in the body reemits `\MTicinmath` (in case of non-oblique letter shape), except if the `subdued` option was used and the chosen math version is *normal* or *bold*.

The effect of this and the other commands of this item is local to the group or environment in which it has been issued.

The description above about the command not being executed if the letter shape is italic or slanted is not quite right, as it refers only to the act of inserting or not italic correction. The `\MTmathactiveletters` component is always executed, however it will be a no-op in `subdued` *normal* and *bold*.

`\MTnoicinmath`: this command deactivates the package added italic corrections. It can be used inside as well as outside of math mode (or in the preamble of the document). Note that it does not deactivate the mathematical activation of the ascii letters. Use `\MTmathstandardletters` for that.

`\MTICinmath`, `\MTnoICinmath`: only acts on the uppercase letters. But recall that `\MTicinmath` is done by default, thus using italic corrections only for uppercase needs to go via `\MTnoicinmath` then `\MTICinmath`.

`\MTicalsoinmathxx`: this command de-activates the de-activation of the italic corrections inside the arguments to the math alphabet commands. It can be issued inside as well as outside of math mode. Will be effective only if `\MTicinmath` or `\MTICinmath` is in force. To cancel its effect either enclose it in a group or environment or re-issue `\MTicinmath` after it.

- `\MTeasy nonlettersobeymathxx`, `\MTeasy nonlettersdonotobeymathxx`: the former is done by default, it makes characters ., /, |, \, #, \$, %, and & (if not excluded by package options) obey math alphabet commands. See also [subsection 1.8.4](#). This functionality does *not* make the characters “math active” (but it does modify `\mathcode`’s, naturally).
- `\MTnonlettersobeymathxx`, `\MTnonlettersdonotobeymathxx`: the former will make (except if excluded by relevant package options) !, ?, ,, :, ;, +, -, =, (, ), [, ], <, and > obey the math alphabet commands (when not used as delimiters). These characters are made “math active”, and each one now expands to two tokens. This makes for example `$a^!$` illegal input and it will have to be coded `$a^{!} $`. Hence, by default, the package does `\MTnonlettersdonotobeymathxx`.
- `\MTexplicitbracesobeymathxx`: extends an earlier `\MTnonlettersobeymathxx` to also treat `\{` and `\}`. But then `\left\{`, `\right\}` must be coded `\left\lbrace`, `\right\brace` rather. There is also `\MTexplicitbracesdonotobeymathxx`.
- `\MTeverymathdefault`: this hook is executed by `\MTversion{<version_name>}` [\(1.3j\)](#) (but if under option `subdued` and switching to the *normal* or *bold* math version its default effect is overruled by an `\MTeverymathoff` executed after it). Its default meaning is:

```

\MTactiveasterisk % this has no effect without option asterisk
\MTprimedoesskip % this makes prime glyph obey extra space
\MTeasy nonlettersobeymathxx
\MTicinmath        % this does \MTmathactiveletters, hence the extra
                     % skips from \MTsetmathskips are obeyed.
\MTmathactivedigits % this is a no-op in absence of option activedigits
\MTfixfonts       % only operant under LuaLaTeX.

```

Under `subdued` option, switching to the *normal* or *bold* version does `\MTeverymathoff` which includes `\MTnonlettersdonotobeymathxx`.

The default `\MTeverymathdefault` which is issued when going back to a *non-normal* or *bold* math version doesn’t do `\MTnonlettersobeymathxx`: thus it is up to the user to correct this if desired.

Notice also that `\MTversion{<version_name>}`, except for *normal* or *bold* if `subdued` does `\MTforalldoesskip` and `\MTexistsdoesskip`, which are not included in `\MTeverymathdefault` actions as they are not related to `\everymath` and `\everydisplay`.

At [1.4](#), the name of this command diverges somewhat from its action as mathematical activation of ascii letters (or, optionally, of digits) will happen on the spot and not during `\everymath` or `\everydisplay` execution.

- `\MTeverymathoff`: does `\MTnormalasterisk`, `\MTnormalprime`, `\MTnonlettersdonotobeymathxx`, `\MTeasy nonlettersdonotobeymathxx`, `\MTmathstandardletters`, `\MTmathstandarddigits` and `\MTdonotfixfonts`. (1.3j)  
(1.4)

Automatically done by `\MTversion{normal}` (or `{bold}`) under option `subdued` (and also `\MTnormalexists` and `\MTnormalforall` are executed then).

The commands `\url/\nolinkurl` of package `hyperref` and `\url` from `url.sty` (which use math mode under the hood) are patched by `mathastext` to do `\MTeverymathoff` automatically: this is needed because `mathastext` modifies anew some mathcodes *each time math mode is entered*, hence may overwrite to some extent the specific preparations done by `{url,hyperref}.sty`. (1.3i)

However, in some cases it may be interesting to be able to apply hacks as described in [subsection 1.8.5](#). You can use now `\MTeverymathoff` as a hook inside `\url` and `\nolinkurl` commands. Perhaps redefine it (locally) to do all of the above except `\MTmathstandardletters` and/or `\MTmathstandarddigits`, and use the [subsection 1.8.5](#) instructions to achieve special effects for some letters or digits in the URLs rendered via `\url` and `\nolinkurl`. (1.4)

### 2.2.3 Expert commands usable only outside of math mode

There is only one pair of commands here: `\MTfixfonts` and `\MTdonotfixfonts`. They are operant only under `LuaATEX`. As `\MTeverymathdefault` and `\MTeverymathoff` use them, they arguably could have been listed here, but only for engine `LuaATEX`.

- `\MTfixfonts`: this is operant only under `LuaATEX`. It has the effect that each time math mode is entered macro `\MTfixmathfonts` will be executed. The latter forces so-called `base` mode for the used text font in math mode, in an effort to (only partially, see code comments) fix the fact that OpenType features such as Lining Figures were in some cases not being applied in math mode when one uses text fonts there (text fonts are declared by `LuaATEX+luaotfload` to use `node` or `harf` mode, which are non-functional in math.) It is invoked automatically by the package (except for `normal` and `bold` math versions under `subdued` option), and in normal situations, there is no reason to use it directly. (1.3o)

**changed:** The hack was updated at [1.4](#) in order to also handle fonts using `Renderer=HarfBuzz`. (1.4)

- `\MTdonotfixfonts`: cancels the job of `\MTfixfonts`. Done automatically in `subdued` mode when in the `normal` or `bold` math version; in normal contexts, there is no reason to use this command. Only operant under `LuaATEX`. (1.3o)

### 2.2.4 Expert commands usable only in math mode

- `\MTfixmathfonts`: this used to be an internal package macro but it is given a public name at [1.3p](#) because I discovered that `$.. \hbox{\mathversion{foo}}$..$` causes an issue and one needs to invoke again `\MTfixmathfonts` *after* the `\hbox`, for some reason. To be used *only* under `LuaATEX` and only for such rare cases where it may be needed. (1.3p)

## 3 Package options

### 3.1 Summary of main options

**italic**: tells **mathastext** to typeset the ascii letters in math using italic shape; indeed, its legacy historical default is to typeset them in roman (upright) shape.

**frenchmath**: lowercase ascii letters in italic shape, uppercase in upright shape. Also lets the Greek letters, if the latter are under **mathastext** influence, be upright, i.e. also the lowercase ones.

**subdued**: tells **mathastext** to not change the default fonts or the math alphabets for the normal and bold math versions. The **mathastext**-ification activates only after `\MTversion{<version_name>}` usage in the document body, where the `<version_name>` was declared as an **mathastext** enriched math version in the preamble via `\Mathastext[<version_name>]` or akin package commands.

**LGRgreek**, **eulergreek**, **symbolgreek**: the Greek letters will be taken, respectively from the text font itself (which must be available in LGR encoding), or respectively the Euler or Symbol font.

**symbolmax**: all characters other than letters and digits, are taken from the Symbol font. This option also makes a number of further glyphs available, such as some basic mathematical arrows, and the sum and product signs. For documents with very simple needs in mathematical symbols, **mathastext** with option **symbolmax** may give in the end a PDF file size quite smaller than the one one would get without the package.<sup>67</sup>

**defaultmathsizes**: prevents **mathastext** from setting up, as it does per default, larger subscripts and superscripts in math mode, and from copying code from the **moresize** package<sup>68</sup> in order to redefine `\Huge` and define a `\HUGE` command.

### 3.2 Complete list of options

Some items are described succinctly as more developed descriptions were given earlier. They may sometimes simplify by omission and not consider all possible configurations, particularly those resulting from usage of the package commands in the preamble to configure math versions.

Note that this list is not in alphabetical order, the items are grouped roughly by themes. So, objectively, the best for the diligent reader is to read thoroughly all descriptions.

---

<sup>67</sup>It is even better if compiled via `latex+dvipdfmx`.

<sup>68</sup>Christian CORNELSEN, Allows font sizes up to 35.83pt, <https://ctan.org/pkg/moresize>.

- **basic**: only mathastextify (ascii) letters and digits. Can be combined with either **nodigits** or **noletters**.
- **subdued**: acts in a subdued way, which means that the L<sup>A</sup>T<sub>E</sub>X “normal” (default) and “bold” (triggered by `\boldmath` or `\mathversion{bold}`, undone by `\unboldmath` or on exit from a scope limiting context such as an environment) math versions are left (not quite: check [subsubsection 1.3.4](#) for specifics) unchanged and the **mathastext** action is triggered only when switching via `\MTversion{<version_name>}` (or its starred variant) in the document body to a version previously defined in the preamble via `\Mathastext[<version_name>]` (or alternative declarative interface such as `\MTDeclareVersion`). <sup>69</sup>
- **italic**: let the Latin letters (both lowercase and uppercase) use the italic shape (`\itdefault`) in math mode. If the package handles Greek letters, also lowercase (but not uppercase) Greek letters will use this a priori italic shape except if some other option such as `upgreek` was used. <sup>70</sup>
- **frenchmath**: configures the lowercase Latin letters to use italic shape (`\itdefault`), and uppercase Latin letters to be in same shape as for digits and operator names (i.e. a priori `\shapedefault`).

If the package handles Greek letters both lowercase (if under control of **mathastext**, i.e. not for `selfGreek`) and uppercase Greek letters will use the same shape as operator names, except if some other option such as `itgreek` was used. <sup>71</sup>

This configuration (i.e. that uppercase Latin letters will be in the same shape as the one for digits and operator names) is **not** undone in the **subdued** “normal” and “bold” math versions. It holds throughout the document.

As a bonus, note that doing

```
\usepackage[basic,subdued,frenchmath]{mathastext}
```

provides a simple manner to obtain the expected shapes of Latin letters in French mathematical typography, in an arbitrary math font configuration from other packages, in case those packages do not provide an option to achieve this.

But, even if **mathastext** is used via `LGRgreek` to configure Greek letters, on the other hand the control sequences for Greek letters are all really restored to their defaults (or whatever was configured by other packages loaded prior to **mathastext**) in the subdued “normal” math version, which limitates the usefulness of the previous paragraph.

On the bright side, the `\alphaup`, `\alphait`, ..., control sequences will however be with their **mathastext** meaning, see `LGRgreek` for more information.

It is *not* possible (except of course if one is ready to do some low-level T<sub>E</sub>X coding to re-execute where needed in the document body a few lines of the package internals with appropriate

---

<sup>69</sup>Under this option `\MTversion{normal}` and `\MTversion{bold}` execute automatically `\MTmathoperatorsdonotbeymathxx`, `\MTeasynonlettersdonotbeymathxx`, `\MTnonlettersdonotbeymathxx`, `\MTmathstandardletters`.

<sup>70</sup>Since 1.3y, in presence of the `LGRgreek` option in addition to `italic`, the `\MTgreekitdefault` shape is then used for lowercase Greek letters and `\MTgreekupdefault` for uppercase.

<sup>71</sup>Under `LGRgreek` and since 1.3y, the `\MTgreekupdefault` is used for Greek letters if no other option such as `itgreek` was employed.

modifications; I said TeX, not L<sup>A</sup>T<sub>E</sub>X, as the latter is very much decided to make impossible any kind of math configuration change at this level if not in the preamble) to achieve a “French math” style only in some math versions and not in others. The reason why is that to achieve distinct shapes for uppercase versus lowercase Latin letters, the uppercase letters are assigned internally to the font (which can change from math version to math version) used for operator names. One can still make them slanted using `\MTshape`, but this will also slant the digits, as they are picked from the same font. On the other hand if we do not use the `frenchmath` option, both uppercase and lowercase Latin letters are always assigned to the same font, so no math version can give them separate distinct shapes. For a small demo though, one can naturally painstakingly use either the `\mathrm` or `\mathnormal` alphabet commands to obtain, say under the `italic` option and no additional configuration, respectively the up shape and the italic shape.

None of the `frenchmath`, `frenchmath*`, and `frenchmath+` options bear any direct connection with the `frenchmath` package by Antoine MISSIER (this is in contrast with the fact that the `decimalcomma` option is directly related with the `decimalcomma` package by the same author as it tells `mathastext` to require it). But see subsubsection 1.4.13 for important information about the utility of `frenchmath*` if the two packages are to be used concurrently.

- new behavior**
- `defaultalphabets`: `mathastext` always defines `\Mathnormal`, `\Mathrm`, `\Mathbf` etc... to refer to the `mathastext`-ified text fonts, and redefines the math alphabets `\mathrm`, `\mathit`, `\mathtt` etc... (but not `\mathcal` of course) to use them. To avoid the remapping and keep the `\mathrm` et al. to refer to the non `mathastext`-ified fonts, use this option. The `\Mathnormal` et al. commands with an initial uppercase will always be available whether or not this option is made use of.  
Prior to 1.3za (and since 1.15f), this option also prevented the package to declare the `\Mathnormal` et al. and `\mathnormalbold` commands. In this context, recall that the dreaded “too many math alphabets” error can only occur on *use* in the document of too many of such commands, and not at the time of their declarations. The author’s notes from time of 1.15f release (2012/10/25) only say that it may not be “useful” to package user to have both (for example) `\mathrm` and `\Mathrm`, which sounds weird if they are to acquire distinct meanings. So since 1.3za both will exist. In the default package configuration `\mathrm` is configured to expand to `\Mathrm` (with some extra behavior under `LGRgreek+`), and with this option or the `defaultrm` option `\mathrm` is kept with its original meaning (and the `LGRgreek+` extras do not work).

- changed:**
- `defaultnormal`, `defaultrm`, `defaultbf`, `defaultit`, `defaultsf`, `defaulttt`: tell `mathastext` to not set up, respectively, the `\mathnormal`, `\mathrm`, `\mathbf`, `\mathit`, `\mathsf`, and `\mathtt` commands to use the `mathastext`-ified font which are accessible always via `\Mathnormal`, `\Mathrm`, `\Mathbf`, `\Mathit`, etc...  
Prior to 1.3za these options also prevented the creation of the corresponding `mathastext` command with an uppercased initial.
  - `ncccomma`: it triggers the loading of the `ncccomma` package<sup>72</sup> and configures `mathastext` for compatibility (this is canceled if `nopunctuation` option is used, or

<sup>72</sup>Alexander I. ROZHENKO, *Use comma as decimal separator in mathematics*, <https://ctan.org/pkg/ncccomma>.

`basic` as it implies it). Note that `mathastext` has NO auto-detection mechanism of `ncccomma`, the correct way is to use the eponymous option.

The effect of the `ncccomma` package will apply to the entire document body, even to portions using the *normal* or *bold* math versions with `mathastext` having been loaded with the `subdued` option. Also, in case of usage of package `babel` with `french` option, the effect of `ncccomma` will also apply to those parts of the document using another language than French.<sup>73</sup>

- `decimalcomma`: it triggers the loading of the `decimalcomma` package<sup>74</sup>. The same remarks apply as for the `ncccomma` option. In particular note that `mathastext` has NO auto-detection mechanism of `decimalcomma`, the correct way is to use the eponymous option. (1.3zb)
- `binarysemicolon`: sets (except if `nopunctuation` is used) the semi-colon to let TeX use spacing of binary type, not punctuation type, around the semi-colon (it is often used in French mathematical typesetting as separator in interval denotations, when the extremities are decimal numbers, as the comma is used as decimal separator). (1.3y)

The effect applies to all math versions, even the *normal* and *bold* math versions with `mathastext` having been loaded with the `subdued` option.

- CHANGED!** • `frenchmath*`: does all three of `frenchmath`, `decimalcomma` and `binarysemicolon`. (1.3zb)

Prior to 1.3zb, this option did what is now available via `frenchmath+`. The 1.3zb change was made as a follow-up consecutive to the 2.7 release `frenchmath`. Indeed this option as explained in subsubsection 1.4.13 is provided as a compatibility layer with `frenchmath`, and it was mandatory to modify its meaning to refer to package `decimalcomma`, not `ncccomma`, consecutive to the internal change of `frenchmath` at its 2.7 release to use `decimalcomma`.

- `frenchmath+`: does all three of `frenchmath`, `ncccomma` and `binarysemicolon`. (1.3zb)  
This is what used to be called `frenchmath*` prior to 1.3zb.
- `endash`, `emdash`: use the text font en-dash (–) or even the em-dash (—, but this seems crazy) for the minus sign rather than -. `endash` option is default for the package.
- `unicodememinus`: use the MINUS SIGN U+2212 (requires `fontspec`.) Or, in the form `unicodememinus=HHHH` with four *uppercased* hexadecimal digits: use the U+HHHH code point. As `noendash` really means “use the hyphen from the text font”, `unicodememinus` remains without effect under it, or, naturally, under `nominus`. Without this option, `mathastext` uses the EN DASH U+2013 by default for OpenType fonts. (1.3q)

---

<sup>73</sup>There is a ‘feature’ of `babel-french` that the effect of package `ncccomma` is canceled if one switches from French to English; and switching back to French does not reenact it. For background on this issue see <https://github.com/latex3/babel/issues/190>.

This does not apply to `decimalcomma` 1.3 or later.

<sup>74</sup>Antoine MISSIER, *Comma for decimal numbers*, <https://ctan.org/pkg/decimalcomma>.

- **asterisk**: this tells **mathastext** to replace the binary math operator `*` and the control sequence `\ast` with versions which uses the text asterisk `*` suitably lowered, and with the correct spaces around it as binary operator. The amount of lowering<sup>75</sup> is decided by the mandatory argument to the command `\MTlowererast{<dimen>}`. The package does `\MTlowererast{.3\height}`. Using the `ex` unit as in `\MTlowererast{.5ex}` is not a good idea as it does not scale properly in the script and scriptscript styles.

Attention that if using this option, inputs such as `$R^*$` or `$R^\ast$` raise errors and *must* be replaced by `$R^{*}$`, respectively `$R^{\ast}$`. The `*` is now ‘mathematically active’<sup>76</sup> and `*` and `\ast` will obey the math alphabet commands (see [subsubsection 1.8.4](#)).

- new:**
- **activedigits**: it makes all digits mathematically active! This is reserved to expert L<sup>A</sup>T<sub>E</sub>X users. See [subsubsection 1.8.5](#) for an example. Do not use this option if you don’t intend to make use of such techniques to achieve special effects at some location of your document at least. (I know this goes without saying, but passing this option and not using it is only adding overhead to all your equations with digits). (1.4)
  - **nodigits**: no **mathastext**-ification of digits.
- new:**
- **noletters**: This is quite antithetical to the package core aim, but here you go. (1.4b)  
This option implies `nohbar` and `defaultmath`.

Note though that **mathastext** will still declare to L<sup>A</sup>T<sub>E</sub>X two extra symbol fonts and define alphabet commands such as `\Mathrm`, `\Mathnormal` and `\mathnormalbold` which map to them. But ascii letters will if not in arguments of these commands not use the **mathastext**-font and all business of active letters (see [subsubsection 1.8.5](#)) is now irrevocably inaccessible.

If you simply want to avoid the overhead of math active letters, use rather `\MTmathstandardletters` in the preamble after having loaded the package (although this does not undo the fact that **mathastext** will have redefined what a letter does if it is catcode active but that remark should have been made in an even smaller typeface).

- **nohbar**: prevents **mathastext** from defining its own `\hbar`.
- **noendash**: the minus sign will be the `-` from the text font, not the en-dash `–`.
- **nolessnomore**: besides `!?, .:; + - = ()[]/#$%&` **mathastext** treats also `<>|` `{ }` and `\.`. Use this option to let it not do it. This is the default in case of OT1-encoding.
- further excluding options: **noexclam !?** **nopunctuation ,.:;** **noplus, nominus, plusnominus + – noequal = noparenthesis ()[]/ nospecials #\$%&** (and **nodigits** and **noletters** mentioned earlier).

---

<sup>75</sup>With the option `symbolmisc`, the asterisk is picked from the Symbol font, and the amount of lowering is non-customizable; however if a math alphabet command is used, the asterisk is then again from a text font and the lowering will be as specified by `\MTlowererast`.

<sup>76</sup>In a hopefully safe way, for example `$\label{eq*1}$` is ok.

- **alldelims**: true by default, means that the characters excluded by `nolessnomore` are treated. Use this option in case of a mono-width OT1-encoded font.
- **nosmalldelims**: this prevents `mathastext` from trying to pick up in the text font the ‘small variants’ of some math delimiters; it only affects what happens when a character such as a left parenthesis ( or [ is used as a delimiter, and in the event that TeX has chosen the smallest sized variant. This has no impact on what happens when they are not used as delimiters: then, and if not disabled by the corresponding options, these characters are always picked up from the text font.<sup>77</sup>
- **symbolgreek, symboldigits**: to let Greek letters (digits) use the Symbol font.
- **symbolre**: replaces `\Re` and `\Im` by the Symbol glyphs  $\mathbb{R}$ ,  $\mathbb{I}$  and defines a `\Dot-Triangle` command (.:).
- **symbolmisc**: takes quite a few glyphs, including logical arrows, product and sum signs from Symbol. They are listed *supra*. Doing `\renewcommand{\int}{\smallint}` will maximize even more the use of the Symbol font.
- **symboldelimiters**: the characters apart from letters and digits will be taken from the Symbol font.
- **symbol**: combines `symbolgreek`, `symbolre`, and `symbolmisc`.
- **symbolmax**: combines `symbol` and `symboldelimiters`.
- **eulergreek, eulerdigits**: to let Greek letters (digits) use the Euler font.
- **LGRgreek**: this configures the Greek letters in math mode to use the text font (i.e. a priori the font which was default at time of loading the package) in LGR-encoding. The command `\MTgreekfont` can be used to set a specific (LGR-encoded) font family. Each use of `\MTgreekfont` must be followed at some point by a `\Mathastext` or `\Mathastext[<version_name>]` to be effective. Any subsequent math version declaration will be influenced by it until `\MTgreekfont` is used again to configure another font for Greek letters.<sup>78</sup>

If `\MTgreekfont` is never used the font family for Greek under option `LGRgreek` will be, in all math versions except under `subdued` for the “normal” and “bold”, the family which was the default at time of loading the package. You must use `\MTgreekfont` to change it.

See further on this topic the `upgreek`, `itgreek`, `upGreek` and `itGreek` options as well as the `\MTupgreek`, `\MTitgreek`, `\MTupGreek` and `\MTitGreek` commands.

---

<sup>77</sup>in this very special situation of option nosmalldelims, the braces are an exception to this rule and they require both of `\MTnonlettersobeymathxx` and `\MTexplicitbracesobeymathxx` for being picked up from the text font when not used as delimiters.

<sup>78</sup>You can check the documentation of the <https://ctan.org/pkg/lgrmath> package for how to find out systematically which fonts are available on your system in LGR encoding.

It is up to the user to ascertain that the font family is indeed available in the LGR encoding; if it is not, only at time of the first math mode typesetting will  $\text{\LaTeX}$  issue warnings such as this one:

```
Font shape `LGR/ptm/m/n' undefined
using `LGR/cmr/m/n' instead on input line 28
```

The `LGRgreek` option also triggers pre-definition of Greek character tokens such as `\alphaup` or `\betaait`, see [subsubsection 1.7.3](#) for the explanations.

Although under `subdued` option `mathastext` restores Latin (but see `frenchmath`) and Greek letters in the “normal” and “bold” math versions it still under `LGRgreek` option keeps in these “subdued” math versions the package declared `\alphaup`, `\alphait`, ..., and the associated `\mathgreekup` and `\mathgreekit` commands to access the underlying fonts, and also since [1.3za](#) `\mathgreekupbold` and `\mathgreekitbold`.

The font used by these math alphabet commands in the subdued “normal” and “bold” is either the one in LGR encoding which was the family default at time of loading the package or the one configured last by `\MTgreekfont` when the command `\Mathastext` (without optional argument) was used in the preamble.

[1.3za](#) fixes here a bug which froze the target font to be the one at time of loading the package: this bug applied (only) to the subdued “normal” and “bold” math versions and was not readily visible as there is a priori no reason to use in these subdued math versions these `mathastext`-provided Greek font alphabets.

- **LGRgreeks:** each declared math version will be supposed to be with a font which is also available in LGR-encoding. This is a shortcut to using `\MTgreekfont` systematically to keep in sync in all declared math versions the font for Greek with the font for Latin letters. Please note that macro `\MTgreekfont` becomes then inoperant, and if you need one math version without this Latin-Greek synching, you will have to use rather `LGRgreek` and then `\MTgreekfont` manually appropriately.
- **LGRgreek+ and LGRgreeks+:** they extend respectively `LGRgreek` or `LGRgreeks` to let Greek letters control sequences when in the scope of `\mathrm`, `\mathit`, and `\mathbf` behave as would be expected by  $\text{\LaTeX}$  users who have not read `fntguide.pdf` or any other  $\text{\LaTeX}$  documentation but have used `unicode-math`. See [subsubsection 1.7.5](#) for details. [\(1.3za\)](#)
- **selfGreek:** this is for a font which is also available in OT1-encoding and contains the glyphs for the default eleven capital Greek letters.  
This option should have been named `OT1Greek` as it bears about the same relation with OT1 encoding (for eleven capital Greek letters) as `LGRgreek` does with the LGR encoding (for the complete no-diacritics Greek alphabet).
- **selfGreeks:** each declared math version will be supposed to be with a font with the eleven capital Greek letters in its OT1-encoded version.
- **upgreek, itgreek:** options to tell `mathastext` to use `\MTgreekupdefault` or `\MTgreekitdefault` for the lowercase and uppercase Greek letters shape. These two

commands can be defined prior to loading the package. This option is operant only under the `LGRgreek(s)` or `selfGreek(s)` options.

- `upGreek`, `itGreek`: influence only uppercase Greek.
  - `mathaccents`: use the text font also for the math accents. As in vanilla L<sup>A</sup>T<sub>E</sub>X, they are taken from the font for the digits and \log-like names. Obey the alphabet changing commands.
  - `unimathaccents`: extends `mathaccents` to OpenType fonts. Gave bad results in (1.3u) my brief testing.
  - `defaultimath`: do not overwrite `\imath` and `\jmath` to use `\inodot` and `\jnodot`.
  - `defaultmathsizes`: do not change the L<sup>A</sup>T<sub>E</sub>X defaults for the sizes of exponents and subscripts.
  - `fouriervec`: provides a `\fouriervec` command. The user can then add in the preamble `\let\vec=\fouriervec`. There is also always available a “poor man” vec accent `\pmvec` for upright letters.
- new:** • `everymath`: this option tells `mathastext` to employ as in the 1.3 releases the `\everymath`/`\everydisplay` registers to store certain actions to be executed at each entrance into math mode. The main change with 1.4 is that mathcode changes done by user (or possibly via language changes in a multilingual `babel` context) in the document body, and which apply to those characters which `mathastext` used to handle as part of `\everymath`/`\everydisplay`, will now have an effect, whereas with earlier releases or this one with the `everymath` option, they may get overruled by `mathastext`. Use `everymath` for backward compatibility if needed (and *only* if needed). Notice though that regarding ascii letters, there is no return to the pre-1.4: they will not acquire their mathcode active status only at each entrance into math mode, even with this option, but once and for all at package loading time, if not `subdued`, or when using `\MTversion` to enter a non-`subdued` math version.

Please report breakages due to the 1.4 release, which made it necessary for you to use this option `everymath` as workaround.

The option is destined to be removed at next major release and it will warn the user about this.

Thanks to Kevin KLEMENT, Tariq PERWEZ and Ricard TORRES for sending bug reports and feature requests when the first version of the package was issued.

Numerous examples will be found there:

<http://jf.burnol.free.fr/mathastext.html>  
<http://jf.burnol.free.fr/showcase.html>

## 4 Change log

### 1.4b [2024/07/27]

- \* Fix a regression at 1.4 regarding option nodigits.
- \* New option: noletters. I am in old age now so I can provide an option completely antithetical to my life work.
- \* Option everymath which is destined to be removed at next major release warns user about it. As major releases tend to happen once per decade I think the constant nagging will become insufferable and you will adapt to the 1.4 changes rather than persisting into using this option.

### 1.4a [2024/07/20]

- \* There was a documentation glitch in 1.4 and also a problem with the \MTprimeskip feature being lost under the emergency fall-back everymath option.

### 1.4 [2024/07/20]

- \* Since 1.2 of 2012/12/20, mathastext has used mathematically active characters to propose certain advanced functionalities. For reasons half lost in the mists of time but whose main one was surely to keep the meaning of the active shape of characters unchanged outside of math mode, this mathematical activation, and (in most cases) the definitions of what active characters do, were done again at \*each\* entrance into math mode. At this 1.4 release, mathastext does not inject \*any\* code whatsoever into the \everymath and \everydisplay toks registers anymore (except for one font-related hack needed under LuaLaTeX, see below). Your documents will compile a tiny bit faster.

- \* In (unusual) documents where users play with catcodes and mathcodes it is impossible to keep exact backward compatibility, because documented user commands which acted formerly a toggles with delayed action now will enact changes immediately if in the document body. In practice consequences are expected to be few, because catcode active characters are (as was already the case with earlier releases) hacked only when they are Babel shorthands and they are then modified in a way altering only their action in math mode. The precise description of

what mathastext does when mathematically activating (or not) a character, depending on circumstances, is to be found among small-print comments in the section "Extended scope of the math alphabets commands". See also the documentation of the \MTmathactiveletters command for some specifics regarding ascii letters.

- \* New option: everymath. It instructs mathastext to revert (partially) to its legacy code which uses \everymath/\everydisplay. This reversal is partial, the handling of ascii letters not being included into it. The everymath option is there only to try as a quick fix in case transition to this release causes a major problem in a user document and time is lacking to investigate. Please report to the author such issues. Option everymath is destined to be removed at next major release.

- \* New option: activedigits. Enjoy.

- \* It is now easier to hook into the mathastext architecture for mathematically activated ascii letters. See the new section "Hacking letters (and even digits) for special tasks".

- \* Bugfix: do not override special behavior of the math mode dot in babel-spanish.

- \* Bugfix: A desperate hack related to LuaLaTeX font matters and dating back to 1.30 2016/05/03 had been for some years in dire need of an update regarding fonts using Renderer=HarfBuzz. This is done now. Thanks to tex.sx user691586 for report. This is currently the sole remaining usage of \everymath/\everydisplay.

- \* Bugfix: an optional feature related to \{ and \} was broken since an upstream LaTeX change at its 2020-02-02 release.

- \* With option symbolmisc, those math symbol macros formerly defined via \DeclareRobustCommand are now declared via \protected\def.

- \* Removal of legacy branches previously kept to support LaTeX earlier than 2020-02-02.

- \* Removal of support for EU1 and EU2 font encodings.

- \* Option noasterisk deprecated at 1.2d 2013/01/02 has (finally) been removed.

- \* Four test files previously included and auto-extracted from the distributed dtx have been dropped. One of them is still available on the package homepage.
  - \* Some parts of the documentation have been massively re-ordered and even to some extent improved. But there may be some occasions where obsolete statements will be found having the legacy `\everymath`/`\everydisplay` situation as background.
- 1.3zb** [2023/12/29]
- \* Update to the `frenchmath*` option to maintain compatibility with the `[frenchmath](https://ctan.org/pkg/frenchmath)` package whose release 2.7 (2023/12/23) has replaced the `ncccomma` package by the `decimalcomma` package.
  - \* The `frenchmath+` option holds the former meaning of `frenchmath*`.
  - \* Option `decimalcomma` to load the eponymous package by Antoine Missier. This is tacitly done by `frenchmath*`.
  - \* No more messages sent to the console output during loading, only info messages going into the log, and using (more or less) the official LaTeX interface: after close to 13 years of development of this package it was perhaps finally the time to do it.
  - \* Documentation improvements. Close to 13 years after the birth of the package, and as it nowadays rarely wakes up from dormancy, this was almost last chance to try to improve a few things.
- 1.3za** [2023/12/20]
- \* Under `LGRgreek` and `LGRgreeks` options, new math alphabets `\mathgreekupbold` and `\mathgreekitbold`.
  - \* New options `LGRgreek+` and `LGRgreeks+`.  
Thanks to Holger Gerhardt for feature request and code ideas. Please find and read the relevant documentation in the PDF.
  - \* The meaning of `defaultalphabets` and related individual options such as `defaultbf` has been modified (reverted to pre 1.15f release): even under these options, the package always creates `\mathnormalbold`, `\Mathnormal`, `\Mathrm`, `\Mathbf` etc..., commands. This may break documents which used these options in order to reserve these command names. This was done with some hesitancy, but for the sake of internal logical coherence.
  - \* Fix an obscure bug with no real consequences regarding interaction of subdued with `LGRgreek` and `\MTgreekfont`. See the `LGRgreek` documentation in the complete list of options for details.
  - \* Fix long-standing hyperlink problems in the documentation: blue color words should now all be functioning hyperlinks.
- 1.3z** [2023/09/01]
- Fix 1.3y regression which broke `selfGreek` option due to internal renamings. Thanks to Stephan Korell for report.
- 1.3y** [2022/11/04]
- (the 1.3x had an annoying documentation bug, and had already been pushed to CTAN, hence the version increase to 1.3y)
- \* `mathastext` now requires the `\expanded` primitive (which is available with all major engines since TeXLive 2019).
  - \* Revisit parts of the documentation (mainly the Examples, and the section on Greek letters) and shuffle the other parts to surely improve things. Mention the `[mathfont](https://ctan.org/pkg/mathfont)` and `[frenchmath](https://ctan.org/pkg/frenchmath)` packages.
  - \* Add the `ncccomma` option which loads the `[ncccomma](https://ctan.org/pkg/ncccomma)` package to allow the comma as decimal separator.
  - \* Add the `binarysemicolon` option to let the semi-colon be of type `\mathbin`, not `\mathpunct`.
  - \* Add the `frenchmath*` option which does all three of `frenchmath`, `ncccomma` and `binarysemicolon`.
  - \* Under the `LGRgreek` and `LGRgreeks` options only:
    - make available upright and italic Greek letters in math mode via `\alphaup`, `\alphait`, ... control sequences, in addition to those not using such postfixed-names.
    - add `\mathgreekup` and `\mathgreekit` math alphabets.

- add `\MTgreekupdefault` and `\MTgreekitdefault`. The former replaces `\updefault` which was used in some places and since LaTeX 2020-02-02 caused systematic Font Warnings about the substitution of up by n.

These new features required an extensive internal refactoring which is expected to not induce changes to most existing documents. But it may induce changes to those using some unusual configuration in the preamble, as made possible via the package macros; this can apply only to documents authored by those few people who actually read the documentation. For full details make sure to read the PDF documentation about this change.

\* Fix "\Digamma under LGRgreek option uses the shape for lowercase not uppercase Greek".

\* Fix some incongruities in log messages related to Greek letters and emitted during math version creation in the preamble.

### 1.3w [2019/11/16]

\* LaTeX 2019-10-01 release (up to patch level 3 inclusive) together with amsmath conspired :-) to break mathastext, in connexion with math accents. This has been fixed upstream, but I am releasing nevertheless a hot fix to this <https://github.com/latex3/latex2e/issues/216> issue (this is compatible with future LaTeX releases).

\* Fix: the `\hbar` is originally a robust command but becomes a `\mathchardef` token if (e.g.) amsfonts is loaded and then with recent LaTeX `\hbar<space>` is made undefined and mathastext definition of it remained without effect. The `\mathastext` own `\hbar` is now defined `\protected`.

\* Fix: option noendash (or symboldelimiters which implies it) caused (since 1.3u) a bug under Unicode engines when setting up the minus sign.

\* Version names declared via the optional argument of `\Mathastext` or as first argument of `\MTDeclareVersion` must not be normal or bold. Enforce that! (this was marked as a bug to fix since 2012/10/24...)

### 1.3v [2019/09/19]

\* LaTeX 2019-10-01 release has made more

math macros robust. This applies in particular to the math accents and to the `\hbar`. This required for `mathastext` to adapt. Also `\leftarrowfill` and `\rightarrowfill` are now defined robust by the kernel, hence `mathastext` does the same. These changes are dropped if `mathastext` detects an older LaTeX format.

\* These LaTeX kernel changes motivated an examination of some redefinitions done (optionally) by `mathastext`:

- The user math alphabet macros got redefined as expanding to some other (robust) math alphabet macros, but were not robust in the strict sense. This does cause some issues for moving arguments in the context of multiple math versions, hence it was a bug. The special behavior of the math alphabet commands (they redefine themselves and other macros on first use) makes is somewhat problematic for `mathastext` to keep them updated across math versions and at the same time strictly LaTeX2e robust. Thus `mathastext` now requires the e-TeX primitive `\protected` and uses it for the definitions of the user level math alphabet macros.

- There are a number of `\mathchardef` tokens which (under certain options and/or configuration via the package user interface), `mathastext` redefines as macros. These macros cause no issue in moving arguments (they are not "fragile"), still it is probably better if they expand only at the time of typesetting. To this effect they are now also `\protected`: `\exists`, `\forall`, `\colon`, `\setminus`, `\mid`, `\prod`, `\sum`, `\imath`, `\jmath`.

- The macro `\vert` (which expands to a `\delimiter`) is now defined robust by LaTeX. Its `mathastext` redefinition is a `\protected` one rather.

- The `\{` and `\}` (which get redefined only under `\MTexplicitbracesobeymathxx` regime) are now strictly robust in the LaTeX2e sense (formerly they were `\let` to some robust macros, and this did not make them strictly LaTeX2e-robust entities).

\* The various changes in `mathastext` described in the previous item apply independently of the LaTeX release version. The LaTeX format itself requires the e-TeX extensions since 2015.

### 1.3u [2019/08/20]

\* new feature: the initial release dealt with only one font, and although shortly thereafter the 1.11 version added support for extended

math versions, it was documented that some font-dependent set-up (minus as endash, dotless i and j, hbar, math accents) was done only once. This release makes the relevant characters font encoding savvy in each mathastext-extended math version. Thus, they should render correctly even with multiple math versions using fonts with varying encodings.

This reinforces importance of using `\MTversion` and not the LaTeX `\mathversion` when switching to a new math version (which got declared via the package interface). The implementation is compatible with Unicode engines and mixed usage of TU encoding (OpenType fonts) with traditional 8bits TeX font encodings. For all engines, all used (8bits) encodings must have been passed as options to the `fontenc` package.

Thanks to Falk Hanisch for feature request and code suggestions.

- \* new option `unimathaccents`: this adds to option `mathaccents` the demand to use the text font accents for OpenType fonts in math mode via the `\Umathaccent` primitive. Indeed, as my testing showed that this gave non-satisfactory results both with XeTeX and LuaTeX regarding the horizontal placement of the accents, the main option `mathaccents` acts only on 8bits encoded fonts.

- \* bugfix: the `\Mathastext` without optional argument forgot to repeat some font-encoding dependent initialization set-up done originally during package loading.

- \* bugfix: under the subdued option macros `\MTmathactiveletters` or `\MTnonlettersobeymathxxx` now act like no-ops if issued explicitly while in the normal or bold math version. Formerly, this was not the case and could cause bugs such as a disappearing minus sign in math mode.

- \* bugfix: the letter `h` used in the `\hbar` obeyed the extra skips as set-up by `\MTsetmathskips`, badly interfering with the horizontal positioning of the bar accent. They are now ignored (as well as the added italic correction).

### **1.3t [2018/08/22]**

- \* bugfix: the 1.3s bugfix about subdued compatibility with `fontspec` was deficient.

- \* bugfix: very old (v1.2, 2012/12/20) bug causing low-level TeX error during package loading (with `pdflatex`) when setting up the math

minus sign to be the text font endash character, in cases with `\encodingdefault` other than OT1, T1 or LY1, e.g. something like T2A.

- \* `\imath` and `\jmath` obey the subdued regime. And the minus sign is now handled especially to ensure perfect compatibility with the subdued option.

- \* breaking change: `mathastext` does not redefine anymore `\i` and `\j` to let them be usable both in text and math mode.

### **1.3s [2018/08/21]**

- \* fix to an issue with subdued option in a `fontspec` context.

### **1.3r [2016/11/06]**

- \* documentation tweaks.

### **1.3q [2016/10/31]**

- \* new option `unicodeminus`.

- \* the Recent Changes section of the documentation has been removed as it was a duplicate of information available in the Change Log.

- \* some other changes in the documentation, in particular the use of straight quotes in verbatim.

### **1.3p [2016/05/13]**

- \* bugfix: release 1.3n had forgotten to activate by default its new customization of the `amsmath` macro `\newmcodes@` (it was done from using `\MTversion` in the document body but not by default at start of body.)

- \* public name `\MTfixmathfonts` for a 1.3o macro.

### **1.3o [2016/05/03]**

- \* `mathastext` fixes an issue related to a feature of LuaLaTeX and `luatofloat` that OpenType fonts are declared in one of two modes: node and base, and only the latter is functional in math mode. But by default text fonts are declared in mode node. Thus `mathastext` now intervenes to make it so that the font it declares in math mode will use mode base. This fixes issues with for example old style figures being used while the text font used lining figures (or vice versa, depending on the font). But see the code comments for more.

### **1.3n** [2016/04/22]

\* at long last, mathastext takes care properly of annoying and perplexing amsmath's `\newmcodes@`. The very recent change in amsopn.sty finally made it compatible with Unicode engines, but anyhow, mathastext must do its own patch to use the correct font. All of this taking into account the various options passed to the package. Lots of trouble for a tiny thing.

### **1.3m** [2016/04/02]

\* minor code maintenance before annual TL freeze.

### **1.3l** [2016/01/29]

\* compatibility with fontspec's upcoming switch from EU1/EU2 to TU common to both Unicode engines.

### **1.3k** [2016/01/24]

\* typos fixed in the documentation. In particular, the README link to the package homepage had remained broken from day one of the package releases: mathastext.html therein was misspelled as mathsastext.html ! (but the pdf documentation had the correct link; as well as the CTAN catalogue).

### **1.3j** [2016/01/15]

\* renamed and modified recent 1.3i's `\MTactivemathoff` into `\MTeverymathoff`. Added `\MTeverymathdefault`.

\* subdued mode is a bit stronger: also the asterisk reverts to the default (if it was modified due to option asterisk), the added extra `\mskip`'s (useful with upright fonts) for `,`, `\exists`, and `\forall` are suppressed rather than re-configured to use `0mu`. Related new commands `\MTexistsdoesskip`, `\MTforalldoesskip`, `\MTprimedoesskip`, `\MTnormalexists`, `\MTnormalforall`, `\MTnormalprime`.

\* the toggle for using mathematically active letters is only emitted once during package loading; the `\Mathastext` command does not do it anymore; the use in the preamble of `\MTmathstandardletters`, or `\MTnoicinmath` and related commands is not overruled by later use of `\Mathastext`.

\* quite a few documentation improvements and rewrites, particularly in the description of commands which are related to the modifications of `mathcodes` (mainly for math activation

of characters or letters) as done by `mathastext` at `\everymath` or `\everydisplay`.

### **1.3i** [2016/01/06]

\* `\url` from `url.sty` as well as `\url` and `\nolinkurl` from `hyperref.sty` use math mode and (by default) the monospace text font. To avoid `mathastext` overwriting the special preparation done by `{url,hyperref}.sty` the commands `\url/\nolinkurl` are patched to do automatically `\MTactivemathoff` (now `\MTeverymathoff`) before entering math mode.

\* the extra skips specified by `\MTsetmathskips` are not inserted around letters if inside the arguments of math alphabet commands, or within operator names.

\* the added explicit italic corrections (for non-oblique fonts) were disabled within math alphabet scopes, except `mathnormal`; they are now disabled within all math alphabets, inclusive of `mathnormal`.

### **1.3h** [2015/10/31]

\* bugfixes: since 1.3d 2014/05/23 the option `symbolgreek` caused `\ell` to become undefined, and, similarly but far worse, options `selfGreek`, `selfGreeks` caused all lowercase Greek letters `\alpha`, `\beta`, etc.. to become undefined.

### **1.3g** [2015/10/15]

\* following 2015/10/01 LaTeX release, removal of the "luatex" prefix from the names of the LuaLaTeX math primitives. Compatibility maintained with older LaTeX formats.

### **1.3f** [2015/09/12]

\* the replacement of amsmath's `\resetMathstrut@`, when it is done, emits an Info rather than a Warning as this could be potentially stressful to some users.

\* the README self-extracts from the dtx source, as a text file `README.md` with Markdown syntax.

### **1.3e** [2015/09/10]

\* bugfix: under option `nosmalldelims`, `\lbrace` and `\rbrace` were redefined as math symbols and could not be used as delimiters.

### **1.3d** [2014/05/23]

\* A 2015/02/26 edit to the documentation mentions the improved compatibility of `mathastext` with the latest (3.34)

beamer release: no more need for `\usefonttheme{professionalfonts}`.

\* new commands `\MTstandardgreek` and `\MTcustomgreek`.

\* The Greek letters, in case of use of one of the package related options, are left to their defaults in the normal and bold math versions if the subdued option was also used (this was so far the case only with options `LGR-greek/LGRgreeks`).

\* `\newmcodes@` of `amsmath` is left untouched if package `lualatex-math` is detected.

### 1.3c [2013/12/14]

\* added a starred variant to `\MTversion` which tells `mathastext` to only do the math set-up and not modify the text fonts.

\* added second optional version name argument to `\Mathastext` and to `\MTDeclareVersion`, to transfer settings for things not otherwise changed by `mathastext` from a math version to the one declared. This is mainly for symbols and large symbols to be the bold ones when the user sets up the series of a `mathastextified` font to be bold in a `mathastext-declared` version.

\* renamed `\defaultprod` to `\MToriginalprod`, `\defaultsum` to `\MToriginalsum`, (this is in case of option `symbolmisc`).

\* changes to the dtx organization; options for generating the documentation can be customized in generated `mathastext.tex` file.

\* 1.2d code for `\#`, `\$`, `\%`, and `\&` modified erroneously the earlier correct 1.2c code and created a bug showing up with more than 16 math families (a possibility only with `lualatex` or `xelatex`).

### 1.3a [2013/09/04]

\* the somewhat silly `\string's` are removed from the `\MTsetmathskips` command of release 1.3, thus allowing its first argument to be a macro, or any expandable code, giving a letter.

\* the `amsmath \resetMathstrut@`, which is incompatible with a mathematically active parenthesis ( is now modified only if necessary (i.e. `\@` only when `\MTnonlettersobeymathxx` is issued) and is restored to its original value if not needed anymore (i.e. after `\MTnonlettersdonotbeymathxx`, as for example when switching to the normal version under option `subdued`).

\* improved documentation.

### 1.3 [2013/09/02]

\* commands `\MTsetmathskips` and `\MTunsetmathskips` added.

\* commands `\MTmathactiveletters` and `\MTmathstandardletters` to govern the math activation of letters independently of its use for insertion of the italic corrections (`\MTicinmath` and `\MThicinmath` correspondingly modified).

\* the new `\luateXUmathcodenum` as available since TL2013 allows identical treatment by `mathastext` of = and - under both `LuaTeX` and `XeTeX`.

\* `\newmcodes@` of `amsmath` is left untouched in case of option `basic`.

\* a sentence containing | which was written to the log during the loading caused a problem if | was active (typically if `\MakeShortVerb{|}` was added to the preamble prior to the loading of `mathastext`).

\* some preemptive measures taken regarding things such as `\mid`, `\lbrace`, and `\rbrace`, as some packages define these things in manners which made the re-definitions done by `mathastext` issue errors.

### 1.2f [2013/01/21]

\* minor code improvements. Change log added to the user manual.

### 1.2e [2013/01/10]

This version should be the last one in the 1.2 series as it seems to correct most of the main problems which were introduced with the massive use of mathematically active characters in versions 1.2 and 1.2b.

\* It is indeed a thorny point when one wants to modify an active character in math mode only (without breaking usage in label's and ref's for example). The package now does that only if the activation originated in the Babel system as it is then possible to modify appropriately the Babel macros `\user@active<char>` and `\normal@char<char>`, at the time of entering math mode (`mathastext` does all its activation job at `\everymath` and `\everydisplay`).

The relevant issues are discussed in section 2.10 of the user manual, in the test file `mathastexttestalphabets.tex`, and in the source code comments for macro `\mst@mathactivate`. The

inherent incompatibility of Babel with packages having made mathematically active the characters itself makes document active is circumvented by this interference of mathastext. A generally applicable Babel patch could be derived from the method used by mathastext.

For the non catcode active characters, mathematical activation is used. This is done at the entrance in math mode.

- \* Sadly, the feature of added italic corrections introduced in version 1.2b did not behave as described in the user manual, due to forgotten group braces. Fixed.

- \* The command `\MTlowerast` from the user manual of v1.2d was not the one implemented in the source code. Fixed.

- \* The test files automatically extracted from a latex run on the dtx file have been revised and extended.

- \* The code is better documented.

#### **1.2d [2013/01/02]**

- \* an incompatibility with amsmath (its macro `\resetMathstrut@`), exists since version 1.2 of the package. This is fixed here.

- \* various improvements in dealing with the asterisk and in the mechanism of letting non-letter symbols obey the math alphabet commands.

- \* the noasterisk option is deprecated and made a no-op.

- \* documentation extended and improved.

#### **1.2c [2012/12/31]**

- \* mathastext now inserts automatically after all (latin) letters in math mode their italic corrections, if the font used is upright (sic). This improves the spacings for the positioning of subscripts. The feature is de-activated inside the math alphabets commands (apart from `\mathnormal`), so as to not prohibit the formation of ligatures.

- \* the documentation has been extended to explain in detail the issues which are relevant to the new feature of added italic corrections.

- \* version 1.2 had some bad bugs when confronted to active characters. This is corrected and additionally `\MTnonlettersdonotbeymathxx` is made the default, as the user input is too much constrained in its absence.

- \* a less fatal, but still annoying, typo had made the dot in 1.2 of type `\mathpunct` rather than `\mathord`.

- \* the inner namespace has been rationalized a bit.

#### **1.2 [2012/12/20]**

- \* a new command sets up the amount of space to be automatically inserted before the derivative glyph (useful when using an upright font).

- \* the scope of the math alphabets has been extended to apply to the non-alphabetical characters, and also to operator names.

- \* the format of the dtx file has changed. The package file is self-extracting from the dtx, and four additional test files are also produced during latex `mathastext.dtx`.

#### **1.15f and 1.15g [2012/10/25]**

- \* `\$, \#, \&, and \%` had been re-defined by mathastext since its inception in a rather strange (but working) way, which could cause surprises to other packages. Fixed.

- \* the subdued mechanism for the math alphabets is implemented in a simpler and more efficient manner than in 1.15e.

- \* the defaultxx options act a bit differently, and are more useful in case of a too many math alphabets situation.

- \* various improvements in the documentation.

- \* general clean up and better commenting of the source code.

#### **1.15e [2012/10/22]**

- \* new user commands to specify skip or glue to be inserted after the math symbols `\exists` and `\forall`

- \* complete (user transparent) rewrite of the code implementing the subdued option; and its action has been extended to apply also to the `\mathbf`, `\mathit`, `\mathsf`, `\mathtt` alphabets and not only to `\mathrm` and `\mathnormal` as in the previous versions.

- \* improvements in the documentation.

#### **1.15d [2012/10/13]**

- \* the Unicode situation is now correctly treated, throughout the code (this had been left

in a half-done way from version 1.14 of April 2011).

- \* this includes an issue related to amsmath and its DeclareMathOperator macro which has been fixed,
- \* and the code related to \relbar and \Relbar (and \models) has been revised.

#### 1.15c [2012/10/05]

- \* it is now possible to use distinct fonts in LGR encoding for the Greek letters according to the current math version.
- \* improvements to the documentation.

#### 1.15b

- \* corrected a 'feature' of 1.15 which was backward-incompatible
- \* improvements to the pdf documentation

#### 1.15 [2012/09/26]

- \* the subdued option allows the mathastextification to act only locally.
- \* some measures taken to deal with amsmath related issues when using xetex or luatex.

#### 1.14c

- \* a bug is fixed: the \Mathastext macro reinitializes the fonts in the normal and bold math versions, but it also erroneously redeclared the math alphabet changing commands which could have been set up in previously defined math versions (via earlier calls to \Mathastext\[version\\_name\]).

#### 1.14b [2011/04/03]

- \* there was a bug with \\$, #, &, % in math mode which showed up when ten or more math families had been declared. This bug affected also the minus sign under the same circumstances, when Unicode engines were used. Fixed.
- \* the options LGRgreek and selfGreek act now a bit differently, and new options LGR-greeks and selfGreeks have been defined.

- \* I also cleaned up a bit the code, for a more structured namespace.

#### 1.14

- \* mathastext now modifies also the math alphabets \mathit, \mathsf and \mathtt, thus making it a quite generic complete manner to adapt the math configuration to fonts provided with no math support.

#### 1.13d

- \* new macros \MTstandardgreek and \MTcustomgreek

#### 1.13b

- \* when the Symbol font is used for \prod and \sum this will be only for inline math; display math will use the default glyphs

#### 1.13 [2011/03/11]

- \* the LGRgreek option is added.
- \* internal changes for better readability of the code.

#### 1.12

- \* various bugs have been corrected.
- \* the endash and alldelims options are active by default.
- \* the package is more Unicode aware.
- \* the \Mathastext command has been improved to facilitate the mechanism of math versions also when using XeTeX or LuaTeX (with package fontspec.)
- \* the en-dash and dotless i and j now work with all encodings, Unicode inclusive.

#### 1.11 [2011/02/06]

- \* optional argument to \Mathastext macro.

#### 1.1 [2011/02/01]

- \* options italic and frenchmath.

#### 1.0 [2011/01/25]

- \* Initial version.

## 5 Implementation

The comments are a kind of palimpsest. Indeed they are not destined to the reader but to the author: when coming back to the source code perhaps years after having last looked at it, all bits of past information even if obsolete are useful. Not only comments but perhaps also some ancient parts of the code itself are a bit strange (the author hardly new any L<sup>A</sup>T<sub>E</sub>X at that time).

For about the same reason, there may be some long macro names which do not fit in the margins and that one sees only partially. The author sometimes has used a workaround to hyphenate, but not systematically. Life is time-limited. At 1.4 large chunks of code have been re-ordered but the global architecture is still somewhat of a mess and doing some such large diffs makes it sometimes difficult to follow small bits of code across commit history, so this is done reluctantly.

The usual catcode regime for letters and digits is assumed and some characters such as \*, ` , = are supposed to be of catcode other at the time of loading of **mathastext**. The source of **mathastext** takes precautions for some other characters such as the right quote ', which may thus be active with no harm at the time of loading (note added 2024/07/16: very hard to understand why I was so paranoid, but I have kept this annoying constraint).

By the way, I think L<sup>A</sup>T<sub>E</sub>X2e should have provided to authors a standard macro to be used at the beginning of a style file to make sure the catcodes are standard. Shorthands created by Babel should be mostly no problem as Babel does the activation only at the \begin{document}.

1.4 removes a few code branches still there for support to old L<sup>A</sup>T<sub>E</sub>X and requires L<sup>A</sup>T<sub>E</sub>X 2020-02-02 (which made \{ and \} \protected; earlier release 2019-10-01 had math macros such as the math accents and \hbar robust and so far we kept supporting both new and old contexts).

```
1 \NeedsTeXFormat{LaTeX2e}[2020/02/02]
2 \ProvidesPackage {mathastext}
3 [2024/07/27 v1.4b Use the text font in math mode (JFB)]
```

1.3zb avoids writing **mathastext** info messages also to console output, only log file. Make prefix occupy 20 not 25 characters for alignment with LaTeX Font Info, as the latter often issues info messages. For similar reason the usages of \PackageInfo will be done with empty lines above and below for better visual separation from the voluminous output of the L<sup>A</sup>T<sub>E</sub>X font system.

```
4 \def\mst@infoline#1{\immediate\write\m@ne
5 {(\space\space\space mathastext:\space\space\space) #1}}
6 \immediate\write\m@ne{}}
7 \PackageInfo{mathastext}{Starting the math mode configuration@gobble}
```

Testing for X<sub>E</sub>T<sub>E</sub>X and L<sub>UA</sub>L<sub>E</sub>T<sub>E</sub>X.

1.3g 2015/10/15: update for the naming of primitives, the situation has evolved both on X<sub>E</sub>T<sub>E</sub>X side and on the L<sub>UA</sub>L<sub>E</sub>T<sub>E</sub>X side (LaTeX base 2015/10/01): I was told "U" named math primitives were always available for L<sub>UA</sub>L<sub>E</sub>T<sub>E</sub>X. For X<sub>E</sub>T<sub>E</sub>X, the XeTeX prefix got replaced by U prefix with 0.99.. a certain number of 9. I opted for rather simple approach of just trying the "modern" names and if they don't exist fall back on earlier (and in danger of being deprecated) names.

```
8 \let\mst@Umathcharnumdef\Umathcharnumdef
9 \let\mst@Umathcodenum \Umathcodenum
10 \let\mst@Umathcode \Umathcode
11 \let\mst@Umathchardef \Umathchardef
12 \let\mst@Umathaccent \Umathaccent
13 \newif\ifmst@XeTeX
```

```

14 \ifx\XeTeXinterchartoks\undefined
15   \mst@XeTeXfalse
16 \else
17   \mst@XeTeXtrue
18 \ifx\mst@Umathcharnumdef\undefined
19   \let\mst@Umathcharnumdef\XeTeXmathcharnumdef
20   \let\mst@Umathcodenum  \XeTeXmathcodenum
21   \let\mst@Umathcode    \XeTeXmathcode
22   \let\mst@Umathchardef \XeTeXmathchardef
23   \let\mst@Umathaccent \XeTeXmathaccent
24 \fi
25 \fi
26 \newif\ifmst@LuaTeX
27 \ifx\directlua\undefined
28   \mst@LuaTeXfalse
29 \else
30   \mst@LuaTeXtrue
31 \ifx\mst@Umathcharnumdef\undefined
32   \let\mst@Umathcharnumdef\luatexUmathcharnumdef
33   \let\mst@Umathcodenum \luatexUmathcodenum
34   \let\mst@Umathcode   \luatexUmathcode
35   \let\mst@Umathchardef \luatexUmathchardef
36   \let\mst@Umathaccent \luatexUmathaccent
37 \fi
38 \fi
39 \newif\ifmst@XeOrLua
40 \ifmst@LuaTeX\mst@XeOrLuatrue\fi
41 \ifmst@XeTeX \mst@XeOrLuatrue\fi
1.4. I only checked this is correct with TL2024. The macro will be used with #1 a catcode 11
or 12 token or a one character control sequence such as \#.
42 \ifmst@XeTeX
43   \def\mst@OnlyIfNotMathActive#1{%
44     \ifnum\mst@Umathcodenum`#1="1FFFFF
45       \expandafter\@gobble
46     \else\expandafter\@firstofone
47     \fi
48   }
49 \else\ifmst@LuaTeX
50   \def\mst@OnlyIfNotMathActive#1{%
51     \ifnum\mst@Umathcodenum`#1="1000000
52       \expandafter\@gobble
53     \else\expandafter\@firstofone
54     \fi
55   }
56 \else
57   \def\mst@OnlyIfNotMathActive#1{%
58     \ifnum\mathcode`#1="8000
59       \expandafter\@gobble
60     \else\expandafter\@firstofone

```

```

61      \fi
62  }
63 \fi\fi

```

**1.2:** all inner macros of **mathastext** now starts with `\mst@` for a cleaner name-space.

**1.31** 2016/01/29: hmm... at this late stage where nobody would expect me to still look at the code, I have found at least two macros which still didn't: `\do@the@endashstuff` and `\do@the@emdashstuff`.

Ok, doing something more serious: compatibility with upcoming TL2016 fontspec and its switch to 'TU' NFSS font encoding in replacement of 'EU1/EU2' Anyhow, the code in **mathastext** has been common to the two Unicode engines for a while, hence it is not hard to adapt to the replacement of EU1/EU2 by TU, maintaining compatibility with legacy installations.

At **1.4** the support for obsolete EU1 and EU2 font encodings has been removed.

**\mst@OneifUniEnc** The `\mst@OneifUniEnc` is expandable but must be used after having set `\mst@tmp@enc...`

```

64 \def\mst@oti{OT1}
65 \def\mst@tu{TU}
66 \def\mst@OneifUniEnc{\ifx\mst@tmp@enc\mst@tu1\else0\fi}
67 \newif\ifmst@goahead
68 \newif\ifmst@abort

```

**\mst@enc** Macros to store the font settings, each math version will store its own records.

```

\mst@fam 69 \def\mst@enc{\encodingdefault}
\mst@ser 70 \def\mst@fam{\familydefault}
\mst@opsh 71 \def\mst@ser{\seriesdefault}
\mst@bold
\mst@ltsh \mst@opsh will hold default shape for operator names.
           \mst@ltsh will hold default shape for letters.

72 \def\mst@opsh{\shapedefault}
73 \def\mst@bold{\bfdefault}
74 \def\mst@ltsh{\shapedefault}

```

**\mst@greekfont** **1.15c:** for use by the LGRgreek and selfGreek options. Defined as an `\edef` in order to be able to set-up once and for all the Greek at the time of `\usepackage`. Modifiable in the preamble via `\MTgreekfont{\font_name}\Mathastext`.

```
75 \edef\mst@greekfont{\familydefault}
```

**Package options** 2011/03/09: **1.13** introduces the option LGRgreek and systematic use of `\if...` conditionals, for better readability (by myself) of the code.

**1.3y** of 2022/11/03 adds `ncccomma`, `binarysemicolon` and `frenchmath*` options.

**1.3za** adds `LGRgreek+` and `LGRgreeks+`.

**1.3zb** adds `decimalcomma` and modifies `frenchmath*` to use it. And provides `frenchmath+` as an alias to former `frenchmath*`. Consecutive to the change at v2.7 of `frenchmath` which replaced `ncccomma` by `decimalcomma` and broke the compatibility recipe explained in subsubsection [1.4.13](#).

**1.4** adds options `everymath` and `activedigits`.

**1.4b** adds `noletters`.

```

76 \newif\ifmst@italic
77 \newif\ifmst@frenchmath
78 \newif\ifmst@ncccomma

```

```

79 \newif\ifmst@decimalcomma
80 \newif\ifmst@binarysemicolon
81   \DeclareOption{italic}{\mst@italictrue
82     \def\mst@ltsh{\itdefault}}
83   \DeclareOption{frenchmath}{\mst@frenchmathtrue\mst@italictrue
84     \def\mst@ltsh{\itdefault}}
85   \DeclareOption{ncccommat}{\mst@ncccommattrue}
86   \DeclareOption{decimalcommat}{\mst@decimalcommattrue}
87   \DeclareOption{binarysemicolon}{\mst@binarysemicolontrue}
88   \DeclareOption{frenchmath*}{\mst@frenchmathtrue\mst@italictrue
89     \def\mst@ltsh{\itdefault}\mst@decimalcommattrue\mst@binarysemicolontrue}
90   \DeclareOption{frenchmath+}{\mst@frenchmathtrue\mst@italictrue
91     \def\mst@ltsh{\itdefault}\mst@ncccommattrue\mst@binarysemicolontrue}
92 \newif\ifmst@endash\mst@endashtrue
93   \DeclareOption{endash}{\mst@endashtrue}
94   \DeclareOption{noendash}{\mst@endashfalse}
95 \newif\ifmst@emdash
96   \DeclareOption{emdash}{\mst@emdashtrue\mst@endashfalse}
97 \newif\ifmst@alldelims
98 \edef\mst@tmp{\encodingdefault}\ifx\mst@oti\mst@tmp\else\mst@alldelimstrue\fi
99   \DeclareOption{alldelims}{\mst@alldelimstrue}
100   \DeclareOption{nolessnomore}{\mst@alldelimsfalse}
101 \newif\ifmst@nosmalldelims
102   \DeclareOption{nosmalldelims}{\mst@nosmalldelimstrue}
103 \newif\ifmst@noplus
104   \DeclareOption{noplus}{\mst@noplustrue}
105 \newif\ifmst@nominus
106   \DeclareOption{nominus}{\mst@nominustrue}
107 \DeclareOption{noplusnominus}{\ExecuteOptions{noplus,nominus}}
108 \newif\ifmst@noparen
109   \DeclareOption{noparenthesis}{\mst@noparenttrue}
110 \newif\ifmst@nopunct
111   \DeclareOption{nopunctuation}{\mst@nopuncttrue}
112 \newif\ifmst@noequal
113   \DeclareOption{noequal}{\mst@noequaltrue}
114 \newif\ifmst@noexclam
115   \DeclareOption{noexclam}{\mst@noexclamtrue}
116 \newif\ifmst@asterisk
117   \DeclareOption{asterisk}{\mst@asterisktrue}
118 \newif\ifmst@nospecials
119   \DeclareOption{nospecials}{\mst@nospecialstrue}
120 \newif\ifmst@basic
121   \DeclareOption{basic}{\mst@basictrue
122     \ExecuteOptions{noparenthesis,nopunctuation,%
123                   nospecials,nolessnomore}}
124 \newif\ifmst@nohbar
125   \DeclareOption{nohbar}{\mst@nohbartrue}
1.4 adds option activedigits.
126 \newif\ifmst@activedigits

```

```

127      \DeclareOption{activedigits}{\mst@activedigitstrue}
128 \newif\ifmst@nodigits
129      \DeclareOption{nodigits}{\mst@nodigitstrue}
130 \newif\ifmst@defaultimath
131      \DeclareOption{defaultimath}{\mst@defaultimathtrue}

1.4b adds option noletters.

132 \newif\ifmst@noletters
133      \DeclareOption{noletters}{\mst@noletterstrue\ExecuteOptions{nohbar,defaultimath}}
134 \newif\ifmst@mathaccents
135      \DeclareOption{mathaccents}{\mst@mathaccentstrue}
136 \newif\ifmst@unimathaccents
137      \DeclareOption{unimathaccents}{\mst@mathaccentstrue\mst@unimathaccenttrue}
138 \newif\ifmst@needsymbol
139 \newif\ifmst@symboldelimiters
140      \DeclareOption{symboldelimiters}{\mst@needsymboltrue\mst@symboldelimiterstrue}
141 \newif\ifmst@symboldigits
142      \DeclareOption{symboldigits}{\mst@needsymboltrue\mst@symboldigitstrue}
143 \newif\ifmst@symbolgreek
144 \newif\ifmst@customgreek
145      \DeclareOption{symbolgreek}{\mst@needsymboltrue\mst@symbolgreektrue
146                                \mst@customgreektrue }
147 \newif\ifmst@symbolre
148      \DeclareOption{symbolre}{\mst@needsymboltrue\mst@symbolretrue}
149 \newif\ifmst@symbolmisc
150      \DeclareOption{symbolmisc}{\mst@needsymboltrue\mst@symbolmisctrue}
151      \DeclareOption{symbol}{\ExecuteOptions{symbolgreek,symbolmisc,symbolre}}
152      \DeclareOption{symbolmax}{\ExecuteOptions{symbol,symboldelimiters}}
153 \newif\ifmst@needeuler
154 \newif\ifmst@eulerdigits
155      \DeclareOption{eulerdigits}{\mst@needeulertrue\mst@eulerdigitstrue}
156 \newif\ifmst@eulergreek
157      \DeclareOption{eulergreek}{\mst@needeulertrue\mst@eulergreektrue
158                                \mst@customgreektrue }
159 \newif\ifmst@selfGreek
160      \DeclareOption{selfGreek}{\mst@selfGreektrue\mst@customgreektrue}
161 \newif\ifmst@selfGreeks
162      \DeclareOption{selfGreeks}{\mst@selfGreekstrue\mst@selfGreektrue
163                                \mst@customgreektrue }
164 \newif\ifmst@LGRgreek
165      \DeclareOption{LGRgreek}{\mst@LGRgreektrue\mst@customgreektrue}
166 \newif\ifmst@LGRgreeks
167      \DeclareOption{LGRgreeks}{\mst@LGRgreekstrue\mst@LGRgreektrue
168                                \mst@customgreektrue}
169 \newif\ifmst@greekplus
170      \DeclareOption{LGRgreek+}{\ExecuteOptions{LGRgreek}\mst@greekplustrue}
171      \DeclareOption{LGRgreeks+}{\ExecuteOptions{LGRgreeks}\mst@greekplustrue}
172 \def\mst@greek@select{0}
173 \newif\ifmst@itgreek
174 \newif\ifmst@upgreek

```

```

175 \DeclareOption{itgreek}{\mst@itgreektrue}
176 \DeclareOption{upgreek}{\mst@upgreektrue}
177 \DeclareOption{itGreek}{\def\mst@greek@select{1}}
178 \DeclareOption{upGreek}{\def\mst@greek@select{2}}

```

Starting with 1.15f the meaning of the ‘defaultxx’ options has changed. They now prevent `mathastext` from defining additional alphabets rather than prevent it from identifying the ‘mathxx’ with the new ‘Mathxx’. The ‘Mathnormal’ and ‘Mathrm’ alphabet commands are always created as they are SymbolFontAlphabets.

This was again changed at 1.3za. The additional alphabets are always declared, the options only prevent mapping the existing ‘mathxx’ to the new ‘Mathxx’. This may be breaking change if people used these options because they had a need for the `\Mathbf` etc... names.

```

179 \newif\ifmst@defaultnormal
180   \DeclareOption{defaultnormal}{\mst@defaultnormaltrue}
181 \newif\ifmst@defaultrm
182   \DeclareOption{defaultrm}{\mst@defaultrmtrue}
183 \newif\ifmst@defaultbf
184   \DeclareOption{defaultbf}{\mst@defaultbftrue}
185 \newif\ifmst@defaultit
186   \DeclareOption{defaultit}{\mst@defaultittrue}
187 \newif\ifmst@defaultsf
188   \DeclareOption{defaultsf}{\mst@defaultsftrue}
189 \newif\ifmst@defaultttt
190   \DeclareOption{defaultttt}{\mst@defaultttttrue}

```

Here and elsewhere 1.3za has removed an `\ifmst@nonormalbold` conditional.

```

191 \DeclareOption{defaultalphabets}{\ExecuteOptions{defaultnormal,defaultrm,%
192 defaultbf,defaultit,defaultsf,defaultttt}}

```

`mathastext` considers the default script and especially scriptscript sizes to be far too small, and it will modify them. An option maintains the default.

```

193 \newif\ifmst@defaultsizes
194   \DeclareOption{defaultmathsizes}{\mst@defaultsizestrue}
195 \newif\ifmst@twelve
196   \DeclareOption{12pt}{\mst@twelvetrue}
197 \newif\ifmst@fouriervec
198   \DeclareOption{fouriervec}{\mst@fouriervectrue}

```

1.15: the subdued option.

```

199 \newif\ifmst@subdued
200   \DeclareOption{subdued}{\mst@subduedtrue}

```

1.4: the everymath option.

```

201 \newif\ifmst@everymath
202   \DeclareOption{everymath}{\mst@everymathtrue}
203 \PackageWarningNoLine{mathastext}{%
204   `everymath\string' will be removed at next major release.\MessageBreak
205   Please report to the author the circumstances\MessageBreak
206   which mandated its use in the present document}%
207 }

```

**1.3q:** the `unicode` option. Thanks to Tobias BRINK for suggesting its incorporation. The parsing of `\CurrentOption` does not seek any robustness, it just does its job if the option is used correctly.

```

208 \def\mst@unicodeminus {2013}
209 \def\mst@checkoption #1unicodeminus#2\mst@#3\mst@@
210   {\ifx\\#3\\\PackageWarningNoLine{mathastext}
211     {Unknown option `\\CurrentOption\\string'}\else
212     \ifx\\#2\\\def\mst@unicodeminus {2212}\else
213       \expandafter\def\expandafter\mst@unicodeminus\expandafter{\@secondoftwo#2}%
214     \fi\fi}
215 \DeclareOption*%
216   {\expandafter\mst@checkoption\CurrentOption\mst@ unicodeminus\mst@\mst@@}

217 \ProcessOptions\relax

```

`\mst@DeclareMathAccent` I somehow missed realizing L<sup>A</sup>T<sub>E</sub>X 2019-10-01 if used together with `amsmath` made repeated usage of `\DeclareMathAccent` trigger an error: <https://github.com/latex3/latex2e/issues/216>.

This broke usage of `\Mathastext` macro in preamble.

**1.3w** works around this via `\mst@DeclareMathAccent`. And other changes were made in `mathastext` code to cope with these complications around robustness.

```

218 \def\mst@DeclareMathAccent#1{\let#1\mst@undefined
219   \expandafter
220   \let\csname\expandafter\gobble\string#1\space\endcsname\mst@undefined
221   \DeclareMathAccent{#1}}

```

`\mst@normalversionname` Helper macros to test math version names. User is not allowed to redefine via `\Mathastext` with optional argument or via `\MTDeclareVersion` the `normal` and `bold` math versions. Added at **1.3w**, about 7 years late.

```

222 \def\mst@normalversionname{normal}%
223 \def\mst@boldversionname{bold}%

```

`\mst@OnlyIfNotSubdued` **1.3u** adds this check that we are not in a subdued normal or bold math version. We do not push the `#1` out of the TeX conditionals, and anyhow there was no real need for expandable coding.

```

224 \def\mst@OnlyIfNotSubdued#1{%
225   \ifmst@subdued
226     \ifx\math@version\mst@normalversionname
227     \else
228       \ifx\math@version\mst@boldversionname
229       \else
230         #1%
231       \fi
232     \fi
233   \else
234     #1%
235   \fi
236 }%

```

`\exists` **1.15e** 2012/10/21: math skip/glue *after* `\exists` and `\forall`, this is useful with upright letters

in math mode. Each math version has its own user defined values for the skips, stored as macros.

`\forall`

`\exists`

`\MTexists`

`\MTexistsdoesskip`

`\MTnormalforall`

`\MTforalldoesskip`

The redefinitions of  $\exists$  and  $\forall$  are done only at the end of the package as the `symbol` option will also want to redefine these math symbols.

The subdued option (later and only for the normal and bold math version) and the italic option (here) set to zero the package default skips. With [1.2](#) the skips can be modified on the fly in the document, they are not necessarily set in the preamble once and for all for each math version.

[1.3j](#) adds `\MTnormalexists`, `\MTexistsdoesskip`, `\MTnormalforall`, `\MTforalldoesskip`.

Earlier to [1.3j](#), `\let\mst@exists@original\exists` was done at End of Package, now it is done at Begin Document, and same for `\forall`. We pay attention that use of `\MTnormalexists` etc... inside the preamble does not create self-let's.

Also subdued mode will do `\MTnormalexists`, `\MTnormalforall` (earlier than [1.3j](#), it only set the muskips to `0mu`.) Same when using `\MTversion{normal}`, if subdued.

For some (random, legacy) reason, the handling of  $\exists$  and  $\forall$  is part of the things not included inside `\everymath`/`\everydisplay`.

[1.3v](#) The `mathastext`-defined `\exists` and `\forall` are created `\protected`. We feel this matches better with their default definition as `\mathchardef` tokens than dealing with L<sup>A</sup>T<sub>E</sub>X2e robust macros. Besides, the coding is simpler.

```

237 \newmuskip\mst@exists@muskip
238 \newmuskip\mst@forall@muskip
239 \def\mst@exists@skip{1mu}
240 \def\mst@forall@skip{.6667mu}
241 \ifmst@italic\ifmst@frenchmath\else
242   \def\mst@exists@skip{0mu}
243   \def\mst@forall@skip{0mu}
244   \def\mst@prime@skip {0mu}
245 \fi\fi
246 \protected\def\mst@exists{\mst@exists@original\mskip\mst@exists@muskip}
247 \protected\def\mst@forall{\mst@forall@original\mskip\mst@forall@muskip}
248 \AtBeginDocument{%
249   \let\mst@exists@original\exists
250   \let\mst@forall@original\forall
251   \def\MTnormalexists {\let\exists\mst@exists@original }%
252   \def\MTexistsdoesskip {\let\exists\mst@exists }%
253   \def\MTnormalforall {\let\forall\mst@forall@original }%
254   \def\MTforalldoesskip {\let\forall\mst@forall }%

```

The document body starts in the normal math version, whether or not `\Mathastext` command as been used in the preamble (which either re-defines the normal/bold math version or defines another one in case of optional argument), and in case of `subdued` option should use the standard  $\forall$  and  $\exists$ .

```

255 \ifmst@subdued
256 \else
257   \MTexistsdoesskip
258   \MTforalldoesskip
259 \fi
260 }%
261 \newcommand*\MTnormalexists {\AtBeginDocument {\MTnormalexists } }
262 \newcommand*\MTexistsdoesskip {\AtBeginDocument {\MTexistsdoesskip } }
263 \newcommand*\MTnormalforall {\AtBeginDocument {\MTnormalforall } }

```

```

264 \newcommand*\MTforalldoesskip {\AtBeginDocument {\MTforalldoesskip }}

\prime 1.2 2012/12/17: math skip/glue before the \prime glyph. This is useful with the default CM
\mst@prime@skip   glyph and upright letters (in contrast the prime from txfonts works fine with upright letters).
\active@math@prime For this we replace the LATEX kernel \active@math@prime with our own skip-enhanced version
\MTnormalprime  \mst@active@math@prime.

\MTprimedoesskip 1.2b 2012/12/31: doing

```

{\catcode`'=active \global\let'\mst@active@math@prime}

is awfully wrong when the right quote is made active at begin document by some other package  
(as happens with babel for some languages). So **mathastext** treats now the right quote with  
the same method as applied to the other characters it makes mathematically active. This uses  
the macro \mst@mathactivate which is defined later in the package.

Babel does \let\prim@s\bbl@prim@s when ' is made active via its services (the czech and  
slovak languages also store the initial version of \prim@s, else the quote would not work correctly  
when being again of catcode 12), and it doesn't matter if **mathastext** is loaded before or  
after this happens, as the \mst@mathactivate does its job only as part of the \everymath and  
\everydisplay token lists.

1.2e being paranoid, we take precautions against a possibly catcode active right quote at the  
time of loading mathastext.

1.3i adds \MTactiveprime.

1.3j renames it to \MTprimedoesskip. Besides, it makes use in the preamble of \MTnormal-  
prime or \MTprimedoesskip.

1.4 adds the support for the new “non-everymath” implementation, which has to satisfy to  
very different constraints.

The \MTprimedoesskip is not a no-op in subdued math version. This is legacy situation, not  
changed at 1.4.

```

265 \newmuskip\mst@prime@muskip
266 \def\mst@prime@skip{.5mu}
267 \ifmst@italic\ifmst@frenchmath\else\def\mst@prime@skip{0mu}\fi\fi

```

Shouldn't I have rather hacked \prim@s? (answer: perhaps related to Babel see a comment  
above).

TODO: clarify why I used \sp not ^ in \mst@active@math@prime in 2012/2013.

TODO: clarify why I am paranoid regarding the ' catcode here.

The everymath branch was initially superficially refactored at 1.4, but unfortunately as  
\mst@mathactivate had been modified to not handle mathematically active characters, this  
meant that the **mathastext** feature of extra math skip was lost under the **everymath** option,  
due to an oversight by the author. For this among other reasons having mainly to do with code  
comments we did 1.4a.

At 1.4 we can not go via \mst@mathactivate (defined further down in the code) which filters  
out the already mathematically active characters.

Why am I paranoid here about ' catcode at package loading time? (this looks ridiculous...).

```

268 \def\mst@tmp#1{%
269 \def\mst@mathactivateprime{%
270   \ifnum\catcode`#1=\active
271     \@ifundefined{active@char#1}{%
272       {}%
273     {\mst@do@activecase #1{}{\mst@active@math@prime}}%
274   \else

```

```

275      \mst@mathactivate #1{}{\mst@active@math@prime}%
276  \fi
277 }%
The “undo” is needed at 1.4 (but not if everymath).
278 \def\mst@undo@mathactivateprime{\mst@mathdeactivate#1{"8000}}%
279 }\expandafter\mst@tmp$string'
280 \def\mst@active@math@prime{\sp\bgroup\mskip\mst@prime@muskip\prim@s}
281 \ifmst@everymath
282   \newcommand*\MTnormalprime {\let\mst@modifyprime\empty}
283   \newcommand*\MTprimedoesskip{\let\mst@modifyprime\mst@mathactivateprime}%
284   \AtBeginDocument{%
285     \everymath\expandafter
286       {\the\everymath \mst@modifyprime \MTnormalprime}%
287     \everydisplay\expandafter
288       {\the\everydisplay \mst@modifyprime \MTnormalprime}%
MEMO: subdued case will do its own \MTnormalprime at \begin{document} later as part of
\MTeverymathoff.
289   \MTprimedoesskip
290 }
291 \else
1.4 must do things a bit differently.
292   \newcommand*\MTnormalprime {\mst@undo@mathactivateprime}
293   \newcommand*\MTprimedoesskip{\mst@mathactivateprime}
MEMO: subdued case will do its own \MTnormalprime at \begin{document} later as part of
\MTeverymathoff.
294   \AtBeginDocument{\MTprimedoesskip}
295 \fi

```

`\MTexistsskip` 1.15e: These user macros set up the amount of muglue after `\exists` or `\forall`. The normal and bold math versions inherit the same skips; these skips are set to zero in case of the subdued, or the italic option. Each command `\Mathastext[<version_name>]` stores the current values in the definition of the math version.

1.2: `\MTprimeskip` added, the silly `\onlypreamble` are removed and the macros are modified to have immediate effect in the document, independently of their possible use in the preamble for the math versions to store values.

Note (september 2013): the names were badly chosen; `\MTsetprimeskipto` for example would have been a better choice.

```

296 \newcommand*\MTexistsskip[1]{\edef\mst@exists@skip{\#1}%
297   \mst@exists@muskip\mst@exists@skip\relax}
298 \newcommand*\MTforallskip[1]{\edef\mst@forall@skip{\#1}%
299   \mst@forall@muskip\mst@forall@skip\relax}
300 \newcommand*\MTprimeskip[1]{\edef\mst@prime@skip{\#1}%
301   \mst@prime@muskip\mst@prime@skip\relax}
302 \let\Mathastextexistsskip\MTexistsskip
303 \let\Mathastextforallskip\MTforallskip
304 \let\Mathastextprimeskip\MTprimeskip
305 \let\mathastextexistsskip\MTexistsskip

```

```

306 \let\mathastextforallskip\MTforallskip
307 \let\mathastextprimeskip\MTprimeskip

\resetMathstrut@ 2012/12/31: The amsmath macro \resetMathstrut@ is not compatible with a mathematically active opening parenthesis: it does
    \mathchardef\@tempa\mathcode`\\(\relax
and is made a part of the hook \everymath@size inside \glb@settings. This is called from \check@mathfonts which is done in particular in \frozen@everymath, hence before (but wait) what mathastext puts in \everymath. Also, \glb@settings is triggered by \mathversion which must be done outside of math mode.

Alas, with things such as $... \hbox{...$...}...$ mathastext will have already made the parenthesis (mathematically) active. And \boldsymbol from amsbsy disables the \@nomath switch and executes \mathversion{bold} directly in math mode. So we have a problem with \resetMathstrut@.

lualatex-math replaces \resetMathstrut@ with its own version (which also looks at )) and no error is signaled when mathastext has done \mathcode`("=8000, but the \Mathstrutbox@ created by mathastext is then wrong.

The replacement macro avoids a potentially math active (. It assumes that there is still some appropriate glyph in slot 40 of operators and it sets the height and depth of \Mathstrutbox@ to be large enough to accomodate both this glyph and the one from the mathastext font (both in the current math version). If option noparenthesis was used, we leave everything untouched.

In 1.3a, 2013/09/04, the modification is done only at the time of \MTnonlettersobeymathxx. It is canceled by \MTnonlettersdonotobeymathxx. So the code has been moved to these macros and here we just store at the begin document the then meaning of \resetMathstrut@, and check also if \MTnonlettersobeymathxx has been invoked in the preamble.

1.3f 2015/09/12 issues only an Info message not a Warning, as I am becoming aware from another context (etoc) that Warnings are stressful to users, in some integrated environments for editing and compiling LATEX source files.

1.4 adds here an \AtEndOfPackage. As this must be executed (if not in the legacy everymath context) after the redefinition of \MTnonlettersobeymathxx which happens at begin document.

308 \ifmst@noparen\else
309 \AtEndOfPackage{%
310   \AtBeginDocument{%
311     \@ifundefined{resetMathstrut@}%
312     {}%
313     {}%
314     \let\mst@savedresetMathstrut@\resetMathstrut@}

The \ifx\mst@the\the is true iff \MTnonlettersobeymathxx was used in preamble (last compared to \MTnonlettersdonotobeymathxx). Setting \mst@the to \@gobble here will cause \MTnonlettersobeymathxx to indeed modify \resetMathstrut@ (and it resets \mst@the to \the for its behavior in \everymath).

315   \ifx\mst@the\the
316     \let\mst@the\@gobble
317     \MTnonlettersobeymathxx
318   \fi
319 }%
320 }%
321 }%
322 \fi

```

**1.2** 2012/12/20 does some rather daring *math* activation of ; , : ! ? + - = < > ( ) [ ] in math mode to achieve something I wanted to do since a long time: overcome the mutually excluding relation between the variable-family concept and the automatic spacing concept. After loading **mathastext**, these characters now obey the math alphabets commands but still have the automatic spacing. The use as delimiters for those concerned is also ok.

The activation is done via setting the `\mathcode` to "8000 through the macro `\mst@mathactivate` which in turn is put into the `\everymath` and `\everydisplay` token lists. No character is made active in the sense of the `\catcode` (the issues with catcode active characters at the entrance of the math mode are discussed later),

but the concerned characters will now expand in math mode to *two* tokens.

**1.2c** 2012/12/31: hence, this current implementation puts constraints on the input: `$x^?$` or `$x\mathrel?y$` now create errors. They must be input `$x^{?}$`, respectively `$x\mathrel{?}y$`.

The disactivating macro `\MTnonlettersdonotobeymathxx` is made the default.

The mechanism is (even more) off by default for `\{` and `\}` as this is not compatible with their use as delimiters (`\lbrace` and `\rbrace` should be used instead) but it can be activated for them too.

**1.2b** 2012/12/30: there were bad oversights in the **1.2** code for `\mst@mathactivate` related to the possibility for some characters to have been made active (in the sense of the `\catcode`) elsewhere (something which often is done by language definition files of the **babel** system). The code from v1.2b tried to provide correct behavior using a prefix called `\mst@fork` (its definition and its use has since been modified) which let the active character expand to the **mathastext** re-definition *only* in math mode and *only* if `\protect` was `\@typeset@protect`. This indeed took care of situations such as `$\hbox{?}$` with an active `?` or `$\label{eq:1}$` with an active `:` (assuming for the latter that things would have worked ok before the twiddling by **mathastext**).

**1.2e** 2013/01/09: alas `$\ref{eq:1}$` still was a problem. Indeed in that case the **mathastext** prefix had no means to know it was inside a `\ref` so it made the character expand to its **mathastext** redefinition, which is not acceptable inside a `\csname... \endcsname`. What happens with Babel is that it patches things such as `\ref`, `\newlabel...` we can test the `\if@safe@actives` flag to detect it in that case, but this is Babel specific. After having thought hard about this I see no general solution except patching all macros such as `\ref...`(in an imitation of what Babel does). So the final decision is to not do anything when the character is `\catcode active` *except* it it seems that Babel is behind the scenes.

Incidentally, Babel and TikZ are buggy with characters which are `\mathcode active`s. For example the combination of `[french]{babel}` and `mathtools` with its `centercolon` turns `$:$` into an *infinite loop* !!

In the case of Babel the reason is that, generally (but not always, the right quote ' is an exception), the `\normal@char<char>` fall-back is `\string<char>`. But this is wrong if the `\mathcode` is 32768! The fall-back becomes the default if the user switches to a language where `<char>` is 'normal' and then an infinite loop arises.

As a further example (I am not familiar with other languages from the Babel system) with `frenchb` the active `!?:` expand in math mode to `\string!` or `? or ; or :`. This creates an infinite loop if the `\mathcode` is 32768.

For the special case of the right quote ' when it is made active by Babel, its fall-back does not invoke `\string'` so being still of `\mathcode 32768` is not a problem.

I have posted online how Babel should possibly modify its definitions and I use this here. I simplify a bit my proposed replacement of `\normal@char<char>` as the check for `\protect` is superfluous, I think, having been done already at the level of the Babel prefix.

Replacing `\user@active<char>` is indeed not enough, and `\normal@char<char>` also must be

changed, because when the user switches back to a language where the character is ‘normal’ it remains catcode active. The crucial thing is the test of `\if@safe@actives` in the replacement of the `\normal@char<char>`, besides of course the test for math mode in both replacements.

When the character is not catcode active, then `mathastext` uses the math activation method. As the mathcode is not looked at in `\edef`, `\write` or inside `\csname... \endcsname` nothing special needs to be done, I think, in terms of protection against premature expansion. (I did not know that initially).

So, to recapitulate, `mathastext` will use the mechanism of the active `mathcode` if the character is not `catcode` active, and in the opposite case will do something only in the context of Babel, modifying directly its `\user@active<char>` and its `\normal@char<char>` macros and it does NOT then set the `mathcode` to 32768!!], rather it makes *sure* the character is not mathematically active.

As `1.2e` is a bit paranoid it takes precautions against the possibility of characters it treats being active at the time of its loading. Excepted from the scope of the paranoia are the latin letters (that would be crazy!) and also \*, " and the left quote `.

`1.2f` 2013/01/21 with earlier versions (\*) it was important not to do twice the business of `\mst@mathactivate` (think `$\hbox{$?$$}`), so I used (this was a bit wasteful) some sort of boolean macro for each character. But now that there are the `\mst@the..` prefixes, let’s just use them! (don’t know why I did not think of that earlier; perhaps I had in mind some more general character per character customization initially, which I just dropped.)

(\*) it is still important to not do twice the thing when the character is active, in which case the `babel` macros are patched.

As an aside, `$\hbox{\catcode`?=\\active $?$$}` for an ? which was unactive at the first \$ will just make `mathastext` overwrite the definition (assumed here to have been done earlier) of an active ?, but the result is that the inner ? can not be used in `\label` or `\ref`. So testing for active characters should be done always... many things should be done always... I leave as is.

`1.3i` 2016/01/06 removes a spurious end of line space in `\mst@mathactivate` (did not show as anyhow done in math mode).

`1.4` has significantly refactored the coding, there were simplication from a changed way to use `\mst@mathactivate` for letters and added branches to accomodate the renouncement to `\everymath`.

`\mst@do@activecase` Called by `\mst@mathactivate` if #1 is catcode active.

Check if token activation originates apparently into `babel`:

- if NO, nothing is done. The active meaning of #1 is not modified.
- if YES, we hook into `babel` associated macros so that in math mode the catcode active token does what `mathastext` expects it to do. Its `mathcode` is set to the one of the associated `\mathalpha` symbol as declared by `mathastext`, except for asterisk and right tick which simply use their ascii number as `mathcode`.

In the case of `babel-spanish` which has a catcode active right tick, resetting its `mathcode` has the advantage to reveal in output the case of a faulty input using the curly right tick U+8217 which one can get easily from copy paste, for example from the `babel-spanish.pdf` file.

And in general it is dangerous to have a character both catcode active and `mathcode` active.

Some auxiliaries.

```
323 \def\mst@magic@v #1#2#3#4#5{#1#3#4}
324 \def\mst@magic@vi #1#2#3#4#5#6{#1#2#4#5}
325 \def\mst@fork{\ifmmode\mst@magic@v\fi\@thirdoftree}
326 \def\mst@safefork{\ifmmode\if@safe@actives\else\mst@magic@vi\fi\fi\@thirdoftree}
```

Some refactoring (and streamlining) at 1.4 here. There was at some point in the case of a Babel-active token a special hanlding for #1 to use `\MTmathcharletter#1` (and event for digits!). But this is almost impossible to arise in practice:

- Babel commands to set up a shorthand are preamble only (they use `\AtBeginDocument`),
- A shorthand is made active at begin document, and we don't want that for a letter!
- Activation is recorded as an instruction in the `.aux` file which breaks it almost surely (except perhaps for letter Z or such not likely to appear in macro names in the `.aux` file).
- Even if we somehow hack against that (which I did to test) a more subtle problem arises that Babel updates `\nfss@catcodes`, so that the latter will want to make (e.g.) a of catcode 12! This causes breakage very easily at the time of `\process@table` almost as easily as with the a set to be an active character...

#1 here is a character token of catcode 11 or 12. We do something only if the catcode activation appears to have been triggered by `babel`. The test has been moved earlier at 1.4.

```
327 \def\mst@do@activecase#1#2#3{%
```

As letters and digits are impossible here, #2 is either empty (which happens only now for asterisk and right tick) or a single token (`\mathclose`, `\mathopen`,... ). When #2 is not empty, #3 is always a mathchar token. For safety we make sure then the mathcode is not active.

The rationale is to avoid context where people have both catcode and math active and use `\string`. In the case of `babel-spanish` with `activeacute` option it allows to reveal more easily input errors using curly right tick U+8217.

Arguably I probably mainly wanted to do this if the character was found catcode active but not a Babel shorthand. But it ended into the Babel branch and the non-Babel branch for active catcode is to do nothing.

#2 is empty exactly for the case of the right tick and the asterisk. In all other cases, then #3 is a mathchar token.

```
328     \ifx\relax #2\relax\mathcode`#1=\#1\relax\else\mathcode`#1=\#3\relax\fi
```

Less `\expandafter`'s at 1.4. Also, it is now required to make sure:

- not do it twice in succession (else infinite loop),
- and undo it when deactivating.

This was easily done under legacy code (now only used under `everymath` option, and only for non-letters) as it activated only when entering into math mode.

This is more annoying when activation happens in an uncontrolled scope, and we handle this via a `\mst@hackedshorthand@<char>` flag.

MEMO: the undoing is done in `\mst@mathdeactivate` which is invoked only for those non-letters submitted to `\mst@mathactivate`.

```
329     \ifmst@everymath\else\@ifundefined{\mst@hackedshorthand@#1}{\fi
330     \expandafter\let\csname mst@orig@user@active#1\expandafter\endcsname
331             \csname user@active#1\endcsname
332     \expandafter\let\csname mst@orig@normal@char#1\expandafter\endcsname
333             \csname normal@char#1\endcsname
334     \ifmst@everymath\else\{}\fi
```

No more `\edef`'s at 1.4. At this release, in letter case #3 is empty and #2 is a single token which needs no extra brace pair as this brace pair will come from its expansion. We can use `{#2}{#3}` in all cases rather than either `{#2#3}{}{}` versus `{#2}#3` depending on whether #1 is letter or not as was done in the past. Attention that #2 and #3 may each be empty.

```
335     \def\mst@tmp##1##2{\def##1{\mst@fork{#2}{#3}##2}}%
336     \expandafter\mst@tmp\csname user@active#1\expandafter\endcsname
337             \csname mst@orig@user@active#1\endcsname
```

```

338 \def\mst@tmp##1##2{\def##1{\mst@safefork{#2}{#3}##2}}%
339 \expandafter\mst@tmp\csname normal@\char#1\expandafter\endcsname
340 \csname mst@orig@normal@\char#1\endcsname
341 \ifmst@everymath
342 \else
343 \expandafter\let\csname mst@hackedshorthand@#1\endcsname\empty
344 \fi
345 }

```

### \mst@@mathactivate

```

346 \begingroup
347 \catcode`\~=active
348 \def\x{%
349 \endgroup
##1 is always a token of catcode 11 or 12.
350 \ifmst@everymath
351 \def\mst@@mathactivate##1##2##3{%
352 \begingroup
353 \lccode`~=\##1
354 \lccode`##1=`

```

Careful here as ##2 is empty in the asterisk and prime case. And ##3 also is at [1.4](#) empty for letters.

```

355 \lowercase{\endgroup
Refactoring at 1.4 merged the catcode 11 and catcode 12 branches here and in particular avoided
in former case an \edef. This helped into providing the \MTcommandletter⟨letter⟩ as a customiz-
able macro. There was no equivalent to this macro, which here is ##2, prior to 1.4.
356 \mathcode`##1="8000
357 \def~{##2##3}%
358 }%
359 }%
360 \else
361 \def\mst@@mathactivate##1##2##3{%
362 \begingroup
363 \lccode`~=\##1
364 \lccode`##1=`
365 \lowercase{\endgroup
366 \mathcode`##1="8000

```

Also, [1.4](#) possibly execute \mst@@mathactivate everywhere in document body (at version changes for example) or at begin document. Hence this modifies globally the active meaning. So we add some safeguard here using an \ifmmode. And we store the original meaning of the active variant of the token to reset it when “undoing”.

Careful not to do it twice in a row... (but this means \mst@deactivate might not revert to a user custom redefinition done in-between but to a prior one; although if the character is made active the second \mst@@mathactivate would not have been done).

```

367 @ifundefined{mst@prioractivemeaning@##1}
368 {\expandafter\let
369 \csname mst@prioractivemeaning@##1\endcsname ~}

```

```

370          {}%
371          \def~{\ifmmode##2##3\else##1\fi}%
372      }%
373  }%
374 \fi
375 }\x

```

At 1.4 the macro was split into two, to test first whether the character which is encountered is currently with active catcode.

At 1.4 the non-catcode active branch is entered only if the character isn't mathematically active at time of use..

Careful that #2 and #3 may each be empty. The test for being a Babel shorthand is done here and not as prior to `mathastext` @release1.4 inside `\mst@do@activecase`.

```

376 \def\mst@mathactivate#1#2#3{%
377     \ifnum\catcode`#1=\active
378         \@ifundefined{active@char#1}{}{\mst@do@activecase #1{#2}{#3}}%
379     \else
380         \mst@OnlyIfNotMathActive{#1}{\mst@@mathactivate #1{#2}{#3}}%
381     \fi
382 }

```

`\mst@mathdeactivate` This is needed at 1.4 for non-letters which are mathematically activated. See comments above in `\mst@do@activecase`. Works in sync with `\mst@addtodo@nonletters`.

The `\mst@mathdeactivate` is active (sic) only in the non `everymath` situation. It will restore a previously existing active meaning if it has been changed.

```

383 \ifmst@everymath
384 \else
385 \def\mst@mathdeactivate#1#2{%
386     \mathcode`#1=#2\relax
387     \@ifundefined{active@char#1}
388         {\@ifundefined{mst@prioractivemeaning@#1}
389             {}%
390             {\mst@restoreactivemeaning#1%
391                 \expandafter\let\csname mst@prioractivemeaning@#1\endcsname\relax}%
392         }%
393         {\@ifundefined{mst@hackedshorthand@#1}
394             {}%
395             {\expandafter\let\csname user@active#1\expandafter\endcsname
396                 \csname mst@orig@user@active#1\endcsname
397                 \expandafter\let\csname normal@char#1\expandafter\endcsname
398                     \csname mst@orig@normal@char#1\endcsname
399                 \expandafter\let\csname mst@hackedshorthand@#1\endcsname\relax
400             }%
401         }%
402 }%

```

`@restoreactivemeaning` At 1.4 when we undo the mathematical activation we now also restore the prior existing active meaning, if any. Only in the “no `everymath`” branch (because in the `everymath` TeX itself takes care of that on exiting the scope of the math mode).

```

403 \def\mst@restoreactivemeaning#1{%
404     \begingroup
405     \lccode`~=`#1
406     \lccode`#1=`#1
407     \lowercase{\endgroup
408     \expandafter\let\expandafter~\csname mst@prioractivemeaning@#1\endcsname
409     }%
410 }
411 \fi

```

**\mst@do@nonletters**  
**\mst@addtodo@nonletters**  
**\mst@the**  
**Tnonlettersobeymathxx**  
**ettersdonotobeymathxx**

These macros are modified in version 1.3a 2013/09/04 in order to cleverly adjust, or not, the amsmath `\resetMathstrut@`. When used in the preamble, they just modify `\mst@the`. And there is code at begin document to check the status there of `\mst@the` and if its meaning is `\the`, then `\MTnonlettersobeymathxx` is activated again to do the patch. When used in the body they adjust `\resetMathstrut@`.

Notice that the saved meaning is the one at begin document (thus, possibly patched by `lualatex-math` — not anymore since 1.5 of March 2016, as `amsmath.sty` now maintained by LaTeX team has modified `\resetMathStrut@` to make it compatible to Unicode engines) but modifications done after that would not be seen in `\mst@savresetMathstrut@`.

The new version of `\resetMathStrut@` from LaTeX team release 2016/03/03 v2.15a of `amsmath.sty` is still not compatible with a math active opening parenthesis. Hence my patch here is still needed.

At 1.3u `\MTnonlettersobeymathxx` and `\MTeasy@nonlettersobeymathxx` are made no-ops under subdued mode. This fixes some bug if for example the former was used in preamble or immediately after `\begin{document}` making the minus sign math active although the `mathastext` action was supposedly subdued. Similarly `\MTmathactiveletters` is now a no-op if issued under subdued mode in the *normal* or *bold* math versions.

```

412 \newtoks\mst@do@nonletters
413 \ifmst@everymath
414 \else
415     \newtoks\mst@undo@nonletters
416 \fi

```

#1 is a category 12 character, #2 is a `\mathopen`, or `\mathclose`, etc..., #3 is a `\mathchar` (of variable family type).

At 1.4, `\mst@mathactivate` will not do anything if #1 is mathcode active (but not catcode active) at time of use.

```

417 \ifmst@everymath
418     \def\mst@addtodo@nonletters#1#2#3{\mst@do@nonletters\expandafter
419             {\the\mst@do@nonletters\mst@mathactivate#1#2#3}%
420     }%
421 \else

```

We need to automatize some safeguards related to `\mst@do@activecase` when deactivating.

```

422     \def\mst@addtodo@nonletters#1#2#3{\mst@do@nonletters\expandafter
423             {\the\mst@do@nonletters\mst@mathactivate#1#2#3}%
424     \edef\mst@tmp{\noexpand\mst@mathdeactivate#1{\the\mathcode`#1}}%
425     \mst@undo@nonletters\expandafter\expandafter\expandafter
426             {\expandafter\mst@tmp\the\mst@undo@nonletters}%
427     }%

```

```

428 \fi
429 \let\mst@the\@gobble
As \mst@savedresetMathstrut@ will only be defined at begin document, the next two macros
are no-op in the preamble.
430 \def\mst@redefine@resetMathstrut@{%
431     \@ifundefined{mst@savedresetMathstrut@}%
432     {}%
433     {%
434         \ifmst@symboldelimiters
435             \def\resetMathstrut@{%
436                 \setbox\z@\hbox{\the\textfont\symmtsymbol\char40
437                     \the\textfont\symmtoperatorfont\char40
438                     \the\textfont\symoperators\char40}%
439                 \ht\Mathstrutbox@\ht\z@\dp\Mathstrutbox@\dp\z@}%
440         \else
441             \def\resetMathstrut@{%
442                 \setbox\z@\hbox{\the\textfont\symmtoperatorfont\char40
443                     \the\textfont\symoperators\char40}%
444                 \ht\Mathstrutbox@\ht\z@\dp\Mathstrutbox@\dp\z@}%
445         \fi
446         \PackageInfo{mathastext}{\string\resetMathstrut@\space
447             from amsmath replaced for this\MessageBreak group or environment}%
448     }%
449 }%
450 \def\mst@restore@resetMathstrut@{%
451     \@ifundefined{mst@savedresetMathstrut@}{}{%
452         \PackageInfo{mathastext}{restoring for this group or environment
453             the original\MessageBreak
454             amsmath \protect\resetMathstrut@}%
455         \let\resetMathstrut@\mst@savedresetMathstrut@}%
456 }%
457 \ifmst@everymath
458     \newcommand*\MTnonlettersobeymathxx{%
459         \mst@OnlyIfNotSubdued{%
460             \ifx\mst@the\the
461             \else
462                 \mst@redefine@resetMathstrut@
463             \fi
464             \let\mst@the\the
465         }%
466     }%
467     \newcommand*\MTnonlettersdonotobeymathxx{%
468         \ifx\mst@the\@gobble
469         \else
470             \mst@restore@resetMathstrut@
471         \fi
472         \let\mst@the\@gobble
473     }%
474 \else

```

```

475  \newcommand*\MTnonlettersobeymathxx{%
476      \mst@OnlyIfNotSubdued{%
477          \AtBeginDocument{\MTnonlettersobeymathxx}%
478      }%
479  }%
480  \newcommand*\MTnonlettersdonotobeymathxx{%
481      \AtBeginDocument{\MTnonlettersdonotobeymathxx}%
482  }%
483  \AtBeginDocument{%
484      \renewcommand*\MTnonlettersobeymathxx{%
485          \mst@OnlyIfNotSubdued{%
486              \the\mst@do@nonletters
487              \ifx\mst@the\the
488                  \else
489                      \mst@redefine@resetMathstrut@
490                  \fi
491                  \let\mst@the\the
492          }%
493  }%
494  \renewcommand*\MTnonlettersdonotobeymathxx{%
495      \the\mst@undo@nonletters
496      \ifx\mst@the\@gobble
497          \else
498              \mst@restore@resetMathstrut@
499          \fi
500          \let\mst@the\@gobble
501      }%
502  }%
503 \fi

nonlettersobeymathxx
lettersdonotobeymathxx 504 \newtoks\mst@do@easynonletters
505 \ifmst@everymath
506     \newcommand*\MTeasy@nonlettersdonotobeymathxx{\let\mst@theeasy\@gobble}%
507     \newcommand*\MTeasy@nonlettersobeymathxx{%
508         \mst@OnlyIfNotSubdued{\let\mst@theeasy\the}%
509     }%
510     \MTeasy@nonlettersobeymathxx
511 \else
512     \newtoks\mst@undo@easynonletters
513     \newcommand*\MTeasy@nonlettersdonotobeymathxx{\the\mst@undo@easynonletters}%
514     \newcommand*\MTeasy@nonlettersobeymathxx{%
515         \mst@OnlyIfNotSubdued{\the\mst@do@easynonletters}%
516     }%
517     \AtEndOfPackage{\MTeasy@nonlettersobeymathxx}%
518 \fi

ddtodo@easynonletters #1 is a one character control sequence (\., \/, \#, \% or \&) and #2 is a mathchar.
Perhaps I should use the Unicode engine \Umathcode et alia. I do this at other places. However
I realized in 2013 and it is still true in 2024 that LATEX interface \DeclareSymbolFont does not

```

allow to declare more than 16 font families even with  $\text{Lua}\text{\TeX}$  despite the latter allowing 256 such.

So why bother?

[1.4](#) adds to this legacy branch a test to not override a mathematically active “easy” non-letter. Main case is the dot with Babel Spanish.

```

519 \ifmst@everymath
520   \def\mst@addtodo@easynonletters#1#2{%
521     \mst@do@easynonletters\expandafter{%
522       \the\mst@do@easynonletters
523       \mst@OnlyIfNotMathActive{#1}{\mathcode`#1=#2}%
524     }%
525   }%
526   \def\mst@addtodo@easynonletters@U#1#2{%
527     \mst@do@easynonletters\expandafter{%
528       \the\mst@do@easynonletters
529       \mst@OnlyIfNotMathActive{#1}{\mst@Umathcodenum`#1=#2}%
530     }%
531   }%
532 \else

```

The character may have been made mathcode active exterior to `mathastext`. We can not test this for sure at begin document as it may happen later. If such an “easy” character is mathcode active, this can not originate in `mathastext`. So we should not overwrite when we issue `\MTeasynonlettersdonotbeymathxx`. Example I know is with `babel` Spanish which makes the dot math active. With `PDF\TeX` it is also catcode active

This macro may be used with Unicore engines, and `Lu\TeX` and `X\TeX` differ regarding math active characters. I have only tested this (anew) for [1.4](#) for which this branch is needed, so in 2024.

```

533   \def\mst@addtodo@easynonletters#1#2{%
534     \mst@do@easynonletters\expandafter
535       {\the\mst@do@easynonletters
536        \mst@OnlyIfNotMathActive{#1}{\mathcode`#1=#2}}%
537     \def\mst@tmp##1\relax{%
538       \def\mst@tmp{\mst@OnlyIfNotMathActive{#1}{\mathcode`#1=##1\relax}}%
539     }%
540     \expandafter\mst@tmp\the\mathcode`#1\relax
541     \mst@undo@easynonletters\expandafter\expandafter\expandafter
542       {\expandafter\mst@tmp\the\mst@undo@easynonletters}%
543   }%
544   \def\mst@addtodo@easynonletters@U#1#2{%
545     \mst@do@easynonletters\expandafter{%
546       \the\mst@do@easynonletters
547       \mst@OnlyIfNotMathActive{#1}{\mst@Umathcodenum`#1=#2}}%
548     }%
549     \def\mst@tmp##1\relax{%
550       \def\mst@tmp{\mst@OnlyIfNotMathActive{#1}{\mst@Umathcodenum`#1=##1\relax}}%
551     }%
552     \expandafter\mst@tmp\the\mst@Umathcodenum`#1\relax
553     \mst@undo@easynonletters\expandafter\expandafter\expandafter

```

```

554      {\expandafter\mst@tmp\the\mst@undo@easynonletters}%
555  }%
556 \fi

```

\newmcodes@  
\mst@newmcodes@  
\MTresetnewmcodes  
\MTcustomizenevmcodes

**1.15d:** the \newmcodes@ amsmath macro causes an error in Unicode engines as soon someone assigns a Unicode mathcode to the minus sign, and then makes a \DeclareMathOperator declaration. Furthermore it hard-codes the font family 0 as being the one to be used. Moreover just putting the concerned signs -, :, ., \,', \* inside braces emulates enough the behavior (although the tick will give a prime).

**1.3:** now tests if ‘basic’ option was used.

**1.3d:** I should re-examine the situation with \newmcodes@. In the meantime its relaxification will not be done if lualatex-math is loaded. And the whole thing is put at begin document.

**1.3m:** lualatex-math 1.5 n'a pas modifié son traitement de \newmcodes@ mais par contre a supprimé le patch de \resetMathstrut@. Mais la date de release est restée à 2015/09/22 (date de **1.4a**) au lieu de quelque chose comme 2016/03/13 (date pour l'annonce sur CTAN). Il faudra suivre l'évolution future de amsmath.sty maintenant assurée par D.C.

**1.3n** 2016/04/22: there is no more a patch of \newmcodes@ by lualatex-math 1.6 (2016/04/16), as amsmath 2016/03/10 v2.15b has now a version compatible with Lua<sup>T</sup>E<sub>X</sub>.

My very radical \let\newmcodes@\relax was only a temporary measure I adopted for lack of time on October 13, 2012, and apart from avoiding to do that in case lualatex-math was detected, I never came back... finally I handle it myself for **1.3n**. The remaining problem of this macro (now that it does not anymore crash lualatex or vice versa) is that (also with amsmath version 2016/03/10 v2.15b) it hardcodes the font used. The aim of the macro is to modify the type of spacing affected to symbols ', \*, ., -, /, :, in case they are used in operator names.

- As I don't want to monopolize a count register only for computations, let's just be mean if ε-T<sub>E</sub>X not there.
- **mathastext** makes (or not, depending on commands issued by the user) these characters math active (the right tick already is), which complicates recovery of former mathcode. We have mathchar type *macros*, but then the complication is in diverging behaviors of the engines: \numexpr\mst@varfam@minus\relax works with Lua<sup>T</sup>E<sub>X</sub>, not with X<sub>E</sub>T<sub>E</sub>X.
- the \* must presumably really be the non-lowered text glyph.
- for the - I hesitated but do use the hyphen in the end.
- seems I simply don't understand what the amsmath code does with \std@minus. It is used in \relbar and it escapes me why \newmcodes@ would ever want to redefine it, and more importantly why on earth it tests the mathcode of - for that ? yes, \std@minus is defined (at begin document) using the mathcode of -, but what's the connexion to \newmcodes@ ?? Any way **mathastext** defines \relbar with \mst@minus@sign. Thus I just drop this conditional.
- things are complicated by the options such as **nominus**, **noparenthesis**.
- the \newmcodes@ macro is anyhow assuming that if a new math font is used it occupies math groups 0 and 1 !! very bad; fixing it in passing if the character has not been handled by **mathastext** could be envisioned, but that's not **mathastext**'s job.
- years go by, and I remain as baffled as ever about the story of “more than 16 math families”. I will not test again, but I am pretty sure that \DeclareMathSymbol does not work with more than 16 families, thus when I try to be a good boy and use \Umathcode syntax with **symmtoperatorfont** I am perhaps doing unnecessary efforts.

- I noticed that Lua<sup>L</sup>ATE<sub>X</sub> does not apply the “TeX Ligature” (bad name) regarding the right tick APOSTROPHE being transformed into RIGHT SINGLE QUOTATION MARK in math mode, but X<sup>L</sup>ATE<sub>X</sub> does. From the point of view of `mathastext`, the behavior of X<sup>L</sup>ATE<sub>X</sub> is the coherent one. It appears that Lua<sup>L</sup>ATE<sub>X</sub> use in math mode of a text font does not obey the set features. I opened a ticket at <https://github.com/wspr/fontspec/issues/238>, but as usual it is hard to figure out the best place where to report font matters. *This item might be obsolete – not checked (1.3q).*
- Some hesitation about what to do under option `symboldelimiters`. I temporarily used `\symmtsymbol`, except for the right quote and for the hyphen, but finally I drop that and use `\symmtoperatorfont` always. (after testing how it looked like).

All in all this is a great deal of trouble and I understand I postponed back in 2012! I spent some hours on this small thing, with consequent testing and for example this TeX Ligature issue with Unicode engines.

Since 1.3v we require e-TeX extensions, so a test for `\numexpr` has been dropped here.

```

557 \ifmst@basic
558 \else
559 \ifmst@XeOrLua
560   \AtBeginDocument {%
561     \ifx\newmcodes@\@undefined\else
562       \edef\mst@newmcodes@{%
563         \mst@Umathcode `\\noexpand` 0 \symmtoperatorfont 39\relax
564       \ifmst@asterisk
565         \mst@Umathcode `\\noexpand`* 0 \symmtoperatorfont 42\relax
566       \else\mathcode`\\noexpand`* 42
567     \fi
568     \ifmst@nopunct\mathcode `\\noexpand`."613A \mathcode `\\noexpand`: "603A
569   \else
570     \mst@Umathcode `\\noexpand`_. 6 \symmtoperatorfont 46\relax
571     \mst@Umathcode `\\noexpand`:_ 6 \symmtoperatorfont 58\relax
572   \fi
573   \ifmst@nominus\mathcode`\\noexpand`- 45
574   \else
575     \mst@Umathcode `\\noexpand`- 0 \symmtoperatorfont 45\relax
576   \fi
577   \ifmst@noparen\mathcode`\\noexpand`/ 47
578   \else
579     \mst@Umathcode `\\noexpand`/ 0 \symmtoperatorfont 47\relax
580   \fi
581 }%
582 \let\mst@originalnewmcodes@\newmcodes@
583 \fi
584 }%
585 \else
586   \AtBeginDocument {%
587     \ifx\newmcodes@\@undefined\else
588       \edef\mst@newmcodes@{%
589         \mathcode`\\noexpand`' \the\numexpr\symmtoperatorfont*\@cclvi+39\relax
590       \mathcode`\\noexpand`*

```

```

591      \the\numexpr\ifmst@asterisk\symmtoperatorfont*\@cclvi\fi+42\relax
592      \ifmst@nopunct\mathcode `\\noexpand\."613A \mathcode `\\noexpand\!: "603A
593      \else
594          \mathcode`\\noexpand\.\ \the\numexpr\mst@varfam@dot-"1000\relax
595          \mathcode`\\noexpand\:\\ \the\numexpr\mst@varfam@colon-"1000\relax
596      \fi
597      \mathcode`\\noexpand\-
598      \the\numexpr\unless\ifmst@nominus\symmtoperatorfont*\@cclvi\fi+45\relax
599      \mathcode`\\noexpand\/
600      \the\numexpr\unless\ifmst@noparen\symmtoperatorfont*\@cclvi\fi+47\relax\relax
601  }%
602 \let\mst@originalnewmcodes@\newmcodes@
603 \fi
604 }%
605 \fi
606 \fi
607 \newcommand*\MTresetnewmcodes{\ifx\mst@originalnewmcodes@\undefined\else
608                               \let\newmcodes@\mst@originalnewmcodes@\fi}
609 \newcommand*\MTcustomizenevmcodes{\ifx\mst@originalnewmcodes@\undefined\else
610                               \let\newmcodes@\mst@newmcodes@\fi}

```

**mtoperatorfont** Declaration of the current default font as our math font. The characteristics of the used font can be changed by a user call to the macros `\Mathastext` or `\Mathastextwilluse`, which will be defined next. We will also make one internal call to `\Mathastext` to set up the normal and bold math versions, so we will also employ `\SetSymbolFont` later.

```
611 \DeclareSymbolFont{mtoperatorfont}{\mst@enc}{\mst@fam}{\mst@ser}{\mst@opsh}
```

**\operator@font** We modify this `LATEX` internal variable in order for the predefined `\cos`, `\sin`, etc... to be typeset with the `mathastext` font. This will also work for things declared through the `amsmath` package command `\DeclareMathOperator`. The alternative would have been to redefine the ‘operators’ Math Symbol Font. Obviously people who expect that `\operator@font` will always refer to the ‘operators’ math font might be in for a surprise... well, we’ll see.

**\MTmathoperators-** **obeymathxx** **1.2:** rather than just replacing `\symoperators` by `\symmtoperatorfont` I add a modification which makes the declared operator names sensitive to the math alphabets... ouh le vilain!

**\MTmathoperators-** **donot-** **obeymathxx** **612** `\newcommand*{\MTmathoperatorsobeymathxx}{`  
**613** `{\def\operator@font{\mathgroup\ifnum\fam=\m@ne\symmtoperatorfont\else\fam\fi}}`  
**614** `\newcommand*{\MTmathoperatorsdonotobeymathxx}{`  
**615** `{\def\operator@font{\mathgroup\symmtoperatorfont}}`  
**616** `\MTmathoperatorsobeymathxx`

**mtletterfont** At version **1.1**, we add the possibility to mimick the standard behavior, that is to have italic letters and upright digits. Thanks to Tariq PERWEZ and Kevin KLEMENT who asked for such a feature.

```
617 \DeclareSymbolFont{mtletterfont}{\mst@enc}{\mst@fam}{\mst@ser}{\mst@ltsh}
```

**\MTfixmathfonts** There is a long-standing issue <https://github.com/lualatex/luaotfload/issues/204> on `LATEX` not applying OpenType features in math mode (this impacts `\url` macro too, as it uses math mode.) `LATEX` has two modes for handling of OpenType fonts, the default in text being to use the `node` mode, and this mode is non-working in math, thus `mathastext` needs to

force use of `base` mode. Else one sees old style figures where one does not expect them, or the opposite, depending on the default font feature.

Once we know the cause, the fix is relatively easy. I will go for the `\everymath` way, because I don't want to dwelve at all with the details of L<sup>A</sup>T<sub>E</sub>X's handling of math fonts, of size changes, of math versions etc... perhaps in the future L<sup>A</sup>T<sub>E</sub>X will fix the issue upstream by modifying `\DeclareSymbolFont` under LuaL<sup>A</sup>T<sub>E</sub>X + `luatofload` regime, then the present patch by `mathastext` will be unneeded. Naturally, here we care only about the two math fonts used by `mathastext:mtoperatorfont` and `mtletterfont`.

For the `\url` situation, I have posted online a patch.

Not all is resolved, as I comment online at <https://github.com/lualatex/luatofload/issues/204#issuecomment-216465680> that with TeX Gyre Termes for example I can not get simultaneously Old Style and Tabular Figures to work in math mode, although the font name as constructed by my patch (which is like the code below, only simpler as we only have to consider `\textfont0`) is the correct one. Similarly with Vollkorn: I can then not get the two features `lnum` and `tnum` to work simultaneously when specified with `mode=base`. It does work with `mode=node` but this mode "does not work in math mode."

Done for [1.3o](#) of 2016/05/03.

[1.3p](#) renames the macro to `\MTfixmathfonts` for public access.

[1.4](#) intercepts also `mode=harf`. Cf <https://tex.stackexchange.com/questions/722084/change-number-style-with-mathastext> (thanks to user691586 for bug report). The new code unconditionally replaces `mode=foo` by `mode=base`. The complications due to the output of `\fontname` using only category 12 characters are handled in a different way than the 2016 code.

The <https://github.com/latex3/fontspec/issues/525> problem causes additional complications.

Perhaps I should simply zap spaces always rather than check for quotes? Anyway this appears to work.

```

618 \def\mst@fixmathfonts@#1.#2.#3.{%
619 \def\mst@fixmathfonts@##1##2#1##3;##4##5\relax##6\empty##7{%
620   \ifx##3\empty\else
621     \if"##1%
622       \font\mst@mathfont=##1##2#1=base;##4##5\relax
623     \else
624       \mst@arrrrgh@fixmathfonts##1##2#1=base;##4##5#2\empty#3\relax
625     \fi
626     ##7=\mst@mathfont
627   \fi
628 }%
629 \def\mst@arrrrgh@fixmathfonts##1#2##2##3##4\relax{%
630   \ifx##2\empty
631     \font\mst@mathfont="#"1"\relax
632   \else
633     \font\mst@mathfont="#"1"#2##2##3##3\relax
634   \fi
635 }%
636 }%
637 \expandafter\mst@fixmathfonts@\detokenize{mode. at.pt.}%
638 \def\MTfixmathfonts#1{%
639 \def\MTfixmathfonts{%
640   \expandafter\mst@fixmathfonts@\fontname\textfont\symmtoperatorfont

```

```

641 \relax\relax #1=\empty\relax\empty{\textfont\symmtoperatorfont}%
642 \expandafter\mst@fixmathfonts@\fontname\scriptfont\symmtoperatorfont
643 \relax\relax #1=\empty\relax\empty{\scriptfont\symmtoperatorfont}%
644 \expandafter\mst@fixmathfonts@\fontname\scriptscriptfont\symmtoperatorfont
645 \relax\relax #1=\empty\relax\empty{\scriptscriptfont\symmtoperatorfont}%
646 \expandafter\mst@fixmathfonts@\fontname\textfont\symmtletterfont
647 \relax\relax #1=\empty\relax\empty{\textfont\symmtletterfont}%
648 \expandafter\mst@fixmathfonts@\fontname\scriptfont\symmtletterfont
649 \relax\relax #1=\empty\relax\empty{\scriptfont\symmtletterfont}%
650 \expandafter\mst@fixmathfonts@\fontname\scriptscriptfont\symmtletterfont
651 \relax\relax #1=\empty\relax\empty{\scriptscriptfont\symmtletterfont}%
652 }%
653 \expandafter\MTfixmathfonts\expandafter{\detokenize{mode}}%
654 \ifmst@LuaTeX
655 \everymath\expandafter{\the\everymath\mst@fixmathfonts}%
656 \everydisplay\expandafter{\the\everydisplay\mst@fixmathfonts}%
657 \fi
658 \newcommand*\MTfixfonts{\let\mst@fixmathfonts\MTfixmathfonts}%
659 \newcommand*\MTdonotfixfonts{\let\mst@fixmathfonts\empty}%
660 \MTfixfonts

```

\Mathnormal We redefine the default normal, rm, bf, it, sf, and tt alphabets, but this will be done via \renewcommand\*\mathrm{\Mathrm} etc... (not anymore, see comment below).

\Mathbf We follow the standard L<sup>A</sup>T<sub>E</sub>X behavior for \mathbf, which is to pick up the bold series of the roman font (digits and operator names).

\Mathit \Mathsf \Mathtt \Mathnormalbold We will access (if no option is passed for Greek) the \omicron via \mathnormal. But unfortunately the **fourier** package with the upright option does not have an upright omicron obtainable by simply typing \mathnormal{o}. So if **fourier** is loaded we use \mathrm and not \mathnormal.

Actually math alphabet macros are created robust since L<sup>A</sup>T<sub>E</sub>X from 2005, so at [1.3v](#) 2019/09/19 I decided to modify the old **mathastext** approach a bit. Indeed with the old approach a \mathtt in a moving argument translates ultimately into \Mathtt but if for example the new context where it gets expanded is a subdued normal math version, this does not give the same as \mathtt would have given there. This was a bug: imagine \section{\$\mathtt{X}\$} issued in a math version, but the TOC is done in subdued normal version; the output in TOC will often differ (fontsize being put aside) both from out it looked at the section title and from what direct usage of \mathtt in the TOC would have given. I have no strong preference between the two possibilities (to be as in section title, or to be as if \mathtt gets executed in TOC and obeys its local regime), but it is a bug if the result is still a third one. Thus I decided to follow L<sup>A</sup>T<sub>E</sub>X2e and that \mathtt had to remain \mathtt when moving.

But a math alphabet command such as \Mathtt redefines its unprotected meaning on first use as well as the one of the math version macro, hence a \letrobustmacro\mathtt\Mathtt of sorts is no good at all. I thus opted to not hack into the math L<sup>A</sup>T<sub>E</sub>X font support across math versions and to simply use \protected\def in place of obeying strictly L<sup>A</sup>T<sub>E</sub>X2e robustness (except of course in the subdued math versions as there the math alphabets acquire back their original robust meanings.)

Potential breaking change at [1.3za](#), the **defaultbf** etc... options do not prevent the package declaring \Mathbf etc... commands.

[1.3za](#) defines a \Mathnormalbold and then defines \mathnormalbold in terms of it in place of

defining directly `\mathnormalbold` as a math alphabet. This is in relation to implementation of the `LGRgreek+` option. There was some hesitation though to restrict this change to that option only or not.

```

661 \let\mst@alph@omicron\mathnormal
662 \@ifpackageloaded{fourier}{\ifsloped\else\let\mst@alph@omicron\mathrm\fi}{}}
663 \DeclareSymbolFontAlphabet{\Mathnormal}{\mtletterfont}
664 \DeclareSymbolFontAlphabet{\Mathrm}{\mtoperatorfont}
665   \DeclareMathAlphabet{\Mathnormalbold}{\mst@enc}{\mst@fam}{\mst@bold}{\mst@ltsh}
666   \protected\def\mathnormalbold{\Mathnormalbold}
667   \DeclareMathAlphabet{\Mathbf}{\mst@enc}{\mst@fam}{\mst@bold}{\mst@opsh}
668   \DeclareMathAlphabet{\Mathit}{\mst@enc}{\mst@fam}{\mst@ser}{\itdefault}
669   \DeclareMathAlphabet{\Mathsf}{\mst@enc}{\sfdefault}{\mst@ser}{\mst@opsh}
670   \DeclareMathAlphabet{\Mathtt}{\mst@enc}{\ttdefault}{\mst@ser}{\mst@opsh}

```

The `\mathxx` macros being L<sup>A</sup>T<sub>E</sub>X2e robust, or course the meanings here are known, and «original» macros are sort of superfluous but well it works.

```

671 \let\mst@original@normal\mathnormal
672 \let\mst@original@rm\mathrm
673 \let\mst@original@bf\mathbf
674 \let\mst@original@it\mathit
675 \let\mst@original@sf\mathsf
676 \let\mst@original@tt\mathtt
677 \def\mst@restorealphabets{%
678   \let\mathnormal\mst@original@normal
679   \let\mathrm\mst@original@rm
680   \let\mathbf\mst@original@bf
681   \let\mathit\mst@original@it
682   \let\mathsf\mst@original@sf
683   \let\mathtt\mst@original@tt
684 }
685 \ifmst@greekplus

```

`\mst@mathalph` The L<sup>A</sup>T<sub>E</sub>X kernel code regarding math fonts is too complex and rigid for there to be a robust and easy way to know when one is in the argument of `\mathrm` or `\mathbf`, and the code is spread on various chapters of `source2e.pdf`, and the comments are often not up-to-date. So I did not try a too complex hack and decided for [1.3za](#) to add a numeric indicator to let Greek letters react to it. It incorporates a space to be self-delimiting in an `\ifcase` to maintain expandability in numeric context of the to-be-defined Greek control sequences.

```

686 \def\mst@mathalph{-1}
687 \def\mst@setalphabets{%
688   \protected\def
689   \mathnormalbold##1{\def\mst@mathalph{4 }\Mathnormalbold##1\def\mst@mathalph{-1 } }%
690   \ifmst@defaultnormal\else
691     \protected\def
692     \mathnormal##1{\def\mst@mathalph{0 }\Mathnormal##1\def\mst@mathalph{-1 } }%
693   \fi
694   \ifmst@defaultrm\else
695     \protected\def
696     \mathrm##1{\def\mst@mathalph{1 }\Mathrm##1\def\mst@mathalph{-1 } }%

```

```

697   \fi
698   \ifmst@defaultbf\else
699     \protected\def
700       \mathbf{\def\mst@mathalp{2 }\Mathbf{\def\mst@mathalp{-1 }}}%
701   \fi
702   \ifmst@defaultit\else
703     \protected\def
704       \mathit{\def\mst@mathalp{3 }\Mathit{\def\mst@mathalp{-1 }}}%
705   \fi
706   \ifmst@defaultsf\else\protected\def\mathsf{\Mathsf}\fi
707   \ifmst@defaulttt\else\protected\def\mathtt{\Mathtt}\fi
708 }
709 \else
710   \def\mst@setalphabets{%
711     \ifmst@defaultnormal\else\protected\def\mathnormal{\Mathnormal}\fi
712     \ifmst@defaultrm\else\protected\def\mathrm{\Mathrm}\fi
713     \ifmst@defaultbf\else\protected\def\mathbf{\Mathbf}\fi
714     \ifmst@defaultit\else\protected\def\mathit{\Mathit}\fi
715     \ifmst@defaultsf\else\protected\def\mathsf{\Mathsf}\fi
716     \ifmst@defaulttt\else\protected\def\mathtt{\Mathtt}\fi
717   }
718 \fi
719 \ifmst@subdued\else\mst@setalphabets\fi

```

**LGRgreek** [1.14b](#): We can not move the `\DeclareSymbolFont` to the `\Mathastext` macro because it resets the font family in \*all\* math versions, and some could have been defined by the user with previous calls to `\Mathastext`. So we have to have them here. The problem is that at this stage it is impossible to know if we really need (in the case of LGRgreek) two separate shapes for upper and lowercase, and (in the case of selfGreek) a shape distinct from the one used in `mtoperatorfont`. So I opted in the end for declaring possibly one too many font. To achieve more economy the only way would be to keep cumulative track of all previously declared math versions and to redeclare appropriately the LGR or self greek fonts at each call to `\Mathastext` (with no optional argument): a bit painful, and as I am possibly the sole user in the world of this possibility of multiple math versions with this package. Also the advantage to systematically allocate a font for the selfGreek option is that we can force the use of the OT1 encoding.

First we establish the cumulative effect of the greek related options.

[1.15c](#) introduces some possibilities to change the shapes of Greek letters in each math versions, and even the Greek font (in LGR encoding). The commands `\MTitgreek` etc... will be used in-between calls to `\Mathastext` and re-adjust the shapes. And the command `\MTgreekfont` changes the Greek font family.

Note that `\mst@ltsh` expands to `\shapedefault` or `\itdefault` at this location.

Note added 2022/11/02: using `\MTitgreek` etc... once implies that from then on, for subsequent `mathastext`-math versions, the shape of Greek letters will not be kept in sync with the shape and lettershape version parameters, but only react to the configuration decided by these commands (and `italic/frenchmath` options).

Note 2022/10/29: for some time `\updefault` was made into up by L<sup>A</sup>T<sub>E</sub>X (since 2020-02-02 now that I check this out). As a result this triggered Font Warnings in the log about the replacement of `up` by `n`.

[1.3y](#) refactors completely the handling of Greek letter shapes under the `LGRgreek(s)` options

(and only under them). Under these options we don't use one font for lowercase Greek and another one for uppercase Greek (some above code comments have not been updated) but one math font `mtgreekit` for italic Greek and one math font `mtgreekup` for upright Greek. What 'italic' and 'upright' mean is decided by the expansion of `\MTgreekitdefault` and `\MTgreekupdefault`, which give respectively `it` and `n` per default.

If no `itgreek` et al. options or `\MTitgreek` et al. commands have been used, we need to map `\mst@ltsh` (which was used for lowercase Greek, except under `frenchmath` option) and `\mst@opsh` to either 'italic' or 'upright'. This is done by testing if they hold 'it' or 'sl'. If yes we map to 'italic' by setting to false an 'up' Boolean, if not we leave the 'up' Boolean to true.

In order to maintain perfect identical code for non-LGRgreek, the LGRgreek related code is simply added to previously shared constructions. The LGRgreek behavior will remain identical in most documents, but for example those who used some adventurous 'sc' for the main shape (the one used per default for operator names) need to adjust `\MTgreekupdefault` to be 'sc', for the math version being defined, or the default one if this is followed by usage of `\Mathastext`.

The new LGRgreek-specific commands `\MTgreekupdefault` and `\MTgreekitdefault` are the only ones in the package which can possibly be defined previously to loading it. (Perhaps some other macros could be also converted to being modifiable prior to loading `mathastext`, thus avoiding potential need to use `\Mathastext` at least once after loading the package; to be examined next time — which may be a long time in future!).

Unfortunately the [1.3y](#) did some internal renamings here (using `@lgr@` in macro names in place of `@greek@`) which were not everywhere followed up, and this broke the `selfGreek` option. Fixed at [1.3z](#).

```

720 \providecommand*\MTgreekupdefault{n}
721 \providecommand*\MTgreekitdefault{it}
722 \newif\ifmst@greek@lower@up
723 \newif\ifmst@greek@upper@up
724 \def\mst@update@greeksh{
725   \def\mst@greek@lsh{\mst@ltsh}
726   \def\mst@greek@ush{\mst@opsh}
727   \mst@greek@lower@uptrue
728   \expandafter\in@\expanded{{\mst@ltsh.}}{it.,sl.}%
729   \ifin@\mst@greek@lower@upfalse\fi
730   \mst@greek@upper@uptrue
731   \expandafter\in@\expanded{{\mst@opsh.}}{it.,sl.}%
732   \ifin@\mst@greek@upper@upfalse\fi
733 \ifmst@itgreek
734   \def\mst@greek@lsh{\MTgreekitdefault}
735   \def\mst@greek@ush{\MTgreekitdefault}
736   \mst@greek@lower@upfalse
737   \mst@greek@upper@upfalse
738 \fi
739 \ifmst@upgreek
740   \def\mst@greek@lsh{\MTgreekupdefault}
741   \def\mst@greek@ush{\MTgreekupdefault}
742   \mst@greek@lower@uptrue
743   \mst@greek@upper@uptrue
744 \fi
745 \ifmst@frenchmath
746   \ifmst@itgreek\else

```

```

747      \ifmst@upgreek\else
748          \def\mst@greek@lsh{\mst@opsh}
749          \def\mst@greek@ush{\mst@opsh}
750          \mst@greek@lower@uptrue
751          \mst@greek@upper@uptrue
752      \fi\fi
753  \fi
754  \ifcase\mst@greek@select
755      \or
756          \def\mst@greek@ush{\MTgreekitdefault}
757          \mst@greek@upper@upfalse
758      \or
759          \def\mst@greek@ush{\MTgreekupdefault}
760          \mst@greek@upper@uptrue
761  \fi
762 }
763 \mst@update@greeksh

```

**mtgreekup** The 1.3y refactoring was done in order to be able to define `\alphaup`, etc ... control sequences (`\mathchar`'s), as well as the italic ones. Formerly two math fonts were created but to be used respectively with lowercase or uppercase Greek. Now we have two fonts indexed by their shape, and we take advantage to create two math alphabets mapping to the two defined symbol fonts `mtgreekup` and `mtgreekit`.

**mtgreekitbold** 1.3za adds `\mathgreekupbold` and `\mathgreekitbold`.

```

764 \ifmst@LGRgreek
765     \DeclareFontEncoding{LGR}{}{}
766     \DeclareSymbolFont{mtgreekup}{LGR}{\mst@fam}{\mst@ser}{\MTgreekupdefault}
767     \DeclareSymbolFont{mtgreekit}{LGR}{\mst@fam}{\mst@ser}{\MTgreekitdefault}
768     \DeclareSymbolFontAlphabet{\mathgreekup}{mtgreekup}
769     \DeclareSymbolFontAlphabet{\mathgreekit}{mtgreekit}
770     \DeclareMathAlphabet{\mathgreekupbold}{LGR}{\mst@fam}{\mst@bold}{\MTgreekupdefault}
771     \DeclareMathAlphabet{\mathgreekitbold}{LGR}{\mst@fam}{\mst@bold}{\MTgreekitdefault}
772 \else

```

#### mtselfGreekfont

```

773 \ifmst@selfGreek
774     \DeclareSymbolFont{mtselfGreekfont}{OT1}{\mst@fam}{\mst@ser}{\mst@greek@ush}
775 \fi\fi

```

**mteulervm** In case we need the Euler font, we declare it here. It will use `uzeur.fd` from the `eulervm` package

**\MathEuler** of Walter SCHMIDT

**\MathEulerBold**

```

776 \ifmst@needeuler
777 \mst@infoline{will use Euler font; command \string\MTEulerScale}
778 \DeclareSymbolFont{mteulervm}{U}{zeur}{m}{n}
779 \DeclareSymbolFontAlphabet{\MathEuler}{mteulervm}
780 \DeclareMathAlphabet{\MathEulerBold}{U}{zeur}{\mst@bold}{n}
781 \fi
782 \newcommand*\MTEulerScale[1]{\edef\zeu@Scale{#1}}
783 \let\MathastextEulerScale\MTEulerScale

```

$\text{\LaTeX} 2\epsilon$  has a strange initial configuration where the capital Greek letters are of type `mathalpha`, but the lower Greek letters of type `mathord`, so that `\mathbf` does not act on them, although lowercase Greek letters and Latin letters are from the same font. This is because `\mathbf` is set up to be like a bold version of `\mathrm`, and `\mathrm` uses the ‘operators’ font, by default `cmr`, where there are NO lowercase greek letters. This set-up is ok for the Capital Greek letters which are together with the Latin letters in both `cmmi` and `cmr`.

The package `eulervm` sets the lowercase Greek letters to be of type `mathalpha`, the default `\mathbf` and `\mathrm` will act weirdly on them, but a `\mathbold` is defined which will use the bold series of the Euler roman font, it gives something coherent for Latin and Greek *lowercase* letters, and this is possible because the same font contains upright forms for them all.

Here in `mathastext`, Latin letters and Greek letters (lower and upper case) must be (generally) assumed to come from two different fonts, as a result the standard `\mathbf` (and `\mathrm`) will give weird results when used for Greek letters. We could coerce `\mathbf` to do something reasonable (cf <http://tug.org/pipermail/texhax/2011-January/016605.html>) but at this time 30-01-2011 09:42:27 CET I decided I would not try to implement it here. I prefer to respect the default things.

I followed the simpler idea of the `eulervm` package and defined `\MathEuler` and `\MathEuler-Bold` alphabet commands (the `eulervm` package does this only for the bold font).

`\mtsymbol` In case we need the Symbol font, we declare it here. The macro `\psy@scale` will be used to scale the font (see at the very end of this file).

```

784 \ifmst@needsymbol
785   \mst@infoline{will use Symbol font; command \string\MTSymbolScale}
786   \def\psy@scale#1{
787     \DeclareSymbolFont{\mtsymbol}{U}{psy}{m}{n}
788     \DeclareSymbolFontAlphabet{\MathPSymbol}{\mtsymbol}
789     \AtBeginDocument{%
790       \DeclareFontFamily{U}{psy}{}%
791       \DeclareFontShape{U}{psy}{m}{n}{<->s*\[\psy@scale] psyr}{}%
792     }
793   \fi
794 \newcommand*\MTSymbolScale[1]{\edef\psy@scale{#1}}
795 \let\MathastextSymbolScale\MTSymbolScale

```

I did not choose for name `\MathSymbol` as this may be defined somewhere for another thing. There is no bold for the postscript Symbol font distributed with the  $\text{\LaTeX} 2\epsilon$  `psnffs` core package.

`\pmvec` Definition of a poor man version of the `\vec` accent. Done using `\protected\def` at 1.4.

```

796 \protected\def\pmvec#1{%
797   \mathord{\stackrel{\raisebox{-.5ex}{\tiny\boldmath$\mathord{\rightarrow}$}}{\phantom{#1}}%
798   {}#1}%
799 }%
800 }

```

`\fouriervec` The glyph is taken from the Fourier font of Michel BOVANI. Note: (oct 2012) I should not allocate an entire symbol font just for one glyph! But I have not given any serious thought to what one can do to simulate a math accent without doing such a wasteful thing.

```

801 \ifmst@fouriervec
802   \DeclareFontEncoding{FML}{}{%

```

```

803  \DeclareFontSubstitution{FML}{futm}{m}{it}
804  \DeclareSymbolFont{mathastextfourier}{FML}{futm}{m}{it}
805  \SetSymbolFont{mathastextfourier}{bold}{FML}{futm}{b}{it}
806  \mst@DeclareMathAccent{\fouriervec}{\mathord}{mathastextfourier}{7E}
807 \fi

\MTencoding Some public macros to modify our private internals, and we will use them also ourself.
\MTfamily In version 1.1 we add the possibility to have two distinct font shapes for letters and digits.
\MTseries So in fact we could as well have two really unrelated fonts but this is really not the spirit of the
\MTshape package.

\MTboldvariant Note that using these macros in the preamble allows \Mathastext to set up math versions
\MTlettershape with a given font for math mode, and at the same time not modifying the \familydefault or
\romandefault etc...
\MTgreekfont At time of 1.3za I considered letting LGRgreeks and selfGreeks support \MTgreekfont and
this needed a chaneg to \MTfamily here but I dropped the idea. Too wary of documentation
changes.

808 \newcommand*\MTencoding[1]{\def\mst@enc{#1}}
809 \newcommand*\MTfamily[1]{\def\mst@fam{#1}}
810 \newcommand*\MTseries[1]{\def\mst@ser{#1}}
811 \newcommand*\MTshape[1]{\def\mst@opsh{#1}\ifmst@italic\else\def\mst@ltsh{#1}\fi}
812 \newcommand*\MTboldvariant[1]{\def\mst@bold{#1}}
813 \newcommand*\MTlettershape[1]{\def\mst@ltsh{#1}}
814 \let\Mathastextencoding\MTencoding
815 \let\Mathastextfamily\MTfamily
816 \let\Mathastextseries\MTseries
817 \let\Mathastextshape\MTshape
818 \let\Mathastextboldvariant\MTboldvariant
819 \let\Mathastextlettershape\MTlettershape

\MTitgreek 1.15c: These new macros can be used in-between calls to \Mathastext. They reset the
\MTupgreek shapes for Greek letters (applies to LGRgreek(s) and selfGreek(s) options). The \MTgreekfont
\MTitGreek presupposes either LGRgreek or selfGreek (it is inoperant under LGRgreeks or selfGreeks).
\MTupGreek \MTgreekfont{\familydefault} is somewhat like using LGRgreeks or selfGreeks.

\MTgreekfont At time of 1.3za I let \MTgreekfont also have an effect under option LGRgreeks or
selfGreeks, via a refactoring which also modified \MTfamily.

820 \newcommand*\MTitgreek{\mst@itgreektrue\mst@upgreekfalse\def\mst@greek@select{0}}
821 \newcommand*\MTupgreek{\mst@upgreektrue\mst@itgreekfalse\def\mst@greek@select{0}}
822 \newcommand*\MTitGreek{\def\mst@greek@select{1}}
823 \newcommand*\MTupGreek{\def\mst@greek@select{2}}
824 \let\Mathastextitgreek\MTitgreek
825 \let\Mathastextupgreek\MTupgreek
826 \let\MathastextitGreek\MTitGreek
827 \let\MathastextupGreek\MTupGreek
828 \newcommand*\MTgreekfont[1]{\def\mst@greekfont{#1}}
829 \let\Mathastextgreekfont\MTgreekfont

```

At (long...) last we now change the font for the letters of the latin alphabet. In version 1.1, Latin letters have their own font (shape).

1.2b 2012/12/28 now that we understand the great advantages of "8000 we do it also for all letters a-z and A-Z to insert automatically the italic corrections. See the [discussion](#) in the user

manual. Ironically I wrote the code initially for the `italic` option only to realize later it was more suitable to using an *upright* text font in math mode! So this mathematical activation of the letters is not done if the font shape is detected to be `it` or `sl`; to bypass this the command `\MTicinmath` is provided.

**1.2e** 2013/01/10 corrects a bad oversight of **1.2b** in `\mst@mathactivate` which made the reproduction of the user manual illustrations with `$f_i^i$` impossible. As `\mst@mathactivate` was originally used also to get the non-letters obey math alphabet while maintaining the TeX spacings, it added no extra braces. The braces should however be added for expansion of math active letters, in order of things like `x^y` to work as expected. (the group braces do not prevent ligatures when the letters are arguments to the math alphabet commands, the added macros `\mst@itcorr` and `\mst@before@<letter>` expanding to nothing).

Added note 2016/01/06: it should be explicitly said that the extra `{...}` in `\mst@mathactivate` for letters end up creating `\hbox`'es around each letter with its extra skips and explicit italic correction, when present. These skips are thus set at natural width and do not add any break point.

Added note at **1.4**: the extra pair of braces is inserted here at `\mst@DeclareMathLetter`, not at `\mst@mathactivate`.

**1.3** 2013/09/02 extends the use of mathematically active letters to allow the user to specify muglue before and after the letter itself (see `\MTsetmathskips`, below). Mathematically active letters were previously used only to add the italic correction; the math activation has now been separated and put in `\MTmathactiveletters`. There is also `\MTmathactiveLetters` to allow math activation only for the uppercase letters. To cancel the (now default, even with option `italic`) math activation of letters, there is `\MTmathstandardletters`. Version **1.3a** removes some silly `\string`'s from the code, which prevented to pass macros as first argument to the command.

Added note 2016/01/06: Notice that the initially `\relax` tokens `\mst@[before|after]@<letter>` formed with `\csname... \endcsname` do not modify TeX's math layout: `\{ \relax f \relax \}` is like `f` (also for ligatures inside `\mathrm` for example).

The code here was refactored at **1.4** and this simplified `\mst@mathactivate` definition.

The `\mst@before<letter>` were renamed at **1.4** into `\mst@before@<letter>` and are incorporated at the `\mst@DeclareMathLetter` location. Formerly `\mst@<letter>` was only the math symbol, now `\MTmathcharletter<letter>` is used for that and `\MTcommandletter<letter>` is the whole thing to which the active letter expands (the definition of the active letter done by `\mst@mathactivate` is done with a `\def`, not a `\let`).

`mst@DeclareMathLetter` **1.4b** adds `noletters` option.

```

830 \ifmst@noletters
831   \let\MTmathactiveletters\empty
832   \let\MTmathactiveLetters\empty
833   \let\MTmathstandardletters\empty
834 \else
835 \def\mst@DeclareMathLetter#1#2#3#4#5{%
836   \DeclareMathSymbol {#1}{\mathalpha}{mtletterfont}{`#1}%
837   \DeclareMathSymbol {#4}{\mathalpha}{mtletterfont}{`#1}%
838   \def#2{\{#3#4#5\mst@itcorr}\}%
839 }%
840 \atfor\mst@tmp:=abcdefghijklmnopqrstuvwxyz\do{%
841   \expandafter\expandafter\expandafter\mst@DeclareMathLetter
842   \expandafter\mst@tmp

```

```

843           \csname MTcommandletter\mst@tmp\expandafter\endcsname
844           \csname mst@before@\mst@tmp\expandafter\endcsname
845           \csname MTmathcharletter\mst@tmp\expandafter\endcsname
846           \csname mst@after@\mst@tmp\endcsname
847 }%
848 \ifmst@frenchmath \def\mst@font@tbu{\mtoperatorfont}%
849   \else          \def\mst@font@tbu{\mtletterfont}%
850 \fi
851 \def\mst@DeclareMathLetter #1#2#3#4#5{%
852   \DeclareMathSymbol {\#1}{\mathalpha}{\mst@font@tbu}{`#1}%
853   \DeclareMathSymbol {\#4}{\mathalpha}{\mst@font@tbu}{`#1}%
854   \def#2{\#3#4#5\mst@ITcorr}}%
855 }%
856 @tfor\mst@tmp:=ABCDEFGHIJKLMNOPQRSTUVWXYZ\do{%
857   \expandafter\expandafter\expandafter\mst@DeclareMathLetter
858   \expandafter\mst@tmp
859     \csname MTcommandletter\mst@tmp\expandafter\endcsname
860     \csname mst@before@\mst@tmp\expandafter\endcsname
861     \csname MTmathcharletter\mst@tmp\expandafter\endcsname
862     \csname mst@after@\mst@tmp\endcsname
863 }%
864 \def\mst@mathactivate@lowercase{%
865   @tfor\mst@tmp:=abcdefghijklmnopqrstuvwxyz\do{%
866     \expandafter\expandafter\expandafter
867     \mst@mathactivate\expandafter\mst@tmp\csname MTcommandletter\mst@tmp\endcsname{}%
868   }%
869 }%
870 \def\mst@mathactivate@uppercase{%
871   @tfor\mst@tmp:=ABCDEFGHIJKLMNOPQRSTUVWXYZ\do{%
872     \expandafter\expandafter\expandafter
873     \mst@mathactivate\expandafter\mst@tmp\csname MTcommandletter\mst@tmp\endcsname{}%
874   }%
875 }%
876 \def\mst@mathdeactivate@lowercase{%
877   @tfor\mst@tmp:=abcdefghijklmnopqrstuvwxyz\do{%
878     \expandafter\mathcode\expandafter`\mst@tmp=\csname MTmathcharletter\mst@tmp\endcsna
879   }%
880 }%
881 \def\mst@mathdeactivate@uppercase{%
882   @tfor\mst@tmp:=ABCDEFGHIJKLMNOPQRSTUVWXYZ\do{%
883     \expandafter\mathcode\expandafter`\mst@tmp=\csname MTmathcharletter\mst@tmp\endcsna
884   }%
885 }%

```

We redo the definitions with some added layer (silly because will never happen in practice that a letter is Babel-active) related to `\mst@do@activecase` in `babel` context.

```

886 \ifmst@everymath
887 \else
888   \def\mst@mathdeactivate@lowercase{%
889     @tfor\mst@tmp:=abcdefghijklmnopqrstuvwxyz\do{%

```

```

890      \expandafter\mathcode\expandafter`\mst@tmp=
891          \csname MTmathcharletter\mst@tmp\endcsname
892      }%
893  }%
894 \def\mst@mathdeactivate@uppercase{%
895   \tfor\mst@tmp:=ABCDEFGHIJKLMNOPQRSTUVWXYZ\do{%
896     \expandafter\mathcode\expandafter`\mst@tmp=
897         \csname MTmathcharletter\mst@tmp\endcsname
898   }%
899 }%
900 \fi

```

\MTmathactiveletters Important changes at [1.4](#).

\MTmathstandardletters Ascii letters are math-activated at package loading time, rather than again and again each time math mode is entered. But not under `subdued` mode, then the activation is done as part of switching to some math version.

The ordering in this code source is a bit of a mess, and it may be too early here to execute \MTmathactiveletters (I think it is fine now after some major moving around of code chunks but will not waste time checking it) so this will be postponed to end of package loading. Prior to [1.4](#) \MTmathactiveletters could be executed here as it only set some toggle to be obeyed at every math mode entrance.

```

901 \def\mst@mathactivateletters{%
902   \mst@mathactivate@lowercase
903   \mst@mathactivate@uppercase
904 }%
905 \newcommand*\MTmathactiveletters{%
906   \mst@OnlyIfNotSubdued
907   \mst@mathactivateletters
908 }%
909 \AtEndOfPackage{\MTmathactiveletters}%

```

Duplication due to some legacy reasons, do not rely on these internal macro names, beware they change at future release.

```

910 \def\mst@mathactivateLetters{\mst@activate@uppercase}%
911 \newcommand*\MTmathactiveLetters{%
912   \mst@OnlyIfNotSubdued
913   \mst@mathactivateLetters
914 }%
915 \newcommand*\MTmathstandardletters{%
916   \mst@mathdeactivate@lowercase
917   \mst@mathdeactivate@uppercase
918 }%
919 \fi

```

\MTicinmath \MTnoicinmath can also be used from inside math mode.

\MTICinmath \MTicalsoinmathxxx is destined to be used inside \mathnormalbold as I didn't want to add the complication of extracting the family number used inside \mathnormalbold (will perhaps come back if I have time to spend on `source2e`). Added note 2016/01/06: this number is a priori simply `symmtletterfont+1`.

`\MTicinmath` can also be used inside math mode, to revert an earlier `\MTnoicinmath` from inside the same math group.

[1.3i](#) 2016/01/06: For some reason which I have now forgotten I did until then:

```
% \def\mst@itcorr{\ifnum\fam=\m@ne/\else\ifnum\fam=\symmtletterfont/\fi\fi}%
%
```

hence italic corrections were also applied inside `\mathnormal` (for upright fonts; `\mathnormal-bold` math alphabet was not treated like `\mathnormal`). I now drop this to be more in sync with the handling of the extra skips around letters. Everything gets suppressed inside all math alphabets, allowing ligatures, even for `\mathnormal`.

```
920 \newcommand*\MTicinmath{%
921   \MTmathactiveletters
922   \def\mst@itcorr{\ifnum\fam=\m@ne/\fi}%
923   \let\mst@ITcorr\mst@itcorr
924 }
925 \newcommand*\MTICinmath{%
926   \MTmathactiveLetters
927   \def\mst@ITcorr{\ifnum\fam=\m@ne/\fi}%
928 }
929 \newcommand*\MTnoicinmath{\let\mst@itcorr\empty\let\mst@ITcorr\empty}
930 \newcommand*\MTnoICinmath{\let\mst@ITcorr\empty}
931 \newcommand*\MTicalsoinmathxx{%
932   \ifx\mst@itcorr\empty\else\def\mst@itcorr{\fi\fi
933   \ifx\mst@ITcorr\empty\else\def\mst@ITcorr{\fi\fi
934 }
```

`\MTsetmathskips` [1.3](#) 2013/09/02: user level command to specify extra spaces in math mode around the letters (only the 7bit a,b,..,z and A,B,..,Z). First parameter is the letter, second is the math skip to be inserted before, and third the skip to be inserted after; for example `\thickmuskip` or explicitly `0.1mu`.

For this, letters are made mathematically active. This is now the package default (version [1.2](#) did this only in the absence of option `italic`, or more precisely when the font used was not of shape `it` or `s1`). But if `\MTsetmathskips` has not been used for that letter, the only effect of the math activation is, as in [1.2](#), to add the italic correction automatically, except when the font shape is detected to be `it` or `s1`; in these latter cases, although mathematically active, the letter acts in the standard way.

The command `\MTmathstandardletters` turns off math activation and its effects for all letters.

Ligatures within the argument of a math alphabet command are impeached by skips; so `\MTunsetmathskips` is provided to cancel the skips for one specific letter (`f` for example).

[1.3a](#) 2013/09/04: I strangely had `\string#1` inside `\MTsetmathskips`. Phobic of catcode active letters... but with `\string` one needs some `\expandafter` to use `\MTsetmathskips` in an `\@for` loop for example. It is better to allow the first argument to be a macro or anything expanding to a letter, and to not be paranoid about improbable catcode active letters (the user just has to tame them at the time of the `\MTsetmathskip`) so I take out these `\string`'s.

[1.3i](#) 2016/01/06: the extra skips are suppressed for the arguments of math alphabet commands. This applies in particular for amsmath's `\DeclareMathOperator`.

```
935 \newcommand*\MTsetmathskips[3]{%
936   \namedef{mst@before@#1}{\ifnum\fam=\m@ne\mskip#2\relax\fi}%
%
```

```

937     \cnamedef{mst@after@#1}{\ifnum\fam=\m@ne\mskip#3\relax\fi}%
938 }
939 \newcommand*\MTunsetmathskips[1]{%
940     \cnamedef{mst@before@#1}{}%
941     \cnamedef{mst@after@#1}{}%
942 }

\mst@DeclareMathDigit
\MTmathactivedigits
\MTmathstandarddigits In version 1.1, we have now separated digits from letters, so paradoxically it is less problematic to give them the mathalpha type.
1.4 had defined some no-op \MTmathstandarddigits and \MTmathactivedigits but if not under option nodigits. As they are used in \MTeverymathoff and \MTeverymathdefault though this broke the option nodigits (either with subdued or when using \MTversion).
Defining them as \empty so that LATEX defensive mechanism with \newcommand works but this is sooooooo hypothetical context!
943 \let\MTmathactivedigits\empty
944 \let\MTmathstandarddigits\empty
945 \ifmst@nodigits\else
946     \def\mst@font@tbu{mtoperatorfont}%
947     \ifmst@symboldigits \def\mst@font@tbu{mtpsymbol}\fi
948     \ifmst@eulerdigits \def\mst@font@tbu{mteulervm}\fi
949     \DeclareMathSymbol{0}{\mathalpha}{\mst@font@tbu}{`0}%
950     \DeclareMathSymbol{1}{\mathalpha}{\mst@font@tbu}{`1}%
951     \DeclareMathSymbol{2}{\mathalpha}{\mst@font@tbu}{`2}%
952     \DeclareMathSymbol{3}{\mathalpha}{\mst@font@tbu}{`3}%
953     \DeclareMathSymbol{4}{\mathalpha}{\mst@font@tbu}{`4}%
954     \DeclareMathSymbol{5}{\mathalpha}{\mst@font@tbu}{`5}%
955     \DeclareMathSymbol{6}{\mathalpha}{\mst@font@tbu}{`6}%
956     \DeclareMathSymbol{7}{\mathalpha}{\mst@font@tbu}{`7}%
957     \DeclareMathSymbol{8}{\mathalpha}{\mst@font@tbu}{`8}%
958     \DeclareMathSymbol{9}{\mathalpha}{\mst@font@tbu}{`9}%
1.4 adds possibility of mathematically active digits.
959 \ifmst@activedigits
960     \def\mst@DeclareMathDigit #1#2#3{%
961         \DeclareMathSymbol{#3}{\mathalpha}{\mst@font@tbu}{`#1}%
962         \def#2{#3}%
963     }%
964     \ctfor\mst@tmp:=0123456789\do{%
965         \expandafter\expandafter\expandafter\mst@DeclareMathDigit
966         \expandafter\mst@tmp
967             \csname MTcommanddigit\romannumeral\mst@tmp\expandafter\endcsname
968             \csname MTmathchardigit\romannumeral\mst@tmp\endcsname
969     }%
970     \def\mst@mathactivedigits{%
971         \ctfor\mst@tmp:=0123456789\do{%
972             \expandafter\expandafter\expandafter\mst@mathactivate
973             \expandafter\mst@tmp\csname MTcommanddigit\romannumeral\mst@tmp\endcsname{}%
974         }%
975     }%
976     \def\MTmathactivedigits{\mst@OnlyIfNotSubdued\mst@mathactivedigits}%

```

```

977     \MTmathactivedigits
978     \ifmst@everymath
979         \def\MTmathstandardddigits{%
980             \atfor\mst@tmp:=0123456789\do{%
981                 \expandafter\mathcode\expandafter`\mst@tmp
982                     =\csname MTmathchardigit\romannumerals\mst@tmp\endcsname
983             }%
984         }%
985     \else

```

We inject some extra layer (silly because will never happen in practice that a digit token is Babel-active) related to `\mst@do@activecase` in `babel` context.

```

986         \def\MTmathstandardddigits{%
987             \atfor\mst@tmp:=0123456789\do{%
988                 \expandafter\mathcode\expandafter`\mst@tmp
989                     =\csname MTmathchardigit\romannumerals\mst@tmp\endcsname
990             }%
991         }%
992     \fi
993 \fi
994 \fi

```

When `symboldelimiters` is passed as an option, we use the `Symbol` font for the printable characters other than letters and digits.

```

995 \ifmst@symboldelimiters
996 \def\mst@font@tbu{mtsymbol}%
997 \mst@endashfalse
998 \mst@emdashfalse
999 \else
1000 \def\mst@font@tbu{mtoperatorfont}%
1001 \fi

```

[1.2](#) adds the tricks to let non letters/digits obey math alphabets. We have to double the definitions for easy switch on-off of the mechanism, via a token list which is put into `\everymath` and `\everydisplay`.

```

1002 \ifmst@noexclam\else\mst@infoline{\string! and \string?}%
1003 \DeclareMathSymbol{!}{\mathclose}{\mst@font@tbu}{21}%
1004 \DeclareMathSymbol{\mst@varfam@exclam}{\mathalpha}{\mst@font@tbu}{21}%
1005 \expandafter\mst@addtodo@nonletters\string!\mathclose\mst@varfam@exclam
1006 \DeclareMathSymbol{?}{\mathclose}{\mst@font@tbu}{3F}%
1007 \DeclareMathSymbol{\mst@varfam@question}{\mathalpha}{\mst@font@tbu}{3F}%
1008 \expandafter\mst@addtodo@nonletters\string?\mathclose\mst@varfam@question
1009 \fi

```

`\MTlowerast` [1.12d](#) The `\ast` or `*` is defined in `fontmath.ltx` as a binary operator from the `symbols` font. `\mst@doasterisk` Usually the asterisk from the text font is in a raised position. Previous versions of `mathastext` did nothing with `\ast` but strangely defined `*` to be the one from the text font, with type `\mathalpha`. The package now leaves by default both `*` and `\ast` untouched, and if passed option `asterisk` replaces both of them with a lowered text asterisk (or the one from the `Symbol` font), and of type `\mathbin`. A trick is used to optionally get both `*` and `\ast` obey the math alphabets.

The user macro `\MTlowerast` sets the amount of lowering to be applied to the text asterisk.

[1.12e](#) Somehow there was a big omission in [1.12d](#), the command `\MTlowerast` as described in the manual was missing!

[1.3i](#) adds `\MTnormalasterisk` and `\MTactiveasterisk`. They do nothing if package is loaded without option `asterisk`.

[1.4](#) uses `\protected` rather than robust commands. And implements the support for the new default of not using `\everymath`.

The first two `\newcommand*` are because the commands were previously defined unconditionally anyhow, in a way making them no-op's without option `asterisk`. Finally using `\let` here with `\empty` with the idea of less impact on TeX internals, but losing L<sup>A</sup>T<sub>E</sub>X check.

```
1010 \let\MTnormalasterisk\empty
1011 \let\MTactiveasterisk\empty
1012 \ifmst@asterisk\mst@infoline{asterisk: \string\ast\space and *}
1013   \ifmst@symbolmisc
1014     \protected\def\mst@bin@ast{\mathbin{\mathchoice
1015       {\raisebox{-.1\height}{\the\textfont\symmtsymbol\char42}}%
1016       {\raisebox{-.1\height}{\the\textfont\symmtsymbol\char42}}%
1017       {\raisebox{-.1\height}{\the\scriptfont\symmtsymbol\char42}}%
1018       {\raisebox{-.1\height}{\the\scriptscriptfont\symmtsymbol\char42}}}}%
1019     }%
1020   \else
1021     \protected\def\mst@bin@ast{\mathbin{\mathchoice
1022       {\raisebox{-\mst@lowerast}{\the\textfont\symmtoperatorfont\char42}}%
1023       {\raisebox{-\mst@lowerast}{\the\textfont\symmtoperatorfont\char42}}%
1024       {\raisebox{-\mst@lowerast}{\the\scriptfont\symmtoperatorfont\char42}}%
1025       {\raisebox{-\mst@lowerast}{\the\scriptscriptfont\symmtoperatorfont\char42}}}}%
1026     }%
1027   \fi
1028   \protected\def\mst@varfam@ast{\ifnum\fam=\m@ne
1029     \mst@bin@ast
1030   \else
1031     \mathbin{\mathchoice
1032       {\raisebox{-\mst@lowerast}{\the\textfont\fam\char42}}%
1033       {\raisebox{-\mst@lowerast}{\the\textfont\fam\char42}}%
1034       {\raisebox{-\mst@lowerast}{\the\scriptfont\fam\char42}}%
1035       {\raisebox{-\mst@lowerast}{\the\scriptscriptfont\fam\char42}}}}%
1036     \fi}%
1037   \let\mst@ast\mst@bin@ast
1038   \newcommand*\MTlowerast[1]{\def\mst@lowerast{#1}}
1039   \MTlowerast{.3\height}
```

Arguably `mathastext` should have used the “hard” non-letters affiliation here. Probably too late to change this in 2024... and costly in documentation time.

```
1040   \mst@do@easynonletters\expandafter{%
1041     \the\mst@do@easynonletters\let\mst@ast\mst@varfam@ast
1042   }%
1043   \ifmst@everymath
1044     \def\mst@@doasterisk {\let\ast\mst@ast\mst@mathactivate*{}\mst@ast}%
1045     \def\MTnormalasterisk {\let\mst@doasterisk\relax}
```

```

1046 \def\MTactiveasterisk {\let\mst@doasterisk\mst@@doasterisk}
1047 \MTactiveasterisk
1048 \AtBeginDocument{%
1049   \everymath\expandafter
1050   {\the\everymath \mst@doasterisk \MTnormalasterisk }%
1051   \everydisplay\expandafter
1052   {\the\everydisplay\mst@doasterisk \MTnormalasterisk }%
1053 }%
1054 \else
1055 \def\MTnormalasterisk{\AtBeginDocument{\MTnormalasterisk}}
1056 \def\MTactiveasterisk{\AtBeginDocument{\MTactiveasterisk}}

```

For legacy reasons the responsiveness to math alphabets is made part of the handling of “easy” non letters (probably because it is on per default), and this causes me problems of internal logic and even more annoyingly of documentation. I am leaving this standing because it would be too much of a pain at this stage to document a change and it was already quite annoying to better document actual situation.

```

1057 \mst@undo@easynonletters\expandafter{%
1058   \the\mst@do@easynonletters\let\mst@ast\mst@bin@ast
1059 }%

```

For legacy reasons the action of `\MTactiveasterisk` is not testing if in subdued mode.

MEMO: if subdued there is `\MTeverymathoff` added to `\begin{document}` near end of package and it will do `\MTnormalasterisk`.

```

1060 \AtBeginDocument{%
1061   \let\mst@orig@abd@ast\ast
1062   \edef\MTnormalasterisk{\noexpand\mst@mathdeactivate*\{\the\mathcode`*\}%
1063   \let\noexpand\ast\noexpand\mst@orig@abd@ast}%
1064   \def\MTactiveasterisk{\def\ast{\mst@ast}%
1065     \mst@mathactivate*\{}\mst@ast
1066   }%
1067   \MTactiveasterisk
1068 }
1069 \fi
1070 \fi

```

(2011) I renounced to try to do things with all the various dots, they are defined in many different ways, and there is the `amsmath` also. Dealing with this issue would mean a lot a time for a minuscule result. Better to leave the user use the `mathdots` package and accept that we can not avoid the default fonts in that case. So here I just treat . (in the hope to really lessen by 1 the number of fonts embedded at the end in the PDF).

[(Dec. 2012) should I reexamine these definitive sounding remarks?]

`ncccomma` [1.3y](#) of 2022/11/03 adds support for `ncccomma` option.

`decimalcomma` Some non-obvious hack is needed for compatibility with our home-made mechanism of non-letters obeying math alphabet commands. Alternative would have been to not load at all `ncccomma` (or since [1.3zb](#) `decimalcomma`) and provide the functionality purely by our own means; because here in order to support `\MTnonlettersobeymathxx` we are almost contrived to override quasi entirely the contents of these tiny packages.

[1.3zb](#) adds support for the `decimalcomma` option. This was mandatory to keep a compatibility layer with `frenchmath` after its 2.7 release of 2023/12/23.

Hesitation if I should also make it shadow the `ncccomma` option if both are used at same time, or let the older option have priority. Well, let's give priority to the new one so that one can do `\PassOptionsToPackage` and recycle old documents compiled via `\input` to tell them to use the new option.

Much ado about these tiny packages!

```
1071 \ifmst@nopunct\else\mst@infoline{punctuation\string: \string, \string. \string:
1072   \string; and \string\colon}
1073   \DeclareMathSymbol{,}{\mathpunct}{\msft@font@tbu}{",2C}
1074   \DeclareMathSymbol{\mst@varfam@comma}{\mathalpha}{\msft@font@tbu}{",2C}
1075 \ifmst@decimalcomma
1076   \mst@infoline{loading package decimalomma for `smart comma\string'}
1077   \RequirePackage{decimalcomma}[2023/12/28] % 1.3 or later
```

Attention that the **BREAKING CHANGE** to `\AtBeginDocument` at October 2020 L<sup>A</sup>T<sub>E</sub>X release means that, *taking into account that `mathastext` already has employed some `\AtBeginDocument` prior to loading `decimalcomma`*, any code here will be executed **BEFORE** the `\AtBeginDocument` material from `decimalcomma`!

<https://github.com/latex3/latex2e/issues/1226>

So we definitely should not do here some `\mathcode`,\="8000\relax` in the `\AtBeginDocument`, and by the way I don't even recall why I had this line at some point which ended up causing me some much suffering and pain and lost sleep. It seems to have been a silly copy-paste from the `ncccomma` branch next, and that I started experimenting before having even re-read the code I copied pasted and whether it was needed.

`decimalcomma` is a rewrite of `icomma` and it loads the latter for which `babel-french` has a detection mechanism, which as a result avoids the bad interactions with `numprint` plus its `autolanguage` option, which are mentioned below in the `ncccomma` branch. So we don't need here the workaround done below in the `ncccomma` branch. Notice though that in both cases, the 'intelligent' comma feature will be applied to the whole document, even inside those portions where the user has switched to another language such as English. This is to be expected here as nothing is done in a language specific manner, but if we wanted to do so, we might then be confronted with the `babel` issue mentioned next in the `ncccomma` branch.

```
1078   \let\mathcomma\relax
1079   \DeclareMathSymbol{\mathcomma}{\mathpunct}{\msft@font@tbu}{",2C}
```

Due to package `decimalcomma` internals, the hack here, which has to do with the "non letters obey math alphabets" optional `mathastext` feature, has to be done differently than the one we apply below for `ncccomma`. One can not really talk of a hack, as we basically have to redo the whole thing to insert an `\aftergroup` trick.

```
1080   \def\mst@sm@rtcomma{\begingroup\@tfor\@tempa:=0123456789%
1081     \do{\expandafter\ifx\@tempa\@let@token
1082       \aftergroup\mathord
1083       \aftergroup\@gobble
1084       \break@tfor\fi}%
1085     \endgroup\mathpunct\mathcomma}
1086   \mst@do@nonletters\expandafter{\the\mst@do@nonletters
1087     \let\mathcomma\mst@varfam@comma
1088     \let\sm@rtcomma\mst@sm@rtcomma
1089   }
1090   \ifmst@everymath
1091   \else
```

```

1092      \edef\mst@tmp{\mathchardef\mathcomma=\the\mathcode`\,,\relax}%
1093      \mst@undo@nonletters\expandafter\expandafter\expandafter
1094          {\expandafter\mst@tmp\the\mst@undo@nonletters}%
1095  \fi
1096 \else

```

Work around some bad interaction of `ncccomma`, `numprint` with `autolanguage` and `babel-french`.  
See

<https://github.com/latex3/babel/issues/190>

for background. Some hesitation whether I should use the `\noextrasfrench` to work around `babel-french` code influencing non-French sections in the document. Update: I think the last sentence means I was hesitating at time of [1.3y](#) whether to insert some extra code inside the `\noextrasfrench`.

```

1097 \ifmst@ncccomma
1098   \mst@infoline{loading package ncccomma for `smart comma/string'}
1099   \RequirePackage{ncccomma}%
1100   \AtBeginDocument{%
1101     \mathcode`\,="8000\relax
1102     \c@ifpackageloaded{babel}{%
1103       \addto\noextrasfrench{\mathcode`\,="8000\relax}%
1104       \addto\extrasfrench{\mathcode`\,="8000\relax}%
1105     }{}%
1106   }
1107   \let\mathcomma\relax
1108   \DeclareMathSymbol{\mathcomma}{\mathpunct}{\mst@font@tbu}{2C}

```

Complications for compatibility with the `\MTnonlettersobeymathxx` mechanism. No fix done here for usage by `ncccomma` of `\@tempb` with no restoration of its meaning.

```

1109 \edef\mst@NCC@comma{\let\noexpand\empty\mathpunct
1110           \unexpanded\expandafter{\NCC@comma}%
1111           \let\noexpand\empty\noexpand\empty}
1112 \mst@do@nonletters\expandafter{\the\mst@do@nonletters
1113   \let\mathcomma\mst@varfam@comma
1114   \let\NCC@comma\mst@NCC@comma
1115 }
1116 \ifmst@everymath
1117 \else

```

Attention that `ncccomma` (contrarily to `icomma` loaded by `decimalcomma`) has made the comma math active already when we loaded it. So we don't use `\the\mathcode`\,,\relax` here.

```

1118   \edef\mst@tmp{\mathchardef\mathcomma=\the\mathcomma\relax}%
1119   \mst@undo@nonletters\expandafter\expandafter\expandafter
1120       {\expandafter\mst@tmp\the\mst@undo@nonletters}%
1121 \fi
1122 \else

```

Neither option `ncccomma` nor `decimalcomma`. The [1.4](#) non-use of `\everymath` and consequences is accounted for automatically by `\mst@addtodo@nonletters`.

```

1123   \expandafter\mst@addtodo@nonletters\string,\mathpunct\mst@varfam@comma
1124 \fi\fi
math dot.

```

```

1125  \DeclareMathSymbol{.}{\mathord}{\mst@font@tbu}{"2E}
1126  \DeclareMathSymbol{\mst@varfam@dot}{\mathalpha}{\mst@font@tbu}{"2E}
1127  \mst@addtodo@easynonletters\.\mst@varfam@dot
    math colon.

1128  \DeclareMathSymbol{:}{\mathrel}{\mst@font@tbu}{"3A}
1129  \DeclareMathSymbol{\mst@varfam@colon}{\mathalpha}{\mst@font@tbu}{"3A}
1130  \expandafter\mst@addtodo@nonletters\string:\mathrel\mst@varfam@colon
1131  \@ifpackageloaded{amsmath}

    \colon gets defined in amsmath in terms of : with some enlarged explicit spacing. No need to
    intervene.

1132  {}

No amsmath, use standard punctuation spacing.
The reason for \et\colon\undefined is if some package has redefined \colon which then can
not be used in \DeclareMathSymbol anymore (we shamelessly overwrite...)

1133  {%
1134  \let\colon\undefined
1135  \DeclareMathSymbol{\colon}{\mathpunct}{\mst@font@tbu}{"3A}
1136  \let\mst@colon\colon

    1.3v uses \protected for the (optional) \colon redefinition.

1137  \mst@do@nonletters\expandafter{%
1138      \the\mst@do@nonletters
1139      \protected\def\colon{\mathpunct{\mst@varfam@colon}}%
1140  }%

1.4 needs extras.

1141  \ifmst@everymath
1142  \else
1143      \mst@undo@nonletters\expandafter{%
1144          \the\mst@undo@nonletters
1145          \let\colon\mst@colon
1146      }%
1147  \fi
1148 }

Semi-colon. 1.3y adds binarysemicolon option.

1149  \DeclareMathSymbol{\mst@varfam@pointvirgule}{\mathalpha}{\mst@font@tbu}{"3B}
1150  \ifmst@binarysemicolon
1151      \mst@infoline{semi-colon set to be of type \string\mathbin}
1152      \DeclareMathSymbol{;}{\mathbin}{\mst@font@tbu}{"3B}
1153      \expandafter\mst@addtodo@nonletters\string;\mathbin\mst@varfam@pointvirgule
1154  \else
1155      \DeclareMathSymbol{;}{\mathpunct}{\mst@font@tbu}{"3B}
1156      \expandafter\mst@addtodo@nonletters\string;\mathpunct\mst@varfam@pointvirgule
1157  \fi
1158 \fi

```

**\relbar** Due to the way = and - are used by L<sup>A</sup>T<sub>E</sub>X in arrows, we will have to redefine \Relbar and \relbar in order for them to preserve their original meanings.

[1.15d](#): Oct 13, 2012. Belated amendment of the code to be compatible with Unicode engines in case someone changed the mathcode of -. However, for the time being I can do it in an easy way only for X<sub>E</sub>T<sub>E</sub>X, not for LuaL<sub>A</sub>T<sub>E</sub>X. Also I do my modifications to \relbar in a manner testing for the presence of amsmath.

[1.3v](#) 2019/09/19: L<sub>A</sub>T<sub>E</sub>X of 2019-10-01 defines \leftarrowfill and \rightarrowfill as robust macros, so we do the same.

I need to put amsmath under surveillance to check if it decides to robustify \relbar at some point, now that the L<sub>A</sub>T<sub>E</sub>X team has taken over maintenance.

2019/09/16 Use \protected for \right|leftarrowfill in the non \DeclareRobustCommand branch?

```

1159 \ifmst@nominus
1160 \else
1161   \ifmst@XeOrLua
1162     \mst@Umathcharnumdef\mst@minus@sign=\mst@Umathcodenum`-\relax

```

I used this prior to the new \luatexUmathcodenum, as available since TL2013:

```

          \mathchardef\mst@minus@sign=8704\relax % "2200

```

```

1163 \else
1164   \mathchardef\mst@minus@sign=\mathcode`-\relax
1165 \fi
1166 \@ifpackageloaded{amsmath}
1167   {\def\relbar{\mathrel{\mathpalette\mathsmash\mst@minus@sign}}}
1168   {\DeclareRobustCommand\relbar{\mathrel{\smash{\mst@minus@sign}}}}
1169 \ DeclareRobustCommand\rightarrowfill{$\mathrel{\relbar}\mkern-7mu%
1170 \cleaders\hbox{$\mkern-2mu\relbar\mkern-2mu$}\hfill
1171 \mkern-7mu\mathord\rightarrow$}
1172 \ DeclareRobustCommand\leftarrowfill{$\mathrel{\mathord\leftarrow}\mkern-7mu%
1173 \cleaders\hbox{$\mkern-2mu\relbar\mkern-2mu$}\hfill
1174 \mkern-7mu\mathord{\relbar}$}
1175 \fi

```

endash [1.1](#) 2011/01/29: Producing this next piece of code was not a piece of cake for a novice like myself!

[1.11](#) 2011/02/05: Compatibility with Unicode (via use of fontspec encodings EU1 and EU2)

[1.12](#) 2011/02/07: Improved dealing of Unicode possibility.

[1.14b](#) 2011/04/02: Corrected some very irresponsible bug in the Unicode part which caused a problem when 10 or more math families have been allocated.

[1.15](#) 2012/09/24: Added AtBeginDocument to circumvent some amsmath problem with unicode engines.

[1.31](#) 2016/01/29: anticipating TL2016 fontspec's switch to TU.

[1.3t](#) 2018/08/22: fix to very ancient (2012/12/20) bug with \DeclareMathSymbol lacking last argument if encoding not T1, OT1 or LY1 when setting up math mode to use the en-dash character as minus sign (PDF<sub>T</sub>E<sub>X</sub> engine).

\mst@subduedminus [1.3t](#) Further, new macros \mst@subduedminus and \mst@nonsubduedminus, for the good functioning of the subdued option also in case of presence of fontspec. This is the only character for which subdued option works (now) by setting the mathcode on each math version change. Indeed, a typical issue is when the Unicode EN DASH or MINUS is used, but the actual font in subdued normal math version is originally in OT1 or T1 encoding. The only reasonable way to

address this is by actually modifying the assigned mathcode at each version change. This means also that `\MTversion` and not `\mathversion` must be used for good functioning.

[1.3u](#) improves the handling of the minus sign by letting it be compatible with math versions (and not only with the with subdued mechanism but all math versions) having varying font encodings, even possibly classic 8bit font encoding mixed with TU encoding for Unicode engines. For this it is needed to work around a feature of XeTeX/LuaTeX, here is original comment:

afaict it is impossible to use straightforwardly in extended mathcode assignments a control sequence as created by `\Umathchardef`. This is counter-intuitive and breaks expectations.

But the [1.3u](#) mechanism with `\mst@UmathchardefWorkAround@i` introduced a bug which showed under option `noendash` (hence also `symboldelimiters`) with Unicode engines. Fixed at [1.3w](#).

```

1176 \let\mst@subduedminus\empty
1177 \let\mst@nonsubduedminus\empty
1178 \def\mst@dothe@endashstuff#1#2#3{%
1179   \edef\mst@tmp@enc{#3}%
1180   \if1\mst@0neifUniEnc
1181     \mst@Umathchardef#1=2 \symmtoperatorfont "\mst@unicodeminus\relax
1182     \mst@Umathchardef#2=7 \symmtoperatorfont "\mst@unicodeminus\relax
1183   \else
1184     \DeclareMathSymbol{#1}{\mathbin}{\mtoperatorfont}{%
1185       \csname\mst@tmp@enc\string\textendash\endcsname}
1186     \DeclareMathSymbol{#2}{\mathalpha}{\mtoperatorfont}{%
1187       \csname\mst@tmp@enc\string\textendash\endcsname}
1188   \fi
1189 }%
1190 \def\mst@dothe@emdashstuff#1#2#3{%
1191   \edef\mst@tmp@enc{#3}%
1192   \if1\mst@0neifUniEnc
1193     \mst@Umathchardef#1=2 \symmtoperatorfont "2014\relax
1194     \mst@Umathchardef#2=7 \symmtoperatorfont "2014\relax
1195   \else
1196     \DeclareMathSymbol{#1}{\mathbin}{\mtoperatorfont}{%
1197       \csname\mst@tmp@enc\string\textemdash\endcsname}
1198     \DeclareMathSymbol{#2}{\mathalpha}{\mtoperatorfont}{%
1199       \csname\mst@tmp@enc\string\textemdash\endcsname}
1200   \fi
1201 }%
1202 \def\mst@dothe@hyphenstuff#1#2{%
1203   \DeclareMathSymbol{#1}{\mathbin}{\mst@font@tbu}{2D}%
1204   \DeclareMathSymbol{#2}{\mathalpha}{\mst@font@tbu}{2D}%
1205 }%
1206 \def\mst@varfam@minus{\@nameuse{mst@varfam@minus@mv\math@version}}%
1207 \ifmst@nominus\else
1208   \expandafter\mst@addtodo@nonletters\string-\mathbin\mst@varfam@minus
1209   \def\mst@nonsubduedminus{%
1210     \edef\mst@tmp@enc{\csname mst@encoding@\math@version\endcsname}%

```

```

1211 \if1\mst@OneifUniEnc
1212   \mst@Umathcode`\\-=\expandafter
1213     \mst@UmathchardefWorkAround@i
1214     \csname mst@minus@mv\math@version\endcsname
1215     \relax
1216 \else
1217   \mathcode`\\-=\nameuse{mst@minus@mv\math@version}%
1218 \fi
1219 }%

```

The above works only if the `\mst@minus@mv<name>` was really defined via `\Umathchardef`. If it was defined via `\DeclareMathSymbol` then it is a `\mathchar`, not a `\Umathchar`. At least currently (2019). So we need to correct the definition of `\mst@nonsubduedminus`.

```

1220 \ifmst@endash\else\ifmst@emdash\else
1221   \def\mst@nonsubduedminus{%
1222     \mathcode`\\-=\nameuse{mst@minus@mv\math@version}%
1223   }%
1224 \fi\fi
1225 \fi
1226 \def\mst@UmathchardefWorkAround@i
1227   {\expandafter\mst@UmathchardefWorkAround@ii\meaning}%
1228 \def\mst@UmathchardefWorkAround@ii#1"{}%

```

`\mst@hbar@mnormal` 2011/01/31, 1.1 I decide to settle the question of the `\hbar`. The L<sup>A</sup>T<sub>E</sub>X definition is `\def\hbar{{\mathchar'26\mkern-9muh}}` and its advantage is that `h` is in the correct font. But of course not the macron character (`\=`, `\bar`). And anyway `amsfonts` uses a `\DeclareMathSymbol`. Also there is the kern whose length depends on `cmsy` (18mu=1em and em taken from info in `cmsy`).

I will need an `rlap` adapted to math mode, and this is provided by code from Alexander R. PERLIS in his TugBoat article 22 (2001), 350–352, which I found by googling `rlap`. (as an aside, I am only now (April 2, 2011) aware that the package `mathtools` provides the `mathrlap` etc... )

1.31 2016/01/29: anticipating TL2016 fonts's switch to TU.

1.3u 2019/08/20: encoding (8bits) agnostic construct for `hbar`, using same method as for `mathaccents` option. I should add some way to adjust the vertical positioning.

On this occasion I replace `h` by `\mst@h` because the mechanism for before and after skips does not interact well with the `rlap` construct.

1.3v 2019/09/19 adapts to maintain the robustness of `\hbar` which now applies with L<sup>A</sup>T<sub>E</sub>X 2019-10-01.

1.3w works around <https://github.com/latex3/latex2e/issues/216> via `\mst@DeclareMathAccent`. The upstream bug affected the definition of `\mst@ltbar@mnormal` and broke usage of `\Mathastext` in preamble.

1.3w also fixes oversight that `\hbar` may have been redefined via `\DeclareMathSymbol` by some package (e.g. `amsfonts`) and with L<sup>A</sup>T<sub>E</sub>X 2019-10-01 this means `\hbar<space>` is now undefined. Modifying it changed nothing to `\hbar` behavior in such circumstances. Finally we opt for a `\protected` `\hbar` and choose to ignore completely if there is a `\hbar<space>` or not. To avoid extra steps we do not undefine it if it exists, because we would need to restore it in subdued math versions.

```

1229 \let\mst@subduedhbar\empty
1230 \let\mst@nonsubduedhbar\empty

```

```

1231 \ifmst@nohbar\else
1232   \def\mst@subduedhbar{\let\hbar\mst@original@hbar}%
1233   \def\mst@nonsubduedhbar{\expandafter
1234     \let\expandafter\hbar\csname mst@hbar@mv\math@version\endcsname}%
1235 \fi
1236 \def\mst@mathrlap{\mathpalette\mst@mathrlapinternal}
1237 \def\mst@mathrlapinternal#1#2{\rlap{$\mathsurround=0pt#1{#2}$}}
1238 \def\mst@dothe@hbarstuff#1#2#3{%
1239   \edef\mst@tmp@enc{#3}%
1240   \if1\mst@OneifUniEnc
1241     \mst@Umathchardef#1="7 \symmtletterfont "0127 \relax %% or 210F?
1242   \else
1243     \begingroup
1244       \def\@text@composite##1\@text@composite##2{##2}%
1245       \let\add@accent\@firstoftwo
1246       \mst@DeclareMathAccent{#2}{\mathalpha}{\mtletterfont}%
1247         {\csname\mst@tmp@enc\string\=\endcsname{} }%
1248     \endgroup
1249     \protected\def#1{\mst@mathrlap{#2{\ }}\MTmathcharletterh}%
1250   \fi
1251 }%

```

**1.15d:** Oct 13, 2012. The `\mathcode` thing with = is (belatedly, sorry!) made Unicode compatible.

+ , = , \Relbar

```

1252 \ifmst@noplus\else\mst@infoline{\string+ and \string=}
1253 \DeclareMathSymbol{+}{\mathbin}{\mst@font@tbu}{2B}
1254 \DeclareMathSymbol{\mst@varfam@plus}{\mathalpha}{\mst@font@tbu}{2B}
1255 \expandafter\mst@addtodo@nonletters\string+\mathbin\mst@varfam@plus
1256 \fi
1257 \ifmst@noequal\else
1258 \ifmst@XeOrLua
1259   \mst@Umathcharnumdef\mst@equal@sign=\mst@Umathcodenum`=\relax
1260 \else
1261   \mathchardef\mst@equal@sign=\mathcode`=\relax
1262 \fi
1263 \ifeipackageloaded{amsmath}
1264 {\def\Relbar{\mathrel{\mst@equal@sign}}}
1265 {\DeclareRobustCommand\Relbar{\mathrel{\mst@equal@sign}}}
1266 \ DeclareMathSymbol{=}{\mathrel}{\mst@font@tbu}{3D}
1267 \ DeclareMathSymbol{\mst@varfam@equal}{\mathalpha}{\mst@font@tbu}{3D}

```

**\nfss@catcodes** 2012/12/18: Activating = (only in math mode actually) seems very bad but surprisingly works well. However I had a problem with `eu2lmtt.fd` which should not be loaded with an active =. 2012/12/25: Since then I had switched to only math activation. And in fact the problematic = from `eu2lmtt.fd` end up in `\csname...\endcsname` and I have learnt since that TeX does not look at the `\mathcode` inside a `\csname...\endcsname`. Example:

% `\mathcode`x="8000`

```
% \begingroup
% \catcode`x=\active
% \global\everymath{\defx{Hello}}
% \endgroup
% \def\foox{World!}
% $x \csname foox\endcsname$
```

We need nevertheless to inactivate the =, for the following reason. Imagine someone did `\catcode`==\active\def={\string=}`, or another definition which would not lead to a tragedy in a `\csname... \endcsname`. Then the = is active and the re-definition done by `mathastext` will not be compatible with loading `eu2lmtt.fd` (for the first time) from math mode, as this re-definition can not be expanded inside a `\csname... \endcsname`.

2012/12/28: to be on the safe side, I add also ; and + and do it without discriminating between engines

```
1268 \mst@infoline{adding \string= \string; and \string+ to \string\nfss@catcodes}
1269 \g@addto@macro\nfss@catcodes{%
1270   \makeother\=%
1271   \makeother\;%
1272   \makeother\+%
1273 }
1274 \expandafter\mst@addtodo@nonletters\string=\mathrel\mst@varfam@equal
1275 \fi
```

`noparenthesis (, , [, , /` `\lbrack` and `\rbrack` are defined in `latex.ltx` by `\def\lbrack{} \def\rbrack{}` so this fits well with what we do here. `\lparen` and `\rparen` are similarly defined in `mathtools`. On the other hand in `latex.ltx` with `\{` and `\}` are defined (in math mode) in terms of the control sequences `\lbrace` and `\rbrace`. Such control sequences can not be simultaneously math symbols and math delimiters, thus, this complicates things for the `mathastextification`.

```
1276 \ifmst@noparen\else
1277 \mst@infoline{parentheses \string( \string) \string[ \string] and slash \string/}
1278 \ifmst@nosmalldelims
1279   \DeclareMathSymbol{\{}{\mathopen}{\mst@font@tbu}{28}
1280   \DeclareMathSymbol{\}}{\mathclose}{\mst@font@tbu}{29}
1281   \DeclareMathSymbol{\[]{\mathopen}{\mst@font@tbu}{5B}
1282   \DeclareMathSymbol{\]}{\mathclose}{\mst@font@tbu}{5D}
1283   \DeclareMathSymbol{/}{\mathord}{\mst@font@tbu}{2F}
1284 \else
1285   \DeclareMathDelimiter{\{}{\mathopen}{\mst@font@tbu}{28}{largesymbols}{00}
1286   \DeclareMathDelimiter{\}}{\mathclose}{\mst@font@tbu}{29}{largesymbols}{01}
1287   \DeclareMathDelimiter{\[]{\mathopen}{\mst@font@tbu}{5B}{largesymbols}{02}
1288   \DeclareMathDelimiter{\]}{\mathclose}{\mst@font@tbu}{5D}{largesymbols}{03}
1289   \DeclareMathDelimiter{/}{\mathord}{\mst@font@tbu}{2F}{largesymbols}{0E}
1290 \fi
1291 \DeclareMathSymbol{\mst@varfam@lparen}{\mathalpha}{\mst@font@tbu}{40}
1292 \DeclareMathSymbol{\mst@varfam@rparen}{\mathalpha}{\mst@font@tbu}{41}
1293 \DeclareMathSymbol{\mst@varfam@lbrack}{\mathalpha}{\mst@font@tbu}{5B}
1294 \DeclareMathSymbol{\mst@varfam@rbrack}{\mathalpha}{\mst@font@tbu}{5D}
1295 \DeclareMathSymbol{\mst@varfam@slash}{\mathalpha}{\mst@font@tbu}{2F}
```

```

1296 \expandafter\mst@addtodo@nonletters\string(\mathopen\mst@varfam@lparen
1297 \expandafter\mst@addtodo@nonletters\string)\mathclose\mst@varfam@rparen
1298 \expandafter\mst@addtodo@nonletters\string[\mathopen\mst@varfam@lbrack
1299 \expandafter\mst@addtodo@nonletters\string]\mathclose\mst@varfam@rbrack
1300 \mst@addtodo@easynonletters\/\mst@varfam@slash
1301 \fi

```

### alldelims

```

<,>, \
1302 \ifmst@alldelims\mst@infoline{alldelims: \string< \string>
\setminus 1303   \string\backslash\space\string\setminus\space\string\
\backslash 1304   \string\vert\space\string\mid\space\string\{\space \string\}}
1305 \ifmst@nosmalldelims

```

Dec 18, 2012. We then want `\let\backslash\mst@varfam@backslash` to do nothing when the `\backslash` is used as a delimiter. So here the original definition from `latex.ltx` is copied, generally speaking when people use other math symbol fonts they do respect the encoding of the CM symbols and largesymbols, so this is 90% safe. But in truth I should extract from the meaning of `\backslash` the delcode.

At 1.4 I am a bit perplexed at the `\mathalpha` here. Adding a `\mst@mathord@backslash` for matters of option `noeverymath`.

```

1306   \DeclareMathDelimiter{\mst@varfam@backslash}
1307     {\mathalpha}{symbols}{"6E}{largesymbols}{"0F}
1308   \let\mst@mathord@backslash\backslash
1309 \else
1310   \DeclareMathDelimiter{<}{\mathopen}{\mst@font@tbu}{"3C}{largesymbols}{"0A}
1311   \DeclareMathDelimiter{>}{\mathclose}{\mst@font@tbu}{"3E}{largesymbols}{"0B}

```

There is no backslash in the Symbol font hence `mtoperatorfont` here.

```

1312   \DeclareMathDelimiter{\mst@mathord@backslash}
1313     {\mathord}{mtoperatorfont}{"5C}{largesymbols}{"0F}
1314   \let\backslash\mst@mathord@backslash
1315   \DeclareMathDelimiter{\mst@varfam@backslash}
1316     {\mathalpha}{mtoperatorfont}{"5C}{largesymbols}{"0F}
1317 \fi
1318 \DeclareMathSymbol{<}{\mathrel}{\mst@font@tbu}{"3C}
1319 \DeclareMathSymbol{>}{\mathrel}{\mst@font@tbu}{"3E}
1320 \DeclareMathSymbol{\mst@varfam@less}{\mathalpha}{\mst@font@tbu}{"3C}
1321 \DeclareMathSymbol{\mst@varfam@more}{\mathalpha}{\mst@font@tbu}{"3E}
1322 \expandafter\mst@addtodo@nonletters\string<\mathrel\mst@varfam@less
1323 \expandafter\mst@addtodo@nonletters\string>\mathrel\mst@varfam@more
1324 \mst@do@easynonletters\expandafter{\the\mst@do@easynonletters
1325           \let\backslash\mst@varfam@backslash}

```

Extras for 1.4 are needed:

```

1326 \ifmst@everymath
1327 \else
1328   \mst@undo@easynonletters\expandafter{\the\mst@undo@easynonletters
1329           \let\backslash\mst@mathord@backslash}
1330 \fi
1331 \DeclareMathSymbol{\setminus}{\mathbin}{mtoperatorfont}{"5C}
1332 \let\mst@setminus\setminus

```

```

1333 \DeclareMathSymbol{\mst@varfam@setminus}{\mathalpha}{mtoperatorfont}{\text{5C}}
  1.3v adds a \protected here for \setminus.

```

```

1334 \mst@do@nonletters\expandafter{%
1335   \the\mst@do@nonletters
1336   \protected\def\setminus{\mathbin{\mst@varfam@setminus}}%
1337 }

```

Extras for 1.4 are needed:

```

1338 \ifmst@everymath
1339 \else
1340   \mst@undo@nonletters\expandafter{%
1341     \the\mst@undo@nonletters
1342     \let\setminus\mst@setminus
1343   }
1344 \fi

```

\models 1.15d: 13 oct 2012. Before modifying | we must preserve \models.

```

1345 \ifmst@XeOrLua
1346   \mst@Umathcharnumdef\mst@vert@bar=\mst@Umathcodenum`\\relax
1347 \else
1348   \mathchardef\mst@vert@bar=\mathcode`\\relax
1349 \fi
1350 \ DeclareRobustCommand\models{\mathrel{\mst@vert@bar}\joinrel\Relbar}

```

,\mid,\vert (2011) I did not do anything then to try to emulate \Vert with the vertical bar from the text font... and now (2012) **mathastext** is not as radical as it used to be anyhow, so it is too late. Or not (2019)? maybe I *should* do something here...

1.3v 2019/09/19: I discover this rather radical legacy \def\vert{}, which is done here once in the preamble, but I leave it unmodified apart from prefixing it with \protected. I also add a \protected for the definition of \mid (which applies only under \MTnonlettersobeymathxx regime).

```

1351 \ifmst@nosmalldelims
1352   \DeclareMathSymbol{|}{\mathord}{\mst@font@tbu}{124}
1353 \else
1354   \DeclareMathDelimiter{|}{\mathord}{\mst@font@tbu}{124}{largesymbols}{\text{0C}}
1355 \fi
1356 \protected\def\vert{}
1357 \DeclareMathSymbol{\mst@varfam@vbar}{\mathalpha}{\mst@font@tbu}{124}
1358 \mst@addtodo@easynonletters\\mst@varfam@vbar
1359 \let\mid\undefined
1360 \DeclareMathSymbol{\mid}{\mathrel}{\mst@font@tbu}{124}
1361 \let\mst@mid\mid
1362 \mst@do@nonletters\expandafter{%
1363   \the\mst@do@nonletters
1364   \protected\def\mid{\mathrel{\mst@varfam@vbar}}%
1365 }

```

Extras for 1.4 are needed:

```

1366 \ifmst@everymath
1367 \else

```

```

1368     \mst@undo@nonletters\expandafter{%
1369         \the\mst@undo@nonletters
1370         \let\mid\mst@mid
1371     }
1372 \fi

```

\MTexplicitbraces-  
obeymathxx Braces. With version 1.2, \{ and \} will not be acceptable as delimiters anymore if the redefinitions below in \mst@dobraces are enacted. But they will obey math alphabets. Improvements in 1.2a, to preserve robustness.

\MTexplicitbraces-  
donotobeymathxx For 1.3 I make \lbrace and \rbrace undefined first, else problems may arise with some packages.

1.3e suppresses under option nosmalldelims the definitions of \lbrace and \rbrace as math symbols as this made \left\lbrace cause an error, it was a bug.

(obsolete) LaTeXe defines \{ and \} as robust commands since a long time (I don't know since when). The **mathastext** redefinition is done only if user has executed \MTexplicitbrace-sobeymathxx, and it is done only when entering math mode, but there could be some \hbox inside math, hence it has to be careful to be valid in text too.

1.3v maintains strict L<sup>A</sup>T<sub>E</sub>Xe robustness for \{ and \}. This assumes no one fiddled with \{ and \} proper (without space in the name).

L<sup>A</sup>T<sub>E</sub>X made \{ and \} \protected, not robust, at its 2020-02-02 release, so the code used by **mathastext** under \MTexplicitbracesobeymathxx toggle remained without effect since as it configured a change to \{<space> and \}<space>. Fixed at 1.4.

```

1373 \ifmst@nosmalldelims
1374 \else
1375     \let\lbrace\undefined \let\rbrace\undefined
1376     \DeclareMathDelimiter{\lbrace}
1377         {\mathopen}{\mst@font@tbu}{123}{largesymbols}{08}
1378     \DeclareMathDelimiter{\rbrace}
1379         {\mathclose}{\mst@font@tbu}{125}{largesymbols}{09}
1380 \fi
1381 \DeclareMathSymbol{\mst@varfam@lbrace}{\mathalpha}{\mst@font@tbu}{123}
1382 \DeclareMathSymbol{\mst@varfam@rbrace}{\mathalpha}{\mst@font@tbu}{125}
1383 \protected\def\mst@lbrace{\ifmmode\mathopen\mst@varfam@lbrace\else\textbraceleft\fi}
1384 \protected\def\mst@rbrace{\ifmmode\mathclose\mst@varfam@rbrace\else\textbraceright\fi}
1385 \mst@do@nonletters\expandafter{%
1386     \the\mst@do@nonletters
1387     \mst@dobraces{\let{\mst@lbrace\let}\mst@rbrace}%
1388 }
1389 \fi
1390 \newcommand*{\MTexplicitbracesobeymathxx}{\let\mst@dobraces\@firstofone}
1391 \newcommand*{\MTexplicitbracesdonotobeymathxx}{\let\mst@dobraces\@gobble}

```

Extras for 1.4 are needed:

```

1392 \ifmst@everymath
1393 \else
1394     \renewcommand*{\MTexplicitbracesobeymathxx}{%
1395         \let\mst@dobraces\@firstofone
1396         \MTnonlettersobeymathxx
1397     }%

```

```

1398 \renewcommand*\MTexplicitbracesdonotobeymathxx{%
1399     \let\mst@dobraces\gobble
1400     \protected\def{\{\ifmmode \lbrace \else \textbraceleft \fi}%
1401     \protected\def{\}\ifmmode \rbrace \else \textbraceright \fi}%
1402 }%
1403 \mst@undo@nonletters\expandafter{\the\mst@undo@nonletters
1404     \protected\def{\{\ifmmode \lbrace \else \textbraceleft \fi}%
1405     \protected\def{\}\ifmmode \rbrace \else \textbraceright \fi}%
1406 }%
1407 \fi
1408 \MTexplicitbracesdonotobeymathxx

```

**specials** 1.14b 2011/04/02: the redefinitions of #, \$, % and & were buggy (this showed up when 10 or more math families had been created).

**1.15f** 2012/10/23: the code, although working, was perhaps a bit insane and had definitions which could surprise other packages. For example, it did:

```
\renewcommand{\%}{\ifmmode\mt@mmode@percent\else\char37\relax\fi}
```

But it seems this provokes a problem with `microtype`. Perhaps the problem was that the command was not declared robust? For the dollar `LATEX` itself does

```
\DeclareRobustCommand{\$}{\ifmmode\mathdollar\else\textrm{\textdollar}\fi}
```

So here I just modify `\mathdollar`. Then we have in `latex.ltx` the same definitions as in `plain.tex`: `\chardef\%='\%`, `\chardef\&='\&`, and `\chardef\#=+'\#`. It turns out that we can just adjust the mathcodes of these characters and achieve exactly what is wanted for the corresponding one char control sequences. In math mode the control sequence will use the specified mathcode. So here it is *not* a redefinition of the control sequences, purely an adjustment of mathcodes.

**1.2d** 2013/01/01: previous versions imposed the variable family type. I hereby make it possible to de-activate this feature with the macro `\MTeasyanonlettersdonotbeymathxx`. Besides, I have absolutely no idea why I had different looking code depending on the engine X<sub>E</sub>T<sub>E</sub>X, LuaT<sub>E</sub>X or default. Removed.

[1.3c](#) 2013/12/14: I have absolutely no idea why I removed the X<sub>E</sub>T<sub>E</sub>X and LuaT<sub>E</sub>X code at the time of [1.2d](#)! the code for tex/pdftex engine could not accomodate more than 16 math families. Code for X<sub>E</sub>T<sub>E</sub>X and LuaT<sub>E</sub>X again added. (and since TL2013 no more problems with \luatexUmathcode.)

[1.4](#) has done slight refactoring here to share more code related to math activation across the two branches.

```
1409 \ifmst@nospecials
1410 \else
1411   \mst@infoline{\string\#\space\string\mathdollar\space
1412                 \string\%\space\string\&\space}
1413 \ifmst@XeOrLua
1414   \mst@Umathcode`#=0 \symmtoperatorfont "23 \relax
1415   \mst@Umathchardef\mathdollar=0 \symmtoperatorfont "24 \relax
1416   \mst@Umathcode`\%=0 \symmtoperatorfont "25 \relax
1417   \mst@Umathcode`\&=0 \symmtoperatorfont "26 \relax
1418   \mst@Umathchardef\mst@varfam@mathhash      = 7 \symmtoperatorfont "23 \re-
lax
1419   \mst@Umathchardef\mst@varfam@mathdollar    = 7 \symmtoperatorfont "24 \re-
lax
```

```

1420      \mst@Umathchardef\mst@varfam@mathpercent    = 7 \symmtoperatorfont "25 \relax
1421      \mst@Umathchardef\mst@varfam@mathampersand = 7 \symmtoperatorfont "26 \relax
1422      \mst@addtodo@easynonletters@U\#\mst@varfam@mathhash
1423      \mst@addtodo@easynonletters@U\%\mst@varfam@mathpercent
1424      \mst@addtodo@easynonletters@U\&\mst@varfam@mathampersand
1425      \else
1426          \count@=\symmtoperatorfont
1427          \multiply\count@ by \@cclvi
1428          \advance\count@ by 35
1429          \mathcode`\#\count@
1430          \advance\count@ by \@ne
1431          \mathchardef\mathdollar\count@
1432          \advance\count@ by \@ne
1433          \mathcode`\%\count@
1434          \advance\count@ by \@ne
1435          \mathcode`\&\count@
1436          \count@=\symmtoperatorfont
1437          \multiply\count@ by \@cclvi
1438          \advance\count@ by 28707 % = "7023
1439          \mathchardef\mst@varfam@mathhash\count@
1440          \advance\count@ by \@ne
1441          \mathchardef\mst@varfam@mathdollar\count@
1442          \advance\count@ by \@ne
1443          \mathchardef\mst@varfam@mathpercent\count@
1444          \advance\count@ by \@ne
1445          \mathchardef\mst@varfam@mathampersand\count@
1446          \mst@addtodo@easynonletters\#\mst@varfam@mathhash
1447          \mst@addtodo@easynonletters\%\mst@varfam@mathpercent
1448          \mst@addtodo@easynonletters\&\mst@varfam@mathampersand
1449      \fi

```

It is possible to mathematically activate the dollar sign, and to use it in math mode as `\string$...` well, how many documents will have done that? But we do not modify the mathcode of the \$ character anyhow, so why should I add here a `\mst@OnlyIfNotMathActive?` There is no good reason for that.

```

1450  \mst@do@easynonletters\expandafter{\the\mst@do@easynonletters
1451      \let\mathdollar\mst@varfam@mathdollar}%

```

Extras for [1.4](#) are needed. Here too we do not worry about math active dollar character.

```

1452  \ifmst@everymath\else
1453      \edef\mst@tmp{\ifmst@XeOrLua\mst@Umathcharnumdef\else\mathchardef\fi
1454          \mathdollar=\the\mathdollar\relax}%
1455      \mst@undo@easynonletters\expandafter\expandafter\expandafter
1456          {\expandafter\mst@tmp\the\mst@undo@easynonletters}%
1457  \fi
1458 \fi

```

**symbolmisc** We construct (with some effort) some long arrows from the Symbol glyphs, of almost the same lengths as the standard ones. By the way, I always found the `\iff` to be too wide, but I

follow here the default. Also, although there is a `\longmapsto` in standard L<sup>A</sup>T<sub>E</sub>X, if I am not mistaken, there is no `\longto`. So I define one here. I could not construct in the same manner `\Longrightarrow` etc... as the = sign from Symbol does not combine easily with the logical arrows, well, I could have done some box manipulations, but well, life is finite.

`\prod` **1.13b:** I correct the brutal re-definitions of `\prod` and `\sum` from the earlier versions of the `\sum` package; most of the time the Symbol glyphs do appear to be too small in display mode. The new redefinitions do have some defects: `\$\\displaystyle\\prod_1^2$` changes the position of limits but not the glyph itself, and `$$\\textstyle\\prod_1^2$$` change the limits but switches to the CM inline math glyph. So I tried  
`\renewcommand{\\prod}{\\mathchoice{\\mst@prod}{\\prodpsy}{\\prodpsy}{\\prodpsy}}`  
but this did not go well with subscripts and exponents.

October 2012: maybe I should re-examine what I did?

**1.3c** (2013/12/14) renames `\defaultprod` to `\MToriginalprod` and `\defaultsum` to `\MToriginalsum`.

**1.3v** hesitates about making robust here `\prod` and `\sum`. Finally I use `\protected` for them.

**1.4** finally replaces all control sequences defines earlier via `\DeclareRobustCommand` to be defined using `\protected\def`. It also removes `\mst@prod` and `\mst@sum` which were aliases of `\MToriginalprod` and `\MToriginalsum`, and having both must have been some left-over of earlier versions in 2012 or 2013 (unchecked).

```
1459 \ifmst@symbolmisc
1460 \mst@infoline{symbolmisc: miscellaneous math symbols from Symbol font}
1461 \let\MToriginalprod\prod
1462 \DeclareMathSymbol{\prodpsy}{\mathop}{mtpsymbol}{213}
1463 \protected\def\prod{\ifinner\prodpsy\else\MToriginalprod\fi}
1464 \let\MToriginalsum\sum
1465 \DeclareMathSymbol{\sumpsy}{\mathop}{mtpsymbol}{229}
1466 \protected\def\sum{\ifinner\sumpsy\else\MToriginalsum\fi}
```

```
1467 \DeclareMathSymbol{\mst@implies}{\mathrel}{mtpsymbol}{222}
1468 \protected\def\implies{\; \mst@implies \;}
1469 \DeclareMathSymbol{\mst@impliedby}{\mathrel}{mtpsymbol}{220}
1470 \protected\def\impliedby{\; \mst@impliedby \;}
1471 \protected\def\iff{\; \mst@impliedby\mathrel{\mkern-3mu}\mst@implies \;}
1472 \DeclareMathSymbol{\mst@iff}{\mathrel}{mtpsymbol}{219}
1473 \protected\def\shortiff{\; \mst@iff \;}
```

**1.4** drops defining a `\mst@to` and employs `\to` in subsequent definitions

```
1474 \let\to\relax
1475 \DeclareMathSymbol{\to}{\mathrel}{mtpsymbol}{174}
1476 \DeclareMathSymbol{\mst@trait}{\mathrel}{mtpsymbol}{190}
1477 \protected\def\longto{\mkern2mu\mst@trait\mathrel{\mkern-10mu}\to}
1478 \protected\def\mapsto{\mapstochar\mathrel{\mkern0.2mu}\to}
1479 \protected\def\longmapsto{%
1480   \mapstochar\mathrel{\mkern2mu}\mst@trait\mathrel{\mkern-10mu}\to
1481 }
1482 \DeclareMathSymbol{\aleph}{\mathord}{mtpsymbol}{192}
1483 \DeclareMathSymbol{\infty}{\mathord}{mtpsymbol}{165}
1484 \DeclareMathSymbol{\emptyset}{\mathord}{mtpsymbol}{198}
1485 \let\varnothing\emptyset
1486 \DeclareMathSymbol{\nabla}{\mathord}{mtpsymbol}{209}
```

```

1487 \DeclareMathSymbol{\surd}{\mathord}{mptsymbol}{214}
1488 \let\angle\undefined
1489 \DeclareMathSymbol{\angle}{\mathord}{mptsymbol}{208}
1490 \DeclareMathSymbol{\forall}{\mathord}{mptsymbol}{34}
1491 \DeclareMathSymbol{\exists}{\mathord}{mptsymbol}{36}
1492 \DeclareMathSymbol{\neg}{\mathord}{mptsymbol}{216}
1493 \DeclareMathSymbol{\clubsuit}{\mathord}{mptsymbol}{167}
1494 \DeclareMathSymbol{\diamondsuit}{\mathord}{mptsymbol}{168}
1495 \DeclareMathSymbol{\heartsuit}{\mathord}{mptsymbol}{169}
1496 \DeclareMathSymbol{\spadesuit}{\mathord}{mptsymbol}{170}
1497 \DeclareMathSymbol{\smallint}{\mathop}{mptsymbol}{242}
1498 \DeclareMathSymbol{\wedge}{\mathbin}{mptsymbol}{217}
1499 \DeclareMathSymbol{\vee}{\mathbin}{mptsymbol}{218}
1500 \DeclareMathSymbol{\cap}{\mathbin}{mptsymbol}{199}
1501 \DeclareMathSymbol{\cup}{\mathbin}{mptsymbol}{200}
1502 \DeclareMathSymbol{\bullet}{\mathbin}{mptsymbol}{183}
1503 \DeclareMathSymbol{\div}{\mathbin}{mptsymbol}{184}
1504 \DeclareMathSymbol{\otimes}{\mathbin}{mptsymbol}{196}
1505 \DeclareMathSymbol{\oplus}{\mathbin}{mptsymbol}{197}
1506 \DeclareMathSymbol{\pm}{\mathbin}{mptsymbol}{177}
1507 \DeclareMathSymbol{\times}{\mathbin}{mptsymbol}{180}
1508 \DeclareMathSymbol{\propto}{\mathrel}{mptsymbol}{181}
1509 \DeclareMathSymbol{\mid}{\mathrel}{mptsymbol}{124}
1510 \DeclareMathSymbol{\leq}{\mathrel}{mptsymbol}{163}
1511 \DeclareMathSymbol{\geq}{\mathrel}{mptsymbol}{179}
1512 \DeclareMathSymbol{\approx}{\mathrel}{mptsymbol}{187}
1513 \DeclareMathSymbol{\supset}{\mathrel}{mptsymbol}{201}
1514 \DeclareMathSymbol{\subset}{\mathrel}{mptsymbol}{204}
1515 \DeclareMathSymbol{\supseteq}{\mathrel}{mptsymbol}{202}
1516 \DeclareMathSymbol{\subseteq}{\mathrel}{mptsymbol}{205}
1517 \DeclareMathSymbol{\in}{\mathrel}{mptsymbol}{206}
1518 \DeclareMathSymbol{\sim}{\mathrel}{mptsymbol}{126}
1519 \let\cong\undefined
1520 \DeclareMathSymbol{\cong}{\mathrel}{mptsymbol}{64}
1521 \DeclareMathSymbol{\perp}{\mathrel}{mptsymbol}{94}
1522 \DeclareMathSymbol{\equiv}{\mathrel}{mptsymbol}{186}
1523 \let\notin\undefined
1524 \DeclareMathSymbol{\notin}{\mathrel}{mptsymbol}{207}
1525 \DeclareMathDelimiter{\rangle}{\mathclose}{mptsymbol}{241}{largesymbols}{0B}
1527 \DeclareMathDelimiter{\langle}{\mathopen}{mptsymbol}{225}{largesymbols}{0A}
1529 \fi

```

**symbolre** I like the \Re and \Im from Symbol, so I overwrite the CM ones.

```

1530 \ifmst@symbolre
1531 \mst@infoline{symbolre: \string\Re\space and \string\Im\space from Symbol font}
1532 \DeclareMathSymbol{\Re}{\mathord}{mptsymbol}{C2}
1533 \DeclareMathSymbol{\Im}{\mathord}{mptsymbol}{C1}

```

```

1534 \DeclareMathSymbol{\DotTriangle}{\mathord}{mtpsymbol}{92}
1535 \fi

Greek letters LGRgreek > selfGreek > eulergreek > symbolgreek
  1.11 I correct some bugs on how eulergreek and symbolgreek interacted.
  1.12b more bug fixes.
  1.13
    * Option LGRgreek.
    * Also, a behavior has been changed: it regards the selfGreek case, the default shape is now
      the one for letters, not for operator-names and digits. This complies to the ISO standard.
    * bugfix: version 1.12b did not define the \omicron in the case when no Greek-related option
      was passed to the package.
    1.13d has new macros \MTstandardgreek and \MTcustomgreek. And in the subdued case
      \MTstandardgreek is done when switching to the normal or bold math versions (previously
      something like this was only done in case of LGRgreek option. )

1536 \let\mst@mathord\mathalpha
1537 \mst@goaheadtrue
1538 \ifmst@selfGreek
1539   \def\mst@font@tbu{mtselfGreekfont}
1540 \else
1541   \ifmst@eulergreek
1542     \def\mst@font@tbu{mteulervm}
1543   \else
1544     \ifmst@symbolgreek
1545       \def\mst@font@tbu{mtpsymbol}
1546       \let\mst@mathord\mathord
1547     \else
1548       \ifmst@LGRgreek
1549         \mst@goaheadfalse
1550       \else
1551         \mst@goaheadfalse
1552         \def\mst@omicron {\mst@alph@omicron{o}}
1553       \fi
1554     \fi
1555   \fi
1556 \fi
1557 \ifmst@goahead
1558   \DeclareMathSymbol{\mst@Alpha}{\mathord}{\mst@font@tbu}{41}
1559   \DeclareMathSymbol{\mst@Beta}{\mathord}{\mst@font@tbu}{42}
1560   \DeclareMathSymbol{\mst@Epsilon}{\mathord}{\mst@font@tbu}{45}
1561   \DeclareMathSymbol{\mst@Zeta}{\mathord}{\mst@font@tbu}{5A}
1562   \DeclareMathSymbol{\mst@Eta}{\mathord}{\mst@font@tbu}{48}
1563   \DeclareMathSymbol{\mst@Iota}{\mathord}{\mst@font@tbu}{49}
1564   \DeclareMathSymbol{\mst@Kappa}{\mathord}{\mst@font@tbu}{4B}
1565   \DeclareMathSymbol{\mst@Mu}{\mathord}{\mst@font@tbu}{4D}

```

```

1566 \DeclareMathSymbol{\mst@Nu}{\mst@mathord}{\mst@font@tbu}{4E}
1567 \DeclareMathSymbol{\mst@Omicron}{\mst@mathord}{\mst@font@tbu}{4F}
1568 \DeclareMathSymbol{\mst@Rho}{\mst@mathord}{\mst@font@tbu}{50}
1569 \DeclareMathSymbol{\mst@Tau}{\mst@mathord}{\mst@font@tbu}{54}
1570 \DeclareMathSymbol{\mst@Chi}{\mst@mathord}{\mst@font@tbu}{58}

```

When we in fact use Symbol, we have to correct `\Rho` and `\Chi`. And `\Digamma` is non-existent in fact (no F in Symbol, F codes a `\Phi`).

```
1571 \ifx\mst@mathord\mathord
```

symbolgreek but neither eulergreek nor selfGreek

Attention le P de Symbol est un `\Pi` pas un `\Rho`.

Attention le X de Symbol est un `\Xi` pas un `\Chi`.

Attention le F de Symbol est un `\Phi`. Il n'y a pas de `\Digamma`.

```

1572 \DeclareMathSymbol{\mst@Rho}{\mathord}{\mtsymbol}{52}
1573 \DeclareMathSymbol{\mst@Chi}{\mathord}{\mtsymbol}{43}
1574 \DeclareMathSymbol{\mst@Gamma}{\mathord}{\mtsymbol}{47}
1575 \DeclareMathSymbol{\mst@Delta}{\mathord}{\mtsymbol}{44}
1576 \DeclareMathSymbol{\mst@Theta}{\mathord}{\mtsymbol}{51}
1577 \DeclareMathSymbol{\mst@Lambda}{\mathord}{\mtsymbol}{4C}
1578 \DeclareMathSymbol{\mst@Xi}{\mathord}{\mtsymbol}{58}
1579 \DeclareMathSymbol{\mst@Pi}{\mathord}{\mtsymbol}{50}
1580 \DeclareMathSymbol{\mst@Sigma}{\mathord}{\mtsymbol}{53}
1581 \DeclareMathSymbol{\mst@Upsilon}{\mathord}{\mtsymbol}{A1}
1582 \DeclareMathSymbol{\mst@Phi}{\mathord}{\mtsymbol}{46}
1583 \DeclareMathSymbol{\mst@Psi}{\mathord}{\mtsymbol}{59}
1584 \DeclareMathSymbol{\mst@Omega}{\mathord}{\mtsymbol}{57}
1585 \else

```

not symbolgreek but eulergreek or selfGreek. Note 2015/10/31 : apparemment à un moment dans le passé je considérais eulergreek et selfGreek comme pouvant être utilisés simultanément car j'avais ici "or both". Mais je laisse tomber tout effort réel de m'en préoccuper.

```

1586 \DeclareMathSymbol{\mst@Digamma}{\mathalpha}{\mathalpha}{46}
1587 \DeclareMathSymbol{\mst@Gamma}{\mathalpha}{\mathalpha}{00}
1588 \DeclareMathSymbol{\mst@Delta}{\mathalpha}{\mathalpha}{01}
1589 \DeclareMathSymbol{\mst@Theta}{\mathalpha}{\mathalpha}{02}
1590 \DeclareMathSymbol{\mst@Lambda}{\mathalpha}{\mathalpha}{03}
1591 \DeclareMathSymbol{\mst@Xi}{\mathalpha}{\mathalpha}{04}
1592 \DeclareMathSymbol{\mst@Pi}{\mathalpha}{\mathalpha}{05}
1593 \DeclareMathSymbol{\mst@Sigma}{\mathalpha}{\mathalpha}{06}
1594 \DeclareMathSymbol{\mst@Upsilon}{\mathalpha}{\mathalpha}{07}
1595 \DeclareMathSymbol{\mst@Phi}{\mathalpha}{\mathalpha}{08}
1596 \DeclareMathSymbol{\mst@Psi}{\mathalpha}{\mathalpha}{09}
1597 \DeclareMathSymbol{\mst@Omega}{\mathalpha}{\mathalpha}{0A}
1598 \fi
1599 \fi

```

There are differences regarding Euler and Symbol with respect to the available var-letters. We include one or two things like the `wp` and the `partial`.

The lower case Greek letters in default L<sup>A</sup>T<sub>E</sub>X are of type `mathord`. If we use the Euler font it is perhaps better to have them be of type `mathalpha`

```

1600 \ifmst@goahead
1601 \ifmst@eulerGreek
1602 \DeclareMathSymbol{\mst@alpha} {\mathalpha}{mteulervm}{ "0B}
1603 \DeclareMathSymbol{\mst@beta} {\mathalpha}{mteulervm}{ "0C}
1604 \DeclareMathSymbol{\mst@gamma} {\mathalpha}{mteulervm}{ "0D}
1605 \DeclareMathSymbol{\mst@delta} {\mathalpha}{mteulervm}{ "0E}
1606 \DeclareMathSymbol{\mst@epsilon} {\mathalpha}{mteulervm}{ "0F}
1607 \DeclareMathSymbol{\mst@zeta} {\mathalpha}{mteulervm}{ "10}
1608 \DeclareMathSymbol{\mst@eta} {\mathalpha}{mteulervm}{ "11}
1609 \DeclareMathSymbol{\mst@theta} {\mathalpha}{mteulervm}{ "12}
1610 \DeclareMathSymbol{\mst@iota} {\mathalpha}{mteulervm}{ "13}
1611 \DeclareMathSymbol{\mst@kappa} {\mathalpha}{mteulervm}{ "14}
1612 \DeclareMathSymbol{\mst@lambda} {\mathalpha}{mteulervm}{ "15}
1613 \DeclareMathSymbol{\mst@mu} {\mathalpha}{mteulervm}{ "16}
1614 \DeclareMathSymbol{\mst@nu} {\mathalpha}{mteulervm}{ "17}
1615 \DeclareMathSymbol{\mst@xi} {\mathalpha}{mteulervm}{ "18}
1616 \DeclareMathSymbol{\mst@omicron} {\mathalpha}{mteulervm}{ "6F}
1617 \DeclareMathSymbol{\mst@pi} {\mathalpha}{mteulervm}{ "19}
1618 \DeclareMathSymbol{\mst@rho} {\mathalpha}{mteulervm}{ "1A}
1619 \DeclareMathSymbol{\mst@sigma} {\mathalpha}{mteulervm}{ "1B}
1620 \DeclareMathSymbol{\mst@tau} {\mathalpha}{mteulervm}{ "1C}
1621 \DeclareMathSymbol{\mst@upsilon} {\mathalpha}{mteulervm}{ "1D}
1622 \DeclareMathSymbol{\mst@phi} {\mathalpha}{mteulervm}{ "1E}
1623 \DeclareMathSymbol{\mst@chi} {\mathalpha}{mteulervm}{ "1F}
1624 \DeclareMathSymbol{\mst@psi} {\mathalpha}{mteulervm}{ "20}
1625 \DeclareMathSymbol{\mst@omega} {\mathalpha}{mteulervm}{ "21}
1626 %
1627 \DeclareMathSymbol{\mst@varepsilon} {\mathalpha}{mteulervm}{ "22}
1628 \DeclareMathSymbol{\mst@vartheta} {\mathalpha}{mteulervm}{ "23}
1629 \DeclareMathSymbol{\mst@varpi} {\mathalpha}{mteulervm}{ "24}
1630 \let\mst@varrho=\mst@rho
1631 \let\mst@varsigma=\mst@sigma
1632 \DeclareMathSymbol{\mst@varphi} {\mathalpha}{mteulervm}{ "27}
1633 %
1634 \DeclareMathSymbol{\mst@partial} {\mathalpha}{mteulervm}{ "40}
1635 \DeclareMathSymbol{\mst@wp} {\mathalpha}{mteulervm}{ "7D}
1636 \DeclareMathSymbol{\mst@ell} {\mathalpha}{mteulervm}{ "60}
1637 \else
1638 \ifmst@symbolGreek
1639 \DeclareMathSymbol{\mst@alpha} {\mathord}{mtpsymbol}{ "61}
1640 \DeclareMathSymbol{\mst@beta} {\mathord}{mtpsymbol}{ "62}
1641 \DeclareMathSymbol{\mst@gamma} {\mathord}{mtpsymbol}{ "67}
1642 \DeclareMathSymbol{\mst@delta} {\mathord}{mtpsymbol}{ "64}
1643 \DeclareMathSymbol{\mst@epsilon} {\mathord}{mtpsymbol}{ "65}
1644 \DeclareMathSymbol{\mst@zeta} {\mathord}{mtpsymbol}{ "7A}
1645 \DeclareMathSymbol{\mst@eta} {\mathord}{mtpsymbol}{ "68}
1646 \DeclareMathSymbol{\mst@theta} {\mathord}{mtpsymbol}{ "71}
1647 \DeclareMathSymbol{\mst@iota} {\mathord}{mtpsymbol}{ "69}
1648 \DeclareMathSymbol{\mst@kappa} {\mathord}{mtpsymbol}{ "6B}

```

```

1649 \DeclareMathSymbol{\mst@lambda}{\mathord}{mtsymbol}{"6C}
1650 \DeclareMathSymbol{\mst@mu}{\mathord}{mtsymbol}{"6D}
1651 \DeclareMathSymbol{\mst@nu}{\mathord}{mtsymbol}{"6E}
1652 \DeclareMathSymbol{\mst@xi}{\mathord}{mtsymbol}{"78}
1653 \DeclareMathSymbol{\mst@omicron}{\mathord}{mtsymbol}{"6F}
1654 \DeclareMathSymbol{\mst@pi}{\mathord}{mtsymbol}{"70}
1655 \DeclareMathSymbol{\mst@rho}{\mathord}{mtsymbol}{"72}
1656 \DeclareMathSymbol{\mst@sigma}{\mathord}{mtsymbol}{"73}
1657 \DeclareMathSymbol{\mst@tau}{\mathord}{mtsymbol}{"74}
1658 \DeclareMathSymbol{\mst@upsilon}{\mathord}{mtsymbol}{"75}
1659 \DeclareMathSymbol{\mst@phi}{\mathord}{mtsymbol}{"66}
1660 \DeclareMathSymbol{\mst@chi}{\mathord}{mtsymbol}{"63}
1661 \DeclareMathSymbol{\mst@psi}{\mathord}{mtsymbol} {"79}
1662 \DeclareMathSymbol{\mst@omega}{\mathord}{mtsymbol} {"77}
1663 \let\mst@varepsilon=\mst@epsilon
1664 \DeclareMathSymbol{\mst@vartheta}{\mathord}{mtsymbol} {"4A}
1665 \DeclareMathSymbol{\mst@varpi}{\mathord}{mtsymbol} {"76}
1666 \let\mst@varrho=\mst@rho
1667 \DeclareMathSymbol{\mst@varsigma}{\mathord}{mtsymbol} {"56}
1668 \DeclareMathSymbol{\mst@varphi}{\mathord}{mtsymbol} {"6A}
1669 \DeclareMathSymbol{\mst@partial}{\mathord}{mtsymbol} {"B6}
1670 \DeclareMathSymbol{\mst@wp}{\mathord}{mtsymbol} {"C3}
1671 \fi
1672 \fi
1673 \fi

```

\alphaup etc... Completely refactored at [1.3y](#) to define \Alphaup, \Alphait, \alphaup, \alphait, etc... and prepare templates \Alpha, ..., \alpha, ..., which when activating a math version will be submitted to an \expanded, whose behavior will depend on version-specific conditionals.

```

1674 \ifmst@LGRgreek
1675 % cf http://milde.users.sourceforge.net/LGR/lgrxenc.def.html
1676 % et greek.ldf du package babel
1677 \DeclareMathSymbol{\Alphaup}{\mathalpha}{mtgreekup}{65}
1678 \DeclareMathSymbol{\Betaup}{\mathalpha}{mtgreekup}{66}
1679 \DeclareMathSymbol{\Epsilonup}{\mathalpha}{mtgreekup}{69}
1680 \DeclareMathSymbol{\Zetaup}{\mathalpha}{mtgreekup}{90}
1681 \DeclareMathSymbol{\Etaup}{\mathalpha}{mtgreekup}{72}
1682 \DeclareMathSymbol{\Iotaup}{\mathalpha}{mtgreekup}{73}
1683 \DeclareMathSymbol{\Kappaup}{\mathalpha}{mtgreekup}{75}
1684 \DeclareMathSymbol{\Muup}{\mathalpha}{mtgreekup}{77}
1685 \DeclareMathSymbol{\Nuup}{\mathalpha}{mtgreekup}{78}
1686 \DeclareMathSymbol{\Omicronup}{\mathalpha}{mtgreekup}{79}
1687 \DeclareMathSymbol{\Rhoup}{\mathalpha}{mtgreekup}{82}
1688 \DeclareMathSymbol{\Tauup}{\mathalpha}{mtgreekup}{84}
1689 \DeclareMathSymbol{\Chiup}{\mathalpha}{mtgreekup}{81}
1690 %
1691 \DeclareMathSymbol{\Alphait}{\mathalpha}{mtgreekit}{65}
1692 \DeclareMathSymbol{\Betaait}{\mathalpha}{mtgreekit}{66}
1693 \DeclareMathSymbol{\Epsilononit}{\mathalpha}{mtgreekit}{69}

```

```

1694 \DeclareMathSymbol{\Zetaait}{\mathalpha}{mtgreekit}{90}
1695 \DeclareMathSymbol{\Etaait}{\mathalpha}{mtgreekit}{72}
1696 \DeclareMathSymbol{\Iotaait}{\mathalpha}{mtgreekit}{73}
1697 \DeclareMathSymbol{\Kappaait}{\mathalpha}{mtgreekit}{75}
1698 \DeclareMathSymbol{\Muait}{\mathalpha}{mtgreekit}{77}
1699 \DeclareMathSymbol{\Nuait}{\mathalpha}{mtgreekit}{78}
1700 \DeclareMathSymbol{\Omicronit}{\mathalpha}{mtgreekit}{79}
1701 \DeclareMathSymbol{\Rhoait}{\mathalpha}{mtgreekit}{82}
1702 \DeclareMathSymbol{\Tauait}{\mathalpha}{mtgreekit}{84}
1703 \DeclareMathSymbol{\Chiit}{\mathalpha}{mtgreekit}{81}

1704 \DeclareMathSymbol{\Digammaup}{\mathalpha}{mtgreekup}{195}
1705 \DeclareMathSymbol{\Digammait}{\mathalpha}{mtgreekit}{195}
1706 %
1707 \DeclareMathSymbol{\Gammamaup}{\mathalpha}{mtgreekup}{71}
1708 \DeclareMathSymbol{\Deltaup}{\mathalpha}{mtgreekup}{68}
1709 \DeclareMathSymbol{\Thetaup}{\mathalpha}{mtgreekup}{74}
1710 \DeclareMathSymbol{\Lambdau}{\mathalpha}{mtgreekup}{76}
1711 \DeclareMathSymbol{\Xiup}{\mathalpha}{mtgreekup}{88}
1712 \DeclareMathSymbol{\Piup}{\mathalpha}{mtgreekup}{80}
1713 \DeclareMathSymbol{\Sigmaup}{\mathalpha}{mtgreekup}{83}
1714 \DeclareMathSymbol{\Upsilonup}{\mathalpha}{mtgreekup}{85}
1715 \DeclareMathSymbol{\Phiup}{\mathalpha}{mtgreekup}{70}
1716 \DeclareMathSymbol{\Psiup}{\mathalpha}{mtgreekup}{89}
1717 \DeclareMathSymbol{\Omegau}{\mathalpha}{mtgreekup}{87}
1718 %
1719 \DeclareMathSymbol{\Gammait}{\mathalpha}{mtgreekit}{71}
1720 \DeclareMathSymbol{\Deltait}{\mathalpha}{mtgreekit}{68}
1721 \DeclareMathSymbol{\Thetait}{\mathalpha}{mtgreekit}{74}
1722 \DeclareMathSymbol{\Lambdait}{\mathalpha}{mtgreekit}{76}
1723 \DeclareMathSymbol{\Xiit}{\mathalpha}{mtgreekit}{88}
1724 \DeclareMathSymbol{\Piit}{\mathalpha}{mtgreekit}{80}
1725 \DeclareMathSymbol{\Sigmait}{\mathalpha}{mtgreekit}{83}
1726 \DeclareMathSymbol{\Upsilononit}{\mathalpha}{mtgreekit}{85}
1727 \DeclareMathSymbol{\Phiit}{\mathalpha}{mtgreekit}{70}
1728 \DeclareMathSymbol{\Psit}{\mathalpha}{mtgreekit}{89}
1729 \DeclareMathSymbol{\Omegait}{\mathalpha}{mtgreekit}{87}
1730 %
1731 \def\mst@Alpha{\ifmst@greek@upper@up\Alphaup\else\Alphait\fi}%
1732 \def\mst@Beta{\ifmst@greek@upper@up\Betaup\else\Betaait\fi}%
1733 \def\mst@Epsilon{\ifmst@greek@upper@up\Epsilonup\else\Epsilononit\fi}%
1734 \def\mst@Zeta{\ifmst@greek@upper@up\Zetaup\else\Zetaait\fi}%
1735 \def\mst@Eta{\ifmst@greek@upper@up\Etaup\else\Etaait\fi}%
1736 \def\mst@Iota{\ifmst@greek@upper@up\Iotaup\else\Iotaait\fi}%
1737 \def\mst@Kappa{\ifmst@greek@upper@up\Kappaup\else\Kappaait\fi}%
1738 \def\mst@Mu{\ifmst@greek@upper@up\Muup\else\Muait\fi}%
1739 \def\mst@Nu{\ifmst@greek@upper@up\Nuup\else\Nuait\fi}%
1740 \def\mst@Omicron{\ifmst@greek@upper@up\Omicronup\else\Omicronit\fi}%

```

```

1741 \def\mst@Rho{\ifmst@greek@upper@up\Rhoup\else\Rhoit\fi}%
1742 \def\mst@Tau{\ifmst@greek@upper@up\Tauup\else\Tauit\fi}%
1743 \def\mst@Chi{\ifmst@greek@upper@up\Chiup\else\Chiit\fi}%
1744 %
1745 \def\mst@Digamma{\ifmst@greek@upper@up\Digammaup\else\Digammaait\fi}%
1746 %
1747 \def\mst@Gamma{\ifmst@greek@upper@up\Gammaau\else\Gammait\fi}%
1748 \def\mst@Delta{\ifmst@greek@upper@up\Deltaup\else\Deltaait\fi}%
1749 \def\mst@Theta{\ifmst@greek@upper@up\Thetaau\else\Thetaait\fi}%
1750 \def\mst@Lambda{\ifmst@greek@upper@up\Lambdaub\else\Lambdait\fi}%
1751 \def\mst@Xi{\ifmst@greek@upper@up\Xiu\else\Xiit\fi}%
1752 \def\mst@Pi{\ifmst@greek@upper@up\Piu\else\Piit\fi}%
1753 \def\mst@Sigma{\ifmst@greek@upper@up\Sigmaup\else\Sigmait\fi}%
1754 \def\mst@Upsilon{\ifmst@greek@upper@up\Upsilonup\else\Upsilononit\fi}%
1755 \def\mst@Phi{\ifmst@greek@upper@up\Phiiu\else\Phiit\fi}%
1756 \def\mst@Psi{\ifmst@greek@upper@up\Psiiu\else\Psiit\fi}%
1757 \def\mst@Omega{\ifmst@greek@upper@up\Omegau\else\Omegait\fi}%
1758 %
1759 \DeclareMathSymbol{\alphaup}{\mathalpha}{mtgreekup}{97}
1760 \DeclareMathSymbol{\betaup}{\mathalpha}{mtgreekup}{98}
1761 \DeclareMathSymbol{\gammaup}{\mathalpha}{mtgreekup}{103}
1762 \DeclareMathSymbol{\deltaup}{\mathalpha}{mtgreekup}{100}
1763 \DeclareMathSymbol{\epsilonup}{\mathalpha}{mtgreekup}{101}
1764 \DeclareMathSymbol{\zetaup}{\mathalpha}{mtgreekup}{122}
1765 \DeclareMathSymbol{\etau}{\mathalpha}{mtgreekup}{104}
1766 \DeclareMathSymbol{\thetaau}{\mathalpha}{mtgreekup}{106}
1767 \DeclareMathSymbol{\iotaup}{\mathalpha}{mtgreekup}{105}
1768 \DeclareMathSymbol{\kappaup}{\mathalpha}{mtgreekup}{107}
1769 \DeclareMathSymbol{\lambdaup}{\mathalpha}{mtgreekup}{108}
1770 \DeclareMathSymbol{\muup}{\mathalpha}{mtgreekup}{109}
1771 \DeclareMathSymbol{\nuup}{\mathalpha}{mtgreekup}{110}
1772 \DeclareMathSymbol{\xiup}{\mathalpha}{mtgreekup}{120}
1773 \DeclareMathSymbol{\omicronup}{\mathalpha}{mtgreekup}{111}
1774 \DeclareMathSymbol{\piup}{\mathalpha}{mtgreekup}{112}
1775 \DeclareMathSymbol{\rhoup}{\mathalpha}{mtgreekup}{114}
1776 \DeclareMathSymbol{\sigmaup}{\mathalpha}{mtgreekup}{115}
1777 \DeclareMathSymbol{\tauau}{\mathalpha}{mtgreekup}{116}
1778 \DeclareMathSymbol{\upsilonup}{\mathalpha}{mtgreekup}{117}
1779 \DeclareMathSymbol{\phiiu}{\mathalpha}{mtgreekup}{102}
1780 \DeclareMathSymbol{\chiup}{\mathalpha}{mtgreekup}{113}
1781 \DeclareMathSymbol{\psiiu}{\mathalpha}{mtgreekup}{121}
1782 \DeclareMathSymbol{\omegau}{\mathalpha}{mtgreekup}{119}
1783 %
1784 \DeclareMathSymbol{\digammaup}{\mathalpha}{mtgreekup}{147}

```

Only varsigma defined (I should check this again).

```

1785 \DeclareMathSymbol{\varsigmaup}{\mathalpha}{mtgreekup}{99}
1786 %
1787 \DeclareMathSymbol{\alphait}{\mathalpha}{mtgreekit}{97}
1788 \DeclareMathSymbol{\betaait}{\mathalpha}{mtgreekit}{98}

```

```

1789 \DeclareMathSymbol{\gammaait}{\mathalpha}{mtgreekit}{103}
1790 \DeclareMathSymbol{\deltaait}{\mathalpha}{mtgreekit}{100}
1791 \DeclareMathSymbol{\epsilonitonit}{\mathalpha}{mtgreekit}{101}
1792 \DeclareMathSymbol{\zetaait}{\mathalpha}{mtgreekit}{122}
1793 \DeclareMathSymbol{\etaait}{\mathalpha}{mtgreekit}{104}
1794 \DeclareMathSymbol{\thetaait}{\mathalpha}{mtgreekit}{106}
1795 \DeclareMathSymbol{\iotaait}{\mathalpha}{mtgreekit}{105}
1796 \DeclareMathSymbol{\kappaait}{\mathalpha}{mtgreekit}{107}
1797 \DeclareMathSymbol{\lambdaait}{\mathalpha}{mtgreekit}{108}
1798 \DeclareMathSymbol{\muoit}{\mathalpha}{mtgreekit}{109}
1799 \DeclareMathSymbol{\nuoit}{\mathalpha}{mtgreekit}{110}
1800 \DeclareMathSymbol{\xiit}{\mathalpha}{mtgreekit}{120}
1801 \DeclareMathSymbol{\omicronit}{\mathalpha}{mtgreekit}{111}
1802 \DeclareMathSymbol{\piit}{\mathalpha}{mtgreekit}{112}
1803 \DeclareMathSymbol{\rhoit}{\mathalpha}{mtgreekit}{114}
1804 \DeclareMathSymbol{\sigmait}{\mathalpha}{mtgreekit}{115}
1805 \DeclareMathSymbol{\tauit}{\mathalpha}{mtgreekit}{116}
1806 \DeclareMathSymbol{\upsilonitonit}{\mathalpha}{mtgreekit}{117}
1807 \DeclareMathSymbol{\phiit}{\mathalpha}{mtgreekit}{102}
1808 \DeclareMathSymbol{\chiit}{\mathalpha}{mtgreekit}{113}
1809 \DeclareMathSymbol{\psiit}{\mathalpha}{mtgreekit}{121}
1810 \DeclareMathSymbol{\omegait}{\mathalpha}{mtgreekit}{119}
1811 %
1812 \DeclareMathSymbol{\digammaait}{\mathalpha}{mtgreekit}{147}
1813 \DeclareMathSymbol{\varsigmaait}{\mathalpha}{mtgreekit}{99}
1814 %
1815 \def\mst@alpha{\ifmst@greek@lower@up\alphaup\else\alphait\fi}%
1816 \def\mst@beta{\ifmst@greek@lower@up\betaup\else\betaait\fi}%
1817 \def\mst@gamma{\ifmst@greek@lower@up\gammaup\else\gammaait\fi}%
1818 \def\mst@delta{\ifmst@greek@lower@up\deltaup\else\deltaait\fi}%
1819 \def\mst@epsilon{\ifmst@greek@lower@up\epsilonup\else\epsilonitonit\fi}%
1820 \def\mst@zeta{\ifmst@greek@lower@up\zetaup\else\zetaait\fi}%
1821 \def\mst@eta{\ifmst@greek@lower@up\etaup\else\etaait\fi}%
1822 \def\mst@theta{\ifmst@greek@lower@up\thetaup\else\thetaait\fi}%
1823 \def\mst@iota{\ifmst@greek@lower@up\iotaup\else\iotaait\fi}%
1824 \def\mst@kappa{\ifmst@greek@lower@up\kappaup\else\kappaait\fi}%
1825 \def\mst@lambda{\ifmst@greek@lower@up\lambdaup\else\lambdaait\fi}%
1826 \def\mst@mu{\ifmst@greek@lower@up\muup\else\muoit\fi}%
1827 \def\mst@nu{\ifmst@greek@lower@up\nuup\else\nuoit\fi}%
1828 \def\mst@xi{\ifmst@greek@lower@up\xiup\else\xiit\fi}%
1829 \def\mst@omicron{\ifmst@greek@lower@up\omicronup\else\omicronit\fi}%
1830 \def\mst@pi{\ifmst@greek@lower@up\piup\else\piit\fi}%
1831 \def\mst@rho{\ifmst@greek@lower@up\rhoup\else\rhoit\fi}%
1832 \def\mst@sigma{\ifmst@greek@lower@up\sigmaup\else\sigmait\fi}%
1833 \def\mst@tau{\ifmst@greek@lower@up\tauup\else\tauit\fi}%
1834 \def\mst@upsilon{\ifmst@greek@lower@up\upsilonup\else\upsilonitonit\fi}%
1835 \def\mst@phi{\ifmst@greek@lower@up\phiup\else\phiit\fi}%
1836 \def\mst@chi{\ifmst@greek@lower@up\chiup\else\chiit\fi}%
1837 \def\mst@psi{\ifmst@greek@lower@up\psiup\else\psiit\fi}%

```

```

1838 \def\mst@omega{\ifmst@greek@lower@up\omegaup\else\omegait\fi}%
1839 %
1840 \def\mst@digamma{\ifmst@greek@lower@up\digammaup\else\digammait\fi}%
1841 \def\mst@varsigma{\ifmst@greek@lower@up\varsigmaup\else\varsigmait\fi}%
1842 \fi

```

\MTstandardgreek [1.3d](#) 2014/05/23 defines the commands \MTstandardgreek and \MTcustomgreek for package and user. I leave \MTrecordstandardgreek undocumented as I don't want to encourage people to load math packages after **mathastext**.

[1.3h](#) 2015/10/31: corrected \MTcustomgreek as it caused \ell to become undefined under option symbolgreek and, much more catastrophic, caused \alpha, etc.. to become undefined under option selfGreek !

```

1843 \newcommand*\MTstandardgreek{}%
1844 \newcommand*\MTcustomgreek{}%
1845 \newcommand*\MTrecordstandardgreek{}%
1846 \ifmst@customgreek
1847   \renewcommand*\MTrecordstandardgreek{%
1848     \let\mst@origAlpha\Alpha
1849     \let\mst@origBeta\Beta
1850     \let\mst@origGamma\Gamma
1851     \let\mst@origDelta\Delta
1852     \let\mst@origEpsilon\Epsilon
1853     \let\mst@origZeta\Zeta
1854     \let\mst@origEta\Eta
1855     \let\mst@origTheta\Theta
1856     \let\mst@origIota\Iota
1857     \let\mst@origKappa\Kappa
1858     \let\mst@origLambda\Lambda
1859     \let\mst@origMu\Mu
1860     \let\mst@origNu\nu
1861     \let\mst@origXi\xi
1862     \let\mst@origOmicron\Omicron
1863     \let\mst@origPi\Pi
1864     \let\mst@origRho\Rho
1865     \let\mst@origSigma\Sigma
1866     \let\mst@origTau\Tau
1867     \let\mst@origUpsilon\Upsilon
1868     \let\mst@origPhi\Phi
1869     \let\mst@origChi\Chi
1870     \let\mst@origPsi\Psi
1871     \let\mst@origOmega\Omega
1872   }%
1873   \let\mst@origalpha\alpha
1874   \let\mst@origbeta\beta
1875   \let\mst@origgamma\gamma
1876   \let\mst@origdelta\delta
1877   \let\mst@origepsilon\epsilon
1878   \let\mst@origvarepsilon\varepsilon
1879   \let\mst@origzeta\zeta

```

```

1880 \let\mst@origeta\eta
1881 \let\mst@origtheta\theta
1882 \let\mst@origvartheta\vartheta
1883 \let\mst@origiota\iota
1884 \let\mst@origkappa\kappa
1885 \let\mst@origlambda\lambda
1886 \let\mst@origmu\mu
1887 \let\mst@orignu\nu
1888 \let\mst@origxi\xi
1889 \let\mst@origomicron\omicron
1890 \let\mst@origpi\pi
1891 \let\mst@origvarpi\varpi
1892 \let\mst@origrho\rho
1893 \let\mst@origvarrho\varrho
1894 \let\mst@origsigma\sigma
1895 \let\mst@origvarsigma\varsigma
1896 \let\mst@origtau\tau
1897 \let\mst@origupsilon\upsilon
1898 \let\mst@origphi\phi
1899 \let\mst@origvarphi\varphi
1900 \let\mst@origchi\chi
1901 \let\mst@origpsi\psi
1902 \let\mst@origomega\omega
1903 \let\mst@origDigamma\Digamma
1904 \let\mst@origdigamma\digamma
1905 %
1906 \let\mst@origpartial\partial
1907 \let\mst@origwp\wp
1908 \let\mst@origell\ell }%
1909 \MTrecordstandardgreek
1910 \renewcommand*\MTstandardgreek}{%
1911 \let\Alpha\mst@origAlpha
1912 \let\Beta\mst@origBeta
1913 \let\Gamma\mst@origGamma
1914 \let\Delta\mst@origDelta
1915 \let\Epsilon\mst@origEpsilon
1916 \let\Zeta\mst@origZeta
1917 \let\Eta\mst@origEta
1918 \let\Theta\mst@origTheta
1919 \let\Iota\mst@origIota
1920 \let\Kappa\mst@origKappa
1921 \let\Lambda\mst@origLambda
1922 \let\Mu\mst@origMu
1923 \let\Nu\mst@origNu
1924 \let\Xi\mst@origXi
1925 \let\Omicron\mst@origOmicron
1926 \let\Pi\mst@origPi
1927 \let\Rho\mst@origRho
1928 \let\Sigma\mst@origSigma

```

```

1929 \let\Tau\mst@origTau
1930 \let\Upsilon\mst@origUpsilon
1931 \let\Phi\mst@origPhi
1932 \let\Chi\mst@origChi
1933 \let\Psi\mst@origPsi
1934 \let\Omega\mst@origOmega
1935 %
1936 \let\alpha\mst@origalpha
1937 \let\beta\mst@origbeta
1938 \let\gamma\mst@origgamma
1939 \let\delta\mst@origdelta
1940 \let\epsilon\mst@origepsilon
1941 \let\varepsilon\mst@origvarepsilon
1942 \let\zeta\mst@origzeta
1943 \let\eta\mst@origeta
1944 \let\theta\mst@origtheta
1945 \let\vartheta\mst@origvartheta
1946 \let\iota\mst@origiota
1947 \let\kappa\mst@origkappa
1948 \let\lambda\mst@origlambda
1949 \let\mu\mst@origmu
1950 \let\nu\mst@orignu
1951 \let\xi\mst@origxi
1952 \let\omicron\mst@origomicron
1953 \let\pi\mst@origpi
1954 \let\varpi\mst@origvarpi
1955 \let\rho\mst@origrho
1956 \let\varrho\mst@origvarrho
1957 \let\sigma\mst@origsigma
1958 \let\varsigma\mst@origvarsigma
1959 \let\tau\mst@origtau
1960 \let\upsilon\mst@origupsilon
1961 \let\phi\mst@origphi
1962 \let\varphi\mst@origvarphi
1963 \let\chi\mst@origchi
1964 \let\psi\mst@origpsi
1965 \let\omega\mst@origomega
1966 \let\Digamma\mst@origDigamma
1967 \let\digamma\mst@origdigamma
1968 %
1969 \let\partial\mst@origpartial
1970 \let\wp\mst@origwp
1971 \let\ell\mst@origell
1972 }%
1973 \ifmst@greekplus

```

[1.3za](#) implementation of LGRgreek+ option. It is not exactly clear what we should do for `\mathnormal` and `\mathnormalbold`.

This definition allows usage of `\alpha` for example in numerical context. To be completely clean perhaps we should get rid of final `\fi`, but old-fashioned L<sup>A</sup>T<sub>E</sub>X does not have built-in

conveniences, were it not for the nested if's simple `\expandafter` would do, but here we would need three in four places. Or simply wrap the whole in `\expanded`. Anyway, not really important.

```

1974 \def\mst@define@lowergreekletter#1#2{%
1975   \protected\def#1{\ifcase\mst@mathalph
1976     \ifmst@greek@lower@up\mathgreekup{#2}\else\mathgreekit{#2}\fi
1977     \or % rm
1978     \mathgreekup{#2}%
1979     \or % bf
1980     \mathgreekupbold{#2}%
1981     \or % it
1982     \mathgreekit{#2}%
1983     \or % normalbold
1984     \ifmst@greek@lower@up\mathgreekupbold{#2}\else\mathgreekitbold{#2}\fi
1985     \else #2\fi}%
1986   }
1987 \def\mst@define@uppergreekletter#1#2{%
1988   \protected\def#1{\ifcase\mst@mathalph
1989     \ifmst@greek@upper@up\mathgreekup{#2}\else\mathgreekit{#2}\fi
1990     \or % rm
1991     \mathgreekup{#2}%
1992     \or % bf
1993     \mathgreekupbold{#2}%
1994     \or % it
1995     \mathgreekit{#2}%
1996     \or % mathnormalbold
1997     \ifmst@greek@upper@up\mathgreekupbold{#2}\else\mathgreekitbold{#2}\fi
1998     \else #2\fi}%
1999   }
2000 \renewcommand*\MTcustomgreek{%
2001   \mst@define@uppergreekletter\Alpha\mst@Alpha
2002   \mst@define@uppergreekletter\Beta\mst@Beta
2003   \mst@define@uppergreekletter\Epsilon\mst@Epsilon
2004   \mst@define@uppergreekletter\Zeta\mst@Zeta
2005   \mst@define@uppergreekletter\Eta\mst@Eta
2006   \mst@define@uppergreekletter\Iota\mst@Iota
2007   \mst@define@uppergreekletter\Kappa\mst@Kappa
2008   \mst@define@uppergreekletter\Mu\mst@Mu
2009   \mst@define@uppergreekletter\Nu\mst@Nu
2010   \mst@define@uppergreekletter\Omicron\mst@Omicron
2011   \mst@define@uppergreekletter\Rho\mst@Rho
2012   \mst@define@uppergreekletter\Tau\mst@Tau
2013   \mst@define@uppergreekletter\Chi\mst@Chi
2014   \mst@define@uppergreekletter\Digamma\mst@Digamma
2015   \mst@define@uppergreekletter\Gamma\mst@Gamma
2016   \mst@define@uppergreekletter\Delta\mst@Delta
2017   \mst@define@uppergreekletter\Theta\mst@Theta
2018   \mst@define@uppergreekletter\Lambda\mst@Lambda
2019   \mst@define@uppergreekletter\Xi\mst@Xi
2020   \mst@define@uppergreekletter\Pi\mst@Pi

```

```

2021 \mst@define@uppergreekletter\Sigma\mst@Sigma
2022 \mst@define@uppergreekletter\Upsilon\mst@Upsilon
2023 \mst@define@uppergreekletter\Phi\mst@Phi
2024 \mst@define@uppergreekletter\Psi\mst@Psi
2025 \mst@define@uppergreekletter\Omega\mst@Omega
2026 \mst@define@lowergreekletter\alpha\mst@alpha
2027 \mst@define@lowergreekletter\beta\mst@beta
2028 \mst@define@lowergreekletter\gamma\mst@gamma
2029 \mst@define@lowergreekletter\delta\mst@delta
2030 \mst@define@lowergreekletter\epsilon\mst@epsilon
2031 \mst@define@lowergreekletter\zeta\mst@zeta
2032 \mst@define@lowergreekletter\eta\mst@eta
2033 \mst@define@lowergreekletter\theta\mst@theta
2034 \mst@define@lowergreekletter\iota\mst@iota
2035 \mst@define@lowergreekletter\kappa\mst@kappa
2036 \mst@define@lowergreekletter\lambda\mst@lambda
2037 \mst@define@lowergreekletter\mu\mst@mu
2038 \mst@define@lowergreekletter\nu\mst@nu
2039 \mst@define@lowergreekletter\xi\mst@xi
2040 \mst@define@lowergreekletter\omicron\mst@omicron
2041 \mst@define@lowergreekletter\pi\mst@pi
2042 \mst@define@lowergreekletter\rho\mst@rho
2043 \mst@define@lowergreekletter\sigma\mst@sigma
2044 \mst@define@lowergreekletter\tau\mst@tau
2045 \mst@define@lowergreekletter\upsilon\mst@upsilon
2046 \mst@define@lowergreekletter\phi\mst@phi
2047 \mst@define@lowergreekletter\chi\mst@chi
2048 \mst@define@lowergreekletter\psi\mst@psi
2049 \mst@define@lowergreekletter\omega\mst@omega
2050 \mst@define@lowergreekletter\varsigma\mst@varsigma
2051 \mst@define@lowergreekletter\digamma\mst@digamma
2052 }%
2053 \else

```

Under `selfGreek` or other Greek option but not `LGRgreek`, these Greek letter control sequences are already `\mathchar`'s, but under `LGRgreek` they need (well not really, but I feel it is cleaner) expansion which will react to the Boolean saying if using ‘upright’ or ‘italic’. This Boolean setting is recorded when declaring a math version and reenacted when `\MTversion` is encountered in the document body. We must be careful not to contaminate things in the principal mode from math version declarations but I think my (now quite old) code is globally designed to achieve this protection see how `\MTDeclareVersion` is done. The `\MTcustomgreek` will always be executed in preamble at least once, except under `subdued` option.

The `\expanded`'s act on unexpanding tokens if not used under `LGRgreek` regimen.

```

2054 \renewcommand*\{\MTcustomgreek}{%
2055   \expanded{%
2056     \let\noexpand\Alpha\mst@Alpha
2057     \let\noexpand\Beta\mst@Beta
2058     \let\noexpand\Epsilon\mst@Epsilon
2059     \let\noexpand\Zeta\mst@Zeta
2060     \let\noexpand\Eta\mst@Eta

```

```

2061   \let\noexpand\Iota\mst@Iota
2062   \let\noexpand\Kappa\mst@Kappa
2063   \let\noexpand\Mu\mst@Mu
2064   \let\noexpand\Nu\mst@Nu
2065   \let\noexpand\Omicron\mst@Omicron
2066   \let\noexpand\Rho\mst@Rho
2067   \let\noexpand\Tau\mst@Tau
2068   \let\noexpand\Chi\mst@Chi
2069 }%
1.3h: \mst@Digamma not defined if symbolgreek option.
2070   \ifmst@symbolgreek\else
2071     \expanded{\let\noexpand\Digamma\mst@Digamma}%
2072   \fi
2073 \expanded{%
2074   \let\noexpand\Gamma\mst@Gamma
2075   \let\noexpand\Delta\mst@Delta
2076   \let\noexpand\Theta\mst@Theta
2077   \let\noexpand\Lambda\mst@Lambda
2078   \let\noexpand\Xi\mst@Xi
2079   \let\noexpand\Pi\mst@Pi
2080   \let\noexpand\Sigma\mst@Sigma
2081   \let\noexpand\Upsilon\mst@Upsilon
2082   \let\noexpand\Phi\mst@Phi
2083   \let\noexpand\Psi\mst@Psi
2084   \let\noexpand\Omega\mst@Omega
2085 }%
1.3h 2015/10/31 adds this conditional to correct the bad bug in 1.3d 2014/05/23 which caused
\alpha etc... to become undefined under option selfGreek.
2086 \ifmst@selfGreek\else
2087 \expanded{%
2088   \let\noexpand\alpha\mst@alpha
2089   \let\noexpand\beta\mst@beta
2090   \let\noexpand\gamma\mst@gamma
2091   \let\noexpand\delta\mst@delta
2092   \let\noexpand\epsilon\mst@epsilon
2093   \let\noexpand\zeta\mst@zeta
2094   \let\noexpand\eta\mst@eta
2095   \let\noexpand\theta\mst@theta
2096   \let\noexpand\iota\mst@iota
2097   \let\noexpand\kappa\mst@kappa
2098   \let\noexpand\lambda\mst@lambda
2099   \let\noexpand\mu\mst@mu
2100   \let\noexpand\nu\mst@nu
2101   \let\noexpand\xi\mst@xi
2102   \let\noexpand\omicron\mst@omicron
2103   \let\noexpand\pi\mst@pi
2104   \let\noexpand\rho\mst@rho
2105   \let\noexpand\sigma\mst@sigma

```

```

2106   \let\noexpand\tau\mst@tau
2107   \let\noexpand\upsilon\mst@upsilon
2108   \let\noexpand\phi\mst@phi
2109   \let\noexpand\chi\mst@chi
2110   \let\noexpand\psi\mst@psi
2111   \let\noexpand\omega\mst@omega
2112   \let\noexpand\varsigma\mst@varsigma
2113 }%
1.3h: digamma only defined with option LGRgreek.
2114 \ifmst@LGRgreek
2115   \expanded{\let\noexpand\digamma\mst@digamma}%
2116 \fi
Conditional added 1.3h 2015/10/31.
2117 \ifmst@LGRgreek\else
2118   \let\varepsilon\mst@varepsilon
2119   \let\vartheta\mst@vartheta
2120   \let\varpi\mst@varpi
2121   \let\varrho\mst@varrho
2122   \let\varphi\mst@varphi
2123   \let\partial\mst@partial
2124   \let\wp\mst@wp
1.3h: no \mst@ell if symbolgreek (bugfix 1.3h 2015/10/31).
2125 \ifmst@symbolgreek\else\let\ell\mst@ell\fi
2126 \fi
2127 \fi
2128 }%
2129 \fi
2130 \fi
2131 \let\Mathastextstandardgreek\MTstandardgreek
2132 \let\Mathastextcustomgreek\MTcustomgreek
2133 \ifmst@subdued\else\MTcustomgreek\fi

```

\inodot In 1.0, I had them of type `mathord`, here I choose `mathalpha`. If I used `\i` and `\j` from the text font the problem would be with the fontsize, if in scriptstyle. The amsmath `\text` would do the trick.

1.14b 2011/04/02: again this bug in the EU1/EU2 encoding part, as in the code redefining `$` etc in math mode (see above). Fixed.

1.31 2016/01/29: anticipating TL2016 fonts's switch to TU.

1.3t 2018/08/22 removes the definitions done of `\i` and `\j` since 1.12 (as robust commands usable both in text and math mode).

1.3u lets the `\imath` and `\jmath` react to the font encoding at each math version.

1.3v lets the redefined `\imath` and `\jmath` be `\protected`.

```

2134 \def\mst@subdueinodot{%
2135   \let\inodot\mst@original@imath
2136   \let\jnodot\mst@original@jmath
2137 }%
2138 \def\mst@nonsubdueinodot{%
2139   \expandafter\let\expandafter\inodot

```

```

2140           \csname mst@inodot@mv\math@version\endcsname
2141   \expandafter\let\expandafter\jnodot
2142           \csname mst@jnodot@mv\math@version\endcsname
2143 }%
2144 \def\mst@dothe@inodotstuff#1#2#3{%
2145   \edef\mst@tmp@enc{#3}%
2146   \if1\mst@OneifUniEnc
2147     \mst@Umathchardef#1="7 \symmtletterfont "0131 \relax
2148     \mst@Umathchardef#2="7 \symmtletterfont "0237 \relax
2149   \else
2150     \DeclareMathSymbol{#1}{\mathalpha}{mtletterfont}%
2151             {\csname\mst@tmp@enc\string\i\endcsname}
2152     \DeclareMathSymbol{#2}{\mathalpha}{mtletterfont}%
2153             {\csname\mst@tmp@enc\string\j\endcsname}
2154   \fi}%
2155 \ifmst@defaultimath\else\mst@infoline{\string\imath\space and \string\jmath\space}%
2156   \AtEndOfPackage{\AtBeginDocument{%
2157     \protected\def\imath{\inodot}%
2158     \protected\def\jmath{\jnodot}%
2159   }}%
2160 \fi

```

**math accents** *Obsolete comments relative to the 2011 code:*

I don't know how to get from the encoding to the slot positions of the accents (apart from going to look at all possible encodings definition files and putting this info here). In standard L<sup>A</sup>T<sub>E</sub>X, the math accents are taken from the 'operators' font. So we do the same here. Of course there is the problem that the user can define math versions with different encodings. Here I take T1 if it was the default at the time of loading the package, else OT1. [1.12b](#): I add LY1 which is quasi like OT1.

At [1.3u](#) 2019/08/20 I decide to remove the hard-coded slot positions for OT1, T1 and LY1, and replace them with some hack which assumes L<sup>A</sup>T<sub>E</sub>X2e way of handling text accents got executed by the encoding definition file. If not, some breakage on package loading could occur, but this whole thing is conditional on the **mathaccents** option anyway, which per default is not executed.

The \vec accent is not considered here because it has no suitable available glyph in a standard 8bits text font encodings.

Also at [1.3u](#) the math accents adapt to the font encoding at each math version.

(obsolete at [1.4](#)) [1.3v](#) adapts to L<sup>A</sup>T<sub>E</sub>X 2019-10-01 which now comes with robust math accent macros. The «original»-named macros are without the robustifying space (NOT true anymore, see [1.3w](#) next), as they only serve as meaning holders.

(obsolete at [1.4](#)) On the other hand the macros indexed by math version names are (in the pdflatex branch) always defined via \DeclareMathAccent hence they will be robust with 2019-10-01 or later and we must use the \mst@robustifyingspace with them to access their real meaning (this thus differs from the situation with \hbar).

[1.3w](#) The above was a bit optimistic as **amsmath** for example modifies L<sup>A</sup>T<sub>E</sub>X internals and handles math accents differently.

We thus needed to double our \let's as, if **amsmath** is loaded, the cs with space will exist but not be paired in expected way with the original cs. This breaks things by the way if some math

accent is written to an external file under a certain context and executed in another context. The new context will be probably ignored if `amsmath` is loaded, as the external file will have an already expanded-once meaning.

Some macros with space in name might thus be created as `\relax`. Should I rather create `\protected` macros for the math accents with Unicode engines? Anyway, the construct does give good result with the few OpenType text fonts I tested.

```

2161 \let\mst@subduedmathaccents\empty
2162 \let\mst@nonsubduedmathaccents\empty
2163 \ifmst@mathaccents
2164 \def\mst@subduedmathaccents{%
2165   \atfor@\tempa:={grave}{acute}{check}{breve}{bar}%
2166   {dot}{ddot}{mathring}{hat}{tilde}%
2167   \do
2168   {\expandafter\let\csname@\tempa\expandafter\endcsname
2169    \csname mst@original@\@tempa\endcsname
2170   \expandafter\let\csname@\tempa\space\expandafter\endcsname
2171    \csname mst@original@\@tempa\space\endcsname
2172   }%
2173 }%
2174 \def\mst@nonsubduedmathaccents{%
2175   \atfor@\tempa:={grave}{acute}{check}{breve}{bar}%
2176   {dot}{ddot}{mathring}{hat}{tilde}%
2177   \do
2178   {\expandafter\let\csname@\tempa\expandafter\endcsname
2179    \csname mst@\@tempa @mv\math@version\endcsname
2180   \expandafter\let\csname@\tempa\space\expandafter\endcsname
2181    \csname mst@\@tempa @mv\math@version\space\endcsname
2182 }%
2183 }%
2184 \def\mst@dothe@mathaccentsstuff#1#2{%
2185   \begingroup
2186   \edef\mst@tmp@enc{#2}%
2187   \def\@text@composite##1\@text@composite##2##2{%
2188     \let\add@accent\@firstoftwo
2189     \let\add@unicode@accent\@firstoftwo
2190     \if1\mst@OneifUniEnc
2191       \ifmst@unimathaccents
2192         \expandafter\xdef\csname mst@grave@mv#1\mst@robustifyingspace\endcsname
2193         {\mst@Umathaccent
2194          7
2195          \number\symmtoperatorfont\space
2196          \csname#2\string`\endcsname{}\relax}%
2197         \expandafter\xdef\csname mst@acute@mv#1\mst@robustifyingspace\endcsname
2198         {\mst@Umathaccent
2199          7
2200          \number\symmtoperatorfont\space
2201          \csname#2\string`'\endcsname{}\relax}%
2202         \expandafter\xdef\csname mst@check@mv#1\mst@robustifyingspace\endcsname
2203         {\mst@Umathaccent

```

```

2204      7
2205      \number\symmtoperatorfont\space
2206      \csname#2\string\v\endcsname{}\relax}%
2207      \expandafter\xdef\csname mst@breve@mv#1\mst@robustifyingspace\endcsname
2208      {\mst@Umathaccent
2209      7
2210      \number\symmtoperatorfont\space
2211      \csname#2\string\u\endcsname{}\relax}%
2212      \expandafter\xdef\csname mst@bar@mv#1\mst@robustifyingspace\endcsname
2213      {\mst@Umathaccent
2214      7
2215      \number\symmtoperatorfont\space
2216      \csname#2\string\=\endcsname{}\relax}%
2217      \expandafter\xdef\csname mst@dot@mv#1\mst@robustifyingspace\endcsname
2218      {\mst@Umathaccent
2219      7
2220      \number\symmtoperatorfont\space
2221      \csname#2\string.\endcsname{}\relax}%
2222      \expandafter\xdef\csname mst@ddot@mv#1\mst@robustifyingspace\endcsname
2223      {\mst@Umathaccent
2224      7
2225      \number\symmtoperatorfont\space
2226      \csname#2\string\".endcsname{}\relax}%
2227      \expandafter\xdef\csname mst@mathring@mv#1\mst@robustifyingspace\endcsname
2228      {\mst@Umathaccent
2229      7
2230      \number\symmtoperatorfont\space
2231      \csname#2\string\r\endcsname{}\relax}%
2232      \expandafter\xdef\csname mst@hat@mv#1\mst@robustifyingspace\endcsname
2233      {\mst@Umathaccent
2234      7
2235      \number\symmtoperatorfont\space
2236      \csname#2\string\^\endcsname{}\relax}%
2237      \expandafter\xdef\csname mst@tilde@mv#1\mst@robustifyingspace\endcsname
2238      {\mst@Umathaccent
2239      7
2240      \number\symmtoperatorfont\space
2241      \csname#2\string\~\endcsname{}\relax}%
2242  \else

```

[1.3u](#) used some `\def` but this made the accent macro meanings look slightly different depending on whether the math version being set-up was with an 8bit encoding or TU encoding.

For the sake of uniform treatment we modify this at [1.3v](#), but this is a bit complicated regarding timing: we need, in absence of `unimathaccents` option, in math versions with an OpenType font, to let the `\acute` etc... acquire back some prior non-`mathastext` meanings. To allow maximal flexibility, these original meaning get stored at begin document only. But `\mst@nonsubduedmathaccents` assigns to `\acute` etc... (in the robust sense with L<sup>A</sup>T<sub>E</sub>X 2019-10-01 or later) the meaning stored in the macros with the math version in their names. Such `\mst@acute@mvnormal` etc... must thus be ready before `\mst@nonsubduedmathaccents` (or at least before the last such) execution: the code here must get executed after the definition of the

«original»-named macros but prior to the (last one, if multiple) `\mst@nonsubduedmathaccents`.

Hence 1.3v delayed a bit the initial execution of this macro (see further down in the code) compared to what happened in 1.3u.

We are in a group but `\AtEndOfPackage` does the right thing.

```
2243     \AtEndOfPackage{\AtBeginDocument{%
2244     \@tfor\@tempa:={grave}{acute}{check}{breve}{bar}%
2245         {dot}{ddot}{mathring}{hat}{tilde}%
2246     \do
2247     {\expandafter\let
2248         \csname mst@\@tempa @mv#1\expandafter\endcsname
2249         \csname mst@original@\@tempa\endcsname
2250     \expandafter\let
2251         \csname mst@\@tempa @mv#1\space\expandafter\endcsname
2252         \csname mst@original@\@tempa\space\endcsname}%
2253     }%
2254   \fi}
```

This is needed because the pdflatex engine branch will use `\DeclareMathAccent` and it creates robust macros with L<sup>A</sup>T<sub>E</sub>X 2019-10-01 or later. As we want elsewhere in the package code not to have to check if under Unicode engine or not, we need to handle here also some definition of robust macros.

But wouldn't it be simpler to manage `\protected` macros?

```
2255     \@tfor\@tempa:={grave}{acute}{check}{breve}{bar}%
2256         {dot}{ddot}{mathring}{hat}{tilde}%
2257     \do
2258     {\expandafter\xdef\csname mst@\@tempa @mv#1\endcsname
2259         {\noexpand\protect
2260         \expandafter\noexpand\csname mst@\@tempa @mv#1 \endcsname}%
2261     }%
2262   \else
2263     \expandafter\mst@DeclareMathAccent\expandafter
2264         {\csname mst@grave@mv#1\endcsname}{\mathalpha}{\operatorfont}%
2265         {\csname#2\string`\endcsname{}}
2266     \expandafter\mst@DeclareMathAccent\expandafter
2267         {\csname mst@acute@mv#1\endcsname}{\mathalpha}{\operatorfont}%
2268         {\csname#2\string`'\endcsname{}}
2269     \expandafter\mst@DeclareMathAccent\expandafter
2270         {\csname mst@check@mv#1\endcsname}{\mathalpha}{\operatorfont}%
2271         {\csname#2\string`v\endcsname{}}
2272     \expandafter\mst@DeclareMathAccent\expandafter
2273         {\csname mst@breve@mv#1\endcsname}{\mathalpha}{\operatorfont}%
2274         {\csname#2\string`u\endcsname{}}
2275     \expandafter\mst@DeclareMathAccent\expandafter
2276         {\csname mst@bar@mv#1\endcsname}{\mathalpha}{\operatorfont}%
2277         {\csname#2\string`=\endcsname{}}
```

```

2278 \expandafter\mst@DeclareMathAccent\expandafter
2279     {\csname mst@dot@mv#1\endcsname}{\mathalpha}{\mtoperatorfont}%
2280     {\csname#2\string.\endcsname{}}
2281 \expandafter\mst@DeclareMathAccent\expandafter
2282     {\csname mst@ddot@mv#1\endcsname}{\mathalpha}{\mtoperatorfont}%
2283     {\csname#2\string\".\endcsname{}}
2284 \expandafter\mst@DeclareMathAccent\expandafter
2285     {\csname mst@mathring@mv#1\endcsname}{\mathalpha}{\mtoperatorfont}%
2286     {\csname#2\string\r.\endcsname{}}
2287 \expandafter\mst@DeclareMathAccent\expandafter
2288     {\csname mst@hat@mv#1\endcsname}{\mathalpha}{\mtoperatorfont}%
2289     {\csname#2\string\^\endcsname{}}
2290 \expandafter\mst@DeclareMathAccent\expandafter
2291     {\csname mst@tilde@mv#1\endcsname}{\mathalpha}{\mtoperatorfont}%
2292     {\csname#2\string\~\endcsname{}}
2293 \fi
2294 \endgroup
2295 }%
2296 \fi

```

**\MTDeclareVersion** The `\MTDeclareVersion` command is to be used in the preamble to declare a math version. A more complicated variant would also specify a choice of series for the Euler and Symbol font: anyhow Symbol only has the medium series, and Euler has medium and bold, so what is lacking is the possibility to create a version with a bold Euler. There is already one such version: the default **bold** one. And there is always the possibility to add to the preamble `\SetSymbolFont{mteulervm}{versionname}{U}{zeur}{bx}{n}` if one wants to have a math version with bold Euler characters.

For version 1.1 we add an optional parameter specifying the shape to be used for letters.

Note: (2012/10/24) I really should check whether the user attempts to redefine the ‘normal’ and ‘bold’ versions and issue a warning in that case! Finally done at 1.3w 2019/11/16! Better late than never...

1.3c (2013/12/14) adds an extra optional parameter after all previous ones, to inherit the settings from another version. Typically to be used with [bold]. I take this opportunity to sanitize a bit some line endings to avoid generating (in the preamble, document macros were already careful of course) too many space tokens, at least inside macros. And I modify (correct? perhaps it was on purpose) the strange way I used `\onlypreamble` in earlier version.

1.3u adds storage of macros holding the needed meanings for `\imath`, `\hbar`, math accents, and the minus symbol, version wise.

1.3w adds the check to forbid **normal** and **bold** as version names.

```

2297 \newcommand*\MTDeclareVersion[6] []{%
2298   \edef\mst@declareversionargs{{#1}{#2}{#3}{#4}{#5}{#6}}%
2299   \edef\mst@version{#2}%
2300   \if0\ifx\mst@version\mst@normalversionname0\else
2301     \ifx\mst@version\mst@boldversionname0\else
2302       1\fi\fi
2303   \expandafter\expandafter\expandafter
2304   \MTDoNotDeclareVersion@\expandafter\@gobblefour
2305 \fi
2306 \relax\DeclareMathVersion{\mst@version}\MTDeclareVersion@

```

```

2307 }%
2308 \newcommand*\MTDoNotDeclareVersion@[1] []{%
2309   \PackageWarningNoLine{mathastext}{You asked to declare a version with name
2310   `\'mst@version'.^^J%
2311   \@spaces Sorry but you are not allowed to do that.^^J%
2312   \@spaces \ifmst@subdued Anyway the `subdued' option is in force\else
2313     Use rather \string\Mathastext\space macro (with no optional argument)\fi
2314 }{%
2315 \newcommand*\MTDeclareVersion@[1] []{%
2316   \edef\mst@tmp{\#1}%
2317   \ifx\mst@tmp\empty\else
2318     \global\expandafter\let\csname mv@\mst@version\expandafter\endcsname
2319     \csname mv@\#1\endcsname
2320     \PackageInfo{mathastext}%
2321       {Math version `\'mst@version\string'\MessageBreak
2322        declared\on@line\MessageBreak
2323        inherits from `\'#1\string'\@gobble}%
2324   \fi
2325   \expandafter\MTDeclareVersion@@\mst@declareversionargs
2326 }%
2327 \newcommand*\MTDeclareVersion@@[6]{%
2328   \expandafter\edef\csname mst@encoding@\mst@version\endcsname{\#3}%
2329   \expandafter\edef\csname mst@family@\mst@version\endcsname{\#4}%
2330   \expandafter\edef\csname mst@series@\mst@version\endcsname{\#5}%
2331   \expandafter\edef\csname mst@shape@\mst@version\endcsname{\#6}%
2332   \expandafter\edef\csname mst@boldvariant@\mst@version\endcsname{\mst@bold}%
2333   \expandafter\edef\csname mst@itdefault@\mst@version\endcsname{\itdefault}%
2334   \expandafter\edef\csname mst@rmdefault@\mst@version\endcsname{\rmdefault}%
2335   \expandafter\edef\csname mst@sfdefault@\mst@version\endcsname{\sfdefault}%
2336   \expandafter\edef\csname mst@ttdefault@\mst@version\endcsname{\ttdefault}%
2337   \expandafter\edef\csname mst@exists@skip@\mst@version\endcsname
2338     {\mst@exists@skip}%
2339   \expandafter\edef\csname mst@forall@skip@\mst@version\endcsname
2340     {\mst@forall@skip}%
2341   \expandafter\edef\csname mst@prime@skip@\mst@version\endcsname
2342     {\mst@prime@skip}%
2343   \def\mst@tmp{\#1}%
2344   \ifx\mst@tmp\empty
2345     \ifmst@italic
2346       \SetSymbolFont{mtletterfont}{\#2}{\#3}{\#4}{\#5}{\mst@ltsh}%
2347       \immediate\write\m@ne{ }%
2348       \PackageInfo{mathastext}%
2349         {\ifmst@noletters
2350           \else
2351             Latin letters in math version `\'#2\string'\MessageBreak
2352             declared\on@line\MessageBreak
2353             will use the font \#3/\#4/\#5/\mst@ltsh
2354             \ifmst@frenchmath\space(uppercase: \#6)\fi\MessageBreak
2355           \fi

```

```

2356          Other characters (digits, ...) and \protect\log-like names\MessageBreak
2357          \ifmst@noletters
2358              will use the font #3/#4/#5/#6%
2359          \else
2360              will be in `#6$string' shape%
2361          \fi\@gobble}%
2362      \immediate\write\m@ne{ }%
2363      \expandafter\edef\csname mst@ltshape@\mst@version\endcsname{\mst@ltsh}%
2364  \else
2365      \SetSymbolFont{mtletterfont}{#2}{#3}{#4}{#5}{#6}%
2366      \ifmst@noletters
2367      \else
2368          \immediate\write\m@ne{ }%
2369          \PackageInfo{mathastext}%
2370              {Latin letters in math version `#2$string'\MessageBreak
2371              declared\on@line\MessageBreak
2372              will use the fonts #3/#4/#5(\mst@bold)/#6\@gobble}%
2373      \fi
2374      \immediate\write\m@ne{ }%
2375      \expandafter\edef\csname mst@ltshape@\mst@version\endcsname{#6}%
2376  \fi
2377 \else
#1 not empty.
2378  \SetSymbolFont{mtletterfont}{#2}{#3}{#4}{#5}{#1}%
2379  \immediate\write\m@ne{ }%
2380  \PackageInfo{mathastext}%
2381      {\ifmst@noletters
2382      \else
2383          Latin letters in math version `#2$string'\MessageBreak
2384          declared\on@line\MessageBreak
2385          will use the font #3/#4/#5/#1%
2386          \ifmst@frenchmath\space(uppercase: #6)\fi\MessageBreak
2387      \fi
2388          Other characters (digits, ...) and
2389          \protect\log-like names\MessageBreak
2390          \ifmst@noletters
2391              will use the font #3/#4/#5/#6%
2392          \else
2393              will be in `#6$string' shape%
2394          \fi\@gobble}%
2395  \immediate\write\m@ne{ }%
2396  \expandafter\edef\csname mst@ltshape@\mst@version\endcsname{#1}%
2397 \fi
Here and elsewhere 1.3za has removed an \ifmst@nonormalbold conditional.
2398  \SetMathAlphabet{\Mathnormalbold}{#2}{#3}{#4}{\mst@bold}%
2399      {\csname mst@ltshape@\mst@version\endcsname}%
2400  \SetSymbolFont{mtoperatorfont}{#2}{#3}{#4}{#5}{#6}%

```

Since [1.3za](#) (and prior to [1.15f](#)) these math alphabet commands are always defined.

```

2401 \SetMathAlphabet{\Mathbf}{#2}{#3}{#4}{\mst@bold}{#6}
2402 \SetMathAlphabet{\Mathit}{#2}{#3}{#4}{#5}{\itdefault}
2403 \SetMathAlphabet{\Mathsf}{#2}{#3}{\sfdefault}{#5}{#6}
2404 \SetMathAlphabet{\Mathtt}{#2}{#3}{\ttdefault}{#5}{#6}
2405 \ifmst@needeuler
2406   \SetMathAlphabet{\MathEulerBold}{#2}{U}{zeur}{\mst@bold}{n}%
2407 \fi

```

**LGRgreeks** In the case of option LGRgreeks (selfGreeks), it is expected that the fonts used in each math versions exist in LGR (OT1) encoding. We first recalculate the shapes to be used for lowercase and uppercase Greek letters depending on the frenchmath and [it/up][g/G]reek options as well as on the (local to this version) shapes for letters and digits.

**1.3y** replaces `\updefault` by `\MTgreekupdefault` and `\itdefault` by `\MTgreekitdefault`. It also prepares to store two Boolean settings saying whether lowercase respectively uppercase Greek letters will use ‘upright’ or ‘italic’ (`LGRgreek(s)` only).

The **1.3y** refactoring of `LGRgreek` is done via a decoupling, thus things are done here under `selfGreek` or other Greek options which ultimately serve nothing and conversely things are done here for `LGRgreek` which are superfluous.

```

2408 \def\mst@greek@lsh@loc{\csname mst@ltshape@\mst@version\endcsname}%
2409 \def\mst@greek@ush@loc{\csname mst@shape@\mst@version\endcsname}%
2410 \mst@greek@lower@uptrue
2411   \expandafter\in@\expanded{{\mst@greek@lsh@loc.}}{it.,sl.}%
2412   \ifin@\mst@greek@lower@upfalse\fi
2413 \mst@greek@upper@uptrue
2414   \expandafter\in@\expanded{{\mst@greek@ush@loc.}}{it.,sl.}%
2415   \ifin@\mst@greek@upper@upfalse\fi
2416 \ifmst@itgreek
2417   \def\mst@greek@lsh@loc{\MTgreekitdefault}%
2418   \def\mst@greek@ush@loc{\MTgreekitdefault}%
2419     \mst@greek@lower@upfalse
2420     \mst@greek@upper@upfalse
2421 \fi
2422 \ifmst@upgreek
2423   \def\mst@greek@lsh@loc{\MTgreekupdefault}%
2424   \def\mst@greek@ush@loc{\MTgreekupdefault}%
2425     \mst@greek@lower@uptrue
2426     \mst@greek@upper@uptrue
2427 \fi
2428 \ifmst@frenchmath
2429   \ifmst@itgreek\else
2430     \ifmst@upgreek\else
2431       \def\mst@greek@lsh@loc{\csname mst@shape@\mst@version\endcsname}%
2432       \def\mst@greek@ush@loc{\csname mst@shape@\mst@version\endcsname}%
2433       \mst@greek@lower@uptrue
2434       \mst@greek@upper@uptrue
2435     \fi\fi
2436 \fi
2437 \ifcase\mst@greek@select
2438   \or

```

```

2439      \def\mst@greek@ush@loc{\MTgreekitdefault}%
2440      \mst@greek@upper@upfalse
2441      \or
2442      \def\mst@greek@ush@loc{\MTgreekupdefault}%
2443      \mst@greek@upper@uptrue
2444  \fi

1.3za refactoring to reduce code duplication; I briefly considered trying to enhance \MTgreek-
font to work also with LGRgreeks and selfGreeks but I have dropped the idea for now.

2445  \ifmst@LGRgreeks \def\mst@greekfont{\#4}\fi
2446  \ifmst@selfGreeks\def\mst@greekfont{\#4}\fi
2447  \ifmst@LGRgreek
2448      \SetSymbolFont{mtgreekup}{\#2}{LGR}{\mst@greekfont}{\#5}{\MTgreekupdefault}%
2449      \SetSymbolFont{mtgreekit}{\#2}{LGR}{\mst@greekfont}{\#5}{\MTgreekitdefault}%
2450      \SetMathAlphabet{\mathgreekupbold}{\#2}{LGR}{\mst@greekfont}
2451          {\mst@bold}{\MTgreekupdefault}%
2452      \SetMathAlphabet{\mathgreekitbold}{\#2}{LGR}{\mst@greekfont}
2453          {\mst@bold}{\MTgreekitdefault}%

This is where the shape of uppercase/lowercase Greek letters is recorded, for \MTversion's
triggered \MTcustomgreek to do the right thing.

2454  \expandafter\let\csname ifmst@greek@\mst@version @upper@up\expandafter\endcsname
2455      \csname ifmst@greek@upper@up\endcsname
2456  \expandafter\let\csname ifmst@greek@\mst@version @lower@up\expandafter\endcsname
2457      \csname ifmst@greek@lower@up\endcsname
2458 \immediate\write\m@ne{%%
2459 \PackageInfo{mathastext}{Greek letters (upper:
2460     `ifmst@greek@upper@up\MTgreekupdefault\else\MTgreekitdefault\fi\string',
2461     lower:
2462     `ifmst@greek@lower@up\MTgreekupdefault\else\MTgreekitdefault\fi\string')\MessageBreak
2463         will use font family `'\mst@greekfont\string' (LGR)\MessageBreak
2464         in mathastext
2465         math version `'\mst@version\string'\MessageBreak
2466         declared}%
2467 \immediate\write\m@ne{%%
2468     \else
2469     \ifmst@selfGreek
2470         \SetSymbolFont{mtselfGreekfont}{\#2}{OT1}{\mst@greekfont}{\#5}{\mst@greek@ush@loc}%
2471 \immediate\write\m@ne{%%
2472 \PackageInfo{mathastext}{Capital Greek letters (shape `'\mst@greek@ush@loc\string'
2473             will use the font\MessageBreak
2474             family `'\mst@greekfont\string' (OT1) in mathastext\MessageBreak
2475             math version `'\mst@version\string' declared}%
2476 \immediate\write\m@ne{%%
2477     \fi
2478     \fi
2479     \edef\mst@tmp{\expandafter\noexpand\csname mst@hbar@mv#2\endcsname
2480         \expandafter\noexpand\csname mst@ltbar@mv#2\endcsname}%
2481     \expandafter\mst@dothe@hbarstuff\mst@tmp{#3}%
2482     \edef\mst@tmp{\expandafter\noexpand\csname mst@inodot@mv#2\endcsname

```

```

2483           \expandafter\noexpand\csname mst@jnodot@mv#2\endcsname}%
2484   \expandafter\mst@dothe@inodotstuff\mst@tmp{#3}%
2485   \ifmst@mathaccents
2486     \mst@dothe@mathaccentsstuff{#2}{#3}%
2487   \fi
2488   \edef\mst@tmp{\expandafter\noexpand\csname mst@minus@mv#2\endcsname}%
2489     \expandafter\noexpand\csname mst@varfam@minus@mv#2\endcsname}%
2490   \ifmst@endash
2491     \expandafter\mst@dothe@endashstuff\mst@tmp{#3}%
2492   \else
2493     \ifmst@emdash
2494       \expandafter\mst@dothe@emdashstuff\mst@tmp{#3}%
2495     \else
2496       \expandafter\mst@dothe@hyphenstuff\mst@tmp
2497     \fi
2498   \fi
2499 }%
2500 \let\MathastextDeclareVersion\MTDeclareVersion

```

**\MTversion** This is a wrapper around L<sup>A</sup>T<sub>E</sub>X's `\mathversion`: here we have an optional argument allowing a quick and easy change of the text fonts additionally to the math fonts. Present already in the `\MTversion@s` initial version of the package (January 2011.)

**\MTversion@C** **1.15:** some modifications for the subdued option vs `LGRgreek` and for the math muskips after `\exists` and `\forall`.

**1.2:** with the subdued option sets the math alphabets in the normal and bold math versions do not apply to operator names and non-alphabetical symbols. The switch for braces is left as it is.

**1.2b:** with the subdued option, the italic corrections are not added. Else, we check the shape of letters in this version. Also, there was a bug since **1.15:** the values of the math skips were taken not from the settings for the math version (#2) but from those of the optional argument (#1), if present...

**1.3:** activation of italic corrections is now separated from actual math activation of letters.

**1.3c:** a starred variant is added which does not modify the text fonts, only the math set-up.

**1.3d:** replaced in `\MTversion@` things like `\edef\mst@encoding{...}` and

`\renewcommand{\encodingdefault}{\mst@encoding}`

by `\edef\encodingdefault{...}` etc... All those `\mst@...{...}` things were useless. I also redefine `\seriesdefault` rather than `\mddefault`.

**1.3d:** mechanism of restoration of Greek in subdued normal and bold versions has been to all cases, and not only for the `LGRgreek` option.

**1.3u:** version savvy (i.e. font-encoding savvy) minus sign, `\hbar`, `\imath`, math accents.

**1.3y:** Booleans recovered from stored data in the math version will configure the things `\MTcustomgreek` do, under `LGRgreek` option.

```

2501 \newcommand*\MTversion {\@ifstar\MTversion@s\MTversion@}
2502 \newcommand*\MTversion@s [1]{\mathversion{#1}\MTversion@C}
2503 \newcommand*\MTversion@ [2] []{%

```

This defines `\mathversion` as expanded #2.

```

2504   \mathversion{#2}%
2505   \edef\mst@tmpa{#1}%
2506   \ifx\mst@tmpa\empty

```

```

2507      \let\mst@tmp\math@version
2508  \else
2509      \let\mst@tmp\mst@tmpa
2510  \fi
2511  \edef\encodingdefault {\csname mst@encoding@\mst@tmp\endcsname}%
2512  \edef\familydefault {\csname mst@family@\mst@tmp\endcsname}%
2513  \edef\seriesdefault {\csname mst@series@\mst@tmp\endcsname}%
2514  \edef\shapedefault {\csname mst@shape@\mst@tmp\endcsname}%
2515  \edef\bfdefault {\csname mst@boldvariant@\mst@tmp\endcsname}%
2516  \edef\itdefault {\csname mst@itdefault@\mst@tmp\endcsname}%
2517  \edef\rmdefault {\csname mst@rmdefault@\mst@tmp\endcsname}%
2518  \edef\sfdefault {\csname mst@sfdefault@\mst@tmp\endcsname}%
2519  \edef\ttdefault {\csname mst@ttdefault@\mst@tmp\endcsname}%
2520  \usefont{\encodingdefault}{\familydefault}{\seriesdefault}{\shapedefault}%
2521  \MTversion@@
2522 }%

```

[1.3j](#) has a stronger subdued which does `\MTnormalprime`, `\MTnormalexists`, `\MTnormalforall` rather than setting the skips to `0mu`. Hence `\MTversion` by default should do `\MTprimedoesskip`, `\MTexistsdoesskip`, `\MTforalldoesskip`.

[1.3u](#) drops the argument, as the info is in `\math@version` from L<sup>A</sup>T<sub>E</sub>X2e code.

```

2523 \newcommand*\MTversion@@ {%
2524     \MTexistsdoesskip
2525     \MTforalldoesskip
2526     \MTprimedoesskip
v1.15e: muskips.
2527     \mst@exists@muskip\csname mst@exists@skip@\math@version\endcsname\relax
2528     \mst@forall@muskip\csname mst@forall@skip@\math@version\endcsname\relax
v1.2: muskip for \prime.
2529     \mst@prime@muskip\csname mst@prime@skip@\math@version\endcsname\relax
v1.2b: italic corrections except for italic/slanted (sic) letters, and of course except in the subdued
normal and bold math versions.

```

v1.3: by default, letters are made mathematically active, even if italic corrections are not used, to allow the action of `\MTsetmathskips`.

```

2530     \edef\mst@tmpa{\csname mst@ltshape@\math@version\endcsname}%
2531     \edef\mst@tmpb{\csname mst@shape@\math@version\endcsname}%

```

[1.15c](#): extending subdued to LGRgreek.

[1.15f](#): subdueing math alphabets in a simpler way than in [1.15e](#).

[1.2b](#): subdueing the activation of characters in math mode.

[1.2d](#): special treatment of the asterisk.

[1.3d](#): extended LGRgreek mechanism of activation/restoration of Greek to all cases.

[1.3j](#): use of `\MTeverymathdefault`, which includes `\MTicinmath`, but must be corrected then according to shape of letters and presence or absence of option `frenchmath`. We do only `\def\mst@ITcorr{\ifnum\fam=\m@ne\else\fi}` and not `\MTICinmath` to not overwrite some user-defined `\MTeverymathdefault`. Code for italic corrections or not according to letter shape is executed after `\MTeverymathdefault` which limits a bit user customizing possibilities, but if I moved it later, I would possibly have to put inside the `\MTicinmath` the check for `it` or `sl`. Similary the `\MTcustomgreek` always executed (if not subdued).

MEMO: `\MTeverymathdefault` is executed *also* if in `subdued` mode but there is a `\MTeverymathoff` done next in the *normal* and *bold* version. It does `\MTicinmath` and `\MTmathactivatedigits` which however are no-ops (only partly for the former, and for the latter always anyhow if no option `activedigits`) in `subdude` mode.

```

2532      \MTmathoperatorsobeymathxx
2533      \MTeverymathdefault
2534      \MTcustomizenevmcodes
2535      \@for\mst@tmpc:=it,sl\do{\ifx\mst@tmpc\mst@tmpa\MTnoicinmath\fi}%
2536      \ifmst@frenchmath
2537          \def\mst@ITcorr{\ifnum\fam=\m@ne\else\fi}%
2538          \@for\mst@tmpc:=it,sl\do{\ifx\mst@tmpc\mst@tmpb\MTnoICinmath\fi}%
2539      \fi

```

[1.3j](#) has a stronger subdued which does `\MTnormalprime`, `\MTnormalexists`, `\MTnormalforall` rather than simply setting the skips to `0mu`. Note: `\MTnormalprime` is done as part of `\MTeverymathoff`.

The `subdued` mode does *not* undo the effect of the `frenchmath` option on uppercase Latin letters: they will use the same shape as digits and operator names! (This should have been made more prominent in user manual more than ten years ago, but is done only today 2023/12/28...).

```

2540      \ifmst@subdued
2541          \ifx\math@version\mst@normalversionname
2542              \mst@restorealphabets
2543              \MTstandardgreek
2544              \MTmathoperatorsdonotobeymathxx
2545              \MTnormalexists
2546              \MTnormalforall

```

[1.4](#) has kept `\MTmathstandardletters` inside `\MTeverymathoff` but its action is now quite different from earlier situation as it resets mathcodes from active to normal status on the spot.

```

2547      \MTeverymathoff
2548      \MTresetnevmcodes

```

[1.3t](#) adds better compatibility with `subdued` mode for `\imath/\jmath` and perfect compatibility for the minus sign.

[1.3u](#) extends this further to allow per-math-version meanings for them.

```

2549      \mst@subduedhbar
2550      \mst@subduedinodot
2551      \mst@subduedmathaccents
2552      \mst@subduedminus
2553      \else
2554          \ifx\math@version\mst@boldversionname
2555              \mst@restorealphabets
2556              \MTstandardgreek
2557              \MTmathoperatorsdonotobeymathxx
2558              \MTnormalexists
2559              \MTnormalforall
2560              \MTeverymathoff
2561              \MTresetnevmcodes
2562              \mst@subduedhbar
2563              \mst@subduedinodot

```

```

2564      \mst@subduedmathaccents
2565      \mst@subduedminus
2566      \else
2567      \mst@setalphabets

```

[1.3y](#) addition for `\MTcustomgreek` under `LGRgreeks` option.

MEMO: the needed mathematical re-activation of letters when switching from *normal* or *bold* to a non-subdued math version has already been done above from the `\MTicinmath` which is part of `\MTeverymathdefault`.

MEMO: idem for digits under option `activedigits`.

```

2568  \expandafter\let\csname ifmst@greek@upper@up\expandafter\endcsname
2569      \csname ifmst@greek@\math@version @upper@up\endcsname
2570  \expandafter\let\csname ifmst@greek@lower@up\expandafter\endcsname
2571      \csname ifmst@greek@\math@version @lower@up\endcsname
2572      \MTcustomgreek
2573      \mst@nonsubduedhbar
2574      \mst@nonsubduedinodot
2575      \mst@nonsubduedmathaccents
2576      \mst@nonsubduedminus
2577      \fi
2578      \fi
2579  \else

```

[1.3y](#) addition for `\MTcustomgreek` under `LGRgreek` option.

MEMO: the mathematical activation of letters happened above from `\MTeverymathdefault`.  
Idem if `activedigits` for digits.

```

2580  \expandafter\let\csname ifmst@greek@upper@up\expandafter\endcsname
2581      \csname ifmst@greek@\math@version @upper@up\endcsname
2582  \expandafter\let\csname ifmst@greek@lower@up\expandafter\endcsname
2583      \csname ifmst@greek@\math@version @lower@up\endcsname
2584      \MTcustomgreek
2585      \mst@nonsubduedhbar
2586      \mst@nonsubduedinodot
2587      \mst@nonsubduedmathaccents
2588      \mst@nonsubduedminus
2589      \fi
2590 }%
2591 \let\MathastextVersion\MTversion
2592 \let\Mathastextversion\MTversion
2593 \let\MTVersion\MTversion
2594 \let\mathastextversion\MTversion

```

`\MTWillUse` This is a preamble-only command, which can be used more than once, only the latest one counts.  
Sets up the math fonts in the normal and bold versions, as does `\Mathastext`.

```

2595 \newcommand*\MTWillUse[5] [] {
2596   \MTencoding{#2}
2597   \MTfamily{#3}
2598   \MTseries{#4}
2599   \MTshape{#5}
2600   \ifmst@italic\MTlettershape{\itdefault}\fi

```

```

2601 \edef\mst@tmp{#1}
2602 \ifx\mst@tmp\empty\else\MTlettershape{#1}\fi
2603 \Mathastext}
2604 \let\MathastextWillUse\MTWillUse
2605 \let\Mathastextwilluse\MTWillUse

```

\Mathastext The command `\Mathastext` can be used anywhere in the preamble and any number of time, the last one is the one that counts.

In version 1.1 we have two fonts: they only differ in shape. The `mtletterfont` is for letters, and the `mtoperatorfont` for digits and log-like operator names. The default is that both are upright.

Starting with version 1.12, an optional argument makes `\Mathastext` act as the declaration of a math version, to be later used in the document.

Versions 1.15x brought some adaptations related to the subdued option.

1.3c adds a second optional parameter to inherit previous settings from another version; mostly done to inherit the bold version fonts for symbols and large symbols. This is done in `\MTDeclareVersion`.

1.3j moves the code related to `\MTicinmath` from `\Mathastext@` to `\AtBeginDocument` (code depending on whether `subdued` option in use). But we omit for this from `\MTicinmath` the `\MTmathactiveletters` and issue the latter during loading of package, hence allowing `\MTmathstandardletters` to be effective in the preamble.

I forgot to document that under `subdued` option the `\Mathastext` command without optional parameter does not any `\SetSymbolFont` etc... but it has a few other tasks to complete nevertheless.

1.3u fixes some long-standing bug that `\Mathastext` did not repeat some font-encoding dependent things: they got done only once during package loading (things regarding the `\hbar`, `\imath`, the math accents and the minus sign). They are now part of the contents of `\Mathastext` macro itself (which is executed during package loading).

1.3y has refactored the LGRgreek associated math fonts.

```

2606 \def\Mathastext {\@ifnextchar[\Mathastext@declare\Mathastext@}%
2607 \def\Mathastext@declare [#1]{%
2608   \edef\mst@tmp{#1}%
2609   \ifx\mst@tmp\empty
2610     \expandafter\@firstoftwo
2611   \else\expandafter\@secondoftwo
2612   \fi
2613   \Mathastext@
2614   {\MTDeclareVersion[\mst@ltsh]{\mst@enc}{\mst@fam}{\mst@ser}{\mst@opsh}}%
2615 }%
2616 \def\Mathastext@ {%
2617   \mst@update@greeksh
2618   \edef\mst@encoding@normal{\mst@enc}%
2619   \edef\mst@family@normal{\mst@fam}%
2620   \edef\mst@series@normal{\mst@ser}%
2621   \edef\mst@shape@normal{\mst@opsh}%
2622   \edef\mst@ltshape@normal{\mst@ltsh}%
2623   \edef\mst@itdefault@normal{\itdefault}%
2624   \edef\mst@rmdefault@normal{\rmdefault}%
2625   \edef\mst@sfdefault@normal{\sfdefault}%

```

```

2626 \edef\mst@ttdefault@normal{\ttdefault}%
2627 \edef\mst@boldvariant@normal{\mst@bold}%
2628 \edef\mst@exists@skip@normal{\mst@exists@skip}%
2629 \edef\mst@forall@skip@normal{\mst@forall@skip}%
2630 \edef\mst@prime@skip@normal{\mst@prime@skip}%
2631 \edef\mst@encoding@bold{\mst@enc}%
2632 \edef\mst@family@bold{\mst@fam}%
2633 \edef\mst@series@bold{\mst@bold}%
2634 \edef\mst@shape@bold{\mst@opsh}%
2635 \edef\mst@ltshape@bold{\mst@ltsh}%
2636 \edef\mst@boldvariant@bold{\mst@bold}%
2637 \edef\mst@itdefault@bold{\itdefault}%
2638 \edef\mst@rmdefault@bold{\rmdefault}%
2639 \edef\mst@sfdefault@bold{\sfdefault}%
2640 \edef\mst@ttdefault@bold{\ttdefault}%
2641 \edef\mst@exists@skip@bold{\mst@exists@skip}%
2642 \edef\mst@forall@skip@bold{\mst@forall@skip}%
2643 \edef\mst@prime@skip@bold{\mst@prime@skip}%
2644 \ifmst@subdued

```

Since 1.3j this branch is actually almost superfluous, as entering `normal` or `bold` with `\MTversion` does `\MTnormalexists`, `\MTnormalforall`, and `\MTnormalprime`. But some default values are needed if the user insists on issuing `\MTexistsdoesskip`, etc... nevertheless.

```

2645 \def\mst@exists@skip@normal{0mu}%
2646 \def\mst@forall@skip@normal{0mu}%
2647 \def\mst@prime@skip@normal{0mu}%
2648 \def\mst@exists@skip@bold{0mu}%
2649 \def\mst@forall@skip@bold{0mu}%
2650 \def\mst@prime@skip@bold{0mu}%
2651 \else
2652 \ifmst@italic
2653 \ifmst@frenchmath
2654 \mst@exists@muskip\mst@exists@skip\relax
2655 \mst@forall@muskip\mst@forall@skip\relax
2656 \mst@prime@muskip\mst@prime@skip\relax
2657 \else
2658 \def\mst@exists@skip@normal{0mu}%
2659 \def\mst@forall@skip@normal{0mu}%
2660 \def\mst@prime@skip@normal{0mu}%
2661 \def\mst@exists@skip@bold{0mu}%
2662 \def\mst@forall@skip@bold{0mu}%
2663 \def\mst@prime@skip@bold{0mu}%
2664 \fi
2665 \else
2666 \mst@exists@muskip\mst@exists@skip\relax
2667 \mst@forall@muskip\mst@forall@skip\relax
2668 \mst@prime@muskip\mst@prime@skip\relax
2669 \fi
2670 \fi

```

Here and elsewhere 1.3za has removed usage of an `\ifmst@nonormalbold` conditional which was added at 1.15f.

```

2671   \SetMathAlphabet{\Mathnormal}{normal}{\mst@encoding@normal}%
2672           {\mst@family@normal}%
2673           {\mst@boldvariant@normal}%
2674           {\mst@ltshape@normal}%
2675   \SetMathAlphabet{\Mathnormal}{bold}{\mst@encoding@bold}%
2676           {\mst@family@bold}%
2677           {\mst@boldvariant@bold}%
2678           {\mst@ltshape@bold}%
2679 \ifmst@subdued\else
2680   \SetSymbolFont{mtletterfont}{normal}{\mst@encoding@normal}%
2681           {\mst@family@normal}%
2682           {\mst@series@normal}%
2683           {\mst@ltshape@normal}%
2684   \SetSymbolFont{mtletterfont}{bold} {\mst@encoding@bold}%
2685           {\mst@family@bold}%
2686           {\mst@series@bold}%
2687           {\mst@ltshape@bold}%
2688   \SetSymbolFont{mtoperatorfont}{normal}{\mst@encoding@normal}%
2689           {\mst@family@normal}%
2690           {\mst@series@normal}%
2691           {\mst@shape@normal}%
2692   \SetSymbolFont{mtoperatorfont}{bold} {\mst@encoding@bold}%
2693           {\mst@family@bold}%
2694           {\mst@series@bold}%
2695           {\mst@shape@bold}%

```

1.3za removes the 1.15f added conditional checks.

```

2696   \SetMathAlphabet{\Mathbf}{normal}{\mst@encoding@normal}%
2697           {\mst@family@normal}%
2698           {\mst@series@bold}%
2699           {\mst@shape@normal}%
2700   \SetMathAlphabet{\Mathbf}{bold}{\mst@encoding@bold}%
2701           {\mst@family@bold}%
2702           {\mst@series@bold}%
2703           {\mst@shape@bold}%
2704   \SetMathAlphabet{\Mathit}{normal}{\mst@encoding@normal}%
2705           {\mst@family@normal}%
2706           {\mst@series@normal}%
2707           {\mst@itdefault@normal}%
2708   \SetMathAlphabet{\Mathit}{bold}{\mst@encoding@bold}%
2709           {\mst@family@bold}%
2710           {\mst@series@bold}%
2711           {\mst@itdefault@bold}%
2712   \SetMathAlphabet{\Mathsf}{normal}{\mst@encoding@normal}%
2713           {\mst@sfdefault@normal}%
2714           {\mst@series@normal}%
2715           {\mst@shape@normal}%

```

```

2716   \SetMathAlphabet{\Mathsf}{bold}{\mst@encoding@bold}%
2717           {\mst@sfdefault@bold}%
2718           {\mst@series@bold}%
2719           {\mst@shape@bold}%
2720   \SetMathAlphabet{\Mathtt}{normal}{\mst@encoding@normal}%
2721           {\mst@ttdefault@normal}%
2722           {\mst@series@normal}%
2723           {\mst@shape@normal}%
2724   \SetMathAlphabet{\Mathtt}{bold}{\mst@encoding@bold}%
2725           {\mst@ttdefault@bold}%
2726           {\mst@series@bold}%
2727           {\mst@shape@bold}%
2728 \fi

```

**\MathEulerBold** [1.14c](#): We reset `mteulervm` and `\MathEulerBold` here as the variant for bold may have been changed by the user via `\Mathastextboldvariant{m}`; and we should keep this local to math versions.

```

2729 \ifmst@needeuler
2730   \SetSymbolFont{mteulervm}{bold}{U}{zeur}{\mst@boldvariant@normal}{n}%
2731   \SetMathAlphabet{\MathEulerBold}{normal}%
2732       {U}{zeur}{\mst@boldvariant@normal}{n}%
2733   \SetMathAlphabet{\MathEulerBold}{bold}%
2734       {U}{zeur}{\mst@boldvariant@bold}{n}%
2735 \fi
2736 \ifmst@needsymbol\SetSymbolFont{mtsymbol}{bold}%
2737     {U}{psy}{\mst@boldvariant@bold}{n}%
2738 \fi

```

**LGRgreek\*** LGRgreek, LGRgreeks, selfGreek, and selfGreeks options.

**selfGreek\*** [1.3y](#) has refactored the `LGRgreek` associated math fonts.

[1.3za](#) adds the math alphabets `\mathgreekitbold` and `\mathgreekupbold`. And it executes this code also in `subdued` mode, because anyhow the symbolfonts `mtgreekup` and `mtgreekit` and associated alphabets have been declared also, at time of loading the package, so not doing it here means that effect of `\MTgreekfont` would be ignored; which was probably a bug. And by the way, documentation says `\MTgreekfont` has no effect under `LGRgreeks` and `selfGreeks` option so we need to enforce it here (for time being).

```

2739 \ifmst@LGRgreeks \edef\mst@greekfont{\mst@fam}\fi
2740 \ifmst@selfGreeks\edef\mst@greekfont{\mst@fam}\fi
2741 \ifmst@LGRgreek
2742   \SetSymbolFont{mtgreekup}{normal}{LGR}%
2743   {\mst@greekfont}{\mst@series@normal}{\MTgreekupdefault}%
2744   \SetSymbolFont{mtgreekup}{bold}{LGR}%
2745   {\mst@greekfont}{\mst@boldvariant@bold}{\MTgreekupdefault}%
2746   \SetSymbolFont{mtgreekit}{normal}{LGR}%
2747   {\mst@greekfont}{\mst@series@normal}{\MTgreekitdefault}%
2748   \SetSymbolFont{mtgreekit}{bold}{LGR}%
2749   {\mst@greekfont}{\mst@boldvariant@bold}{\MTgreekitdefault}%
2750 \SetMathAlphabet{\mathgreekupbold}{normal}{LGR}%

```

```

2751      {\mst@greekfont}{\mst@boldvariant@normal}{\MTgreekupdefault}%
2752 \SetMathAlphabet{\mathgreekupbold}{bold}{LGR}%
2753     {\mst@greekfont}{\mst@boldvariant@bold}{\MTgreekupdefault}%
2754 \SetMathAlphabet{\mathgreekitbold}{normal}{LGR}%
2755     {\mst@greekfont}{\mst@boldvariant@normal}{\MTgreekitdefault}%
2756 \SetMathAlphabet{\mathgreekitbold}{bold}{LGR}%
2757     {\mst@greekfont}{\mst@boldvariant@bold}{\MTgreekitdefault}%
2758 \else
2759   \ifmst@selfGreek
2760     \SetSymbolFont{mtselfGreekfont}{normal}{OT1}%
2761       {\mst@greekfont}{\mst@series@normal}{\mst@greek@ush}%
2762     \SetSymbolFont{mtselfGreekfont}{bold}{OT1}%
2763       {\mst@greekfont}{\mst@boldvariant@bold}{\mst@greek@ush}%
2764   \fi
2765 \fi

```

[1.3za](#) adds the log message in case of `selfGreek` option.

```

2766 \ifmst@subdued
2767 \else
2768   \mst@infoline{Latin letters in the `normal\string', resp. `bold\string',}%
2769   \mst@infoline{math versions are now set up to use the fonts}%
2770   \mst@infoline{\mst@encoding@normal/\mst@family@normal/\mst@series@normal
2771             /\mst@ltshape@normal, resp.
2772             \mst@encoding@normal/\mst@family@normal/\mst@boldvariant@normal
2773             /\mst@ltshape@normal.}%
2774 \ifmst@frenchmath\mst@infoline{(uppercase: \mst@shape@normal)}\fi
2775 \ifmst@LGRgreek
2776   \mst@infoline{Greek letters (upper:
2777     ``\ifmst@greek@upper@up\MTgreekupdefault\else\MTgreekitdefault\fi\string',
2778     lower:
2779     ``\ifmst@greek@lower@up\MTgreekupdefault\else\MTgreekitdefault\fi\string')
2780     will use font}%
2781   \mst@infoline{family ``\mst@greekfont\string' (LGR).}%
2782 \else
2783   \ifmst@selfGreek
2784     \mst@infoline{Capital Greek letters (shape ``\mst@greek@ush\string') will use font}
2785     \mst@infoline{family ``\mst@greekfont\string' (OT1).}%
2786   \fi
2787 \fi
2788 \ifmst@nodigits\else
2789   \mst@infoline{Other characters (digits, ...) and \string\log-like names will be}%
2790   \mst@infoline{typeset with the \mst@shape@normal\space shape.}%
2791 \fi
2792 \fi
2793 \ifmst@nohbar\else
2794   \mst@infoline{\string\hbar}%
2795   \mst@dothe@hbarstuff
2796     \mst@hbar@mvnorm\mst@ltbar@mvnorm\mst@encoding@normal
2797     \let\mst@hbar@mvb\mst@hbar@mvnorm

```

```

2798 \fi
2799 \mst@dothe@inodotstuff\inodot\jnodot\mst@encoding@normal
2800 \let\mst@inodot@mnormal\inodot
2801 \let\mst@inodot@mbold\inodot
2802 \let\mst@jnodot@mnormal\jnodot
2803 \let\mst@jnodot@mbold\jnodot
2804 \ifmst@mathaccents
2805   \mst@infoline{math accents}%
2806   \mst@dothe@mathaccentsstuff{normal}\mst@encoding@normal
2807 \fi
2808 \ifmst@nominus\else
2809   \mst@infoline{minus as endash}%
2810   \ifmst@endash
2811     \mst@dothe@endashstuff\mst@minus@mnormal\mst@varfam@minus@mnormal
2812       \mst@encoding@normal
2813     \mst@dothe@endashstuff\mst@minus@mbold\mst@varfam@minus@mbold
2814       \mst@encoding@normal
2815 \else
2816   \ifmst@emdash
2817     \mst@dothe@emdashstuff\mst@minus@mnormal\mst@varfam@minus@mnormal
2818       \mst@encoding@normal
2819     \mst@dothe@emdashstuff\mst@minus@mbold\mst@varfam@minus@mbold
2820       \mst@encoding@normal
2821   \else
2822     \mst@dothe@hyphenstuff\mst@minus@mnormal\mst@varfam@minus@mnormal
2823     \let\mst@minus@mbold\mst@minus@mnormal
2824     \let\mst@varfam@minus@mbold\mst@varfam@minus@mnormal
2825   \fi
2826 \fi
2827 \fi

```

**1.3zb** moves this info line last and also explicitly mentions `italic` or `frenchmath` (here and at some other locations above).

```

2828 \ifmst@subdued
2829   \mst@infoline{Subdued `normal\string' and `bold\string' math versions.}%
2830 \fi
2831 \ifmst@italic
2832   \mst@infoline{The \ifmst@frenchmath frenchmath \else
2833                           italic \fi option is in effect.}%
2834 \fi
2835 }%
2836 \let\mathastext\Mathastext
2837 \Mathastext

```

Additional appropriate messages to the terminal and the log.

```

2838 \ifmst@eulergreek
2839   \mst@infoline{Greek letters will use the Euler font.}%
2840   \mst@infoline{Use \string\MathastextEulerScale{<factor>} to scale the
2841                 font.}%
2842 \ifmst@subdued

```

```

2843           \mst@infoline{(\subdued mode: `normal\string' and `bold\string' math ver-
  sions)}%
2844           \mst@infoline{\space keep the default Greek letters.)}%
2845       \fi
2846 \else
2847 \ifmst@symbolgreek
2848     \mst@infoline{Greek letters will use the PostScript Symbol font.}%
2849     \mst@infoline{Use \string\MathastextSymbolScale{<factor>} to scale the font.}%
2850 \ifmst@subdued
2851     \mst@infoline{(\subdued mode: `normal\string' and `bold\string' math ver-
  sions)}%
2852     \mst@infoline{\space keep the default Greek letters.)}%
2853   \fi
2854 \fi\fi

```

**Math sizes** I took the code for `\Huge` and `\HUGE` from the `moresize` package of Christian CORNELSEN

```

2855 \ifmst@defaultsizes\else
2856 \providecommand\@xxxpt{29.86}
2857 \providecommand\@xxvpipt{35.83}
2858 \ifmst@twelve
2859   \def\Huge{\@setfontsize\Huge\@xxxpt{36}}
2860   \def\HUGE{\@setfontsize\HUGE\@xxvpipt{43}}
2861 \mst@infoline{\string\Huge\space and \string\HUGE\space have been (re)-defined.}
2862 \else
2863   \def\HUGE{\@setfontsize\HUGE\@xxxpt{36}}
2864 \mst@infoline{\string\HUGE\space has been (re)-defined.}
2865 \fi

```

I choose rather big subscripts.

```

2866 \def\defaultscriptratio{.8333}
2867 \def\defaultscriptscriptratio{.7}
2868 \DeclareMathSizes{9}{9}{7}{5}
2869 \DeclareMathSizes{\@xpt}{\@xpt}{8}{6}
2870 \DeclareMathSizes{\@xipt}{\@xipt}{9}{7}
2871 \DeclareMathSizes{\@xipt}{\@xipt}{10}{8}
2872 \DeclareMathSizes{\@xivpt}{\@xivpt}{\@xiipt}{10}
2873 \DeclareMathSizes{\@xviipt}{\@xviipt}{\@xivpt}{\@xiipt}
2874 \DeclareMathSizes{\@xxpt}{\@xxpt}{\@xviipt}{\@xivpt}
2875 \DeclareMathSizes{\@xxvpt}{\@xxvpt}{\@xxpt}{\@xviipt}
2876 \DeclareMathSizes{\@xxxpt}{\@xxxpt}{\@xxvpt}{\@xxpt}
2877 \DeclareMathSizes{\@xxvpipt}{\@xxvpipt}{\@xxxpt}{\@xxvpt}
2878 \mst@infoline{mathastext has declared larger sizes for subscripts.}
2879 \mst@infoline{To keep LaTeX defaults, use option `defaultmathsizes\string'.}
2880 \fi

```

**\MTeverymathoff** [1.3i](#) 2016/01/06 Compatibility patch with `\url` from `url.sty` and `\url/\nolinkurl` from `hyperref.sty`.

[1.3j](#) 2016/01/15 renamed the macro from `\MTactivemathoff` to `\MTeverymathoff`, as it is not exclusively a matter of math active characters due to `\MTasynonlettersdonotbeymathxx`.

[1.3o](#) 2016/05/03 adds `\MTdonotfixfonts`. Operant with `LuaATEX` only.

[1.4](#) 2024/07/20 keeps the `\MTmathstandardletters` as a component of `\MTeverymathoff`. It was checked that `url` and `hyperref` do not change mathcodes of ascii letters prior to location where `\MTeverymathoff` gets executed, so nothing is overwritten, despite the new mode of action of `\MTmathstandardletters`.

[1.4](#) has `\MTmathstandarddigits` and inserts it into `\MTeverymathoff`.

```

2881 \newcommand*\MTeverymathoff {%
2882   \MTnormalasterisk
2883   \MTnormalprime
2884   \MTnonlettersdonotbeymathxx
2885   \MTeasynonlettersdonotbeymathxx
2886   \MTmathstandardletters
2887   \MTmathstandarddigits
2888   \MTdonotfixfonts
2889 }%
2890 \AtBeginDocument {%
2891   \@ifpackageloaded{hyperref}{%
2892     {\def\Hurl{\begingroup\MTeverymathoff\Url}}%
2893     {\@ifpackageloaded{url}{\DeclareUrlCommand\url{\MTeverymathoff}}{}}
2894 }%

```

`\MTeverymathdefault` [1.3j](#) 2016/01/15 Customizable command which gets executed by `\MTversion` except when switching to `normal/bold` if option `subdued`. The included `\MTicinmath` does `\MTmathactiveletters` which will also activate the math skips around letters.

The `\MTeverymathdefault` does not include `\MTmathoperatorsobeymathxx` as the latter does not correspond to something done during execution of `\the\everymath`.

Should I put `\let\newmcodes@\mst@\newmcodes@` here too ? No, it is not done at `everymath`.

During the loading, the (non subdued) package does `\MTactiveasterisk` (if option asterisk), `\MTprimedoesskip`, `\MTeasynonlettersobeymathxx` and `\MTmathactiveletters`. There is some code at begin document for decisions about italic corrections, this code does not emit again `\MTmathactiveletters`, hence a `\MTmathstandardletters` in the preamble is not overruled. Furthermore the at begin document code will not overrule user emitted `\MTnoicinmath` etc... commands in the preamble.

And user can employ `\MTnormalexists`, etc..., from inside the preamble, it will not be overruled (as it is delayed at begin document to after `mathastext` dealings).

[1.3o](#) 2016/05/03 adds `\MTfixfonts`. Operant with `LuaLaTeX` only.

`\MTmathactivedigits` of [1.4](#) is a no-op except under option `activedigits`.

```

2895 \newcommand*\MTeverymathdefault {%
2896   \MTactiveasterisk
2897   \MTprimedoesskip
2898   \MTeasynonlettersobeymathxx
2899   \MTicinmath
2900   \MTmathactivedigits
2901   \MTfixfonts
2902 }%

```

Things to do last "at `\begin{document}`" change here that mathematical activation of ascii letters is now not incorporated into the `\everymath` and `\everydisplay`.

```

2903 \ifmst@\everymath
2904   \AtBeginDocument{%

```

```

2905   \everymath\expandafter{\the\everymath
2906     \mst@the\mst@do@nonletters \let\mst@the\@gobble
2907       \mst@theeasy\mst@do@easynonletters \let\mst@theeasy\@gobble
2908   }%
2909   \everydisplay\expandafter{\the\everydisplay
2910     \mst@the\mst@do@nonletters \let\mst@the\@gobble
2911       \mst@theeasy\mst@do@easynonletters \let\mst@theeasy\@gobble
2912   }%
2913 }
2914 \fi

```

**1.3j:** moved here to be executed at begin document (and not from inside `\Mathastext@.`)  
The `\MTeverymathoff` does: `\MTnormalasterisk`, `\MTnormalprime`, `\MTnonlettersdonotbeymathxx`, `\MTeasynonlettersdonotbeymathxx`, `\MTmathstandardletters`.

**1.3m:** doing `\MTmathactiveletters` in subdued mode immediately after `\begin{document}` resulted in errors because `\mst@itcorr` had been left undefined. We thus add `\MTnoicinmath` to the subdued initialization.

Since **1.3n** there is `\MTresetnewmcodes` which needs `\mst@originalnewmcodes@`, itself defined at begin document. Thus we have wrapped the whole thing in `\AtEndOfPackage` (at **1.3u** whole code directly moved at end of package).

And **1.3p** adds here `\MTcustomizenewmcodes` which had been regrettably forgotten by **1.3n**.

**1.3t** adds some extras to handle correctly the minus sign and dotless i and j in subdued mode, even in case of usage with fontspec.

**1.3u** similarly lets math accents be correctly subdued.

**1.3v** adapts to `\hbar` and math accents now being robust with L<sup>A</sup>T<sub>E</sub>X 2019-10-01 or later.

**1.3w** pays attention to the fact that `\hbar` may well be a `\mathchar` and not a robust macro!

And no need to worry about `\hbar<space>` finally in revised code.

```

2915 \AtBeginDocument{%
2916   \MTcustomizenewmcodes
2917   \let\mst@original@\hbar\hbar
2918   \let\mst@original@\imath\imath
2919   \let\mst@original@\jmath\jmath
2920   \c@tfor\c@tempa:={grave}{acute}{check}{breve}{bar}%
2921     {\dot}{\ddot}{\mathring}{\hat}{\tilde}%
2922   \do
2923   {\expandafter\let\c@section\mst@original@\c@tempa\expandafter\endcsname
2924     \c@section\c@tempa\endcsname
2925   \expandafter\let\c@section\mst@original@\c@tempa\space\expandafter\endcsname
2926     \c@section\c@tempa\space\endcsname
2927 }%
2928 \ifmst@XeOrLua
2929   \edef\mst@subduedminus
2930     {\mst@Umathcodenum`\noexpand\-=\the\mst@Umathcodenum`-\relax}%
2931 \else
2932   \edef\mst@subduedminus{\mathcode`\noexpand\-=\the\mathcode`-\relax}%
2933 \fi
2934 \ifmst@subdued
2935   \MTeverymathoff
2936   \MTresetnewmcodes
2937   \MTnoicinmath

```

```

2938     \MTmathoperatorsdonotobeymathxx
2939     \let\inodot\imath
2940     \let\jnodot\jmath
2941     \mst@subduedminus
2942 \else
2943     \mst@nonsubduedhbar
1.3v needs \mst@nonsubduedmathaccents to get executed later (see code comments for
\mst@dothe@mathaccentsstuff).
2944     \mst@nonsubduedminus
1.3j: an earlier version of this code was earlier part of \Mathastext@. As we are now in
\AtBeginDocument we try to be careful not to overwrite \MTicinmath, \MTnoicinmath, \MTi-
calsoinmathxx, ... if issued by the user in the preamble, though. And we do not execute
\MTmathactiveletters, it is issued by the package at loading time in order to allow user to
cancel it if desired from inside the preamble.
2945     \ifx\mst@itcorr\@undefined
2946         \def\mst@itcorr{\ifnum\fam=\m@ne\@fi}%
2947         \@for\mst@tmp:=it,sl\do
2948             {\ifx\mst@tmp\mst@ltshape@normal\let\mst@itcorr\@empty\fi }%
2949     \fi
2950     \ifx\mst@ITcorr\@undefined
2951         \let\mst@ITcorr\mst@itcorr
2952         \ifmst@frenchmath
2953             \def\mst@ITcorr{\ifnum\fam=\m@ne\@fi}%
2954             \@for\mst@tmp:=it,sl\do
2955                 {\ifx\mst@tmp\mst@shape@normal\let\mst@ITcorr\@empty\fi }%
2956     \fi
2957     \fi
2958     \fi
2959 }%
2960 \AtEndOfPackage{\AtBeginDocument{\ifmst@subdued\else\mst@nonsubduedmathaccents\fi}}%

```

**subdued** 1.15: The subdued code was initiated in May 2011. I returned to `mathastext` on Sep 24, 2012, and decided to complete what I had started then, but in the mean time I had forgotten almost all of the little I knew about L<sup>A</sup>T<sub>E</sub>X macro programming.

The point was to extract the data about how are ‘letters’ and ‘operators’ in the normal and bold versions, through obtaining the math families of ‘a’ and ‘l’, respectively<sup>1</sup>. Due to the reassigments done for characters by `mathastext` I also had decided in 2011 that the OT1 encoding, if detected, should be replaced by T1

<sup>1</sup>but the `euler` package for example assigns the digits to the *letters* symbol font...

1.15d: Oct 13, 2012. The `\mathcode` thing has to be used with care under Unicode engines. Unfortunately the `\luatexUmathcode` macro is helpless as it is not possible to know if it will return a legacy mathcode or a Unicode mathcode. On the other hand the much saner `\XeTeXmathcodenum` always return a Unicode mathcode.

UPDATE for `mathastext` 1.3 (2013/09/02): since the release of lualatex as included in TL2013, `\luatexUmathcodenum` behaves as `\XeTeXmathcodenum` so `mathastext` 1.3 treats identically under both unicode engines the equal and minus signs (and the vertical bar).

1.15e: Oct 22, 2012. I add the necessary things to also subdue the `\mathbf`, `\mathit`, `\mathsf` and `\mathtt` macros (previous version only took care of the symbol alphabets `\mathnormal` and

\mathrm.) [update: 1.15f does that in a completely different and much simpler way] Notice that the package defines a \mathnormalbold macro, but it will not be subdued in the normal and bold math versions.

1.15f: Oct 23, 2012. The previous version of the code queried the math family of a, respectively 1, to guess and then extract the fonts to be reassigned to mtletterfont and mtoperatorfont (which is done at the end of this .sty file). The present code simply directly uses letters and operators (so mathastext could not subdue itself... if it was somehow cloned), but obtains indeed the corresponding font specifications in normal and bold in a cleaner manner. But it is so much shorter (and avoids the LuaL<sup>A</sup>T<sub>E</sub>X problem with \luatexUmathcode). Anyhow, for example the euler package puts the digits in the letters math family! so the previous method was also error prone. In fact there is no way to do this subdued mechanism on the basis of the legacy code of mathastext. The only way is to rewrite entirely the package to query all mathcodes of things it changes in order to be able to revert these changes (and one would have to do even more hacking for \mathversion{normal} and not only \MTversion{normal} to work).

1.15f: and also I take this opportunity to do the subdued math alphabets things in a much much easier way, see below.

1.3s 2018/08/21: I have half-forgotten the reasons for modifying the font encoding to current \encodingdefault, but at any rate this should not be done in a **fontspec** context, encoding default being (now) TU it is very unlikely modifying from TU or to TU from something else will do any good. I add workaround here for case of **fontspec** being detected via the \encodingdefault setting.

1.3t 2018/08/22: the 1.3s fix erroneously removed the OT1->T1 replacement in TU context.

1.3u: the whole thing will only get executed At Begin Document.

I realize extremely late (2023/12/28) I never said explicitly anywhere it seems in the code comments that the frenchmath option effect is *not* subdued: the uppercase Latin letters \mathcode's are not changed back to their defaults at start of a subdued document or when going to the subdued normal math version! Time to do so before the package enters resolutely dormant maintenance status soon... and I end up really forgetting anything and having wrong expectations on what is the behavior of the package.

```

2961 \ifmst@subdued
2962   \AtBeginDocument{%
2963     \def\mst@reserved#1\getanddefine@fonts\symletters#2#3\@nil{%
2964       \def\mst@normalmv@letter{\#2}}%
2965     \expandafter\mst@reserved\mv@normal\@nil
2966     \def\mst@reserved#1\getanddefine@fonts\symletters#2#3\@nil{%
2967       \def\mst@boldmv@letter{\#2}}%
2968     \expandafter\mst@reserved\mv@bold\@nil
2969     \def\mst@reserved#1\getanddefine@fonts\symoperators#2#3\@nil{%
2970       \def\mst@normalmv@operator{\#2}}%
2971     \expandafter\mst@reserved\mv@normal\@nil
2972     \def\mst@reserved#1\getanddefine@fonts\symoperators#2#3\@nil{%
2973       \def\mst@boldmv@operator{\#2}}%
2974     \expandafter\mst@reserved\mv@bold\@nil
2975     \edef\mst@tmp@enc{\mst@encoding@normal}%
2976     \def\mst@reserved#1/#2/#3/#4/{\gdef\mst@debut{\#1}\gdef\mst@reste{\#2/#3/#4}}%
2977     \begingroup\escapechar\m@ne
2978       \xdef\mst@funnyot{\expandafter\string\csname OT1\endcsname}%
2979       \expandafter\expandafter\expandafter
2980         \mst@reserved\expandafter\string\mst@normalmv@operator/%

```

```

2981 \endgroup
2982 \ifx\mst@debut\mst@funnyoti\ifx\mst@tmp@enc\mst@oti\def\mst@tmp@enc{T1}\fi\fi
2983 \edef\mst@normalmv@operator{\expandafter\noexpand\csname
2984     \if1\mst@OneifUniEnc
2985         \ifx\mst@debut\mst@funnyoti T1\else\mst@debut\fi
2986     \else
2987         \mst@tmp@enc
2988     \fi/\mst@reste\endcsname}%
2989 \edef\mst@tmp@enc{\mst@encoding@bold}%
2990 \begingroup\escapechar\m@ne
2991     \expandafter\expandafter\expandafter
2992         \mst@reserved\expandafter\string\mst@boldmv@operator/%
2993 \endgroup
2994 \ifx\mst@debut\mst@funnyoti\ifx\mst@tmp@enc\mst@oti\def\mst@tmp@enc{T1}\fi\fi
2995 \edef\mst@boldmv@operator{\expandafter\noexpand\csname
2996     \if1\mst@OneifUniEnc
2997         \ifx\mst@debut\mst@funnyoti T1\else\mst@debut\fi
2998     \else
2999         \mst@tmp@enc
3000     \fi/\mst@reste\endcsname}%
3001 \expandafter\SetSymbolFont@
3002     \expandafter\mv@normal\mst@normalmv@letter\symmtletterfont
3003 \expandafter\SetSymbolFont@
3004     \expandafter\mv@bold\mst@boldmv@letter\symmtletterfont
3005 \expandafter\SetSymbolFont@
3006     \expandafter\mv@normal\mst@normalmv@operator\symmtoperatorfont
3007 \expandafter\SetSymbolFont@
3008     \expandafter\mv@bold\mst@boldmv@operator\symmtoperatorfont
3009 \immediate\write\m@ne{}%
3010 \PackageInfo{mathastext}{...entering subdued mode...\MessageBreak ...done}%
3011 \immediate\write\m@ne{}%
3012 }%
3013 \fi

```

**Preamble-only...** “Only preamble” restrictions. I was way too much obedient back in 2011, particularly taking into account how much of a pain it has been and still is that things such as `\DeclareMathSymbol` or `\DeclareMathAccent` are preamble-only. But keeping this for time being, however not using `\OnLyPreamble` which breaks one’s heart when tracing to see how much place it takes, so we do it in one go.

```

3014 \expandafter \gdef \expandafter \c@preamblecmds \expandafter {\c@preamblecmds
3015 \do\MTitgreek
3016 \do\MTupgreek
3017 \do\MTitGreek
3018 \do\MTitGreek
3019 \do\Mathastextitgreek
3020 \do\Mathastextupgreek
3021 \do\MathastextitGreek
3022 \do\MathastextitGreek
3023 \do\MTgreekfont

```

```
3024 \do\Mathastextgreekfont
3025 \do\MTgreekupdefault
3026 \do\MTgreekitdefault
3027 \do\MTDeclareVersion
3028 \do\MathastextDeclareVersion
3029 \do\MTWillUse
3030 \do\MathastextWillUse
3031 \do\Mathastextwilluse
3032 \do\Mathastext
3033 \do\mathastext
3034 }
3035 \immediate\write\m@ne{}
3036 \PackageInfo{mathastext}{Loading is complete. \space You can now use \string\Mathastext
3037 \space to\MessageBreak
3038 modify the normal and bold math versions. \space
3039 Use it\MessageBreak
3040 with optional argument or use \string\MTDeclareVersion\space
3041 to\MessageBreak
3042 declare additional math versions\@gobble}
3043 \endinput
```