

# The CWEAVE processor

(Version 4.11 [T<sub>E</sub>X Live])

|  | Section             | Page |
|--|---------------------|------|
| <b>Introduction</b> .....                          | <a href="#">1</a>   | 1    |
| Data structures exclusive to CWEAVE .....          | <a href="#">20</a>  | 6    |
| Lexical scanning .....                             | <a href="#">35</a>  | 7    |
| Inputting the next token .....                     | <a href="#">43</a>  | 7    |
| <b>Phase one processing</b> .....                  | <a href="#">67</a>  | 10   |
| Low-level output routines .....                    | <a href="#">85</a>  | 11   |
| Routines that copy T <sub>E</sub> X material ..... | <a href="#">98</a>  | 12   |
| <b>Parsing</b> .....                               | <a href="#">105</a> | 14   |
| Implementing the productions .....                 | <a href="#">112</a> | 24   |
| Initializing the scraps .....                      | <a href="#">193</a> | 27   |
| Output of tokens .....                             | <a href="#">206</a> | 28   |
| <b>Phase two processing</b> .....                  | <a href="#">227</a> | 31   |
| <b>Phase three processing</b> .....                | <a href="#">247</a> | 34   |
| <b>Extensions to CWEB</b> .....                    | <a href="#">270</a> | 36   |
| Formatting alternatives .....                      | <a href="#">271</a> | 37   |
| Output file update .....                           | <a href="#">273</a> | 38   |
| Print “version” information .....                  | <a href="#">276</a> | 39   |
| <b>Index</b> .....                                 | <a href="#">278</a> | 40   |

Copyright © 1987, 1990, 1993, 2000 Silvio Levy and Donald E. Knuth

Permission is granted to make and distribute verbatim copies of this document provided that the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this document under the conditions for verbatim copying, provided that the entire resulting derived work is given a different name and distributed under the terms of a permission notice identical to this one.

**1\*** **Introduction.** This is the CWEAVE program by Silvio Levy and Donald E. Knuth, based on WEAVE by Knuth. We are thankful to Steve Avery, Nelson Beebe, Hans-Hermann Bode (to whom the original C++ adaptation is due), Klaus Guntermann, Norman Ramsey, Tomas Rokicki, Joachim Schmitter, Joachim Schrod, Lee Wittenberg, Saroj Mahapatra, Cesar Augusto Rorato Crusius, and others who have contributed improvements.

The “banner line” defined here should be changed whenever CWEAVE is modified.

```
#define banner "This is CWEAVE, Version 4.11"    ▷ will be extended by the TEX Live versionstring ◁
⟨ Include files 5* ⟩
⟨ Preprocessor definitions ⟩
⟨ Common code for CWEAVE and CTANGLE 3* ⟩
⟨ Typedef declarations 22 ⟩
⟨ Private variables 21 ⟩
⟨ Predeclaration of procedures 4* ⟩
```

**2\*** CWEAVE has a fairly straightforward outline. It operates in three phases: First it inputs the source file and stores cross-reference data, then it inputs the source once again and produces the T<sub>E</sub>X output file, finally it sorts and outputs the index.

Please read the documentation for COMMON, the set of routines common to CTANGLE and CWEAVE, before proceeding further.

```
int main(int ac,    ▷ argument count ◁
        char **av) ▷ argument values ◁
{
    argc ← ac; argv ← av; program ← cweave; ⟨ Set initial values 24 ⟩
    common_init(); ⟨ Start TEX output 89* ⟩
    if (show_banner) cb_show_banner();    ▷ print a “banner line” ◁
    ⟨ Store all the reserved words 34 ⟩
    phase_one();    ▷ read all the user’s text and store the cross-references ◁
    phase_two();    ▷ read all the text again and translate it to TEX form ◁
    phase_three();  ▷ output the cross-reference index ◁
    if (tracing ≡ fully ∧ ¬show_progress) new_line();
    return wrap_up();    ▷ and exit gracefully ◁
}
```

**3\*** The next few sections contain stuff from the file “common.w” that must be included in both “ctangle.w” and “cweave.w”. It appears in file “common.h”, which is also included in “common.w” to propagate possible changes from this COMMON interface consistently.

First comes general stuff:

```
⟨ Common code for CWEAVE and CTANGLE 3* ⟩ ≡
typedef uint8_t eight_bits;
typedef uint16_t sixteen_bits;
typedef enum {
    ctangle, cweave, ctwill
} cweb;
extern cweb program;    ▷ CTANGLE or CWEAVE or CTWILL? ◁
extern int phase;    ▷ which phase are we in? ◁
```

See also sections 6\*, 7\*, 8\*, 10\*, 11\*, 13\*, 15\*, 16\*, and 276\*.

This code is used in section 1\*.

**4\*** The procedure that gets everything rolling:

```
⟨Predeclaration of procedures 4*⟩ ≡
extern void common_init(void);
```

See also sections [9\\*](#), [12\\*](#), [14\\*](#), [25\\*](#), [40](#), [45](#), [65](#), [69](#), [71](#), [83](#), [86](#), [90](#), [95](#), [98](#), [115](#), [118](#), [122](#), [181](#), [189](#), [194](#), [201](#), [210](#), [214](#), [228](#), [235](#), [244](#), [248](#), [258](#), and [267](#).

This code is used in section [1\\*](#).

**5\*** You may have noticed that almost all "strings" in the CWEB sources are placed in the context of the ‘\_’ macro. This is just a shortcut for the ‘*gettext*’ function from the “GNU gettext utilities.” For systems that do not have this library installed, we wrap things for neutral behavior without internationalization. For backward compatibility with pre-ANSI compilers, we replace the “standard” header file ‘*stdbool.h*’ with the KPATHSEA interface ‘*simpletypes.h*’.

```
#define _(s) gettext(s)
⟨Include files 5*⟩ ≡
#include <ctype.h>    ▷ definition of isalpha, isdigit and so on ◁
#include <kpathsea/simpletypes.h>    ▷ boolean, true and false ◁
#include <stddef.h>    ▷ definition of ptrdiff_t ◁
#include <stdint.h>    ▷ definition of uint8_t and uint16_t ◁
#include <stdio.h>    ▷ definition of printf and friends ◁
#include <stdlib.h>    ▷ definition of getenv and exit ◁
#include <string.h>    ▷ definition of strlen, strcmp and so on ◁
#ifndef HAVE_GETTEXT
#define HAVE_GETTEXT 0
#endif
#if HAVE_GETTEXT
#include <libintl.h>
#else
#define gettext(a) a
#endif
```

See also section [19](#).

This code is used in section [1\\*](#).

**6\*** Code related to the character set:

```

#define and_and °4    ▷ '&&'; corresponds to MIT's ∧ ◁
#define lt_lt °20    ▷ '<<'; corresponds to MIT's ⊂ ◁
#define gt_gt °21    ▷ '>>'; corresponds to MIT's ⊃ ◁
#define plus_plus °13   ▷ '++'; corresponds to MIT's ↑ ◁
#define minus_minus °1   ▷ '--'; corresponds to MIT's ↓ ◁
#define minus_gt °31   ▷ '->'; corresponds to MIT's → ◁
#define non_eq °32    ▷ '!='; corresponds to MIT's ≠ ◁
#define lt_eq °34     ▷ '<='; corresponds to MIT's ≤ ◁
#define gt_eq °35     ▷ '>='; corresponds to MIT's ≥ ◁
#define eq_eq °36     ▷ '=='; corresponds to MIT's ≡ ◁
#define or_or °37     ▷ '||'; corresponds to MIT's ∨ ◁
#define dot_dot_dot °16  ▷ '...'; corresponds to MIT's ∅ ◁
#define colon_colon °6   ▷ '::~'; corresponds to MIT's ∈ ◁
#define period_ast °26  ▷ '.*'; corresponds to MIT's ⊗ ◁
#define minus_gt_ast °27 ▷ '->*'; corresponds to MIT's ↗ ◁

#define compress(c) if (loc++ ≤ limit) return c

```

⟨ Common code for CWEAVE and CTANGLE 3\* ⟩ +≡

```

extern char section_text[]; ▷ text being sought for ◁
extern char *section_text_end; ▷ end of section_text ◁
extern char *id_first; ▷ where the current identifier begins in the buffer ◁
extern char *id_loc; ▷ just after the current identifier in the buffer ◁

```

**7\*** Code related to input routines:

```

#define xisalpha(c) (isalpha((int)(c)) ∧ ((eight_bits)(c) < °200))
#define xisdigit(c) (isdigit((int)(c)) ∧ ((eight_bits)(c) < °200))
#define xisspace(c) (isspace((int)(c)) ∧ ((eight_bits)(c) < °200))
#define xislower(c) (islower((int)(c)) ∧ ((eight_bits)(c) < °200))
#define xisupper(c) (isupper((int)(c)) ∧ ((eight_bits)(c) < °200))
#define isxdigit(c) (isxdigit((int)(c)) ∧ ((eight_bits)(c) < °200))
#define isxalpha(c) ((c ≡ '_' ∨ (c ≡ '$')) ▷ non-alpha characters allowed in identifier ◁
#define ishigh(c) ((eight_bits)(c) > °177)

```

⟨ Common code for CWEAVE and CTANGLE 3\* ⟩ +≡

```

extern char buffer[]; ▷ where each line of input goes ◁
extern char *buffer_end; ▷ end of buffer ◁
extern char *loc; ▷ points to the next character to be read from the buffer ◁
extern char *limit; ▷ points to the last character in the buffer ◁

```

**8\*** Code related to file handling:

```

format line x    ▷ make line an unreserved word ◁
#define max_include_depth 10
    ▷ maximum number of source files open simultaneously, not counting the change file ◁
#define max_file_name_length 1024
#define cur_file file[include_depth]    ▷ current file ◁
#define cur_file_name file_name[include_depth]    ▷ current file name ◁
#define cur_line line[include_depth]    ▷ number of current line in current file ◁
#define web_file file[0]    ▷ main source file ◁
#define web_file_name file_name[0]    ▷ main source file name ◁
⟨Common code for CWEAVE and CTANGLE 3*⟩ +≡
extern int include_depth;    ▷ current level of nesting ◁
extern FILE *file[];    ▷ stack of non-change files ◁
extern FILE *change_file;    ▷ change file ◁
extern char file_name[][max_file_name_length];    ▷ stack of non-change file names ◁
extern char change_file_name[];    ▷ name of change file ◁
extern char *found_filename;    ▷ filename found by kpse_find_file ◁
extern int line[];    ▷ number of current line in the stacked files ◁
extern int change_line;    ▷ number of current line in change file ◁
extern int change_depth;    ▷ where @y originated during a change ◁
extern boolean input_has_ended;    ▷ if there is no more input ◁
extern boolean changing;    ▷ if the current line is from change_file ◁
extern boolean web_file_open;    ▷ if the web file is being read ◁

```

**9\*** ⟨Predeclaration of procedures **4\***⟩ +≡

```

extern boolean get_line(void);    ▷ inputs the next line ◁
extern void check_complete(void);    ▷ checks that all changes were picked up ◁
extern void reset_input(void);    ▷ initialize to read the web file and change file ◁

```

**10\*** Code related to section numbers:

```

⟨Common code for CWEAVE and CTANGLE 3*⟩ +≡
extern sixteen_bits section_count;    ▷ the current section number ◁
extern boolean changed_section[];    ▷ is the section changed? ◁
extern boolean change_pending;    ▷ is a decision about change still unclear? ◁
extern boolean print_where;    ▷ tells CTANGLE to print line and file info ◁

```

**11\*** Code related to identifier and section name storage:

```
#define length(c) (size_t)((c + 1)-byte_start - (c)-byte_start)  ▷ the length of a name ◁
#define print_id(c) term_write((c)-byte_start, length(c))  ▷ print identifier ◁
#define llink link  ▷ left link in binary search tree for section names ◁
#define rlink dummy.Rlink  ▷ right link in binary search tree for section names ◁
#define root name_dir→rlink  ▷ the root of the binary search tree for section names ◁
#define ilk dummy.ilk  ▷ used by CWEAVE only ◁
```

(Common code for CWEAVE and CTANGLE 3\*) +≡

```
typedef struct name_info {
  char *byte_start;  ▷ beginning of the name in byte_mem ◁
  struct name_info *link;
  union {
    struct name_info *Rlink;  ▷ right link in binary search tree for section names ◁
    eight_bits ilk;  ▷ used by identifiers in CWEAVE only ◁
  } dummy;
  void *equiv_or_xref;  ▷ info corresponding to names ◁
} name_info;  ▷ contains information about an identifier or section name ◁
typedef name_info *name_pointer;  ▷ pointer into array of name_infos ◁
typedef name_pointer *hash_pointer;
extern char byte_mem[];  ▷ characters of names ◁
extern char *byte_mem_end;  ▷ end of byte_mem ◁
extern char *byte_ptr;  ▷ first unused position in byte_mem ◁
extern name_info name_dir[];  ▷ information about names ◁
extern name_pointer name_dir_end;  ▷ end of name_dir ◁
extern name_pointer name_ptr;  ▷ first unused position in name_dir ◁
extern name_pointer hash[];  ▷ heads of hash lists ◁
extern hash_pointer hash_end;  ▷ end of hash ◁
extern hash_pointer hash_ptr;  ▷ index into hash-head array ◁
```

**12\*** (Predeclaration of procedures 4\*) +≡

```
extern name_pointer id_lookup(const char *, const char *, eight_bits);
  ▷ looks up a string in the identifier table ◁
extern name_pointer section_lookup(char *, char *, boolean);  ▷ finds section name ◁
extern void print_prefix_name(name_pointer);
extern void print_section_name(name_pointer);
extern void sprint_section_name(char *, name_pointer);
extern boolean names_match(name_pointer, const char *, size_t, eight_bits);
  ▷ two routines defined in ctangle.w and cweave.w ◁
extern void init_node(name_pointer);
```

**13\*** Code related to error handling:

```
#define spotless 0  ▷ history value for normal jobs ◁
#define harmless_message 1  ▷ history value when non-serious info was printed ◁
#define error_message 2  ▷ history value when an error was noted ◁
#define fatal_message 3  ▷ history value when we had to stop prematurely ◁
#define mark_harmless() if (history ≡ spotless) history ← harmless_message
#define mark_error() history ← error_message
#define confusion(s) fatal(_("!␣This␣can't␣happen:␣"), s)
```

(Common code for CWEAVE and CTANGLE 3\*) +≡

```
extern int history;  ▷ indicates how bad this run was ◁
```

## 14\* &lt;Predeclaration of procedures 4\*&gt; +≡

```

extern int wrap_up(void);    ▷ indicate history and exit ◁
extern void err_print(const char *);    ▷ print error message and context ◁
extern void fatal(const char *,const char *);    ▷ issue error message and die ◁
extern void overflow(const char *);    ▷ succumb because a table has overflowed ◁
extern void cb_show_banner(void);    ▷ copy banner back to common.w ◁
extern void print_stats(void);    ▷ defined in ctangle.w and cweave.w ◁

```

## 15\* Code related to command line arguments:

```

#define show_banner flags['b']    ▷ should the banner line be printed? ◁
#define show_progress flags['p']    ▷ should progress reports be printed? ◁
#define show_happiness flags['h']    ▷ should lack of errors be announced? ◁
#define show_stats flags['s']    ▷ should statistics be printed at end of run? ◁
#define make_xrefs flags['x']    ▷ should cross references be output? ◁
#define check_for_change flags['c']    ▷ check temporary output for changes ◁

```

## &lt;Common code for CWEAVE and CTANGLE 3\*&gt; +≡

```

extern int argc;    ▷ copy of ac parameter to main ◁
extern char **argv;    ▷ copy of av parameter to main ◁
extern char C_file_name[];    ▷ name of C_file ◁
extern char tex_file_name[];    ▷ name of tex_file ◁
extern char idx_file_name[];    ▷ name of idx_file ◁
extern char scn_file_name[];    ▷ name of scn_file ◁
extern char check_file_name[];    ▷ name of check_file ◁
extern boolean flags[];    ▷ an option for each 7-bit code ◁
extern const char *use_language;    ▷ prefix to cwebmac.tex in TEX output ◁

```

## 16\* Code related to output:

```

#define update_terminal() fflush(stdout)    ▷ empty the terminal output buffer ◁
#define new_line() putchar('\n')
#define term_write(a,b) fflush(stdout),fwrite(a,sizeof(char),b,stdout)

```

## &lt;Common code for CWEAVE and CTANGLE 3\*&gt; +≡

```

extern FILE *C_file;    ▷ where output of CTANGLE goes ◁
extern FILE *tex_file;    ▷ where output of CWEAVE goes ◁
extern FILE *idx_file;    ▷ where index from CWEAVE goes ◁
extern FILE *scn_file;    ▷ where list of sections from CWEAVE goes ◁
extern FILE *active_file;    ▷ currently active file for CWEAVE output ◁
extern FILE *check_file;    ▷ temporary output file ◁

```

17\* The following parameters are sufficient to handle T<sub>E</sub>X (converted to CWEB), so they should be sufficient for most applications of CWEB.

```

#define buf_size 1000    ▷ maximum length of input line, plus one ◁
#define longest_name 10000    ▷ file names, section names, and section texts shouldn't be longer than this ◁
#define long_buf_size (buf_size + longest_name)    ▷ for CWEAVE ◁
#define max_bytes 1000000
    ▷ the number of bytes in identifiers, index entries, and section names; must be less than 224 ◁
#define max_names 10239    ▷ number of identifiers, strings, section names; must be less than 10240 ◁
#define max_sections 4000    ▷ greater than the total number of sections ◁

```

## 18\* End of COMMON interface.

**23\*** `#define max_refs 65535` ▷ number of cross-references; must be less than 65536 ◁

⟨Private variables 21⟩ +≡

```
static xref_info xmem[max_refs];    ▷ contains cross-reference information ◁
static xref_pointer xmem_end ← xmem + max_refs - 1;
static xref_pointer xref_ptr;      ▷ the largest occupied position in xmem ◁
static sixteen_bits xref_switch, section_xref_switch;  ▷ either zero or def_flag ◁
```

**25\*** A new cross-reference for an identifier is formed by calling `new_xref`, which discards duplicate entries and ignores non-underlined references to one-letter identifiers or C's reserved words.

If the user has sent the `no_xref` flag (the `-x` option of the command line), it is unnecessary to keep track of cross-references for identifiers. If one were careful, one could probably make more changes around section ⟨Match a production at `pp`, or increase `pp` if there is no match 121⟩ to avoid a lot of identifier looking up.

```
#define append_xref(c)
    if (xref_ptr ≡ xmem_end) overflow(_("cross-reference"));
    else (++xref_ptr)-num ← c
#define no_xref ¬make_xrefs
#define is_tiny(p) length(p) ≡ 1
#define unindexed(a) ((a) < res_wd_end ∧ (a)-ilk ≥ custom)
    ▷ tells if uses of a name are to be indexed ◁
```

⟨Predeclaration of procedures 4\*⟩ +≡

```
static void new_xref(name_pointer);
static void new_section_xref(name_pointer);
static void set_file_flag(name_pointer);
```

**30\*** The first position of `tok_mem` that is unoccupied by replacement text is called `tok_ptr`, and the first unused location of `tok_start` is called `text_ptr`. Thus, we usually have `*text_ptr ≡ tok_ptr`.

`#define max_toks 65535` ▷ number of symbols in C texts being parsed; must be less than 65536 ◁  
`#define max_texts 10239` ▷ number of phrases in C texts being parsed; must be less than 10240 ◁

⟨Private variables 21⟩ +≡

```
static token tok_mem[max_toks];    ▷ tokens ◁
static token_pointer tok_mem_end ← tok_mem + max_toks - 1;  ▷ end of tok_mem ◁
static token_pointer tok_ptr;      ▷ first unused position in tok_mem ◁
static token_pointer max_tok_ptr;  ▷ largest value of tok_ptr ◁
static token_pointer tok_start[max_texts];  ▷ directory into tok_mem ◁
static text_pointer tok_start_end ← tok_start + max_texts - 1;  ▷ end of tok_start ◁
static text_pointer text_ptr;      ▷ first unused position in tok_start ◁
static text_pointer max_text_ptr;  ▷ largest value of text_ptr ◁
```



**57\*** C strings and character constants, delimited by double and single quotes, respectively, can contain newlines or instances of their own delimiters if they are protected by a backslash. We follow this convention, but do not allow the string to be longer than *longest\_name*.

⟨Get a string 57\*⟩ ≡

```

{ char delim ← c;    ▷ what started the string ◁
  id_first ← section_text + 1; id_loc ← section_text;
  if (delim ≡ '\ ' ∧ loc - 2 ≡ '@') {
    *++id_loc ← '@'; *++id_loc ← '@';
  }
  *++id_loc ← delim;
  if (delim ≡ 'L' ∨ delim ≡ 'u' ∨ delim ≡ 'U') ⟨Get a wide character constant 58⟩
  if (delim ≡ '<') delim ← '>';    ▷ for file names in #include lines ◁
  while (true) {
    if (loc ≥ limit) {
      if (*(limit - 1) ≠ '\\') {
        err_print(-("!String didn't end")); loc ← limit; break;
      }
      if (get_line() ≡ false) {
        err_print(-("!Input ended in middle of string")); loc ← buffer; break;
      }
    }
    if ((c ← *loc++) ≡ delim) {
      if (++id_loc ≤ section_text_end) *id_loc ← c;
      break;
    }
    if (c ≡ '\\') {
      if (loc ≥ limit) continue;
      else {
        if (++id_loc ≤ section_text_end) {
          *id_loc ← '\\'; c ← *loc++;
        }
      }
    }
    if (++id_loc ≤ section_text_end) *id_loc ← c;
  }
  if (id_loc ≥ section_text_end) {
    printf("%s", -("\n!String too long:")); term_write(section_text + 1, 25); printf("...");
    mark_error();
  }
  id_loc++; return string;
}

```

This code is used in sections 44 and 59\*.

**59\*** After an @ sign has been scanned, the next character tells us whether there is more work to do.

```

⟨Get control code and possible section name 59*⟩ ≡
  switch (ccode[c ← *loc++]) {
  case translit_code: err_print(_("!Use_@l_in_limbo_only")); continue;
  case underline: xref_switch ← def_flag; continue;
  case trace: tracing ← c - '0'; continue;
  case section_name: ⟨Scan the section name and make cur_section point to it 60⟩
  case verbatim: ⟨Scan a verbatim string 66*⟩
  case ord: ⟨Get a string 57*⟩
  case xref_roman: case xref_wildcard: case xref_typewriter: case noop: case TEX_string:
    skip_restricted(); /*fallthrough*/
  default: return ccode[c];
  }

```

This code is used in section 44.

```

62* ⟨Put section name into section_text 62*⟩ ≡
  while (true) {
  if (loc > limit ∧ get_line() ≡ false) {
    err_print(_("!Input_ended_in_section_name")); loc ← buffer + 1; break;
  }
  c ← *loc; ⟨If end of name or erroneous control code, break 63*⟩
  loc++;
  if (k < section_text_end) k++;
  if (xisspace(c)) {
    c ← ' ';
    if (*(k - 1) ≡ ' ') k--;
  }
  *k ← c;
}
if (k ≥ section_text_end) {
  printf("%s", _("!\n!Section_name_too_long:")); term_write(section_text + 1, 25); printf("...");
  mark_harmless();
}
if (*k ≡ ' ' ∧ k > section_text) k--;

```

This code is used in section 60.

```

63* ⟨If end of name or erroneous control code, break 63*⟩ ≡
  if (c ≡ '@') {
    c ← *(loc + 1);
    if (c ≡ '>') {
      loc += 2; break;
    }
  }
  if (ccode[c] ≡ new_section) {
    err_print(_("!Section_name_didn't_end")); break;
  }
  if (c ≠ '@') {
    err_print(_("!Control_codes_are_forbidden_in_section_name")); break;
  }
  *(++k) ← '@'; loc++;    ▷ now c ≡ *loc again ◁
}

```

This code is used in section 62\*.

**64\*** This function skips over a restricted context at relatively high speed.

```
static void skip_restricted(void)
{
    id_first ← loc; *(limit + 1) ← '@';
false_alarm:
    while (*loc ≠ '@') loc++;
    id_loc ← loc;
    if (loc++ > limit) {
        err_print(_("!Control_text_didn't_end")); loc ← limit;
    }
    else {
        if (*loc ≡ '@' ∧ loc ≤ limit) {
            loc++; goto false_alarm;
        }
        if (*loc++ ≠ '>') err_print(_("!Control_codes_are_forbidden_in_control_text"));
    }
}
```

**66\*** At the present point in the program we have  $*(loc - 1) \equiv verbatim$ ; we set *id\_first* to the beginning of the string itself, and *id\_loc* to its ending-plus-one location in the buffer. We also set *loc* to the position just after the ending delimiter.

```
⟨Scan a verbatim string 66*⟩ ≡
    id_first ← loc++; *(limit + 1) ← '@'; *(limit + 2) ← '>';
    while (*loc ≠ '@' ∨ *(loc + 1) ≠ '>') loc++;
    if (loc ≥ limit) err_print(_("!Verbatim_string_didn't_end"));
    id_loc ← loc; loc += 2; return verbatim;
```

This code is used in section 59\*.

**70\*** ⟨Store cross-reference data for the current section 70\*⟩ ≡

```
{
    if (++section_count ≡ max_sections) overflow(_("section_number"));
    changed_section[section_count] ← changing; ▷ it will become true if any line changes ◁
    if (*(loc - 1) ≡ '*' ∧ show_progress) {
        printf("%d", (int) section_count); update_terminal(); ▷ print a progress report ◁
    }
    ⟨Store cross-references in the TEX part of a section 74*⟩
    ⟨Store cross-references in the definition part of a section 77⟩
    ⟨Store cross-references in the C part of a section 80⟩
    if (changed_section[section_count]) change_exists ← true;
}
```

This code is used in section 68.

**74\*** In the T<sub>E</sub>X part of a section, cross-reference entries are made only for the identifiers in C texts enclosed in |...|, or for control texts enclosed in @^...@> or @. ...@> or @: ...@>.

⟨Store cross-references in the T<sub>E</sub>X part of a section 74\*⟩ ≡

```

while (true) {
  switch (next_control ← skip_TEX()) {
    case translit_code: err_print(_("!Use_@l_in_limbo_only")); continue;
    case underline: xref_switch ← def_flag; continue;
    case trace: tracing ← *(loc - 1) - '0'; continue;
    case '|': C_xref(section_name); break;
    case xref_roman: case xref_wildcard: case xref_typewriter: case noop: case section_name: loc -= 2;
      next_control ← get_next();    ▷ scan to @> ◁
      if (next_control ≥ xref_roman ∧ next_control ≤ xref_typewriter) {
        ⟨Replace '@@' by '@' 75⟩
        new_xref(id_lookup(id_first, id_loc, next_control - identifier));
      }
      break;
  }
  if (next_control ≥ format_code) break;
}

```

This code is used in section 70\*.

**79\*** A much simpler processing of format definitions occurs when the definition is found in limbo.

⟨Process simple format in limbo 79\*⟩ ≡

```

if (get_next() ≠ identifier) err_print(_("!Missing_left_identifier_of_@s"));
else {
  lhs ← id_lookup(id_first, id_loc, normal);
  if (get_next() ≠ identifier) err_print(_("!Missing_right_identifier_of_@s"));
  else {
    rhs ← id_lookup(id_first, id_loc, normal); lhs-ilk ← rhs-ilk;
  }
}

```

This code is used in section 41.

**82\*** The following recursive procedure walks through the tree of section names and prints out anomalies.

```

static void section_check(name_pointer p)    ▷ print anomalies in subtree p ◁
{
  if (p) {
    section_check(p-llink); cur_xref ← (xref_pointer) p-xref;
    if ((an_output ← (cur_xref-num ≡ file_flag)) ≡ true) cur_xref ← cur_xref-xlink;
    if (cur_xref-num < def_flag) {
      printf("%s", _("!Never_defined:◁")); print_section_name(p); putchar('>');
      mark_harmless();
    }
    while (cur_xref-num ≥ cite_flag) cur_xref ← cur_xref-xlink;
    if (cur_xref ≡ xmem ∧ ¬an_output) {
      printf("%s", _("!Never_used:◁")); print_section_name(p); putchar('>'); mark_harmless();
    }
    section_check(p-rlink);
  }
}

```

**89\*** In particular, the *finish\_line* procedure is called near the very beginning of phase two. We initialize the output variables in a slightly tricky way so that the first line of the output file will be dependent of the user language set by the '+1' option and its argument. If you call **CWEAVE** with '+1X' (or '-1X' as well), where 'X' is the (possibly empty) string of characters to the right of '1', 'X' will be prepended to 'cwebmac.tex', e.g., if you call **CWEAVE** with '+1deutsch', you will receive the line '\input deutschcwebmac'. Without this option the first line of the output file will be '\input cwebmac'.

```
<Start TEX output 89* > ≡
  out_ptr ← out_buf + 1; out_line ← 1; active_file ← tex_file; tex_puts("\\input_");
  tex_printf(use_language); tex_puts("cwebma"); *out_ptr ← 'c';
```

This code is used in section 2\*.

**94\*** We get to this section only in the unusual case that the entire output line consists of a string of backslashes followed by a string of nonblank non-backslashes. In such cases it is almost always safe to break the line by putting a '%' just before the last character.

```
<Print warning message, break the line, return 94* > ≡
{
  printf(_("\n!_Line_had_to_be_broken_(output_1._%d):\n"), out_line);
  term_write(out_buf + 1, out_ptr - out_buf - 1); new_line(); mark_harmless();
  flush_buffer(out_ptr - 1, true, true); return;
}
```

This code is used in section 93.

```
99* static void copy_limbo(void)
{
  while (true) {
    if (loc > limit ∧ (finish_line(), get_line() ≡ false)) return;
    *(limit + 1) ← '@';
    while (*loc ≠ '@') out(*(loc++));
    if (loc++ ≤ limit) {
      switch (ccode[(eight_bits)*loc++]) {
        case new_section: return;
        case translit_code: out_str("\\ATL"); break;
        case '@': out('@'); break;
        case noop: skip_restricted(); break;
        case format_code:
          if (get_next() ≡ identifier) get_next();
          if (loc ≥ limit) get_line(); ▷ avoid blank lines in output ◁
          break; ▷ the operands of @s are ignored on this pass ◁
        default: err_print(_("\!_Double_@_should_be_used_in_limbo")); out('@');
      }
    }
  }
}
```

**101\*** The *copy\_comment* function issues a warning if more braces are opened than closed, and in the case of a more serious error it supplies enough braces to keep T<sub>E</sub>X from complaining about unbalanced braces. Instead of copying the T<sub>E</sub>X material into the output buffer, this function copies it into the token memory (in phase two only). The abbreviation *app\_tok(t)* is used to append token *t* to the current token list, and it also makes sure that it is possible to append at least one further token without overflow.

```
#define app_tok(c)
    {
        if (tok_ptr + 2 > tok_mem_end) overflow(_("token"));
        *(tok_ptr++) ← c;
    }
static int copy_comment(    ▷ copies TEX code in comments ◁
    boolean is_long_comment,    ▷ is this a traditional C comment? ◁
    int bal)    ▷ brace balance ◁
{
    char c;    ▷ current character being copied ◁
    while (true) {
        if (loc > limit) {
            if (is_long_comment) {
                if (get_line() ≡ false) {
                    err_print(_("!_Input_ended_in_mid-comment")); loc ← buffer + 1; goto done;
                }
            }
            else {
                if (bal > 1) err_print(_("!_Missing_}_in_comment"));
                goto done;
            }
        }
        c ← *(loc++);
        if (c ≡ '|') return bal;
        if (is_long_comment) ◁ Check for end of comment 102* ◁
        if (phase ≡ 2) {
            if (ishigh(c)) app_tok(quoted_char);
            app_tok(c);
        }
        ◁ Copy special things when c ≡ '@', '\\\ ' 103* ◁
        if (c ≡ '{') bal++;
        else if (c ≡ '}') {
            if (bal > 1) bal--;
            else {
                err_print(_("!_Extra_}_in_comment"));
                if (phase ≡ 2) tok_ptr--;
            }
        }
    }
done: ◁ Clear bal and return 104 ◁
}
```

```

102* <Check for end of comment 102*> ≡
  if (c ≡ '*' ^ *loc ≡ '/') {
    loc++;
    if (bal > 1) err_print(_(!_Missing_}_in_comment"));
    goto done;
  }

```

This code is used in section 101\*.

```

103* <Copy special things when c ≡ '@', '\\', 103*> ≡
  if (c ≡ '@') {
    if (*(loc++) ≠ '@') {
      err_print(_(!_Illegal_use_of_@_in_comment")); loc -= 2;
      if (phase ≡ 2) *(tok_ptr - 1) ← '_';
      goto done;
    }
  }
  else {
    if (c ≡ '\\ ^ *loc ≠ '@') {
      if (phase ≡ 2) app_tok(*(loc++));
      else loc++;
    }
  }
}

```

This code is used in section 101\*.

**110\*** The raw input is converted into scraps according to the following table, which gives category codes followed by the translations. The symbol ‘\*\*’ stands for ‘&{identifier}’, i.e., the identifier itself treated as a reserved word. The right-hand column is the so-called *mathness*, which is explained further below.

An identifier *c* of length 1 is translated as `\|c` instead of as `\{c}`. An identifier CAPS in all caps is translated as `\.{CAPS}` instead of as `\{CAPS}`. An identifier that has become a reserved word via **typedef** is translated with `\&` replacing `\` and *raw\_int* replacing *exp*.

A string of length greater than 20 is broken into pieces of size at most 20 with discretionary breaks in between.

|                                      |  |       |
|--------------------------------------|--|-------|
| <code>!=</code>                      | <i>binop</i> : <code>\I</code>                                       | yes   |
| <code>&lt;=</code>                   | <i>binop</i> : <code>\Z</code>                                       | yes   |
| <code>&gt;=</code>                   | <i>binop</i> : <code>\G</code>                                       | yes   |
| <code>==</code>                      | <i>binop</i> : <code>\E</code>                                       | yes   |
| <code>&amp;&amp;</code>              | <i>binop</i> : <code>\W</code>                                       | yes   |
| <code>  </code>                      | <i>binop</i> : <code>\V</code>                                       | yes   |
| <code>++</code>                      | <i>unop</i> : <code>\PP</code>                                       | yes   |
| <code>--</code>                      | <i>unop</i> : <code>\MM</code>                                       | yes   |
| <code>-&gt;</code>                   | <i>binop</i> : <code>\MG</code>                                      | yes   |
| <code>&gt;&gt;</code>                | <i>binop</i> : <code>\GG</code>                                      | yes   |
| <code>&lt;&lt;</code>                | <i>binop</i> : <code>\LL</code>                                      | yes   |
| <code>::</code>                      | <i>colcol</i> : <code>\DC</code>                                     | maybe |
| <code>.*</code>                      | <i>binop</i> : <code>\PA</code>                                      | yes   |
| <code>-&gt;*</code>                  | <i>binop</i> : <code>\MGA</code>                                     | yes   |
| <code>...</code>                     | <i>raw_int</i> : <code>\, \ldots\,</code>                            | yes   |
| <code>"string"</code>                | <i>exp</i> : <code>\.{string with special characters quoted}</code>  | maybe |
| <code>@=string@&gt;</code>           | <i>exp</i> : <code>\vb{string with special characters quoted}</code> | maybe |
| <code>@'7'</code>                    | <i>exp</i> : <code>\.{@'7'}</code>                                   | maybe |
| <code>077</code> or <code>\77</code> | <i>exp</i> : <code>\T{\^77}</code>                                   | maybe |
| <code>0x7f</code>                    | <i>exp</i> : <code>\T{\^7f}</code>                                   | maybe |
| <code>0b10111</code>                 | <i>exp</i> : <code>\T{\10111}</code>                                 | maybe |
| <code>77</code>                      | <i>exp</i> : <code>\T{77}</code>                                     | maybe |
| <code>77L</code>                     | <i>exp</i> : <code>\T{77\$L}</code>                                  | maybe |
| <code>0.1E5</code>                   | <i>exp</i> : <code>\T{0.1\_5}</code>                                 | maybe |
| <code>0x10p3</code>                  | <i>exp</i> : <code>\T{\^10}\p{3}</code>                              | maybe |
| <code>1'000'000</code>               | <i>exp</i> : <code>\T{1\_000\_000}</code>                            | maybe |
| <code>+</code>                       | <i>ubinop</i> : <code>+</code>                                       | yes   |
| <code>-</code>                       | <i>ubinop</i> : <code>-</code>                                       | yes   |
| <code>*</code>                       | <i>raw_ubin</i> : <code>*</code>                                     | yes   |
| <code>/</code>                       | <i>binop</i> : <code>/</code>  | yes   |
| <code>&lt;</code>                    | <i>prelangle</i> : <code>\langle</code>                              | yes   |
| <code>=</code>                       | <i>binop</i> : <code>\K</code>                                       | yes   |
| <code>&gt;</code>                    | <i>prerangle</i> : <code>\rangle</code>                              | yes   |
| <code>.</code>                       | <i>binop</i> : <code>.</code>  | yes   |
| <code> </code>                       | <i>binop</i> : <code>\OR</code>                                      | yes   |
| <code>^</code>                       | <i>binop</i> : <code>\XOR</code>                                     | yes   |
| <code>%</code>                       | <i>binop</i> : <code>\MOD</code>                                     | yes   |
| <code>?</code>                       | <i>question</i> : <code>\?</code>                                    | yes   |
| <code>!</code>                       | <i>unop</i> : <code>\R</code>  | yes   |
| <code>~</code>                       | <i>unop</i> : <code>\CM</code>                                       | yes   |
| <code>&amp;</code>                   | <i>raw_ubin</i> : <code>\AND</code>                                  | yes   |
| <code>(</code>                       | <i>lpar</i> : <code>(</code>   | maybe |
| <code>)</code>                       | <i>rpar</i> : <code>)</code>   | maybe |
| <code>[</code>                       | <i>lbrack</i> : <code>[</code>                                       | maybe |



|                           |  |       |
|---------------------------|--|-------|
| ]                         | <i>rbrack:</i> ]   | maybe |
| {                         | <i>lbrace:</i> {   | yes   |
| }                         | <i>lbrace:</i> }   | yes   |
| ,                         | <i>comma:</i> ,  | yes   |
| ;                         | <i>semi:</i> ;   | maybe |
| :                         | <i>colon:</i> :  | no    |
| # (within line)           | <i>ubinop:</i> \#  | yes   |
| # (at beginning)          | <i>lproc:</i> force <i>preproc_line</i> \#                         | no    |
| end of # line             | <i>rproc:</i> force  | no    |
| identifier                | <i>exp:</i> \{\identifier with underlines and dollar signs quoted} | maybe |
| <code>alignas</code>      | <i>alignas_like:</i> **  | maybe |
| <code>alignof</code>      | <i>sizeof_like:</i> **   | maybe |
| <code>and</code>          | <i>alfop:</i> **   | yes   |
| <code>and_eq</code>       | <i>alfop:</i> **   | yes   |
| <code>asm</code>          | <i>sizeof_like:</i> **   | maybe |
| <code>auto</code>         | <i>int_like:</i> **  | maybe |
| <code>bitand</code>       | <i>alfop:</i> **   | yes   |
| <code>bitor</code>        | <i>alfop:</i> **   | yes   |
| <code>bool</code>         | <i>raw_int:</i> **   | maybe |
| <code>break</code>        | <i>case_like:</i> **   | maybe |
| <code>case</code>         | <i>case_like:</i> **   | maybe |
| <code>catch</code>        | <i>catch_like:</i> **  | maybe |
| <code>char</code>         | <i>raw_int:</i> **   | maybe |
| <code>char8_t</code>      | <i>raw_int:</i> **   | maybe |
| <code>char16_t</code>     | <i>raw_int:</i> **   | maybe |
| <code>char32_t</code>     | <i>raw_int:</i> **   | maybe |
| <code>class</code>        | <i>struct_like:</i> **   | maybe |
| <code>clock_t</code>      | <i>raw_int:</i> **   | maybe |
| <code>compl</code>        | <i>alfop:</i> **   | yes   |
| <code>complex</code>      | <i>int_like:</i> **  | yes   |
| <code>concept</code>      | <i>int_like:</i> **  | maybe |
| <code>const</code>        | <i>const_like:</i> **  | maybe |
| <code>consteval</code>    | <i>const_like:</i> **  | maybe |
| <code>constexpr</code>    | <i>const_like:</i> **  | maybe |
| <code>constinit</code>    | <i>const_like:</i> **  | maybe |
| <code>const_cast</code>   | <i>raw_int:</i> **   | maybe |
| <code>continue</code>     | <i>case_like:</i> **   | maybe |
| <code>co_await</code>     | <i>case_like:</i> **   | maybe |
| <code>co_return</code>    | <i>case_like:</i> **   | maybe |
| <code>co_yield</code>     | <i>case_like:</i> **   | maybe |
| <code>decltype</code>     | <i>sizeof_like:</i> **   | maybe |
| <code>default</code>      | <i>default_like:</i> **  | maybe |
| <code>define</code>       | <i>define_like:</i> **   | maybe |
| <code>defined</code>      | <i>sizeof_like:</i> **   | maybe |
| <code>delete</code>       | <i>delete_like:</i> **   | maybe |
| <code>div_t</code>        | <i>raw_int:</i> **   | maybe |
| <code>do</code>           | <i>do_like:</i> **   | maybe |
| <code>double</code>       | <i>raw_int:</i> **   | maybe |
| <code>dynamic_cast</code> | <i>raw_int:</i> **   | maybe |
| <code>elif</code>         | <i>if_like:</i> **   | maybe |
| <code>else</code>         | <i>else_like:</i> **   | maybe |
| <code>endif</code>        | <i>if_like:</i> **   | maybe |

|                  |  |       |
|------------------|--|-------|
| enum             | <i>struct_like</i> : **                        | maybe |
| error            | <i>if_like</i> : **                            | maybe |
| explicit         | <i>int_like</i> : **                           | maybe |
| export           | <i>int_like</i> : **                           | maybe |
| extern           | <i>int_like</i> : **                           | maybe |
| FILE             | <i>raw_int</i> : **                            | maybe |
| false            | <i>normal</i> : **                             | maybe |
| float            | <i>raw_int</i> : **                            | maybe |
| for              | <i>for_like</i> : **                           | maybe |
| fpos_t           | <i>raw_int</i> : **                            | maybe |
| friend           | <i>int_like</i> : **                           | maybe |
| goto             | <i>case_like</i> : **                          | maybe |
| if               | <i>if_like</i> : **                            | maybe |
| ifdef            | <i>if_like</i> : **                            | maybe |
| ifndef           | <i>if_like</i> : **                            | maybe |
| imaginary        | <i>int_like</i> : **                           | maybe |
| include          | <i>if_like</i> : **                            | maybe |
| inline           | <i>int_like</i> : **                           | maybe |
| int              | <i>raw_int</i> : **                            | maybe |
| jmp_buf          | <i>raw_int</i> : **                            | maybe |
| ldiv_t           | <i>raw_int</i> : **                            | maybe |
| line             | <i>if_like</i> : **                            | maybe |
| long             | <i>raw_int</i> : **                            | maybe |
| make_pair        | <i>ftemplate</i> : <code>\\{make\_pair}</code> | maybe |
| mutable          | <i>int_like</i> : **                           | maybe |
| namespace        | <i>struct_like</i> : **                        | maybe |
| new              | <i>new_like</i> : **                           | maybe |
| noexcept         | <i>attr</i> : **                               | maybe |
| not              | <i>alfop</i> : **                              | yes   |
| not_eq           | <i>alfop</i> : **                              | yes   |
| NULL             | <i>exp</i> : <code>\NULL</code>                | yes   |
| nullptr          | <i>exp</i> : <code>\NULL</code>                | yes   |
| offsetof         | <i>raw_int</i> : **                            | maybe |
| operator         | <i>operator_like</i> : **                      | maybe |
| or               | <i>alfop</i> : **                              | yes   |
| or_eq            | <i>alfop</i> : **                              | yes   |
| pragma           | <i>if_like</i> : **                            | maybe |
| private          | <i>public_like</i> : **                        | maybe |
| protected        | <i>public_like</i> : **                        | maybe |
| ptrdiff_t        | <i>raw_int</i> : **                            | maybe |
| public           | <i>public_like</i> : **                        | maybe |
| register         | <i>int_like</i> : **                           | maybe |
| reinterpret_cast | <i>raw_int</i> : **                            | maybe |
| requires         | <i>int_like</i> : **                           | maybe |
| restrict         | <i>int_like</i> : **                           | maybe |
| return           | <i>case_like</i> : **                          | maybe |
| short            | <i>raw_int</i> : **                            | maybe |
| sig_atomic_t     | <i>raw_int</i> : **                            | maybe |
| signed           | <i>raw_int</i> : **                            | maybe |
| size_t           | <i>raw_int</i> : **                            | maybe |
| sizeof           | <i>sizeof_like</i> : **                        | maybe |
| static           | <i>int_like</i> : **                           | maybe |

|                                       |  |       |
|---------------------------------------|--|-------|
| <code>static_assert</code>            | <code>sizeof_like: **</code>   | maybe |
| <code>static_cast</code>              | <code>raw_int: **</code>   | maybe |
| <code>struct</code>                   | <code>struct_like: **</code>   | maybe |
| <code>switch</code>                   | <code>for_like: **</code>  | maybe |
| <code>template</code>                 | <code>template_like: **</code>   | maybe |
| <code>TeX</code>                      | <code>exp: \TeX</code>   | yes   |
| <code>this</code>                     | <code>exp: \this</code>  | yes   |
| <code>thread_local</code>             | <code>raw_int: **</code>   | maybe |
| <code>throw</code>                    | <code>case_like: **</code>   | maybe |
| <code>time_t</code>                   | <code>raw_int: **</code>   | maybe |
| <code>try</code>                      | <code>else_like: **</code>   | maybe |
| <code>typedef</code>                  | <code>typedef_like: **</code>  | maybe |
| <code>typeid</code>                   | <code>sizeof_like: **</code>   | maybe |
| <code>typename</code>                 | <code>struct_like: **</code>   | maybe |
| <code>undef</code>                    | <code>if_like: **</code>   | maybe |
| <code>union</code>                    | <code>struct_like: **</code>   | maybe |
| <code>unsigned</code>                 | <code>raw_int: **</code>   | maybe |
| <code>using</code>                    | <code>using_like: **</code>  | maybe |
| <code>va_dcl</code>                   | <code>decl: **</code>  | maybe |
| <code>va_list</code>                  | <code>raw_int: **</code>   | maybe |
| <code>virtual</code>                  | <code>int_like: **</code>  | maybe |
| <code>void</code>                     | <code>raw_int: **</code>   | maybe |
| <code>volatile</code>                 | <code>const_like: **</code>  | maybe |
| <code>wchar_t</code>                  | <code>raw_int: **</code>   | maybe |
| <code>while</code>                    | <code>for_like: **</code>  | maybe |
| <code>xor</code>                      | <code>alfop: **</code>   | yes   |
| <code>xor_eq</code>                   | <code>alfop: **</code>   | yes   |
| <code>@,</code>                       | <code>insert: \,</code>  | maybe |
| <code>@ </code>                       | <code>insert: opt 0</code>   | maybe |
| <code>@/</code>                       | <code>insert: force</code>   | no    |
| <code>@#</code>                       | <code>insert: big_force</code>   | no    |
| <code>@+</code>                       | <code>insert: big_cancel {} break_space {} big_cancel</code>                         | no    |
| <code>@;</code>                       | <code>semi:</code>   | maybe |
| <code>@[</code>                       | <code>begin_arg:</code>  | maybe |
| <code>@]</code>                       | <code>end_arg:</code>  | maybe |
| <code>@&amp;</code>                   | <code>insert: \J</code>  | maybe |
| <code>@h</code>                       | <code>insert: force \ATH force</code>  | no    |
| <code>@&lt; section name @&gt;</code> | <code>section_scrap: \Xn: translated section name\X</code>                           | maybe |
| <code>@( section name @)</code>       | <code>section_scrap: \Xn:\.{section name with special characters quoted\,}\X*</code> | maybe |
| <code>/* comment */</code>            | <code>insert: cancel \C{translated comment} force</code>                             | no    |
| <code>// comment</code>               | <code>insert: cancel \SHC{translated comment} force</code>                           | no    |

The construction `@t stuff @>` contributes `\hbox{stuff}` to the following scrap.

---

\* The `\,` (thin space) is omitted in “*inner* T<sub>E</sub>X mode.”

**111.\*** Here is a table of all the productions. Each production that combines two or more consecutive scraps implicitly inserts a \$ where necessary, that is, between scraps whose abutting boundaries have different *mathness*. In this way we never get double \$\$.

A translation is provided when the resulting scrap is not merely a juxtaposition of the scraps it comes from. An asterisk\* next to a scrap means that its first identifier gets an underlined entry in the index, via the function *make\_underlined*. Two asterisks\*\* means that both *make\_underlined* and *make\_reserved* are called; that is, the identifier's ilk becomes *raw\_int*. A dagger † before the production number refers to the notes at the end of this section, which deal with various exceptional cases.

We use *in*, *out*, *back*, *bsp*, and *din* as shorthands for *indent*, *outdent*, *backup*, *break\_space*, and *dindent*, respectively.

| LHS  | → RHS  | Translation  | Example  |
|--|--|--|--|
| 0 $\left\{ \begin{array}{l} \textit{any} \\ \textit{any any} \\ \textit{any any any} \end{array} \right\} \textit{insert}$   | → $\left\{ \begin{array}{l} \textit{any} \\ \textit{any any} \\ \textit{any any any} \end{array} \right\}$                 |  | stmt; ▷ comment ◁  |
| †1 $\textit{exp} \left\{ \begin{array}{l} \textit{lbrace} \\ \textit{int\_like} \\ \textit{decl} \end{array} \right\}$   | → $\textit{fn\_decl} \left\{ \begin{array}{l} \textit{lbrace} \\ \textit{int\_like} \\ \textit{decl} \end{array} \right\}$ | $F = \textit{din} E^*$   | $\textit{main}() \{$<br>$\textit{main}(ac, av) \mathbf{int} ac;$ |
| 2 $\textit{exp unop}$  | → $\textit{exp}$   |  | $x++$  |
| 3 $\textit{exp} \left\{ \begin{array}{l} \textit{binop} \\ \textit{ubinop} \end{array} \right\} \textit{exp}$  | → $\textit{exp}$   |  | $x/y$<br>$x + y$   |
| 4 $\textit{exp comma exp}$   | → $\textit{exp}$   | $E_1 C \textit{opt} 9 E_2$   | $f(x, y)$  |
| 5 $\textit{exp} \left\{ \begin{array}{l} \textit{lpar rpar} \\ \textit{cast} \end{array} \right\} \textit{colon}$  | → $\textit{exp} \left\{ \begin{array}{l} \textit{lpar rpar} \\ \textit{cast} \end{array} \right\} \textit{base}$           |  | $\mathbf{C}() :$<br>$\mathbf{C}(\mathbf{int} i) :$               |
| 6 $\textit{exp semi}$  | → $\textit{stmt}$  |  | $x = 0;$   |
| 7 $\textit{exp colon}$   | → $\textit{tag}$   | $E^* C$  | $\textit{found}:$  |
| 8 $\textit{exp rbrace}$  | → $\textit{stmt rbrace}$   |  | end of <b>enum</b> list  |
| 9 $\textit{exp} \left\{ \begin{array}{l} \textit{lpar rpar} \\ \textit{cast} \end{array} \right\} \left\{ \begin{array}{l} \textit{const\_like} \\ \textit{case\_like} \end{array} \right\}$ | → $\textit{exp} \left\{ \begin{array}{l} \textit{lpar rpar} \\ \textit{cast} \end{array} \right\}$                         | $\left\{ \begin{array}{l} R = R \sqcup C \\ C_1 = C_1 \sqcup C_2 \end{array} \right\}$ | $f() \mathbf{const}$<br>$f(\mathbf{int}) \mathbf{throw}$         |
| 10 $\textit{exp} \left\{ \begin{array}{l} \textit{exp} \\ \textit{cast} \end{array} \right\}$  | → $\textit{exp}$   |  | $\textit{time}()$  |
| 11 $\textit{lpar} \left\{ \begin{array}{l} \textit{exp} \\ \textit{ubinop} \end{array} \right\} \textit{rpar}$   | → $\textit{exp}$   |  | $(x)$<br>$(*)$   |
| 12 $\textit{lpar rpar}$  | → $\textit{exp}$   | $L \setminus, R$   | functions, declarations  |
| 13 $\textit{lpar} \left\{ \begin{array}{l} \textit{decl\_head} \\ \textit{int\_like} \\ \textit{cast} \end{array} \right\} \textit{rpar}$  | → $\textit{cast}$  |  | $(\mathbf{char} *)$  |
| 14 $\textit{lpar} \left\{ \begin{array}{l} \textit{decl\_head} \\ \textit{int\_like} \\ \textit{exp} \end{array} \right\} \textit{comma}$  | → $\textit{lpar}$  | $L \left\{ \begin{array}{l} D \\ I \\ E \end{array} \right\} C \textit{opt} 9$         | $(\mathbf{int},$   |
| 15 $\textit{lpar} \left\{ \begin{array}{l} \textit{stmt} \\ \textit{decl} \end{array} \right\}$  | → $\textit{lpar}$  | $\left\{ \begin{array}{l} LS \sqcup \\ LD \sqcup \end{array} \right\}$                 | $(k = 5;$<br>$(\mathbf{int} k = 5;$                              |
| 16 $\textit{unop} \left\{ \begin{array}{l} \textit{exp} \\ \textit{int\_like} \end{array} \right\}$  | → $\textit{exp}$   |  | $\neg x$<br>$\sim C$   |
| 17 $\textit{ubinop cast rpar}$   | → $\textit{cast rpar}$   | $C = \{U\} C$  | $*\mathbf{CPtr}$   |
| 18 $\textit{ubinop} \left\{ \begin{array}{l} \textit{exp} \\ \textit{int\_like} \end{array} \right\}$  | → $\left\{ \begin{array}{l} \textit{exp} \\ \textit{int\_like} \end{array} \right\}$                                       | $\{U\} \left\{ \begin{array}{l} E \\ I \end{array} \right\}$                           | $*x$<br>$*\mathbf{CPtr}$   |
| 19 $\textit{ubinop binop}$   | → $\textit{binop}$   | $\textit{math\_rel} U \{B\}$   | $*=$   |
| 20 $\textit{binop binop}$  | → $\textit{binop}$   | $\textit{math\_rel} \{B_1\} \{B_2\}$   | $\gg=$   |

|     |   |  |  |  |
|-----|---|--|--|--|
| 21  | $cast \left\{ \begin{array}{l} lpar \\ exp \end{array} \right\}$  | $\rightarrow \left\{ \begin{array}{l} lpar \\ exp \end{array} \right\}$                          | $\left\{ \begin{array}{l} CL \\ C \setminus, E \end{array} \right\}$               | $(double)(x + 2)$<br>$(double) x$                  |
| 22  | $cast\ semi$  | $\rightarrow exp\ semi$  |  | $(int);$   |
| 23  | $sizeof\_like\ cast$  | $\rightarrow exp$  |  | $sizeof (double)$                                  |
| 24  | $sizeof\_like\ exp$   | $\rightarrow exp$  | $S \sqcup E$   | $sizeof\ x$  |
| 25  | $int\_like \left\{ \begin{array}{l} int\_like \\ struct\_like \end{array} \right\}$   | $\rightarrow \left\{ \begin{array}{l} int\_like \\ struct\_like \end{array} \right\}$            | $I \sqcup \left\{ \begin{array}{l} I \\ S \end{array} \right\}$                    | <b>extern char</b>                                 |
| 26  | $int\_like\ exp \left\{ \begin{array}{l} raw\_int \\ struct\_like \end{array} \right\}$   | $\rightarrow int\_like \left\{ \begin{array}{l} raw\_int \\ struct\_like \end{array} \right\}$   |  | <b>extern "Ada" int</b>                            |
| 27  | $int\_like \left\{ \begin{array}{l} exp \\ ubinop \\ colon \end{array} \right\}$  | $\rightarrow decl\_head \left\{ \begin{array}{l} exp \\ ubinop \\ colon \end{array} \right\}$    | $D = I \sqcup$   | <b>int x</b><br><b>int *x</b><br><b>unsigned :</b> |
| 28  | $int\_like \left\{ \begin{array}{l} semi \\ binop \end{array} \right\}$   | $\rightarrow decl\_head \left\{ \begin{array}{l} semi \\ binop \end{array} \right\}$             |  | <b>int x;</b><br><b>int f(int = 4)</b>             |
| 29  | $public\_like\ colon$   | $\rightarrow tag$  |  | <b>private:</b>                                    |
| 30  | $public\_like$  | $\rightarrow int\_like$  |  | <b>private</b>                                     |
| 31  | $colcol \left\{ \begin{array}{l} exp \\ int\_like \end{array} \right\}$   | $\rightarrow \left\{ \begin{array}{l} exp \\ int\_like \end{array} \right\}$                     | $qualifier\ C \left\{ \begin{array}{l} E \\ I \end{array} \right\}$                | <b>C :: x</b>                                      |
| 32  | $colcol\ colcol$  | $\rightarrow colcol$   |  | <b>C :: B ::</b>                                   |
| 33  | $decl\_head\ comma$   | $\rightarrow decl\_head$   | $DC\ opt9$   | <b>int x,</b>                                      |
| 34  | $decl\_head\ ubinop$  | $\rightarrow decl\_head$   | $D \{ U \}$  | <b>int *</b>                                       |
| †35 | $decl\_head\ exp$   | $\rightarrow decl\_head$   | $DE^*$   | <b>int x</b>                                       |
| 36  | $decl\_head \left\{ \begin{array}{l} binop \\ colon \end{array} \right\} exp \left\{ \begin{array}{l} comma \\ semi \\ rpar \end{array} \right\}$ | $\rightarrow decl\_head \left\{ \begin{array}{l} comma \\ semi \\ rpar \end{array} \right\}$     | $D = D \left\{ \begin{array}{l} B \\ C \end{array} \right\} E$                     | <b>int f(int x = 2)</b><br><b>int b : 1</b>        |
| 37  | $decl\_head\ cast$  | $\rightarrow decl\_head$   |  | <b>int f(int)</b>                                  |
| †38 | $decl\_head \left\{ \begin{array}{l} int\_like \\ lbrace \\ decl \end{array} \right\}$  | $\rightarrow fn\_decl \left\{ \begin{array}{l} int\_like \\ lbrace \\ decl \end{array} \right\}$ | $F = din\ D$   | <b>long time() {</b>                               |
| 39  | $decl\_head\ semi$  | $\rightarrow decl$   |  | <b>int n;</b>                                      |
| 40  | $decl\ decl$  | $\rightarrow decl$   | $D_1\ force\ D_2$  | <b>int n; double x;</b>                            |
| †41 | $decl \left\{ \begin{array}{l} stmt \\ function \end{array} \right\}$   | $\rightarrow \left\{ \begin{array}{l} stmt \\ function \end{array} \right\}$                     | $D\ big\_force \left\{ \begin{array}{l} S \\ F \end{array} \right\}$               | <b>extern n; main() { }</b>                        |
| 42  | $base \left\{ \begin{array}{l} int\_like \\ exp \end{array} \right\} comma$   | $\rightarrow base$   | $B \sqcup \left\{ \begin{array}{l} I \\ E \end{array} \right\} C\ opt9$            | <b>: public A,</b><br><b>: i(5),</b>               |
| 43  | $base \left\{ \begin{array}{l} int\_like \\ exp \end{array} \right\} lbrace$  | $\rightarrow lbrace$   | $B \sqcup \left\{ \begin{array}{l} I \\ E \end{array} \right\} \sqcup L$           | <b>D : public A {</b>                              |
| 44  | $struct\_like\ lbrace$  | $\rightarrow struct\_head$   | $S \sqcup L$   | <b>struct {</b>                                    |
| 45  | $struct\_like \left\{ \begin{array}{l} exp \\ int\_like \end{array} \right\} semi$  | $\rightarrow decl\_head\ semi$   | $S \sqcup \left\{ \begin{array}{l} E^{**} \\ I^{**} \end{array} \right\}$          | <b>struct forward;</b>                             |
| 46  | $struct\_like \left\{ \begin{array}{l} exp \\ int\_like \end{array} \right\} lbrace$  | $\rightarrow struct\_head$   | $S \sqcup \left\{ \begin{array}{l} E^{**} \\ I^{**} \end{array} \right\} \sqcup L$ | <b>struct name_info {</b>                          |
| 47  | $struct\_like \left\{ \begin{array}{l} exp \\ int\_like \end{array} \right\} colon$   | $\rightarrow struct\_like \left\{ \begin{array}{l} exp \\ int\_like \end{array} \right\} base$   |  | <b>class C :</b>                                   |
| †48 | $struct\_like \left\{ \begin{array}{l} exp \\ int\_like \end{array} \right\}$   | $\rightarrow int\_like$  | $S \sqcup \left\{ \begin{array}{l} E \\ I \end{array} \right\}$                    | <b>struct name_info z;</b>                         |

|     |  |  |  |   |
|-----|--|--|--|---|
| 49  | $struct\_head \left\{ \begin{array}{c} decl \\ stmt \\ function \end{array} \right\} rbrace$ | $\rightarrow int\_like$  | $S \text{ in force } \left\{ \begin{array}{c} D \\ S \\ F \end{array} \right\} \text{ out force } R$ | <b>struct</b> { declaration }               |
| 50  | $struct\_head rbrace$  | $\rightarrow int\_like$  | $S \setminus, R$   | <b>class C</b> { }                          |
| 51  | $fn\_decl decl$  | $\rightarrow fn\_decl$   | $F \text{ force } D$   | $f(z)$ <b>double</b> $z$ ;                  |
| †52 | $fn\_decl stmt$  | $\rightarrow function$   | $F \text{ out out force } S$   | $main() \dots$                              |
| 53  | $function \left\{ \begin{array}{c} stmt \\ decl \\ function \end{array} \right\}$            | $\rightarrow \left\{ \begin{array}{c} stmt \\ decl \\ function \end{array} \right\}$ | $F \text{ big\_force } \left\{ \begin{array}{c} S \\ D \\ F \end{array} \right\}$                    | outer block                                 |
| 54  | $lbrace rbrace$  | $\rightarrow stmt$   | $L \setminus, R$   | empty statement                             |
| †55 | $lbrace \left\{ \begin{array}{c} stmt \\ decl \\ function \end{array} \right\} rbrace$       | $\rightarrow stmt$   | $force L \text{ in force } S \text{ force back } R \text{ out force}$                                | compound statement                          |
| 56  | $lbrace exp [comma] rbrace$  | $\rightarrow exp$  |  | initializer                                 |
| 57  | $if\_like exp$   | $\rightarrow if\_clause$   | $I \sqcup E$   | <b>if</b> ( $z$ )                           |
| 58  | $else\_like colon$   | $\rightarrow else\_like \text{ base}$  |  | <b>try</b> :                                |
| 59  | $else\_like lbrace$  | $\rightarrow else\_head lbrace$  |  | <b>else</b> {                               |
| 60  | $else\_like stmt$  | $\rightarrow stmt$   | $force E \text{ in bsp } S \text{ out force}$  | <b>else</b> $x = 0$ ;                       |
| 61  | $else\_head \left\{ \begin{array}{c} stmt \\ exp \end{array} \right\}$                       | $\rightarrow stmt$   | $force E \text{ bsp noop cancel } S \text{ force}$   | <b>else</b> { $x = 0$ ; }                   |
| 62  | $if\_clause lbrace$  | $\rightarrow if\_head lbrace$  |  | <b>if</b> ( $x$ ) {                         |
| 63  | $if\_clause stmt else\_like if\_like$  | $\rightarrow if\_like$   | $force I \text{ in bsp } S \text{ out force } E \sqcup I$  | <b>if</b> ( $x$ ) $y$ ; <b>else if</b>      |
| 64  | $if\_clause stmt else\_like$   | $\rightarrow else\_like$   | $force I \text{ in bsp } S \text{ out force } E$   | <b>if</b> ( $x$ ) $y$ ; <b>else</b>         |
| 65  | $if\_clause stmt$  | $\rightarrow else\_like \text{ stmt}$  |  | <b>if</b> ( $x$ ) $y$ ;                     |
| 66  | $if\_head \left\{ \begin{array}{c} stmt \\ exp \end{array} \right\} else\_like if\_like$     | $\rightarrow if\_like$   | $force I \text{ bsp noop cancel } S \text{ force } E \sqcup I$                                       | <b>if</b> ( $x$ ) { $y$ ; } <b>else if</b>  |
| 67  | $if\_head \left\{ \begin{array}{c} stmt \\ exp \end{array} \right\} else\_like$              | $\rightarrow else\_like$   | $force I \text{ bsp noop cancel } S \text{ force } E$  | <b>if</b> ( $x$ ) { $y$ ; } <b>else</b>     |
| 68  | $if\_head \left\{ \begin{array}{c} stmt \\ exp \end{array} \right\}$                         | $\rightarrow else\_head \left\{ \begin{array}{c} stmt \\ exp \end{array} \right\}$   |  | <b>if</b> ( $x$ ) { $y$ }                   |
| †69 | $do\_like stmt else\_like semi$  | $\rightarrow stmt$   | $D \text{ bsp noop cancel } S \text{ cancel noop bsp } ES$   | <b>do</b> $f(x)$ ; <b>while</b> ( $g(x)$ ); |
| 70  | $case\_like semi$  | $\rightarrow stmt$   |  | <b>return</b> ;                             |
| 71  | $case\_like colon$   | $\rightarrow tag$  |  | <b>default</b> :                            |
| 72  | $case\_like exp$   | $\rightarrow exp$  | $C \sqcup E$   | <b>return</b> 0                             |
| †73 | $catch\_like \left\{ \begin{array}{c} cast \\ exp \end{array} \right\}$                      | $\rightarrow fn\_decl$   | $C \text{ din } \left\{ \begin{array}{c} C \\ E \end{array} \right\}$                                | <b>catch</b> (...)                          |
| 74  | $tag tag$  | $\rightarrow tag$  | $T_1 \text{ bsp } T_2$   | <b>case</b> 0: <b>case</b> 1:               |
| 75  | $tag \left\{ \begin{array}{c} stmt \\ decl \\ function \end{array} \right\}$                 | $\rightarrow \left\{ \begin{array}{c} stmt \\ decl \\ function \end{array} \right\}$ | $force \text{ back } T \text{ bsp } S$   | <b>case</b> 0: $z = 0$ ;                    |
| †76 | $stmt \left\{ \begin{array}{c} stmt \\ decl \\ function \end{array} \right\}$                | $\rightarrow \left\{ \begin{array}{c} stmt \\ decl \\ function \end{array} \right\}$ | $S \left\{ \begin{array}{c} force S \\ big\_force D \\ big\_force F \end{array} \right\}$            | $x = 1$ ; $y = 2$ ;                         |
| 77  | $semi$   | $\rightarrow stmt$   | $\sqcup S$   | empty statement                             |
| †78 | $lproc \left\{ \begin{array}{c} if\_like \\ else\_like \\ define\_like \end{array} \right\}$ | $\rightarrow lproc$  |  | <b>#include</b>                             |
|     |  |  |  | <b>#else</b>                                |
|     |  |  |  | <b>#define</b>                              |
| 79  | $lproc rproc$  | $\rightarrow insert$   |  | <b>#endif</b>                               |

|      |   |  |  |   |
|------|---|--|--|---|
| 80   | $lproc \left\{ \begin{array}{l} exp \\ function \end{array} \right\} rproc$   | $\rightarrow insert$   | $I_{\sqcup} \left\{ \begin{array}{l} E[\sqcup 5E] \\ F \end{array} \right\}$ | <b>#define</b> <i>a</i> 1<br><b>#define</b> <i>a</i> { <i>b</i> ; } |
| 81   | <i>section_scrap semi</i>   | $\rightarrow stmt$   | <i>MS force</i>  | $\langle section\ name \rangle;$                                    |
| 82   | <i>section_scrap</i>  | $\rightarrow exp$  |  | $\langle section\ name \rangle$                                     |
| 83   | <i>insert function</i>  | $\rightarrow function$   |  | <b>#include</b> before <i>main</i>                                  |
| 84   | <i>prelangle</i>  | $\rightarrow binop$  | <  | < not in template   |
| 85   | <i>prerangle</i>  | $\rightarrow binop$  | >  | > not in template   |
| 86   | <i>langle prerangle</i>   | $\rightarrow cast$   | $L \setminus, P$   | $\langle \rangle$   |
| 87   | $langle \left\{ \begin{array}{l} decl\_head \\ int\_like \\ exp \end{array} \right\} prerangle$   | $\rightarrow cast$   |  | $\langle class\ C \rangle$  |
| 88   | $langle \left\{ \begin{array}{l} decl\_head \\ int\_like \\ exp \end{array} \right\} comma$   | $\rightarrow langle$   | $L \left\{ \begin{array}{l} D \\ I \\ E \end{array} \right\} C\ opt9$        | $\langle class\ C,$   |
| 89   | <i>template_like exp prelangle</i>  | $\rightarrow template\_like\ exp\ langle$  |  | <b>template</b> <i>a</i> (100)                                      |
| 90   | <i>template_like</i> $\left\{ \begin{array}{l} exp \\ raw\_int \end{array} \right\}$  | $\rightarrow \left\{ \begin{array}{l} exp \\ raw\_int \end{array} \right\}$                  | $T_{\sqcup} \left\{ \begin{array}{l} E \\ R \end{array} \right\}$            | <b>C::template</b> <i>a</i> ( )                                     |
| 91   | <i>template_like</i>  | $\rightarrow raw\_int$   |  | <b>template</b> $\langle class\ T \rangle$                          |
| 92   | <i>new_like lpar exp rpar</i>   | $\rightarrow new\_like$  |  | <b>new</b> ( <i>nothrow</i> )                                       |
| 93   | <i>new_like cast</i>  | $\rightarrow exp$  | $N_{\sqcup} C$   | <b>new</b> ( <b>int</b> *)  |
| †94  | <i>new_like</i>   | $\rightarrow new\_exp$   |  | <b>new</b> <b>C</b> ( )   |
| 95   | <i>new_exp</i> $\left\{ \begin{array}{l} int\_like \\ const\_like \end{array} \right\}$   | $\rightarrow new\_exp$   | $N_{\sqcup} \left\{ \begin{array}{l} I \\ C \end{array} \right\}$            | <b>new const int</b>  |
| 96   | <i>new_exp struct_like</i> $\left\{ \begin{array}{l} exp \\ int\_like \end{array} \right\}$   | $\rightarrow new\_exp$   | $N_{\sqcup} S_{\sqcup} \left\{ \begin{array}{l} E \\ I \end{array} \right\}$ | <b>new struct S</b>   |
| 97   | <i>new_exp raw_ubin</i>   | $\rightarrow new\_exp$   | $N \{ R \}$  | <b>new int</b> *[2]   |
| 98   | <i>new_exp</i> $\left\{ \begin{array}{l} lpar \\ exp \end{array} \right\}$  | $\rightarrow exp \left\{ \begin{array}{l} lpar \\ exp \end{array} \right\}$                  | $E = N \left\{ \begin{array}{l} \end{array} \right\}$                        | <b>operator</b> [ ]( <b>int</b> )<br><b>new int</b> (2)             |
| †99  | <i>new_exp</i>  | $\rightarrow exp$  |  | <b>new int</b> ;  |
| 100  | <i>ftemplate prelangle</i>  | $\rightarrow ftemplate\ langle$  |  | <i>make_pair</i> $\langle \mathbf{int}, \mathbf{int} \rangle$       |
| 101  | <i>ftemplate</i>  | $\rightarrow exp$  |  | <i>make_pair</i> (1, 2)   |
| 102  | <i>for_like exp</i>   | $\rightarrow else\_like$   | $F_{\sqcup} E$   | <b>while</b> (1)  |
| 103  | <i>raw_ubin const_like</i>  | $\rightarrow raw\_ubin$  | $RC \setminus_{\sqcup}$  | <b>*const</b> <i>x</i>  |
| 104  | <i>raw_ubin</i>   | $\rightarrow ubinop$   |  | <b>*</b> <i>x</i>   |
| 105  | <i>const_like</i>   | $\rightarrow int\_like$  |  | <b>const</b> <i>x</i>   |
| 106  | <i>raw_int prelangle</i>  | $\rightarrow raw\_int\ langle$   |  | <b>C</b> $\langle$  |
| 107  | <i>raw_int colcol</i>   | $\rightarrow colcol$   |  | <b>C::</b>  |
| 108  | <i>raw_int cast</i>   | $\rightarrow raw\_int$   |  | <b>C</b> $\langle class\ T \rangle$                                 |
| 109  | <i>raw_int lpar</i>   | $\rightarrow exp\ lpar$  |  | <b>complex</b> ( <i>x</i> , <i>y</i> )                              |
| †110 | <i>raw_int</i>  | $\rightarrow int\_like$  |  | <b>complex</b> <i>z</i>   |
| †111 | <i>operator_like</i> $\left\{ \begin{array}{l} binop \\ unop \\ ubinop \end{array} \right\}$  | $\rightarrow exp$  | $O \{ \left\{ \begin{array}{l} B \\ U \\ U \end{array} \right\} \}$          | <b>operator</b> +   |
| 112  | <i>operator_like</i> $\left\{ \begin{array}{l} new\_like \\ delete\_like \end{array} \right\}$  | $\rightarrow exp$  | $O_{\sqcup} \left\{ \begin{array}{l} N \\ S \end{array} \right\}$            | <b>operator delete</b>  |
| 113  | <i>operator_like comma</i>  | $\rightarrow exp$  |  | <b>operator</b> ,   |
| †114 | <i>operator_like</i>  | $\rightarrow new\_exp$   |  | <b>operator char</b> *  |
| 115  | <i>typedef_like</i> $\left\{ \begin{array}{l} int\_like \\ cast \end{array} \right\} \left\{ \begin{array}{l} comma \\ semi \end{array} \right\}$ | $\rightarrow typedef\_like\ exp \left\{ \begin{array}{l} comma \\ semi \end{array} \right\}$ |  | <b>typedef int I</b> ,  |

|      |  |  |   |   |
|------|--|--|---|---|
| 116  | <i>typedef_like int_like</i>   | → <i>typedef_like</i>  | $T_{\sqcup}I$   | <b>typedef char</b>                     |
| †117 | <i>typedef_like exp</i>  | → <i>typedef_like</i>  | $T_{\sqcup}E^{**}$  | <b>typedef I @[@] (*P)</b>              |
| 118  | <i>typedef_like comma</i>  | → <i>typedef_like</i>  | $TC$  | <b>typedef int x,</b>                   |
| 119  | <i>typedef_like semi</i>   | → <i>decl</i>  |   | <b>typedef int x, y;</b>                |
| 120  | <i>typedef_like ubinop</i> $\left\{ \begin{array}{l} \textit{cast} \\ \textit{ubinop} \end{array} \right\}$                  | → <i>typedef_like</i> $\left\{ \begin{array}{l} \textit{cast} \\ \textit{ubinop} \end{array} \right\}$ | $\left\{ \begin{array}{l} C = \{U\}C \\ U_2 = \{U_1\}U_2 \end{array} \right\}$        | <b>typedef ** (CPtr)</b>                |
| 121  | <i>delete_like lbrack rbrack</i>   | → <i>delete_like</i>   | $DL \setminus, R$   | <b>delete[]</b>                         |
| 122  | <i>delete_like exp</i>   | → <i>exp</i>   | $D_{\sqcup}E$   | <b>delete p</b>                         |
| †123 | <i>question exp</i> $\left\{ \begin{array}{l} \textit{colon} \\ \textit{base} \end{array} \right\}$                          | → <i>binop</i>   |   | ? <i>x</i> :<br>? <i>f</i> ( ) :        |
| 124  | <i>begin_arg end_arg</i>   | → <i>exp</i>   |   | @[char*@]                               |
| 125  | <i>any_other end_arg</i>   | → <i>end_arg</i>   |   | char*@                                  |
| 126  | <i>alignas_like decl_head</i>  | → <i>attr</i>  |   | <b>alignas(struct s *)</b>              |
| 127  | <i>alignas_like exp</i>  | → <i>attr</i>  |   | <b>alignas(8)</b>                       |
| 128  | <i>lbrack lbrack</i>   | → <i>attr_head</i>   |   | attribute begins                        |
| 129  | <i>lbrack</i>  | → <i>lpar</i>  |   | [ elsewhere                             |
| 130  | <i>rbrack</i>  | → <i>rpar</i>  |   | ] elsewhere                             |
| 131  | <i>attr_head rbrack rbrack</i>   | → <i>attr</i>  |   | [[. . .]]                               |
| 132  | <i>attr_head exp</i>   | → <i>attr_head</i>   |   | [[ <i>deprecated</i>                    |
| 133  | <i>attr_head using_like exp colon</i>  | → <i>attr_head</i>   |   | [[ <b>using NS:</b>                     |
| 134  | <i>attr</i> $\left\{ \begin{array}{l} \textit{lbrace} \\ \textit{stmt} \end{array} \right\}$                                 | → $\left\{ \begin{array}{l} \textit{lbrace} \\ \textit{stmt} \end{array} \right\}$                     | $A_{\sqcup} \left\{ \begin{array}{l} S \\ L \end{array} \right\}$                     | [[ <i>likely</i> ]] {                   |
| 135  | <i>attr tag</i>  | → <i>tag</i>   | $A_{\sqcup}T$   | [[ <i>likely</i> ]] <b>case 0:</b>      |
| 136  | <i>attr semi</i>   | → <i>stmt</i>  |   | [[ <i>fallthrough</i> ]];               |
| 137  | <i>attr attr</i>   | → <i>attr</i>  | $A_1 \sqcup A_2$  | <b>alignas(x)</b> [[. . .]]             |
| 138  | <i>attr decl_head</i>  | → <i>decl_head</i>   |   | [[ <i>nodiscard</i> ]] <i>f</i> ( )     |
| 139  | <i>decl_head attr</i>  | → <i>decl_head</i>   |   | ( <b>int x</b> [[ <i>deprecated</i> ]]) |
| 140  | <i>using_like</i>  | → <i>int_like</i>  |   | <b>using</b> not in attributes          |
| 141  | <i>struct_like attr</i>  | → <i>struct_like</i>   | $S_{\sqcup}A$   | <b>struct</b> [[ <i>deprecated</i> ]]   |
| 142  | <i>exp attr</i>  | → <i>exp</i>   | $E_{\sqcup}A$   | <b>enum {x</b> [[. . .]]}               |
| 143  | <i>attr typedef_like</i>   | → <i>typedef_like</i>  | $A_{\sqcup}T$   | [[ <i>deprecated</i> ]] <b>typedef</b>  |
| 144  | <i>raw_int lbrack</i>  | → <i>exp</i>   |   | <b>int[3]</b>                           |
| 145  | <i>attr_head comma</i>   | → <i>attr_head</i>   |   | [[ <i>x, y</i>                          |
| 146  | <i>if_head attr</i>  | → <i>if_head</i>   | $I_{\sqcup}A$   | <b>if (x)</b> [[ <i>unlikely</i> ]] {   |
| 147  | <i>lbrack lbrack rbrack rbrack</i>   | → <i>exp</i>   |   | [[ ]]                                   |
| 148  | <i>attr function</i>   | → <i>function</i>  | $A_{\sqcup}F$   | attribute and function                  |
| 149  | <i>default_like colon</i>  | → <i>case_like colon</i>   |   | <b>default:</b>                         |
| 150  | <i>default_like</i>  | → <i>exp</i>   |   | <i>f</i> ( ) = <b>default;</b>          |
| 151  | <i>struct_like struct_like</i>   | → <i>struct_like</i>   | $S_1 \sqcup S_2$  | <b>enum class</b>                       |
| 152  | <i>exp colcol int_like</i>   | → <i>int_like</i>  |   | <i>std::atomic</i>                      |
| †153 | <i>langle struct_like</i> $\left\{ \begin{array}{l} \textit{exp} \\ \textit{int_like} \end{array} \right\}$ <i>comma</i>     | → <i>langle</i>  | $LS_{\sqcup} \left\{ \begin{array}{l} E^{**} \\ I^{**} \end{array} \right\} C_{opt9}$ | < <b>typename</b> <i>t</i> ,            |
| †154 | <i>langle struct_like</i> $\left\{ \begin{array}{l} \textit{exp} \\ \textit{int_like} \end{array} \right\}$ <i>prerangle</i> | → <i>cast</i>  | $LS_{\sqcup} \left\{ \begin{array}{l} E^{**} \\ I^{**} \end{array} \right\} P$        | < <b>typename</b> <i>t</i> >            |
| 155  | <i>template_like cast struct_like</i>  | → <i>struct_like</i>   | $T_{\sqcup}CS$  | <b>template</b> <...> <b>class</b>      |
| 156  | <i>tag rbrace</i>  | → <i>decl rbrace</i>   |   | <b>public:</b> }                        |
| 157  | <i>fn_decl attr</i>  | → <i>fn_decl</i>   | $F_{\sqcup}A$   | <b>void f</b> ( ) <b>noexcept</b>       |
| 158  | <i>alignas_like cast</i>   | → <i>attr</i>  |   | <b>alignas(int)</b>                     |



## †Notes

- Rules 1, 38, 52, and 73: The *dins* and *outs* are suppressed if **CWEAVE** has been invoked with the **-i** option.
- Rules 35, 117: The *exp* must not be immediately followed by *lpar*, *lbrack*, *exp*, or *cast*.
- Rule 41: The *big\_force* becomes *force* if **CWEAVE** has been invoked with the **-o** option.
- Rule 48: The *exp* or *int\_like* must not be immediately followed by *base*.
- Rule 55: The second *force* becomes *bsp* if **CWEAVE** has been invoked with the **-F** option.
- Rule 69: The **do . . . while** loop is wrapped in *force* if **CWEAVE** is invoked with the **-f** option.
- Rule 76: The *force* in the *stmt* line becomes *bsp* if **CWEAVE** has been invoked with the **-f** option, and the *big\_force* in the *decl* and *function* lines becomes *force* if **CWEAVE** has been invoked with the **-o** option.
- Rule 78: The *define\_like* case calls *make\_underlined* on the following scrap.
- Rule 94: The *new\_like* must not be immediately followed by *lpar*.
- Rule 99: The *new\_exp* must not be immediately followed by *raw\_int*, *struct\_like*, or *colcol*.
- Rule 110: The *raw\_int* must not be immediately followed by *langle*.
- Rule 111: The operator after *operator\_like* must not be immediately followed by a *binop*.
- Rule 114: The *operator\_like* must not be immediately followed by *raw\_ubin*.
- Rule 123: The mathness of the *colon* or *base* changes to ‘yes’.
- Rules 153, 154: *make\_reserved* is called only if **CWEAVE** has been invoked with the **+t** option.

**128\*** Now comes the code that tries to match each production starting with a particular type of scrap. Whenever a match is discovered, the *squash* or *reduce* function will cause the appropriate action to be performed.

```

⟨ Cases for exp 128* ⟩ ≡
  if (cat1 ≡ lbrace ∨ cat1 ≡ int_like ∨ cat1 ≡ decl) {
    make_underlined(pp);
    if (indent_param_decl) big_app(dindent);
    big_app1(pp); reduce(pp, 1, fn_decl, 0, 1);
  }
  else if (cat1 ≡ unop) squash(pp, 2, exp, -2, 2);
  else if ((cat1 ≡ binop ∨ cat1 ≡ ubinop) ∧ cat2 ≡ exp) squash(pp, 3, exp, -2, 3);
  else if (cat1 ≡ comma ∧ cat2 ≡ exp) {
    big_app2(pp); app(opt); app('9'); big_app1(pp + 2); reduce(pp, 3, exp, -2, 4);
  }
  else if (cat1 ≡ lpar ∧ cat2 ≡ rpar ∧ cat3 ≡ colon) reduce(pp + 3, 0, base, 0, 5);
  else if (cat1 ≡ cast ∧ cat2 ≡ colon) reduce(pp + 2, 0, base, 0, 5);
  else if (cat1 ≡ semi) squash(pp, 2, stmt, -1, 6);
  else if (cat1 ≡ colon) {
    make_underlined(pp); squash(pp, 2, tag, -1, 7);
  }
  else if (cat1 ≡ rbrace) reduce(pp, 0, stmt, -1, 8);
  else if (cat1 ≡ lpar ∧ cat2 ≡ rpar ∧ (cat3 ≡ const_like ∨ cat3 ≡ case_like)) {
    big_app1_insert(pp + 2, '□'); reduce(pp + 2, 2, rpar, 0, 9);
  }
  else if (cat1 ≡ cast ∧ (cat2 ≡ const_like ∨ cat2 ≡ case_like)) {
    big_app1_insert(pp + 1, '□'); reduce(pp + 1, 2, cast, 0, 9);
  }
  else if (cat1 ≡ exp ∨ cat1 ≡ cast) squash(pp, 2, exp, -2, 10);
  else if (cat1 ≡ attr) {
    big_app1_insert(pp, '□'); reduce(pp, 2, exp, -2, 142);
  }
  else if (cat1 ≡ colcol ∧ cat2 ≡ int_like) squash(pp, 3, int_like, -2, 152);

```

This code is used in section 121.

```

138* ⟨Cases for decl_head 138*⟩ ≡
  if (cat1 ≡ comma) {
    big_app2(pp); app(opt); app('9'); reduce(pp, 2, decl_head, -1, 33);
  }
  else if (cat1 ≡ ubinop) {
    big_app1_insert(pp, '{'); big_app('}'); reduce(pp, 2, decl_head, -1, 34);
  }
  else if (cat1 ≡ exp ∧ cat2 ≠ lpar ∧ cat2 ≠ lbrack ∧ cat2 ≠ exp ∧ cat2 ≠ cast) {
    make_underlined(pp + 1); squash(pp, 2, decl_head, -1, 35);
  }
  else if ((cat1 ≡ binop ∨ cat1 ≡ colon) ∧ cat2 ≡ exp ∧ (cat3 ≡ comma ∨ cat3 ≡ semi ∨ cat3 ≡ rpar))
    squash(pp, 3, decl_head, -1, 36);
  else if (cat1 ≡ cast) squash(pp, 2, decl_head, -1, 37);
  else if (cat1 ≡ int_like ∨ cat1 ≡ lbrace ∨ cat1 ≡ decl) {
    if (indent_param_decl) big_app(dindent);
    squash(pp, 1, fn_decl, 0, 38);
  }
  else if (cat1 ≡ semi) squash(pp, 2, decl, -1, 39);
  else if (cat1 ≡ attr) {
    big_app1_insert(pp, '□'); reduce(pp, 2, decl_head, -1, 139);
  }

```

This code is used in section 121.

```

139* ⟨Cases for decl 139*⟩ ≡
  if (cat1 ≡ decl) {
    big_app1_insert(pp, force); reduce(pp, 2, decl, -1, 40);
  }
  else if (cat1 ≡ stmt ∨ cat1 ≡ function) {
    big_app1_insert(pp, order_decl_stmt ? big_force : force); reduce(pp, 2, cat1, -1, 41);
  }

```

This code is used in section 121.

```

143* ⟨Cases for fn_decl 143*⟩ ≡
  if (cat1 ≡ decl) {
    big_app1_insert(pp, force); reduce(pp, 2, fn_decl, 0, 51);
  }
  else if (cat1 ≡ stmt) {
    big_app1(pp);
    if (indent_param_decl) {
      app(outdent); app(outdent);
    }
    big_app(force); big_app1(pp + 1); reduce(pp, 2, function, -1, 52);
  }
  else if (cat1 ≡ attr) {
    big_app1_insert(pp, '□'); reduce(pp, 2, fn_decl, 0, 157);
  }

```

This code is used in section 121.

```

153* ⟨Cases for catch_like 153*⟩ ≡
  if (cat1 ≡ cast ∨ cat1 ≡ exp) {
    big_app1(pp);
    if (indent_param_decl) big_app(dindent);
    big_app1(pp + 1); reduce(pp, 2, fn_decl, 0, 73);
  }

```

This code is used in section 121.

```

156* ⟨Cases for stmt 156*⟩ ≡
  if (cat1 ≡ stmt ∨ cat1 ≡ decl ∨ cat1 ≡ function) {
    big_app1_insert(pp, (cat1 ≡ decl ∨ cat1 ≡ function) ? (order_decl_stmt ? big_force : force) :
      (force_lines ? force : break_space)); reduce(pp, 2, cat1, -1, 76);
  }

```

This code is used in section 121.

**186\*** And here now is the code that applies productions as long as possible. Before applying the production mechanism, we must make sure it has good input (at least four scraps, the length of the lhs of the longest rules), and that there is enough room in the memory arrays to hold the appended tokens and texts. Here we use a very conservative test; it's more important to make sure the program will still work if we change the production rules (within reason) than to squeeze the last bit of space from the memory arrays.

```

#define safe_tok_incr 20
#define safe_text_incr 10
#define safe_scrap_incr 10
⟨Reduce the scraps using the productions until no more rules apply 186*⟩ ≡
  while (true) {
    ⟨Make sure the entries pp through pp + 3 of cat are defined 187⟩
    if (tok_ptr + safe_tok_incr > tok_mem_end) {
      if (tok_ptr > max_tok_ptr) max_tok_ptr ← tok_ptr;
      overflow(_("token"));
    }
    if (text_ptr + safe_text_incr > tok_start_end) {
      if (text_ptr > max_text_ptr) max_text_ptr ← text_ptr;
      overflow(_("text"));
    }
    if (pp > lo_ptr) break;
    init_mathness ← cur_mathness ← maybe_math;
    ⟨Match a production at pp, or increase pp if there is no match 121⟩
  }

```

This code is used in section 188.

**190\*** If the initial sequence of scraps does not reduce to a single scrap, we concatenate the translations of all remaining scraps, separated by blank spaces, with dollar signs surrounding the translations of scraps where appropriate.

```

⟨Combine the irreducible scraps that remain 190*⟩ ≡
  ⟨If semi-tracing, show the irreducible scraps 191*⟩
  for (j ← scrap_base; j ≤ lo_ptr; j++) {
    if (j ≠ scrap_base) app(' ');
    if (j-mathness % 4 ≡ yes_math) app('$');
    app(tok_flag + (int)(j-trans - tok_start));
    if (j-mathness/4 ≡ yes_math) app('$');
    if (tok_ptr + 6 > tok_mem_end) overflow(_("token"));
  }
  freeze_text(); return text_ptr - 1;

```

This code is used in section 188.

```

191* ⟨If semi-tracing, show the irreducible scraps 191*⟩ ≡
  if (lo_ptr > scrap_base ∧ tracing ≡ partly) {
    printf(_("\\nIrreducible scrap sequence in section%d:"), (int) section_count);
    mark_harmless();
    for (j ← scrap_base; j ≤ lo_ptr; j++) {
      putchar(' '); print_cat(j-cat);
    }
  }

```

This code is used in section 190\*.

```

192* ⟨If tracing, print an indication of where we are 192*⟩ ≡
  if (tracing ≡ fully) {
    printf(_("\\nTracing after l.%d:\\n"), cur_line); mark_harmless();
    if (loc > buffer + 50) {
      printf("..."); term_write(loc - 51, 51);
    }
    else term_write(buffer, loc - buffer);
  }

```

This code is used in section 188.

```

197* ⟨Make sure that there is room for the new scraps, tokens, and texts 197*⟩ ≡
  if (scrap_ptr + safe_scrap_incr > scrap_info_end ∨ tok_ptr + safe_tok_incr > tok_mem_end
      ∨ text_ptr + safe_text_incr > tok_start_end) {
    if (scrap_ptr > max_scr_ptr) max_scr_ptr ← scrap_ptr;
    if (tok_ptr > max_tok_ptr) max_tok_ptr ← tok_ptr;
    if (text_ptr > max_text_ptr) max_text_ptr ← text_ptr;
    overflow(_("scrap/token/text"));
  }

```

This code is used in sections 196 and 205.

**199\*** The following code must use *app\_tok* instead of *app* in order to protect against overflow. Note that  $tok\_ptr + 1 \leq max\_toks$  after *app\_tok* has been used, so another *app* is legitimate before testing again.

Many of the special characters in a string must be prefixed by ‘\’ so that T<sub>E</sub>X will print them properly.

⟨Append a string or constant 199\*⟩ ≡

```
{ int count ← -1;    ▷ characters remaining before string break ◁
  switch (next_control) {
  case constant: app_str("\\T{"); break;
  case string: count ← 20; app_str("\\.{"); break;
  default: app_str("\\vb{");
  }
  while (id_first < id_loc) {
  if (count ≡ 0) {    ▷ insert a discretionary break in a long string ◁
    app_str("}\}\}\}\.{""); count ← 20;
  }
  switch (*id_first) {
  case '␣': case '\\': case '#': case '$': case '^': case '{': case '}': case '~': case '&':
    case '_': app('\\'); break;
  case '%':
    if (next_control ≡ constant) {
      app_str("}\}\p{");    ▷ special macro for 'hex exponent' ◁
      id_first++;    ▷ skip '%' ◁
    }
    else app('\\');
    break;
  case '@':
    if (*(id_first + 1) ≡ '@') id_first++;
    else err_print(_("!Double@_should_be_used_in_strings"));
    break;
  default:    ▷ high-bit character handling ◁
    if ((eight_bits)(*id_first) > °177) app_tok(quoted_char);
  }
  app_tok(*id_first++); count--;
}
app('}'); app_scrap(exp, maybe_math);
}
```

This code is used in section 196.

**203\*** When the ‘|’ that introduces C text is sensed, a call on *C\_translate* will return a pointer to the T<sub>E</sub>X translation of that text. If scraps exist in *scrap\_info*, they are unaffected by this translation process.

```
static text_pointer C_translate(void)
{
  text_pointer p;    ▷ points to the translation ◁
  scrap_pointer save_base ← scrap_base;    ▷ holds original value of scrap_base ◁
  scrap_base ← scrap_ptr + 1; C_parse(section_name);    ▷ get the scraps together ◁
  if (next_control ≠ '|') err_print(_("!Missing'|'after_C_text"));
  app_tok(cancel); app_scrap(insert, maybe_math);    ▷ place a cancel token as a final "comment" ◁
  p ← translate();    ▷ make the translation ◁
  if (scrap_ptr > max_scr_ptr) max_scr_ptr ← scrap_ptr;
  scrap_ptr ← scrap_base - 1; scrap_base ← save_base;    ▷ scrap the scraps ◁
  return p;
}
```

**211\*** To insert token-list  $p$  into the output, the *push\_level* subroutine is called; it saves the old level of output and gets a new one going. The value of *cur\_mode* is not changed.

```
static void push_level(    ▷ suspends the current level ◁
    text_pointer p)
{
    if (stack_ptr ≡ stack_end) overflow(_("stack"));
    if (stack_ptr > stack)    ▷ save current state ◁
        *stack_ptr ← cur_state;
    stack_ptr++;
    if (stack_ptr > max_stack_ptr) max_stack_ptr ← stack_ptr;
    cur_tok ← *p; cur_end ← *(p + 1);
}
```

**224\*** ⟨Skip next character, give error if not ‘@’ 224\*⟩ ≡

```
if (*k++ ≠ '@') {
    printf("%s", _("\n!Illegal control code in section name:"));
    print_section_name(cur_section_name); printf(">"); mark_error();
}
```

This code is used in section 223.

**225\*** The C text enclosed in |...| should not contain ‘|’ characters, except within strings. We put a ‘|’ at the front of the buffer, so that an error message that displays the whole buffer will look a little bit sensible. The variable *delim* is zero outside of strings, otherwise it equals the delimiter that began the string being copied.

⟨Copy the C text into the *buffer* array 225\*⟩ ≡

```
j ← limit + 1; *j ← '|'; delim ← 0;
while (true) {
    if (k ≥ k_limit) {
        printf("%s", _("\n!C text in section name didn't end:"));
        print_section_name(cur_section_name); printf(">"); mark_error(); break;
    }
    b ← *(k++);
    if (b ≡ '@' ∨ (b ≡ '\\' ∧ delim ≠ 0)) ⟨Copy a quoted character into the buffer 226*⟩
    else {
        if (b ≡ '\\' ∨ b ≡ '"') {
            if (delim ≡ 0) delim ← b;
            else if (delim ≡ b) delim ← 0;
        }
        if (b ≠ '|' ∨ delim ≠ 0) {
            if (j > buffer + long_buf_size - 3) overflow(_("buffer"));
            *(++j) ← b;
        }
        else break;
    }
}
```

This code is used in section 223.

```
226* ⟨Copy a quoted character into the buffer 226\*⟩ ≡  
  {  
    if ( $j > buffer + long\_buf\_size - 4$ ) overflow_("buffer");  
     $*(++j) \leftarrow b$ ;  $*(++j) \leftarrow *(k++)$ ;  
  }
```

This code is used in section [225\\*](#).

**227\*** **Phase two processing.** We have assembled enough pieces of the puzzle in order to be ready to specify the processing in CWEAVE's main pass over the source file. Phase two is analogous to phase one, except that more work is involved because we must actually output the T<sub>E</sub>X material instead of merely looking at the CWEB specifications.

```
static void phase_two(void)
{
  phase ← 2; reset_input();
  if (show_progress) printf("%s", _("\nWriting the output file..."));
  section_count ← 0; format_visible ← true; copy_limbo(); finish_line();
  flush_buffer(out_buf, false, false);    ▷ insert a blank line, it looks nice ◁
  while (¬input_has_ended) ◁ Translate the current section 230
}
```

**232\*** In the T<sub>E</sub>X part of a section, we simply copy the source text, except that index entries are not copied and C text within | ... | is translated.

```
◁ Translate the TEX part of the current section 232* ≡
do switch (next_control ← copy_TEX()) {
  case '|': init_stack(); output_C(); break;
  case '@': out('@'); break;
  case TEX_string: case noop: case xref_roman: case xref_wildcard: case xref_typewriter:
    case section_name: loc -= 2; next_control ← get_next();    ▷ skip to @> ◁
    if (next_control ≡ TEX_string) err_print(_(!TEX_string_should_be_in_C_text_only));
    break;
  case thin_space: case math_break: case ord: case line_break: case big_line_break: case no_line_break:
    case join: case pseudo_semi: case macro_arg_open: case macro_arg_close: case output_defs_code:
    err_print(_(!You_can't_do_that_in_TEX_text)); break;
} while (next_control < format_code);
```

This code is used in section 230.



**236\*** Keeping in line with the conventions of the C preprocessor (and otherwise contrary to the rules of CWEB) we distinguish here between the case that ‘(’ immediately follows an identifier and the case that the two are separated by a space. In the latter case, and if the identifier is not followed by ‘(’ at all, the replacement text starts immediately after the identifier. In the former case, it starts after we scan the matching ‘)’.

```

⟨Start a macro definition 236*⟩ ≡
{
  if (save_line ≠ out_line ∨ save_place ≠ out_ptr ∨ space_checked) app(backup);
  if (¬space_checked) {
    emit_space_if_needed(); save_position();
  }
  app_str("\\D"); ▷ this will produce '#define ' ◁
  if ((next_control ← get_next()) ≠ identifier) err_print(-("!Improper_macro_definition"));
  else {
    app('$'); app_cur_id(false);
    if (*loc ≡ '(') {
      reswitch:
        switch (next_control ← get_next()) {
          case '(': case ',': app(next_control); goto reswitch;
          case identifier: app_cur_id(false); goto reswitch;
          case ')': app(next_control); next_control ← get_next(); break;
          case dot_dot_dot: app_str("\\, \\ldots\\,"); app_scrap(raw_int, no_math);
            if ((next_control ← get_next()) ≡ ')') {
              app(next_control); next_control ← get_next(); break;
            }
            /*otherwise_fall_through*/
          default: err_print(-("!Improper_macro_definition")); break;
        }
    }
  }
  else next_control ← get_next();
  app_str("$"); app(break_space); app_scrap(dead, no_math);
  ▷ scrap won't take part in the parsing ◁
}
}

```

This code is used in section 233.

```

237* ⟨Start a format definition 237*⟩ ≡
{
  doing_format ← true;
  if (*(loc - 1) ≡ 's' ∨ *(loc - 1) ≡ 'S') format_visible ← false;
  if (¬space_checked) {
    emit_space_if_needed(); save_position();
  }
  app_str("\\F"); ▷ this will produce 'format' ◁
  next_control ← get_next();
  if (next_control ≡ identifier) {
    app(id_flag + (int)(id_lookup(id_first, id_loc, normal) - name_dir)); app(break_space);
    ▷ this is syntactically separate from what follows ◁
    next_control ← get_next();
    if (next_control ≡ identifier) {
      app(id_flag + (int)(id_lookup(id_first, id_loc, normal) - name_dir)); app_scrap(exp, maybe_math);
      app_scrap(semi, maybe_math); next_control ← get_next();
    }
  }
  if (scrap_ptr ≠ scrap_info + 2) err_print(_("!Improper_format_definition"));
}

```

This code is used in section 233.

**240\*** The title of the section and an ≡ or +≡ are made into a scrap that should not take part in the parsing.

```

⟨Check that '=' or '+=' follows this section name, and emit the scraps to start the section definition 240*⟩ ≡
do next_control ← get_next(); while (next_control ≡ '+'); ▷ allow optional '+=' ◁
if (next_control ≠ '=' ∧ next_control ≠ eq_eq)
  err_print(_("!You_need_an_sign_after_the_section_name"));
else next_control ← get_next();
if (out_ptr > out_buf + 1 ∧ *out_ptr ≡ 'Y' ∧ *(out_ptr - 1) ≡ '\\') app(backup);
▷ the section name will be flush left ◁
app(section_flag + (int)(this_section - name_dir)); cur_xref ← (xref_pointer) this_section-xref;
if (cur_xref-num ≡ file_flag) cur_xref ← cur_xref-xlink;
app_str("${}");
if (cur_xref-num ≠ section_count + def_flag) {
  app_str("\\mathrel+"); ▷ section name is multiply defined ◁
  this_section ← name_dir; ▷ so we won't give cross-reference info here ◁
}
app_str("\\E"); ▷ output an equivalence sign ◁
app_str("{}$"); app(force); app_scrap(dead, no_math); ▷ this forces a line break unless '@+' follows ◁

```

This code is used in section 239.

```

241* ⟨Emit the scrap for a section name if present 241*⟩ ≡
if (next_control < section_name) {
  err_print(_("!You_can't_do_that_in_C_text")); next_control ← get_next();
}
else if (next_control ≡ section_name) {
  app(section_flag + (int)(cur_section - name_dir)); app_scrap(section_scrap, maybe_math);
  next_control ← get_next();
}

```

This code is used in section 239.

**247\* Phase three processing.** We are nearly finished! `CWEAVE`'s only remaining task is to write out the index, after sorting the identifiers and index entries.

If the user has set the `no_xref` flag (the `-x` option on the command line), just finish off the page, omitting the index, section name list, and table of contents.

```
static void phase_three(void)
{
    phase ← 3; finish_line();    ▷ the bulk of tex_file has been written ◁
    if (no_xref) out_str("\\end");
    else {
        if (show_progress) printf("%s",_("\nWriting the index..."));
        if (change_exists) {
            ⟨Tell about changed sections 249⟩
            finish_line(); flush_buffer(out_buf, false, false);    ▷ insert a blank line, it looks nice ◁
        }
        out_str("\\inx"); finish_line();
        if ((idx_file ← fopen(idx_file_name, "wb")) ≡ Λ)
            fatal(_("! Cannot open index file"), idx_file_name);
        active_file ← idx_file;    ▷ change active file to the index file ◁
        ⟨Do the first pass of sorting 251⟩
        ⟨Sort and output the index 259⟩
        finish_line(); fclose(active_file);    ▷ finished with idx_file ◁
        active_file ← tex_file;    ▷ switch back to tex_file for a tic ◁
        out_str("\\fin"); finish_line();
        if ((scn_file ← fopen(scn_file_name, "wb")) ≡ Λ)
            fatal(_("! Cannot open section file"), scn_file_name);
        active_file ← scn_file;    ▷ change active file to section listing file ◁
        ⟨Output all the section names 268⟩
        finish_line(); fclose(active_file);    ▷ finished with scn_file ◁
        active_file ← tex_file;    ▷ switch back to tex_file for the last time ◁
        if (group_found) out_str("\\con"); else out_str("\\end");
    }
    finish_line(); fclose(active_file); active_file ← tex_file ← Λ;
    if (check_for_change) ⟨Update the result when it has changed 273*⟩
    if (show_happiness) {
        if (show_progress) new_line();
        printf("%s",_("Done. "));
    }
    check_complete();    ▷ was all of the change file used? ◁
}
```

**257\*** Procedure *unbucket* goes through the buckets and adds nonempty lists to the stack, using the collating sequence specified in the *collate* array. The parameter to *unbucket* tells the current depth in the buckets. Any two sequences that agree in their first 255 character positions are regarded as identical.

```
#define infinity 255    ▷ ∞ (approximately) ◁
static void unbucket(   ▷ empties buckets having depth d ◁
    eight_bits d)
{
    int c;    ▷ index into bucket; cannot be a simple char because of sign comparison below ◁
    for (c ← 100 + 128; c ≥ 0; c--)
        if (bucket[collate[c]]) {
            if (sort_ptr ≥ scrap_info_end) overflow(_("sorting"));
            sort_ptr++;
            if (sort_ptr > max_sort_ptr) max_sort_ptr ← sort_ptr;
            if (c ≡ 0) sort_ptr-depth ← infinity;
            else sort_ptr-depth ← d;
            sort_ptr-head ← bucket[collate[c]]; bucket[collate[c]] ← Λ;
        }
}
```

**269\*** Because on some systems the difference between two pointers is a `ptrdiff_t` rather than an `int`, we use `%td` to print these quantities.

```
void print_stats(void)
{
    puts(_("Memory usage statistics:"));
    printf(_("%td names (out of %ld)\n"), (ptrdiff_t)(name_ptr - name_dir), (long) max_names);
    printf(_("%td cross-references (out of %ld)\n"), (ptrdiff_t)(xref_ptr - xmem), (long) max_refs);
    printf(_("%td bytes (out of %ld)\n"), (ptrdiff_t)(byte_ptr - byte_mem), (long) max_bytes);
    puts(_("Parsing:"));
    printf(_("%td scraps (out of %ld)\n"), (ptrdiff_t)(max_scr_ptr - scrap_info), (long) max_scraps);
    printf(_("%td texts (out of %ld)\n"), (ptrdiff_t)(max_text_ptr - tok_start), (long) max_texts);
    printf(_("%td tokens (out of %ld)\n"), (ptrdiff_t)(max_tok_ptr - tok_mem), (long) max_toks);
    printf(_("%td levels (out of %ld)\n"), (ptrdiff_t)(max_stack_ptr - stack), (long) stack_size);
    puts(_("Sorting:"));
    printf(_("%td levels (out of %ld)\n"), (ptrdiff_t)(max_sort_ptr - scrap_info), (long) max_scraps);
}
```

**270\*** **Extensions to CWEB.** The following sections introduce new or improved features that have been created by numerous contributors over the course of a quarter century.

Care has been taken to keep the original section numbering intact, so this new material should nicely integrate with the original “**270. Index.**”

**271.\* Formatting alternatives.** CWEAVE indents declarations after old-style function definitions and long parameter lists of modern function definitions. With the `-i` option they will come out flush left.

```
#define indent_param_decl flags['i']    ▷ should formal parameter declarations be indented? ◁  
⟨Set initial values 24⟩ +≡  
    indent_param_decl ← true;
```

**272.\*** The original manual described the `-o` option for CWEAVE, but this was not yet present. Here is a simple implementation. The purpose is to suppress the extra space between local variable declarations and the first statement in a function block.

```
#define order_decl_stmt flags['o']    ▷ should declarations and statements be separated? ◁  
⟨Set initial values 24⟩ +≡  
    order_decl_stmt ← true;
```

**273\*** **Output file update.** Most C projects are controlled by a `Makefile` that automatically takes care of the temporal dependencies between the different source modules. It may be convenient that `CWEB` doesn't create new output for all existing files, when there are only changes to some of them. Thus the `make` process will only recompile those modules where necessary. You can activate this feature with the `+c` command-line option. The idea and basic implementation of this mechanism can be found in the program `NUWEB` by Preston Briggs, to whom credit is due.

```

⟨Update the result when it has changed 273*⟩ ≡
{
  if ((tex_file ← fopen(tex_file_name, "r")) ≠ Λ) {
    boolean comparison ← false;
    if ((check_file ← fopen(check_file_name, "r")) ≡ Λ)
      fatal(("!_Cannot_open_output_file_"), check_file_name);
    ⟨Compare the temporary output to the previous output 274*⟩
    fclose(tex_file); tex_file ← Λ; fclose(check_file); check_file ← Λ;
    ⟨Take appropriate action depending on the comparison 275*⟩
  }
  else rename(check_file_name, tex_file_name);    ▷ This was the first run ◁
  strcpy(check_file_name, "");    ▷ We want to get rid of the temporary file ◁
}

```

This code is used in section 247\*.

**274\*** We hope that this runs fast on most systems.

```

⟨Compare the temporary output to the previous output 274*⟩ ≡
do {
  char x[BUFSIZ], y[BUFSIZ];
  int x_size ← fread(x, sizeof(char), BUFSIZ, tex_file);
  int y_size ← fread(y, sizeof(char), BUFSIZ, check_file);
  comparison ← (x_size ≡ y_size) ∧ ¬memcmp(x, y, x_size);
} while (comparison ∧ ¬feof(tex_file) ∧ ¬feof(check_file));

```

This code is used in section 273\*.

**275\*** Note the superfluous call to `remove` before `rename`. We're using it to get around a bug in some implementations of `rename`.

```

⟨Take appropriate action depending on the comparison 275*⟩ ≡
if (comparison) remove(check_file_name);    ▷ The output remains untouched ◁
else {
  remove(tex_file_name); rename(check_file_name, tex_file_name);
}

```

This code is used in section 273\*.

**276\*** **Print “version” information.** Don’t do this at home, kids! Push our local macro to the variable in `COMMON` for printing the *banner* and the *versionstring* from there.

```
#define max_banner 50
```

```
<Common code for CWEAVE and CTANGLE 3*> +≡
```

```
extern char cb_banner[];
```

```
277* <Set initial values 24> +≡
```

```
strncpy(cb_banner, banner, max_banner - 1);
```



**278\* Index.** If you have read and understood the code for Phase III above, you know what is in this index and how it got here. All sections in which an identifier is used are listed with that identifier, except that reserved words are indexed only when they appear in format definitions, and the appearances of identifiers in section names are not indexed. Underlined entries correspond to where the identifier was declared. Error messages, control sequences put into the output, and a few other things like “recursion” are indexed here too.

The following sections were changed by the change file: [1](#), [2](#), [3](#), [4](#), [5](#), [6](#), [7](#), [8](#), [9](#), [10](#), [11](#), [12](#), [13](#), [14](#), [15](#), [16](#), [17](#), [18](#), [23](#), [25](#), [30](#), [57](#), [59](#), [62](#), [63](#), [64](#), [66](#), [70](#), [74](#), [79](#), [82](#), [89](#), [94](#), [99](#), [101](#), [102](#), [103](#), [110](#), [111](#), [128](#), [138](#), [139](#), [143](#), [153](#), [156](#), [186](#), [190](#), [191](#), [192](#), [197](#), [199](#), [203](#), [211](#), [224](#), [225](#), [226](#), [227](#), [232](#), [236](#), [237](#), [240](#), [241](#), [247](#), [257](#), [269](#), [270](#), [271](#), [272](#), [273](#), [274](#), [275](#), [276](#), [277](#), [278](#).

|  |   |
|--|---|
| <code>\)</code> : <a href="#">199*</a>   | <code>\LL</code> : <a href="#">198</a> .  |
| <code>\*</code> : <a href="#">96</a> .   | <code>\M</code> : <a href="#">231</a> .   |
| <code>\,</code> : <a href="#">129</a> , <a href="#">133</a> , <a href="#">142</a> , <a href="#">145</a> , <a href="#">163</a> , <a href="#">174</a> , <a href="#">196</a> , <a href="#">198</a> , <a href="#">236*</a> | <code>\MG</code> : <a href="#">198</a> .  |
| <code>\.</code> : <a href="#">199*</a> , <a href="#">218</a> , <a href="#">222</a> , <a href="#">262</a> .   | <code>\MGA</code> : <a href="#">198</a> .   |
| <code>\?</code> : <a href="#">196</a> .  | <code>\MM</code> : <a href="#">198</a> .  |
| <code>\[</code> : <a href="#">263</a> .  | <code>\MOD</code> : <a href="#">196</a> .   |
| <code>\_</code> : <a href="#">53</a> , <a href="#">169</a> , <a href="#">199*</a> , <a href="#">223</a> .  | <code>\MRL</code> : <a href="#">217</a> .   |
| <code>\#</code> : <a href="#">196</a> , <a href="#">199*</a> , <a href="#">223</a> .   | <code>\N</code> : <a href="#">231</a> .   |
| <code>\\$</code> : <a href="#">97</a> , <a href="#">199*</a> , <a href="#">223</a> .   | <code>\NULL</code> : <a href="#">202</a> .  |
| <code>\%</code> : <a href="#">199*</a> , <a href="#">223</a> .   | <code>\OR</code> : <a href="#">196</a> .  |
| <code>\&amp;</code> : <a href="#">199*</a> , <a href="#">218</a> , <a href="#">223</a> , <a href="#">262</a> .   | <code>\p</code> : <a href="#">199*</a>  |
| <code>\:</code> : <a href="#">199*</a> , <a href="#">218</a> , <a href="#">223</a> , <a href="#">262</a> .   | <code>\PA</code> : <a href="#">198</a> .  |
| <code>\^</code> : <a href="#">199*</a> , <a href="#">223</a> .   | <code>\PB</code> : <a href="#">205</a> , <a href="#">216</a> .  |
| <code>\{</code> : <a href="#">196</a> , <a href="#">199*</a> , <a href="#">223</a> .   | <code>\PP</code> : <a href="#">198</a> .  |
| <code>\}</code> : <a href="#">196</a> , <a href="#">199*</a> , <a href="#">223</a> .   | <code>\Q</code> : <a href="#">243</a> .   |
| <code>\~</code> : <a href="#">199*</a> , <a href="#">223</a> .   | <code>\R</code> : <a href="#">196</a> .   |
| <code>\_</code> : <a href="#">97</a> , <a href="#">199*</a> , <a href="#">223</a> .  | <code>\rangle</code> : <a href="#">196</a> .  |
| <code>\ </code> : <a href="#">218</a> , <a href="#">262</a> .  | <code>\SHC</code> : <a href="#">205</a> .   |
| <code>\A</code> : <a href="#">243</a> .  | <code>\T</code> : <a href="#">199*</a>  |
| <code>\AND</code> : <a href="#">196</a> .  | <code>\U</code> : <a href="#">243</a> .   |
| <code>\ATH</code> : <a href="#">196</a> .  | <code>\V</code> : <a href="#">198</a> .   |
| <code>\ATL</code> : <a href="#">99*</a>  | <code>\vb</code> : <a href="#">199*</a>   |
| <code>\B</code> : <a href="#">234</a> .  | <code>\W</code> : <a href="#">198</a> .   |
| <code>\C</code> : <a href="#">205</a> .  | <code>\X</code> : <a href="#">222</a> .   |
| <code>\ch</code> : <a href="#">249</a> .   | <code>\XOR</code> : <a href="#">196</a> .   |
| <code>\CM</code> : <a href="#">196</a> .   | <code>\Y</code> : <a href="#">229</a> , <a href="#">234</a> , <a href="#">240*</a>  |
| <code>\con</code> : <a href="#">247*</a>   | <code>\Z</code> : <a href="#">198</a> .   |
| <code>\D</code> : <a href="#">236*</a>   | <code>\1</code> : <a href="#">219</a> , <a href="#">221</a> .   |
| <code>\DC</code> : <a href="#">198</a> .   | <code>\2</code> : <a href="#">219</a> , <a href="#">221</a> .   |
| <code>\E</code> : <a href="#">198</a> , <a href="#">240*</a>   | <code>\3</code> : <a href="#">219</a> .   |
| <code>\end</code> : <a href="#">247*</a>   | <code>\4</code> : <a href="#">219</a> .   |
| <code>\ET</code> : <a href="#">245</a> .   | <code>\5</code> : <a href="#">158</a> , <a href="#">220</a> .   |
| <code>\F</code> : <a href="#">237*</a>   | <code>\6</code> : <a href="#">220</a> , <a href="#">234</a> .   |
| <code>\fi</code> : <a href="#">246</a> .   | <code>\7</code> : <a href="#">220</a> , <a href="#">234</a> .   |
| <code>\fin</code> : <a href="#">247*</a>   | <code>\8</code> : <a href="#">219</a> .   |
| <code>\G</code> : <a href="#">198</a> .  | <code>\9</code> : <a href="#">262</a> .   |
| <code>\GG</code> : <a href="#">198</a> .   | <code>\:</code> <a href="#">5*</a>  |
| <code>\I</code> : <a href="#">198</a> , <a href="#">261</a> , <a href="#">266</a> .  | <code>a</code> : <a href="#">120</a> , <a href="#">215</a> , <a href="#">217</a> .  |
| <code>\inx</code> : <a href="#">247*</a>   | <code>abnormal</code> : <a href="#">20</a> , <a href="#">32</a> .   |
| <code>\J</code> : <a href="#">196</a> .  | <code>ac</code> : <a href="#">2*</a> , <a href="#">15*</a>  |
| <code>\K</code> : <a href="#">196</a> .  | <code>active_file</code> : <a href="#">16*</a> , <a href="#">86</a> , <a href="#">89*</a> , <a href="#">247*</a>  |
| <code>\langle</code> : <a href="#">196</a> .   | <code>alfop</code> : <a href="#">20</a> , <a href="#">34</a> , <a href="#">107</a> , <a href="#">110*</a> , <a href="#">202</a> , <a href="#">218</a> .         |
| <code>\ldots</code> : <a href="#">198</a> , <a href="#">236*</a>   | <code>alignas_like</code> : <a href="#">20</a> , <a href="#">34</a> , <a href="#">107</a> , <a href="#">110*</a> , <a href="#">111*</a> , <a href="#">121</a> . |

- all\_caps*: [262](#).  
*an\_output*: [81](#), [82\\*](#), [222](#), [223](#), [242](#).  
*and\_and*: [6\\*](#), [51](#), [198](#).  
*app*: [118](#), [120](#), [128\\*](#), [129](#), [137](#), [138\\*](#), [140](#), [143\\*](#), [148](#),  
[150](#), [151](#), [158](#), [161](#), [162](#), [163](#), [190\\*](#), [196](#), [199\\*](#), [200](#),  
[202](#), [205](#), [216](#), [217](#), [234](#), [236\\*](#), [237\\*](#), [240\\*](#), [241\\*](#), [266](#).  
*app\_cur\_id*: [196](#), [201](#), [202](#), [236\\*](#).  
*app\_scrap*: [195](#), [196](#), [198](#), [199\\*](#), [202](#), [203\\*](#), [205](#),  
[234](#), [236\\*](#), [237\\*](#), [240\\*](#), [241\\*](#).  
*app\_str*: [118](#), [120](#), [158](#), [169](#), [196](#), [198](#), [199\\*](#), [200](#),  
[205](#), [236\\*](#), [237\\*](#), [240\\*](#).  
*app\_tok*: [101\\*](#), [103\\*](#), [104](#), [120](#), [199\\*](#), [200](#), [203\\*](#),  
[205](#), [234](#).  
*append\_xref*: [25\\*](#), [26](#), [27](#), [28](#), [127](#).  
*argc*: [2\\*](#), [15\\*](#).  
*argv*: [2\\*](#), [15\\*](#), [125](#).  
ASCII code dependencies: [6\\*](#), [36](#), [256](#).  
*attr*: [20](#), [34](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [128\\*](#), [138\\*](#), [141](#),  
[143\\*](#), [149](#), [176](#), [178](#), [179](#).  
*attr\_head*: [106](#), [107](#), [111\\*](#), [121](#), [177](#), [178](#).  
*av*: [2\\*](#), [15\\*](#).  
*b*: [87](#), [217](#).  
*backup*: [109](#), [111\\*](#), [117](#), [145](#), [154](#), [217](#), [220](#), [236\\*](#), [240\\*](#).  
*bal*: [73](#), [101\\*](#), [102\\*](#), [104](#), [205](#).  
*banner*: [1\\*](#), [14\\*](#), [276\\*](#), [277\\*](#).  
*base*: [106](#), [107](#), [111\\*](#), [121](#), [128\\*](#), [140](#), [141](#), [147](#), [175](#).  
*begin\_arg*: [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [196](#).  
*begin\_C*: [36](#), [38](#), [80](#), [238](#), [239](#).  
*begin\_comment*: [36](#), [51](#), [72](#), [73](#), [193](#), [205](#).  
*begin\_math*: [120](#).  
*begin\_short\_comment*: [36](#), [51](#), [72](#), [73](#), [193](#), [205](#).  
*big\_app*: [118](#), [120](#), [128\\*](#), [129](#), [131](#), [132](#), [135](#), [138\\*](#),  
[140](#), [141](#), [142](#), [143\\*](#), [145](#), [147](#), [148](#), [149](#), [150](#), [151](#),  
[153\\*](#), [154](#), [157](#), [159](#), [166](#), [172](#), [173](#), [178](#), [183](#).  
*big\_app1*: [118](#), [120](#), [128\\*](#), [132](#), [135](#), [140](#), [141](#),  
[142](#), [143\\*](#), [145](#), [147](#), [148](#), [149](#), [150](#), [151](#), [153\\*](#),  
[158](#), [166](#), [174](#), [183](#).  
*big\_app1\_insert*: [118](#), [128\\*](#), [131](#), [134](#), [135](#), [138\\*](#), [139\\*](#),  
[140](#), [141](#), [143\\*](#), [144](#), [146](#), [149](#), [150](#), [152](#), [154](#), [156\\*](#),  
[158](#), [164](#), [165](#), [166](#), [168](#), [172](#), [173](#), [174](#), [179](#).  
*big\_app1\_insert\_str*: [118](#), [129](#), [133](#), [142](#), [145](#),  
[163](#), [174](#).  
*big\_app2*: [118](#), [128\\*](#), [129](#), [138\\*](#), [151](#), [158](#), [159](#),  
[169](#), [183](#).  
*big\_app2\_insert*: [118](#), [163](#), [178](#).  
*big\_app3*: [118](#), [129](#), [163](#), [183](#).  
*big\_app4*: [118](#), [183](#).  
*big\_cancel*: [109](#), [110\\*](#), [117](#), [120](#), [196](#), [217](#), [220](#).  
*big\_force*: [109](#), [110\\*](#), [111\\*](#), [117](#), [120](#), [139\\*](#), [144](#), [156\\*](#),  
[196](#), [217](#), [220](#), [234](#).  
*big\_line\_break*: [36](#), [38](#), [196](#), [232\\*](#).  
*binop*: [105](#), [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [128\\*](#), [131](#), [132](#),  
[135](#), [138\\*](#), [161](#), [162](#), [172](#), [175](#), [196](#), [198](#).  
*blink*: [250](#), [251](#), [259](#), [260](#), [261](#).  
**boolean**: [5\\*](#), [8\\*](#), [9\\*](#), [10\\*](#), [12\\*](#), [15\\*](#), [21](#), [32](#), [46](#), [48](#), [73](#),  
[81](#), [86](#), [87](#), [95](#), [97](#), [98](#), [101\\*](#), [201](#), [202](#), [205](#), [217](#),  
[229](#), [234](#), [235](#), [262](#), [273\\*](#).  
*break\_out*: [90](#), [92](#), [93](#).  
*break\_space*: [109](#), [110\\*](#), [111\\*](#), [117](#), [145](#), [147](#), [148](#),  
[149](#), [150](#), [151](#), [154](#), [156\\*](#), [196](#), [206](#), [217](#), [219](#),  
[220](#), [236\\*](#), [237\\*](#).  
*bucket*: [250](#), [251](#), [257\\*](#), [260](#).  
*buf\_size*: [17\\*](#).  
*buffer*: [7\\*](#), [44](#), [53](#), [57\\*](#), [62\\*](#), [88](#), [101\\*](#), [192\\*](#), [217](#), [225\\*](#), [226\\*](#).  
*buffer\_end*: [7\\*](#), [49](#).  
BUFSIZ: [274\\*](#).  
bug, known: [200](#).  
*byte\_mem*: [11\\*](#), [29](#), [97](#), [217](#), [253](#), [262](#), [269\\*](#).  
*byte\_mem\_end*: [11\\*](#).  
*byte\_ptr*: [11\\*](#), [269\\*](#).  
*byte\_start*: [11\\*](#), [32](#), [43](#), [76](#), [97](#), [218](#), [251](#), [260](#), [262](#).  
*c*: [44](#), [100](#), [101\\*](#), [107](#), [182](#), [183](#), [217](#), [251](#), [257\\*](#), [260](#).  
C text...didn't end: [225\\*](#).  
*C\_file*: [15\\*](#), [16\\*](#).  
*C\_file\_name*: [15\\*](#).  
*c\_line\_write*: [86](#), [87](#).  
*C\_parse*: [193](#), [194](#), [203\\*](#), [204](#), [205](#).  
*C\_translate*: [201](#), [203\\*](#), [205](#), [216](#).  
*C\_xref*: [71](#), [72](#), [73](#), [74\\*](#), [193](#), [204](#).  
*cancel*: [109](#), [110\\*](#), [111\\*](#), [117](#), [148](#), [150](#), [151](#), [203\\*](#),  
[205](#), [206](#), [217](#), [219](#), [220](#).  
Cannot open index file: [247\\*](#).  
Cannot open output file: [273\\*](#).  
Cannot open section file: [247\\*](#).  
*carryover*: [86](#), [87](#).  
*case\_found*: [122](#), [123](#).  
*case\_like*: [20](#), [34](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [123](#), [128\\*](#), [180](#).  
*cast*: [106](#), [107](#), [111\\*](#), [121](#), [128\\*](#), [129](#), [131](#), [134](#), [138\\*](#),  
[153\\*](#), [163](#), [164](#), [165](#), [171](#), [173](#), [176](#).  
*cat*: [112](#), [119](#), [121](#), [124](#), [182](#), [185](#), [187](#), [188](#), [191\\*](#),  
[193](#), [195](#), [252](#), [253](#).  
*cat\_name*: [106](#), [107](#), [108](#).  
*catch\_like*: [20](#), [34](#), [107](#), [110\\*](#), [111\\*](#), [121](#).  
*cat1*: [121](#), [128\\*](#), [129](#), [130](#), [131](#), [132](#), [133](#), [134](#), [135](#),  
[136](#), [137](#), [138\\*](#), [139\\*](#), [140](#), [141](#), [142](#), [143\\*](#), [144](#), [145](#),  
[146](#), [147](#), [148](#), [149](#), [150](#), [151](#), [152](#), [153\\*](#), [154](#), [156\\*](#),  
[158](#), [159](#), [160](#), [163](#), [164](#), [165](#), [166](#), [167](#), [168](#), [169](#),  
[171](#), [172](#), [173](#), [174](#), [175](#), [176](#), [177](#), [178](#), [179](#), [180](#).  
*cat2*: [121](#), [128\\*](#), [129](#), [131](#), [135](#), [138\\*](#), [140](#), [141](#), [142](#),  
[145](#), [149](#), [150](#), [151](#), [158](#), [163](#), [164](#), [165](#), [166](#),  
[172](#), [173](#), [174](#), [175](#), [177](#), [178](#).  
*cat3*: [121](#), [128\\*](#), [138\\*](#), [145](#), [149](#), [150](#), [151](#), [158](#),  
[163](#), [165](#), [177](#), [178](#).

- cb\_banner*: [276\\*](#), [277\\*](#)  
*cb\_show\_banner*: [2\\*](#), [14\\*](#)  
*ccode*: [37](#), [38](#), [39](#), [41](#), [42](#), [43](#), [59\\*](#), [63\\*](#), [99\\*](#), [100](#).  
*change\_depth*: [8\\*](#)  
*change\_exists*: [21](#), [68](#), [70\\*](#), [247\\*](#)  
*change\_file*: [8\\*](#)  
*change\_file\_name*: [8\\*](#)  
*change\_line*: [8\\*](#)  
*change\_pending*: [10\\*](#)  
*changed\_section*: [10\\*](#), [21](#), [68](#), [70\\*](#), [96](#), [249](#).  
*changing*: [8\\*](#), [70\\*](#)  
*check\_complete*: [9\\*](#), [247\\*](#)  
*check\_file*: [15\\*](#), [16\\*](#), [273\\*](#), [274\\*](#)  
*check\_file\_name*: [15\\*](#), [273\\*](#), [275\\*](#)  
*check\_for\_change*: [15\\*](#), [247\\*](#)  
*cite\_flag*: [22](#), [24](#), [27](#), [72](#), [82\\*](#), [242](#), [243](#), [266](#).  
*colcol*: [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [128\\*](#), [137](#), [166](#),  
[171](#), [198](#).  
*collate*: [255](#), [256](#), [257\\*](#)  
*colon*: [106](#), [107](#), [110\\*](#), [111\\*](#), [128\\*](#), [135](#), [136](#), [138\\*](#), [141](#),  
[147](#), [152](#), [175](#), [178](#), [180](#), [196](#).  
*colon\_colon*: [6\\*](#), [51](#), [198](#).  
*comma*: [105](#), [106](#), [107](#), [110\\*](#), [111\\*](#), [118](#), [128\\*](#), [129](#),  
[138\\*](#), [140](#), [145](#), [163](#), [172](#), [173](#), [178](#), [196](#).  
*common\_init*: [2\\*](#), [4\\*](#)  
*comparison*: [273\\*](#), [274\\*](#), [275\\*](#)  
*compress*: [6\\*](#), [51](#).  
*confusion*: [13\\*](#), [123](#), [183](#).  
*const\_like*: [20](#), [34](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [128\\*](#), [166](#), [169](#).  
*constant*: [43](#), [53](#), [196](#), [199\\*](#)  
Control codes are forbidden...: [63\\*](#), [64\\*](#)  
Control text didn't end: [64\\*](#)  
*copy\_comment*: [73](#), [98](#), [101\\*](#), [205](#).  
*copy\_limbo*: [98](#), [99\\*](#), [227\\*](#)  
*copy\_T<sub>E</sub>X*: [98](#), [100](#), [232\\*](#)  
*count*: [199\\*](#)  
*ctangle*: [3\\*](#)  
*ctwill*: [3\\*](#)  
*cur\_byte*: [253](#), [260](#).  
*cur\_depth*: [253](#), [259](#), [260](#).  
*cur\_end*: [207](#), [208](#), [211\\*](#), [215](#).  
*cur\_file*: [8\\*](#)  
*cur\_file\_name*: [8\\*](#)  
*cur\_line*: [8\\*](#), [192\\*](#)  
*cur\_mathness*: [119](#), [120](#), [161](#), [162](#), [182](#), [186\\*](#)  
*cur\_mode*: [207](#), [208](#), [211\\*](#), [215](#), [217](#), [219](#), [220](#), [222](#).  
*cur\_name*: [213](#), [215](#), [218](#), [222](#), [223](#), [250](#), [251](#),  
[260](#), [261](#), [262](#), [265](#).  
*cur\_section*: [43](#), [60](#), [72](#), [80](#), [196](#), [239](#), [241\\*](#)  
*cur\_section\_char*: [43](#), [60](#), [80](#).  
*cur\_section\_name*: [217](#), [223](#), [224\\*](#), [225\\*](#)  
*cur\_state*: [208](#), [211\\*](#), [212](#).  
*cur\_tok*: [207](#), [208](#), [211\\*](#), [215](#), [217](#).  
*cur\_val*: [253](#), [263](#).  
*cur\_xref*: [81](#), [82\\*](#), [222](#), [240\\*](#), [242](#), [243](#), [245](#), [263](#),  
[264](#), [265](#), [266](#).  
*custom*: [20](#), [25\\*](#), [34](#), [202](#), [218](#), [262](#).  
*custom\_out*: [218](#).  
*cweave*: [2\\*](#), [3\\*](#)  
**cweb**: [3\\*](#)  
*d*: [182](#), [183](#), [257\\*](#)  
*dead*: [106](#), [107](#), [236\\*](#), [240\\*](#)  
DEBUG: [115](#), [116](#).  
*decl*: [34](#), [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [128\\*](#), [129](#), [138\\*](#),  
[139\\*](#), [142](#), [143\\*](#), [144](#), [145](#), [154](#), [156\\*](#), [173](#).  
*decl\_head*: [106](#), [107](#), [111\\*](#), [121](#), [129](#), [135](#), [138\\*](#),  
[141](#), [163](#), [176](#), [179](#).  
*def\_flag*: [22](#), [23\\*](#), [24](#), [26](#), [27](#), [43](#), [59\\*](#), [74\\*](#), [77](#), [78](#), [80](#),  
[82\\*](#), [95](#), [125](#), [126](#), [222](#), [240\\*](#), [242](#), [243](#), [263](#).  
*default\_like*: [20](#), [34](#), [107](#), [110\\*](#), [111\\*](#), [121](#).  
*define\_like*: [20](#), [34](#), [107](#), [110\\*](#), [111\\*](#), [158](#).  
*definition*: [36](#), [38](#), [77](#), [233](#).  
*delete\_like*: [20](#), [34](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [172](#), [174](#).  
*delim*: [57\\*](#), [58](#), [217](#), [218](#), [225\\*](#)  
*deprecated*: [111\\*](#)  
*depth*: [252](#), [253](#), [257\\*](#), [259](#).  
*digit\_suffix*: [53](#), [55](#), [56](#).  
*dindent*: [109](#), [111\\*](#), [117](#), [120](#), [128\\*](#), [138\\*](#), [153\\*](#), [217](#).  
*dindent\_pending*: [217](#), [220](#).  
*do\_like*: [20](#), [34](#), [107](#), [110\\*](#), [111\\*](#), [121](#).  
*doing\_format*: [218](#), [229](#), [233](#), [237\\*](#)  
*done*: [101\\*](#), [102\\*](#), [103\\*](#)  
*dot\_dot\_dot*: [6\\*](#), [51](#), [198](#), [236\\*](#)  
Double @ should be used...: [99\\*](#), [199\\*](#)  
*dst*: [75](#).  
*dummy*: [11\\*](#)  
**eight\_bits**: [3\\*](#), [7\\*](#), [11\\*](#), [12\\*](#), [32](#), [37](#), [40](#), [41](#), [42](#), [44](#), [45](#),  
[67](#), [71](#), [72](#), [98](#), [99\\*](#), [100](#), [112](#), [181](#), [182](#), [183](#), [193](#),  
[194](#), [199\\*](#), [200](#), [214](#), [215](#), [217](#), [253](#), [255](#), [257\\*](#), [258](#).  
*else\_head*: [106](#), [107](#), [111\\*](#), [121](#), [147](#), [150](#).  
*else\_like*: [20](#), [34](#), [105](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [149](#),  
[150](#), [151](#), [158](#), [168](#).  
*emit\_space\_if\_needed*: [229](#), [236\\*](#), [237\\*](#), [239](#).  
*end\_arg*: [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [196](#).  
*end\_field*: [207](#), [208](#).  
*end\_math*: [120](#).  
*end\_translation*: [109](#), [117](#), [207](#), [216](#), [217](#), [220](#).  
*eq\_eq*: [6\\*](#), [51](#), [198](#), [240\\*](#)  
*equiv\_or\_xref*: [11\\*](#), [24](#).  
*err\_print*: [14\\*](#), [57\\*](#), [59\\*](#), [62\\*](#), [63\\*](#), [64\\*](#), [66\\*](#), [74\\*](#), [79\\*](#), [99\\*](#),  
[101\\*](#), [102\\*](#), [103\\*](#), [199\\*](#), [203\\*](#), [232\\*](#), [236\\*](#), [237\\*](#), [240\\*](#), [241\\*](#).  
*error\_message*: [13\\*](#)  
*exit*: [5\\*](#)

- exp*: 105, [106](#), 107, 110\*, 111\*, 118, 121, 124, 125, 128\*, 129, 130, 131, 133, 134, 135, 137, 138\*, 140, 141, 145, 146, 148, 150, 152, 153\*, 158, 159, 163, 164, 165, 166, 167, 168, 171, 172, 173, 174, 175, 176, 177, 178, 180, 196, 199\*, 202, 237\*.
- Extra } in comment: 101\*.
- fallthrough*: 111\*.
- false*: [5](#)\*, 32, 41, 42, 44, 46, 48, 50, 57\*, 60, 62\*, 68, 86, 88, 93, 99\*, 100, 101\*, 217, 219, 220, 227\*, 229, 233, 236\*, 237\*, 246, 247\*, 262, 273\*.
- false\_alarm*: [64](#)\*.
- fatal*: 13\*, [14](#)\*, 247\*, 273\*.
- fatal\_message*: [13](#)\*.
- fclose*: 247\*, 273\*.
- feof*: 274\*.
- fflush*: 16\*, 86.
- file*: [8](#)\*.
- file\_flag*: [24](#), 28, 81, 82\*, 222, 240\*, 242.
- file\_name*: [8](#)\*.
- find\_first\_ident*: [122](#), [123](#), 124, 125.
- finish\_C*: 200, 233, [234](#), [235](#), 239.
- finish\_line*: [86](#), [88](#), 89\*, 99\*, 100, 220, 227\*, 234, 243, 246, 247\*, 263, 266.
- first*: [32](#).
- flag*: [243](#), 245.
- flags*: [15](#)\*, 155, 163, 204, 271\*, 272\*.
- flush\_buffer*: [86](#), [87](#), 88, 93, 94\*, 227\*, 246, 247\*.
- fn\_decl*: [106](#), 107, 111\*, 121, 128\*, 138\*, 143\*, 153\*.
- footnote*: 242, [243](#), [244](#), 266.
- fopen*: 247\*, 273\*.
- for\_like*: [20](#), 34, 107, 110\*, 111\*, 121.
- force*: [109](#), 110\*, 111\*, 115, 117, 139\*, 142, 143\*, 145, 147, 148, 149, 150, 151, 154, 156\*, 159, 196, 205, 206, 217, 220, 234, 240\*.
- force\_first*: 145, [155](#).
- force\_lines*: 151, [155](#), 156\*, 219.
- format\_code*: [36](#), 38, 41, 71, 72, 73, 74\*, 77, 99\*, 193, 204, 205, 232\*, 233.
- format\_visible*: 227\*, [229](#), 233, 237\*.
- found*: 125.
- found\_filename*: [8](#)\*.
- fprintf*: 86.
- fputc*: 86.
- fputs*: 86, 108.
- fread*: 274\*.
- freeze\_text*: [181](#), 182, 190\*, 195, 205, 217.
- ftemplate*: [106](#), 107, 110\*, 111\*, 121, 202.
- fully*: 2\*, 39, [184](#), 185, 192\*.
- func\_template*: [20](#), 34, 202, 262.
- function*: [106](#), 107, 111\*, 121, 139\*, 142, 143\*, 144, 145, 154, 156\*, 158, 160, 179.
- fwrite*: 16\*, 86.
- gather\_digits\_while*: [53](#), 54, 55, 56.
- get\_exponent*: [53](#), 54.
- get\_line*: [9](#)\*, 41, 42, 44, 50, 57\*, 62\*, 88, 99\*, 100, 101\*.
- get\_next*: 43, [44](#), [45](#), 46, 67, 72, 74\*, 77, 78, 79\*, 80, 99\*, 193, 232\*, 236\*, 237\*, 239, 240\*, 241\*.
- get\_output*: 213, [214](#), [215](#), 216, 217, 219, 220.
- getenv*: [5](#)\*.
- gettext*: [5](#)\*.
- group\_found*: [229](#), 231, 247\*.
- gt\_eq*: [6](#)\*, 51, 198.
- gt\_gt*: [6](#)\*, 51, 198.
- harmless\_message*: [13](#)\*.
- hash*: [11](#)\*, 251.
- hash\_end*: [11](#)\*, 251.
- hash\_pointer**: [11](#)\*.
- hash\_ptr*: [11](#)\*, 251.
- HAVE\_GETTEXT: [5](#)\*.
- head*: 252, [253](#), 257\*, 259, 260, 261.
- Head*: [252](#), 253.
- hi\_ptr*: 112, [113](#), 124, 185, 187, 188.
- high-bit character handling: 7\*, 109, 199\*, 200, 255, 256, 257\*.
- history*: [13](#)\*, 14\*.
- i*: [182](#).
- id\_first*: [6](#)\*, 43, 52, 53, 57\*, 64\*, 66\*, 72, 74\*, 75, 78, 79\*, 199\*, 200, 202, 237\*.
- id\_flag*: [115](#), 116, 123, 124, 125, 202, 215, 237\*.
- id\_loc*: [6](#)\*, 43, 52, 53, 54, 55, 56, 57\*, 58, 64\*, 66\*, 72, 74\*, 75, 78, 79\*, 199\*, 200, 202, 237\*.
- id\_lookup*: [12](#)\*, 32, 34, 43, 72, 74\*, 78, 79\*, 202, 237\*.
- identifier*: 43, 52, 71, 72, 74\*, 78, 79\*, 99\*, 196, 213, 215, 217, 218, 236\*, 237\*.
- idx\_file*: 15\*, [16](#)\* 247\*.
- idx\_file\_name*: [15](#)\*, 247\*.
- if\_clause*: 105, [106](#), 107, 111\*, 121, 146.
- if\_head*: [106](#), 107, 111\*, 121, 149.
- if\_like*: [20](#), 34, 105, 107, 110\*, 111\*, 121, 149, 150, 158.
- ignore*: [36](#), 37, 71, 73, 196, 205, 216.
- Ilk*: [11](#)\*.
- ilk*: [11](#)\*, 20, 25\*, 32, 78, 79\*, 122, 123, 124, 202, 218, 262.
- Illegal control code...: 224\*.
- Illegal use of @...: 103\*.
- Improper format definition: 237\*.
- Improper macro definition: 236\*.
- include\_depth*: [8](#)\*.
- indent*: [109](#), 111\*, 117, 142, 145, 147, 149, 217, 220.
- indent\_param\_decl*: 128\*, 138\*, 143\*, 153\*, [271](#)\*.
- infinity*: [257](#)\* 259.
- init\_mathness*: [119](#), 120, 161, 162, 182, 186\*.
- init\_node*: [12](#)\*, [24](#), [32](#).

- init\_stack*: [208](#), [232\\*](#), [233](#), [239](#), [266](#).  
*inner*: [110\\*](#), [206](#), [207](#), [215](#), [220](#), [222](#).  
*inner\_tok\_flag*: [115](#), [116](#), [123](#), [205](#), [215](#), [216](#).  
Input ended in mid-comment: [101\\*](#)  
Input ended in middle of string: [57\\*](#)  
Input ended in section name: [62\\*](#)  
*input\_has\_ended*: [8\\*](#), [40](#), [68](#), [227\\*](#)  
*insert*: [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [158](#), [196](#), [200](#),  
[203\\*](#), [205](#), [234](#).  
*inserted*: [109](#), [117](#), [123](#), [158](#), [196](#), [205](#), [217](#), [220](#).  
*int\_like*: [20](#), [34](#), [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [128\\*](#), [129](#),  
[130](#), [131](#), [135](#), [136](#), [137](#), [138\\*](#), [140](#), [141](#), [142](#),  
[163](#), [166](#), [170](#), [171](#), [173](#).  
INT\_MAX: [19](#), [231](#).  
Irreducible scrap sequence...: [191\\*](#)  
*is\_long\_comment*: [73](#), [101\\*](#), [205](#).  
*is\_tiny*: [25\\*](#), [26](#), [218](#), [262](#).  
*isalpha*: [5\\*](#), [7\\*](#), [44](#), [52](#).  
*isdigit*: [5\\*](#), [7\\*](#), [52](#).  
*ishigh*: [7\\*](#), [44](#), [52](#), [101\\*](#)  
*islower*: [7\\*](#)  
*isspace*: [7\\*](#)  
*isupper*: [7\\*](#)  
*isxalpha*: [7\\*](#), [44](#), [52](#), [97](#), [218](#).  
*isxdigit*: [7\\*](#)  
*j*: [87](#), [116](#), [123](#), [182](#), [183](#), [188](#), [217](#).  
*join*: [36](#), [38](#), [196](#), [232\\*](#)  
*k*: [60](#), [88](#), [93](#), [97](#), [182](#), [183](#), [217](#).  
*k\_limit*: [217](#), [223](#), [225\\*](#)  
*k\_section*: [249](#).  
*kpse\_find\_file*: [8\\*](#)  
*l*: [32](#).  
*langle*: [106](#), [107](#), [111\\*](#), [121](#), [163](#), [164](#), [167](#), [171](#).  
*lbrace*: [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [128\\*](#), [138\\*](#), [140](#),  
[141](#), [147](#), [149](#), [179](#), [196](#).  
*lbrack*: [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [138\\*](#), [171](#), [173](#),  
[174](#), [177](#), [196](#).  
*left\_preproc*: [46](#), [47](#), [196](#).  
*length*: [11\\*](#), [25\\*](#), [32](#).  
*lhs*: [76](#), [78](#), [79\\*](#)  
*lhs\_not\_simple*: [121](#).  
*likely*: [111\\*](#)  
*limit*: [6\\*](#), [7\\*](#), [35](#), [41](#), [42](#), [44](#), [50](#), [57\\*](#), [62\\*](#), [64\\*](#), [66\\*](#), [88](#),  
[99\\*](#), [100](#), [101\\*](#), [217](#), [223](#), [225\\*](#)  
*line*: [8\\*](#)  
Line had to be broken: [94\\*](#)  
*line\_break*: [36](#), [38](#), [196](#), [232\\*](#)  
*line\_length*: [85](#).  
*link*: [11\\*](#), [251](#).  
*llink*: [11\\*](#), [82\\*](#), [266](#).  
*lo\_ptr*: [112](#), [113](#), [124](#), [182](#), [185](#), [186\\*](#), [187](#), [188](#),  
[190\\*](#), [191\\*](#)  
*loc*: [6\\*](#), [7\\*](#), [35](#), [41](#), [42](#), [44](#), [49](#), [50](#), [51](#), [52](#), [53](#), [54](#), [55](#),  
[56](#), [57\\*](#), [58](#), [59\\*](#), [60](#), [62\\*](#), [63\\*](#), [64\\*](#), [66\\*](#), [70\\*](#), [74\\*](#), [99\\*](#), [100](#),  
[101\\*](#), [102\\*](#), [103\\*](#), [192\\*](#), [217](#), [223](#), [231](#), [232\\*](#), [236\\*](#), [237\\*](#)  
*long\_buf\_size*: [17\\*](#), [225\\*](#), [226\\*](#)  
*longest\_name*: [17\\*](#), [57\\*](#), [217](#).  
*lpar*: [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [128\\*](#), [129](#), [133](#), [138\\*](#),  
[165](#), [166](#), [171](#), [173](#), [177](#), [196](#).  
*lproc*: [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [158](#), [196](#).  
*lt\_eq*: [6\\*](#), [51](#), [198](#).  
*lt\_lt*: [6\\*](#), [51](#), [198](#).  
*m*: [26](#), [126](#).  
*macro\_arg\_close*: [36](#), [38](#), [196](#), [232\\*](#)  
*macro\_arg\_open*: [36](#), [38](#), [196](#), [232\\*](#)  
*main*: [2\\*](#), [15\\*](#), [116](#).  
*make\_output*: [214](#), [216](#), [217](#), [222](#), [234](#), [266](#).  
*make\_pair*: [111\\*](#)  
*make\_pb*: [204](#), [205](#), [216](#).  
*make\_reserved*: [111\\*](#), [122](#), [124](#), [125](#), [141](#), [163](#), [173](#).  
*make\_underlined*: [111\\*](#), [122](#), [125](#), [128\\*](#), [138\\*](#), [141](#),  
[158](#), [163](#), [173](#).  
*make\_xrefs*: [15\\*](#), [25\\*](#)  
*mark\_error*: [13\\*](#), [57\\*](#), [224\\*](#), [225\\*](#)  
*mark\_harmless*: [13\\*](#), [62\\*](#), [82\\*](#), [94\\*](#), [191\\*](#), [192\\*](#)  
*math\_break*: [36](#), [38](#), [196](#), [232\\*](#)  
*math\_rel*: [109](#), [111\\*](#), [115](#), [117](#), [131](#), [132](#), [217](#).  
*mathness*: [110\\*](#), [111\\*](#), [112](#), [119](#), [120](#), [175](#), [182](#),  
[185](#), [190\\*](#), [195](#).  
*max\_banner*: [276\\*](#), [277\\*](#)  
*max\_bytes*: [17\\*](#), [269\\*](#)  
*max\_file\_name\_length*: [8\\*](#)  
*max\_include\_depth*: [8\\*](#)  
*max\_names*: [17\\*](#), [250](#), [269\\*](#)  
*max\_refs*: [23\\*](#), [269\\*](#)  
*max\_scr\_ptr*: [113](#), [114](#), [197\\*](#), [203\\*](#), [234](#), [269\\*](#)  
*max\_scrap*: [113](#), [188](#), [269\\*](#)  
*max\_sections*: [17\\*](#), [24](#), [70\\*](#)  
*max\_sort\_ptr*: [253](#), [254](#), [257\\*](#), [269\\*](#)  
*max\_stack\_ptr*: [208](#), [209](#), [211\\*](#), [269\\*](#)  
*max\_text\_ptr*: [30\\*](#), [31](#), [186\\*](#), [197\\*](#), [216](#), [234](#), [269\\*](#)  
*max\_texts*: [30\\*](#), [188](#), [269\\*](#)  
*max\_tok\_ptr*: [30\\*](#), [31](#), [186\\*](#), [197\\*](#), [216](#), [234](#), [269\\*](#)  
*max\_toks*: [30\\*](#), [188](#), [199\\*](#), [205](#), [269\\*](#)  
*maybe\_math*: [119](#), [120](#), [186\\*](#), [196](#), [198](#), [199\\*](#), [202](#),  
[203\\*](#), [237\\*](#), [241\\*](#)  
*memcmp*: [274\\*](#)  
*memcpy*: [87](#), [256](#).  
Memory usage statistics:: [269\\*](#)  
*minus\_gt*: [6\\*](#), [51](#), [198](#).  
*minus\_gt\_ast*: [6\\*](#), [51](#), [198](#).  
*minus\_minus*: [6\\*](#), [51](#), [198](#).  
Missing ' | '...: [203\\*](#)  
Missing } in comment: [101\\*](#), [102\\*](#)

- Missing left identifier...: [79\\*](#)  
Missing right identifier...: [79\\*](#)  
*mistake*: [44](#), [53](#).  
**mode**: [207](#).  
*mode\_field*: [207](#), [208](#).  
*n*: [26](#), [96](#), [126](#), [182](#), [183](#).  
*name\_dir*: [11\\*](#) [24](#), [80](#), [116](#), [123](#), [124](#), [125](#), [196](#),  
[202](#), [215](#), [237\\*](#) [239](#), [240\\*](#) [241\\*](#) [242](#), [251](#), [259](#),  
[260](#), [261](#), [266](#), [269\\*](#).  
*name\_dir\_end*: [11\\*](#)  
*name\_done*: [262](#).  
**name\_info**: [11\\*](#) [20](#).  
**name\_pointer**: [11\\*](#) [12\\*](#) [25\\*](#) [26](#), [27](#), [28](#), [32](#), [43](#),  
[76](#), [82\\*](#) [83](#), [95](#), [97](#), [122](#), [126](#), [202](#), [213](#), [217](#),  
[238](#), [250](#), [252](#), [266](#), [267](#).  
*name\_ptr*: [11\\*](#) [34](#), [269\\*](#)  
*names\_match*: [12\\*](#) [32](#).  
Never defined: <section name>: [82\\*](#)  
Never used: <section name>: [82\\*](#)  
*new\_exp*: [106](#), [107](#), [111\\*](#) [121](#), [165](#), [166](#), [172](#).  
*new\_like*: [20](#), [34](#), [107](#), [110\\*](#) [111\\*](#) [121](#), [165](#), [172](#).  
*new\_line*: [2\\*](#) [16\\*](#) [94\\*](#) [247\\*](#)  
*new\_section*: [36](#), [38](#), [41](#), [42](#), [44](#), [50](#), [63\\*](#) [99\\*](#) [100](#).  
*new\_section\_xref*: [25\\*](#) [27](#), [72](#), [80](#).  
*new\_xref*: [25\\*](#) [26](#), [72](#), [74\\*](#) [78](#), [126](#).  
*next\_control*: [67](#), [71](#), [72](#), [73](#), [74\\*](#) [77](#), [78](#), [80](#), [193](#),  
[196](#), [199\\*](#) [203\\*](#) [204](#), [205](#), [216](#), [232\\*](#) [233](#), [236\\*](#),  
[237\\*](#) [238](#), [239](#), [240\\*](#) [241\\*](#)  
*next\_name*: [250](#), [251](#), [260](#).  
*next\_xref*: [264](#), [265](#).  
*no\_ident\_found*: [122](#), [123](#).  
*no\_line\_break*: [36](#), [38](#), [196](#), [232\\*](#)  
*no\_math*: [119](#), [120](#), [185](#), [196](#), [205](#), [234](#), [236\\*](#) [240\\*](#)  
*no\_xref*: [25\\*](#) [26](#), [126](#), [247\\*](#)  
*non\_eq*: [6\\*](#) [51](#), [198](#).  
*noop*: [36](#), [38](#), [41](#), [59\\*](#) [74\\*](#) [99\\*](#) [111\\*](#) [148](#), [150](#), [151](#),  
[196](#), [217](#), [232\\*](#).  
*normal*: [20](#), [32](#), [34](#), [71](#), [78](#), [79\\*](#) [110\\*](#) [202](#), [237\\*](#) [262](#).  
*not\_an\_identifier*: [262](#).  
*num*: [22](#), [24](#), [25\\*](#) [26](#), [27](#), [28](#), [78](#), [82\\*](#) [126](#), [127](#),  
[222](#), [240\\*](#) [242](#), [243](#), [245](#), [263](#).  
*off*: [39](#), [184](#).  
*operator\_found*: [122](#), [123](#), [124](#), [125](#).  
*operator\_like*: [20](#), [34](#), [107](#), [110\\*](#) [111\\*](#) [121](#), [123](#).  
*opt*: [105](#), [109](#), [110\\*](#) [111\\*](#) [117](#), [128\\*](#) [129](#), [138\\*](#) [140](#),  
[163](#), [196](#), [217](#), [219](#), [220](#).  
*or\_or*: [6\\*](#) [51](#), [198](#).  
*ord*: [36](#), [38](#), [46](#), [59\\*](#) [232\\*](#)  
*order\_decl\_stmt*: [139\\*](#) [156\\*](#) [272\\*](#)  
*out*: [90](#), [91](#), [97](#), [99\\*](#) [100](#), [111\\*](#) [216](#), [217](#), [218](#), [219](#),  
[220](#), [222](#), [223](#), [231](#), [232\\*](#) [243](#), [245](#), [249](#), [262](#), [263](#).  
*out\_buf*: [85](#), [86](#), [87](#), [88](#), [89\\*](#) [92](#), [93](#), [94\\*](#) [100](#), [220](#),  
[227\\*](#) [234](#), [240\\*](#) [246](#), [247\\*](#)  
*out\_buf\_end*: [85](#), [86](#), [90](#).  
*out\_line*: [85](#), [87](#), [89\\*](#) [94\\*](#) [229](#), [236\\*](#)  
*out\_name*: [95](#), [97](#), [218](#), [262](#).  
*out\_ptr*: [85](#), [87](#), [88](#), [89\\*](#) [90](#), [93](#), [94\\*](#) [100](#), [220](#),  
[229](#), [234](#), [236\\*](#) [240\\*](#)  
*out\_section*: [95](#), [96](#), [222](#), [231](#), [245](#), [249](#), [263](#).  
*out\_str*: [90](#), [91](#), [96](#), [99\\*](#) [216](#), [217](#), [219](#), [221](#), [222](#), [229](#),  
[231](#), [234](#), [245](#), [246](#), [247\\*](#) [249](#), [261](#), [262](#), [263](#), [266](#).  
*outdent*: [109](#), [111\\*](#) [117](#), [142](#), [143\\*](#) [145](#), [147](#),  
[149](#), [217](#), [220](#).  
*outer*: [206](#), [207](#), [208](#), [219](#), [220](#).  
*outer\_parse*: [201](#), [204](#), [205](#), [233](#), [239](#).  
*outer\_xref*: [71](#), [73](#), [77](#), [80](#), [204](#).  
*output\_C*: [214](#), [216](#), [223](#), [232\\*](#)  
*output\_defs\_code*: [36](#), [38](#), [196](#), [232\\*](#)  
**output\_state**: [207](#), [208](#).  
*overflow*: [14\\*](#) [25\\*](#) [70\\*](#) [101\\*](#) [186\\*](#) [190\\*](#) [197\\*](#) [211\\*](#),  
[225\\*](#) [226\\*](#) [257\\*](#)  
*p*: [26](#), [27](#), [28](#), [32](#), [82\\*](#) [97](#), [115](#), [116](#), [123](#), [124](#), [125](#),  
[126](#), [202](#), [203\\*](#) [205](#), [211\\*](#) [216](#), [217](#), [234](#), [262](#), [266](#).  
*partly*: [39](#), [184](#), [191\\*](#)  
*per\_cent*: [86](#), [87](#).  
*period\_ast*: [6\\*](#) [51](#), [198](#).  
*phase*: [3\\*](#) [68](#), [101\\*](#) [103\\*](#) [104](#), [222](#), [227\\*](#) [247\\*](#)  
*phase\_one*: [2\\*](#) [68](#), [69](#).  
*phase\_three*: [2\\*](#) [247\\*](#) [248](#).  
*phase\_two*: [2\\*](#) [227\\*](#) [228](#).  
*plus\_plus*: [6\\*](#) [51](#), [198](#).  
*pop\_level*: [212](#), [215](#).  
*pp*: [112](#), [113](#), [118](#), [121](#), [128\\*](#) [129](#), [130](#), [131](#), [132](#),  
[133](#), [134](#), [135](#), [136](#), [137](#), [138\\*](#) [139\\*](#) [140](#), [141](#),  
[142](#), [143\\*](#) [144](#), [145](#), [146](#), [147](#), [148](#), [149](#), [150](#),  
[151](#), [152](#), [153\\*](#) [154](#), [156\\*](#) [157](#), [158](#), [159](#), [160](#),  
[161](#), [162](#), [163](#), [164](#), [165](#), [166](#), [167](#), [168](#), [169](#),  
[170](#), [171](#), [172](#), [173](#), [174](#), [175](#), [176](#), [177](#), [178](#),  
[179](#), [180](#), [182](#), [185](#), [186\\*](#) [187](#), [188](#).  
*prelangle*: [106](#), [107](#), [110\\*](#) [111\\*](#) [121](#), [164](#), [167](#),  
[171](#), [196](#), [200](#).  
*preproc\_line*: [109](#), [110\\*](#) [117](#), [196](#), [217](#), [219](#).  
*preprocessing*: [46](#), [47](#), [50](#).  
*prerangle*: [106](#), [107](#), [110\\*](#) [111\\*](#) [121](#), [163](#), [196](#), [200](#).  
*print\_cat*: [108](#), [185](#), [191\\*](#)  
*print\_id*: [11\\*](#) [116](#).  
*print\_prefix\_name*: [12\\*](#)  
*print\_section\_name*: [12\\*](#) [82\\*](#) [116](#), [224\\*](#) [225\\*](#)  
*print\_stats*: [14\\*](#) [269\\*](#)  
*print\_text*: [115](#), [116](#).  
*print\_where*: [10\\*](#)  
*printf*: [5\\*](#) [57\\*](#) [62\\*](#) [70\\*](#) [82\\*](#) [94\\*](#) [116](#), [117](#), [185](#), [191\\*](#),  
[192\\*](#) [224\\*](#) [225\\*](#) [227\\*](#) [231](#), [247\\*](#) [269\\*](#)



- program*: [2\\*](#) [3\\*](#)  
*pseudo\_semi*: [36](#), [38](#), [196](#), [232\\*](#)  
**ptrdiff\_t**: [5\\*](#)  
*public\_like*: [20](#), [34](#), [107](#), [110\\*](#) [111\\*](#) [121](#).  
*push\_level*: [210](#), [211\\*](#) [215](#), [217](#).  
*putchar*: [16\\*](#) [82\\*](#) [116](#), [117](#), [185](#), [191\\*](#)  
*puts*: [269\\*](#)  
*q*: [26](#), [27](#), [28](#), [78](#), [123](#), [126](#), [205](#), [243](#).  
*qualifier*: [109](#), [111\\*](#) [123](#), [137](#), [217](#).  
*question*: [106](#), [107](#), [110\\*](#) [111\\*](#) [121](#), [196](#).  
*quote\_alpha*: [97](#).  
*quoted\_char*: [101\\*](#) [109](#), [117](#), [199\\*](#) [200](#), [217](#).  
*r*: [27](#), [78](#), [116](#), [123](#), [126](#).  
*raw\_int*: [20](#), [34](#), [107](#), [110\\*](#) [111\\*](#) [121](#), [123](#), [124](#), [135](#),  
[164](#), [166](#), [171](#), [198](#), [236\\*](#)  
*raw\_ubin*: [20](#), [107](#), [110\\*](#) [111\\*](#) [121](#), [166](#), [169](#),  
[172](#), [196](#).  
*rbrace*: [106](#), [107](#), [111\\*](#) [128\\*](#) [142](#), [145](#), [154](#), [196](#).  
*rbrack*: [106](#), [107](#), [110\\*](#) [111\\*](#) [121](#), [174](#), [177](#), [178](#), [196](#).  
recursion: [82\\*](#) [216](#), [266](#).  
*reduce*: [118](#), [121](#), [128\\*](#) [129](#), [131](#), [132](#), [133](#), [134](#),  
[135](#), [136](#), [138\\*](#) [139\\*](#) [140](#), [141](#), [142](#), [143\\*](#) [144](#),  
[145](#), [146](#), [147](#), [148](#), [149](#), [150](#), [151](#), [152](#), [153\\*](#),  
[154](#), [156\\*](#) [158](#), [159](#), [161](#), [162](#), [163](#), [164](#), [165](#),  
[166](#), [167](#), [168](#), [169](#), [170](#), [171](#), [172](#), [173](#), [174](#),  
[177](#), [178](#), [179](#), [180](#), [181](#), [182](#), [183](#).  
*remove*: [275\\*](#)  
*rename*: [273\\*](#) [275\\*](#)  
*res\_flag*: [115](#), [116](#), [123](#), [124](#), [202](#), [215](#).  
*res\_wd\_end*: [25\\*](#) [34](#), [76](#).  
*res\_word*: [213](#), [214](#), [215](#), [217](#), [218](#).  
*reserve\_typenames*: [163](#).  
reserved words: [34](#).  
*reset\_input*: [9\\*](#) [68](#), [227\\*](#)  
*restart*: [215](#).  
*reswitch*: [217](#), [220](#), [236\\*](#)  
*rhs*: [76](#), [78](#), [79\\*](#)  
*right\_preproc*: [46](#), [50](#), [196](#).  
*Rlink*: [11\\*](#)  
*rlink*: [11\\*](#) [20](#), [82\\*](#) [266](#).  
*roman*: [20](#), [71](#), [262](#).  
*root*: [11\\*](#) [84](#), [268](#).  
*rpar*: [106](#), [107](#), [110\\*](#) [111\\*](#) [121](#), [128\\*](#) [129](#), [131](#),  
[138\\*](#) [165](#), [196](#).  
*rproc*: [106](#), [107](#), [110\\*](#) [111\\*](#) [158](#), [196](#).  
*s*: [91](#), [96](#), [120](#), [231](#).  
*safe\_scrap\_incr*: [186\\*](#) [197\\*](#)  
*safe\_text\_incr*: [186\\*](#) [197\\*](#)  
*safe\_tok\_incr*: [186\\*](#) [197\\*](#)  
*save\_base*: [203\\*](#)  
*save\_limit*: [217](#), [223](#).  
*save\_line*: [229](#), [236\\*](#)  
*save\_loc*: [217](#), [223](#).  
*save\_mode*: [217](#), [220](#).  
*save\_next\_control*: [216](#).  
*save\_place*: [229](#), [236\\*](#)  
*save\_position*: [229](#), [230](#), [236\\*](#) [237\\*](#)  
*save\_text\_ptr*: [216](#).  
*save\_tok\_ptr*: [216](#).  
*scn\_file*: [15\\*](#) [16\\*](#) [247\\*](#)  
*scn\_file\_name*: [15\\*](#) [247\\*](#)  
**scrap**: [112](#), [113](#).  
*scrap\_base*: [112](#), [113](#), [114](#), [182](#), [185](#), [188](#), [190\\*](#),  
[191\\*](#) [203\\*](#)  
*scrap\_info*: [112](#), [113](#), [114](#), [203\\*](#) [234](#), [237\\*](#) [254](#),  
[259](#), [266](#), [269\\*](#)  
*scrap\_info\_end*: [113](#), [197\\*](#) [257\\*](#)  
**scrap\_pointer**: [112](#), [113](#), [118](#), [120](#), [122](#), [124](#), [125](#),  
[181](#), [182](#), [183](#), [188](#), [203\\*](#) [253](#).  
*scrap\_ptr*: [112](#), [113](#), [114](#), [124](#), [185](#), [187](#), [188](#), [193](#),  
[195](#), [197\\*](#) [203\\*](#) [234](#), [237\\*](#) [253](#), [266](#).  
*scrapping*: [201](#), [202](#).  
*scratch*: [217](#), [223](#).  
*sec\_depth*: [229](#), [231](#).  
Section name didn't end: [63\\*](#)  
Section name too long: [62\\*](#)  
*section\_check*: [82\\*](#) [83](#), [84](#).  
*section\_code*: [213](#), [214](#), [215](#), [217](#).  
*section\_count*: [10\\*](#) [21](#), [26](#), [27](#), [68](#), [70\\*](#) [126](#), [191\\*](#),  
[227\\*](#) [230](#), [231](#), [240\\*](#) [249](#).  
*section\_flag*: [115](#), [116](#), [123](#), [196](#), [215](#), [240\\*](#) [241\\*](#) [266](#).  
*section\_lookup*: [12\\*](#) [60](#), [61](#).  
*section\_name*: [36](#), [38](#), [43](#), [59\\*](#) [60](#), [71](#), [72](#), [73](#), [74\\*](#),  
[80](#), [196](#), [203\\*](#) [232\\*](#) [239](#), [241\\*](#)  
*section\_print*: [266](#), [267](#), [268](#).  
*section\_scrap*: [106](#), [107](#), [110\\*](#) [111\\*](#) [121](#), [196](#), [241\\*](#)  
*section\_text*: [6\\*](#) [43](#), [53](#), [57\\*](#) [60](#), [61](#), [62\\*](#)  
*section\_text\_end*: [6\\*](#) [57\\*](#) [62\\*](#)  
*section\_xref\_switch*: [22](#), [23\\*](#) [24](#), [27](#), [72](#), [80](#).  
*semi*: [106](#), [107](#), [110\\*](#) [111\\*](#) [121](#), [128\\*](#) [133](#), [135](#), [138\\*](#),  
[141](#), [151](#), [152](#), [159](#), [173](#), [179](#), [196](#), [237\\*](#)  
*set\_file\_flag*: [25\\*](#) [28](#), [80](#).  
*sharp\_include\_line*: [44](#), [48](#), [49](#), [50](#).  
*show\_banner*: [2\\*](#) [15\\*](#)  
*show\_happiness*: [15\\*](#) [247\\*](#)  
*show\_progress*: [2\\*](#) [15\\*](#) [70\\*](#) [227\\*](#) [231](#), [247\\*](#)  
*show\_stats*: [15\\*](#)  
**sixteen\_bits**: [3\\*](#) [10\\*](#) [22](#), [23\\*](#) [26](#), [29](#), [95](#), [96](#), [116](#),  
[123](#), [124](#), [126](#), [215](#), [216](#), [243](#), [244](#), [249](#), [253](#).  
*sizeof\_like*: [20](#), [34](#), [107](#), [110\\*](#) [111\\*](#) [121](#).  
*skip\_limbo*: [40](#), [41](#), [68](#), [98](#).  
*skip\_restricted*: [41](#), [59\\*](#) [64\\*](#) [65](#), [99\\*](#)  
*skip\_T<sub>E</sub>X*: [40](#), [42](#), [74\\*](#) [98](#).  
*snprintf*: [96](#), [231](#).

- sort\_pointer:** [253](#).
- sort\_ptr:* [252](#), [253](#), [257\\*](#), [259](#), [260](#), [261](#).
- space\_checked:* [229](#), [233](#), [236\\*](#), [237\\*](#)
- spec\_ctrl:* [71](#), [72](#), [193](#).
- special string characters: [199\\*](#)
- spotless:* [13\\*](#)
- sprint\_section\_name:* [12\\*](#), [223](#).
- squash:* [118](#), [121](#), [128\\*](#), [129](#), [130](#), [133](#), [134](#), [135](#),  
[136](#), [137](#), [138\\*](#), [145](#), [152](#), [157](#), [158](#), [160](#), [163](#), [165](#),  
[171](#), [172](#), [173](#), [175](#), [176](#), [177](#), [178](#), [179](#), [181](#), [183](#).
- src:* [75](#).
- stack:* [207](#), [208](#), [209](#), [211\\*](#), [269\\*](#)
- stack\_end:* [208](#), [211\\*](#)
- stack\_pointer:** [207](#), [208](#).
- stack\_ptr:* [207](#), [208](#), [211\\*](#), [212](#).
- stack\_size:* [208](#), [269\\*](#)
- stdout:* [16\\*](#), [108](#).
- stmt:* [105](#), [106](#), [107](#), [111\\*](#), [121](#), [128\\*](#), [129](#), [139\\*](#), [142](#),  
[143\\*](#), [144](#), [145](#), [147](#), [148](#), [149](#), [150](#), [151](#), [152](#),  
[154](#), [156\\*](#), [157](#), [159](#), [179](#).
- strcmp:* [5\\*](#)
- strcpy:* [107](#), [273\\*](#)
- string:* [43](#), [57\\*](#), [196](#), [199\\*](#)
- String didn't end: [57\\*](#)
- String too long: [57\\*](#)
- strlen:* [5\\*](#), [106](#), [223](#).
- strncmp:* [32](#), [49](#), [60](#), [220](#).
- strncpy:* [277\\*](#)
- struct\_head:* [106](#), [107](#), [111\\*](#), [121](#), [141](#).
- struct\_like:* [20](#), [34](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [135](#), [141](#),  
[163](#), [164](#), [166](#).
- system dependencies: [3\\*](#), [5\\*](#), [182](#), [187](#), [211\\*](#), [212](#),  
[231](#), [256](#), [269\\*](#), [275\\*](#)
- t:* [32](#).
- tag:* [106](#), [107](#), [111\\*](#), [121](#), [128\\*](#), [136](#), [152](#), [154](#), [179](#).
- template\_like:* [20](#), [34](#), [107](#), [110\\*](#), [111\\*](#), [121](#).
- term\_write:* [11\\*](#), [16\\*](#), [57\\*](#), [62\\*](#), [94\\*](#), [192\\*](#)
- TeX string should be...: [232\\*](#)
- tex\_file:* [15\\*](#), [16\\*](#), [89\\*](#), [247\\*](#), [273\\*](#), [274\\*](#)
- tex\_file\_name:* [15\\*](#), [273\\*](#), [275\\*](#)
- tex\_printf:* [86](#), [89\\*](#)
- tex\_putc:* [86](#), [87](#).
- tex\_puts:* [86](#), [89\\*](#)
- TEX\_string:* [36](#), [38](#), [43](#), [59\\*](#), [196](#), [232\\*](#)
- text\_pointer:** [29](#), [30\\*](#), [112](#), [115](#), [116](#), [122](#), [123](#),  
[188](#), [189](#), [201](#), [203\\*](#), [205](#), [210](#), [211\\*](#), [216](#), [234](#).
- text\_ptr:* [30\\*](#), [31](#), [116](#), [123](#), [181](#), [182](#), [186\\*](#), [188](#), [190\\*](#),  
[195](#), [197\\*](#), [205](#), [216](#), [217](#), [234](#), [266](#).
- thin\_space:* [36](#), [38](#), [196](#), [232\\*](#)
- This can't happen: [13\\*](#)
- this\_section:* [238](#), [239](#), [240\\*](#), [242](#).
- this\_xref:* [264](#), [265](#).
- tok\_field:* [207](#), [208](#).
- tok\_flag:* [115](#), [116](#), [120](#), [123](#), [190\\*](#), [205](#), [215](#), [234](#).
- tok\_loc:* [124](#), [125](#).
- tok\_mem:* [30\\*](#), [31](#), [115](#), [116](#), [118](#), [207](#), [208](#), [215](#),  
[222](#), [234](#), [266](#), [269\\*](#)
- tok\_mem\_end:* [30\\*](#), [101\\*](#), [186\\*](#), [190\\*](#), [197\\*](#)
- tok\_ptr:* [30\\*](#), [31](#), [101\\*](#), [103\\*](#), [118](#), [181](#), [186\\*](#), [188](#), [190\\*](#),  
[197\\*](#), [199\\*](#), [205](#), [216](#), [234](#), [266](#).
- tok\_start:* [29](#), [30\\*](#), [31](#), [112](#), [120](#), [123](#), [181](#), [190\\*](#), [205](#),  
[215](#), [216](#), [234](#), [266](#), [269\\*](#)
- tok\_start\_end:* [30\\*](#), [186\\*](#), [197\\*](#)
- tok\_value:* [124](#).
- token:** [29](#), [30\\*](#), [118](#), [120](#).
- token\_pointer:** [29](#), [30\\*](#), [116](#), [122](#), [123](#), [124](#),  
[125](#), [207](#), [216](#).
- tolower:* [251](#), [260](#).
- toupper:* [53](#).
- trace:* [36](#), [39](#), [59\\*](#), [74\\*](#)
- tracing:* [2\\*](#), [59\\*](#), [74\\*](#), [184](#), [185](#), [191\\*](#), [192\\*](#)
- Tracing after...: [192\\*](#)
- Trans:* [112](#).
- trans:* [112](#), [118](#), [120](#), [124](#), [125](#), [182](#), [188](#), [190\\*](#),  
[193](#), [195](#), [252](#).
- trans\_plus:* [112](#), [253](#).
- translate:* [188](#), [189](#), [203\\*](#), [234](#).
- translit\_code:* [36](#), [38](#), [59\\*](#), [74\\*](#), [99\\*](#)
- true:* [5\\*](#), [41](#), [42](#), [44](#), [47](#), [49](#), [57\\*](#), [60](#), [62\\*](#), [70\\*](#), [74\\*](#), [82\\*](#),  
[86](#), [93](#), [94\\*](#), [99\\*](#), [100](#), [101\\*](#), [155](#), [186\\*](#), [196](#), [201](#),  
[204](#), [217](#), [218](#), [220](#), [222](#), [225\\*](#), [227\\*](#), [229](#), [231](#), [233](#),  
[234](#), [237\\*](#), [239](#), [242](#), [245](#), [262](#), [271\\*](#), [272\\*](#)
- typedef\_like:* [20](#), [34](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [173](#), [179](#).
- typewriter:* [20](#), [71](#), [262](#).
- ubinop:* [105](#), [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [128\\*](#), [129](#),  
[135](#), [138\\*](#), [169](#), [172](#), [173](#), [196](#), [202](#).
- uint16\_t:** [3\\*](#), [5\\*](#)
- uint8\_t:** [3\\*](#), [5\\*](#)
- unbucket:* [257\\*](#), [258](#), [259](#), [260](#).
- underline:* [36](#), [38](#), [59\\*](#), [74\\*](#)
- underline\_xref:* [122](#), [125](#), [126](#).
- unindexed:* [25\\*](#), [26](#), [78](#).
- UNKNOWN: [107](#).
- unop:* [106](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [128\\*](#), [172](#), [196](#), [198](#).
- update\_node:* [26](#), [27](#), [28](#), [33](#), [127](#).
- update\_terminal:* [16\\*](#), [70\\*](#), [116](#), [231](#).
- Use @l in limbo...: [59\\*](#), [74\\*](#)
- use\_language:* [15\\*](#), [89\\*](#)
- using\_like:* [20](#), [34](#), [107](#), [110\\*](#), [111\\*](#), [121](#), [178](#).
- verbatim:* [36](#), [38](#), [43](#), [59\\*](#), [66\\*](#), [196](#).
- Verbatim string didn't end: [66\\*](#)
- versionstring:* [1\\*](#), [276\\*](#)
- visible:* [234](#).
- web\_file:* [8\\*](#)



*web\_file\_name*: [8](#)\*  
*web\_file\_open*: [8](#)\*  
*wildcard*: [20](#), [71](#), [262](#).  
*wrap-up*: [2](#)\*, [14](#)\*  
 Writing the index...: [247](#)\*  
 Writing the output file...: [227](#)\*  
*x*: [274](#)\*  
*x\_size*: [274](#)\*  
*xisalpha*: [7](#)\*  
*xisdigit*: [7](#)\*, [44](#), [53](#), [56](#), [231](#).  
*xislower*: [7](#)\*, [218](#), [262](#).  
*xisspace*: [7](#)\*, [44](#), [49](#), [62](#)\*, [88](#), [100](#).  
*xisupper*: [7](#)\*, [251](#), [260](#).  
*xisxdigit*: [7](#)\*, [54](#).  
*xlink*: [22](#), [26](#), [27](#), [28](#), [78](#), [82](#)\*, [126](#), [127](#), [222](#), [240](#)\*,  
     [242](#), [245](#), [263](#), [265](#).  
*xmem*: [22](#), [23](#)\*, [24](#), [26](#), [27](#), [32](#), [78](#), [82](#)\*, [126](#), [251](#),  
     [263](#), [265](#), [269](#)\*  
*xmem\_end*: [23](#)\*, [25](#)\*  
*xref*: [22](#), [24](#), [26](#), [27](#), [28](#), [32](#), [33](#), [78](#), [82](#)\*, [126](#), [127](#),  
     [222](#), [240](#)\*, [242](#), [251](#), [265](#).  
**xref\_info**: [22](#), [23](#)\*  
**xref\_pointer**: [22](#), [23](#)\*, [26](#), [27](#), [28](#), [78](#), [81](#), [82](#)\*, [126](#),  
     [127](#), [222](#), [240](#)\*, [242](#), [243](#), [264](#), [265](#).  
*xref\_ptr*: [22](#), [23](#)\*, [24](#), [25](#)\*, [26](#), [27](#), [28](#), [33](#), [127](#), [269](#)\*  
*xref\_roman*: [36](#), [38](#), [43](#), [59](#)\*, [71](#), [74](#)\*, [196](#), [232](#)\*  
*xref\_switch*: [22](#), [23](#)\*, [24](#), [26](#), [43](#), [59](#)\*, [60](#), [74](#)\*, [77](#),  
     [78](#), [125](#), [126](#).  
*xref\_typewriter*: [36](#), [38](#), [43](#), [59](#)\*, [71](#), [72](#), [74](#)\*, [196](#), [232](#)\*  
*xref\_wildcard*: [36](#), [38](#), [43](#), [59](#)\*, [71](#), [74](#)\*, [196](#), [232](#)\*  
*y*: [274](#)\*  
*y\_size*: [274](#)\*  
*yes\_math*: [119](#), [120](#), [161](#), [162](#), [175](#), [185](#), [190](#)\*,  
     [196](#), [198](#), [202](#).  
 You can't do that...: [232](#)\*, [241](#)\*  
 You need an = sign...: [240](#)\*

- ⟨ Append a TeX string, without forming a scrap 200 ⟩ Used in section 196.
- ⟨ Append a string or constant 199\* ⟩ Used in section 196.
- ⟨ Append the scrap appropriate to *next\_control* 196 ⟩ Used in section 193.
- ⟨ Cases for *alignas\_like* 176 ⟩ Used in section 121.
- ⟨ Cases for *attr\_head* 178 ⟩ Used in section 121.
- ⟨ Cases for *attr* 179 ⟩ Used in section 121.
- ⟨ Cases for *base* 140 ⟩ Used in section 121.
- ⟨ Cases for *binop* 132 ⟩ Used in section 121.
- ⟨ Cases for *case\_like* 152 ⟩ Used in section 121.
- ⟨ Cases for *cast* 133 ⟩ Used in section 121.
- ⟨ Cases for *catch\_like* 153\* ⟩ Used in section 121.
- ⟨ Cases for *colcol* 137 ⟩ Used in section 121.
- ⟨ Cases for *const\_like* 170 ⟩ Used in section 121.
- ⟨ Cases for *decl\_head* 138\* ⟩ Used in section 121.
- ⟨ Cases for *decl* 139\* ⟩ Used in section 121.
- ⟨ Cases for *default\_like* 180 ⟩ Used in section 121.
- ⟨ Cases for *delete\_like* 174 ⟩ Used in section 121.
- ⟨ Cases for *do\_like* 151 ⟩ Used in section 121.
- ⟨ Cases for *else\_head* 148 ⟩ Used in section 121.
- ⟨ Cases for *else\_like* 147 ⟩ Used in section 121.
- ⟨ Cases for *exp* 128\* ⟩ Used in section 121.
- ⟨ Cases for *fn\_decl* 143\* ⟩ Used in section 121.
- ⟨ Cases for *for\_like* 168 ⟩ Used in section 121.
- ⟨ Cases for *ftemplate* 167 ⟩ Used in section 121.
- ⟨ Cases for *function* 144 ⟩ Used in section 121.
- ⟨ Cases for *if\_clause* 149 ⟩ Used in section 121.
- ⟨ Cases for *if\_head* 150 ⟩ Used in section 121.
- ⟨ Cases for *if\_like* 146 ⟩ Used in section 121.
- ⟨ Cases for *insert* 160 ⟩ Used in section 121.
- ⟨ Cases for *int\_like* 135 ⟩ Used in section 121.
- ⟨ Cases for *langle* 163 ⟩ Used in section 121.
- ⟨ Cases for *lbrace* 145 ⟩ Used in section 121.
- ⟨ Cases for *lbrack* 177 ⟩ Used in section 121.
- ⟨ Cases for *lpar* 129 ⟩ Used in section 121.
- ⟨ Cases for *lproc* 158 ⟩ Used in section 121.
- ⟨ Cases for *new\_exp* 166 ⟩ Used in section 121.
- ⟨ Cases for *new\_like* 165 ⟩ Used in section 121.
- ⟨ Cases for *operator\_like* 172 ⟩ Used in section 121.
- ⟨ Cases for *prelangle* 161 ⟩ Used in section 121.
- ⟨ Cases for *prerangle* 162 ⟩ Used in section 121.
- ⟨ Cases for *public\_like* 136 ⟩ Used in section 121.
- ⟨ Cases for *question* 175 ⟩ Used in section 121.
- ⟨ Cases for *raw\_int* 171 ⟩ Used in section 121.
- ⟨ Cases for *raw\_ubin* 169 ⟩ Used in section 121.
- ⟨ Cases for *section\_scrap* 159 ⟩ Used in section 121.
- ⟨ Cases for *semi* 157 ⟩ Used in section 121.
- ⟨ Cases for *sizeof\_like* 134 ⟩ Used in section 121.
- ⟨ Cases for *stmt* 156\* ⟩ Used in section 121.
- ⟨ Cases for *struct\_head* 142 ⟩ Used in section 121.
- ⟨ Cases for *struct\_like* 141 ⟩ Used in section 121.
- ⟨ Cases for *tag* 154 ⟩ Used in section 121.
- ⟨ Cases for *template\_like* 164 ⟩ Used in section 121.

- ⟨ Cases for *typedef\_like* 173 ⟩ Used in section 121.
- ⟨ Cases for *ubinop* 131 ⟩ Used in section 121.
- ⟨ Cases for *unop* 130 ⟩ Used in section 121.
- ⟨ Cases involving nonstandard characters 198 ⟩ Used in section 196.
- ⟨ Check for end of comment 102\* ⟩ Used in section 101\*.
- ⟨ Check if next token is **include** 49 ⟩ Used in section 47.
- ⟨ Check if we're at the end of a preprocessor command 50 ⟩ Used in section 44.
- ⟨ Check that '=' or '==' follows this section name, and emit the scraps to start the section definition 240\* ⟩  
Used in section 239.
- ⟨ Clear *bal* and **return** 104 ⟩ Used in section 101\*.
- ⟨ Combine the irreducible scraps that remain 190\* ⟩ Used in section 188.
- ⟨ Common code for CWEAVE and CTANGLE 3\*, 6\*, 7\*, 8\*, 10\*, 11\*, 13\*, 15\*, 16\*, 276\* ⟩ Used in section 1\*.
- ⟨ Compare the temporary output to the previous output 274\* ⟩ Used in section 273\*.
- ⟨ Compress two-symbol operator 51 ⟩ Used in section 44.
- ⟨ Copy a quoted character into the buffer 226\* ⟩ Used in section 225\*.
- ⟨ Copy special things when  $c \equiv '@', '\\'$  103\* ⟩ Used in section 101\*.
- ⟨ Copy the C text into the *buffer* array 225\* ⟩ Used in section 223.
- ⟨ Do the first pass of sorting 251 ⟩ Used in section 247\*.
- ⟨ Emit the scrap for a section name if present 241\* ⟩ Used in section 239.
- ⟨ Get a binary constant 55 ⟩ Used in section 53.
- ⟨ Get a constant 53 ⟩ Used in section 44.
- ⟨ Get a hexadecimal constant 54 ⟩ Used in section 53.
- ⟨ Get a string 57\* ⟩ Used in sections 44 and 59\*.
- ⟨ Get a wide character constant 58 ⟩ Used in section 57\*.
- ⟨ Get an identifier 52 ⟩ Used in section 44.
- ⟨ Get an octal constant 56 ⟩ Used in section 53.
- ⟨ Get control code and possible section name 59\* ⟩ Used in section 44.
- ⟨ If end of name or erroneous control code, **break** 63\* ⟩ Used in section 62\*.
- ⟨ If semi-tracing, show the irreducible scraps 191\* ⟩ Used in section 190\*.
- ⟨ If tracing, print an indication of where we are 192\* ⟩ Used in section 188.
- ⟨ Include files 5\*, 19 ⟩ Used in section 1\*.
- ⟨ Insert new cross-reference at  $q$ , not at beginning of list 127 ⟩ Used in section 126.
- ⟨ Invert the cross-reference list at *cur\_name*, making *cur\_xref* the head 265 ⟩ Used in section 263.
- ⟨ Look ahead for strongest line break, **goto reswitch** 220 ⟩ Used in section 219.
- ⟨ Make sure that there is room for the new scraps, tokens, and texts 197\* ⟩ Used in sections 196 and 205.
- ⟨ Make sure the entries  $pp$  through  $pp + 3$  of *cat* are defined 187 ⟩ Used in section 186\*.
- ⟨ Match a production at  $pp$ , or increase  $pp$  if there is no match 121 ⟩ Cited in section 25\*. Used in section 186\*.
- ⟨ Output a control, look ahead in case of line breaks, possibly **goto reswitch** 219 ⟩ Used in section 217.
- ⟨ Output a section name 222 ⟩ Used in section 217.
- ⟨ Output all the section names 268 ⟩ Used in section 247\*.
- ⟨ Output all the section numbers on the reference list *cur\_xref* 245 ⟩ Used in section 243.
- ⟨ Output an identifier 218 ⟩ Used in section 217.
- ⟨ Output index entries for the list at *sort\_ptr* 261 ⟩ Used in section 259.
- ⟨ Output saved *indent* or *outdent* tokens 221 ⟩ Used in sections 217 and 220.
- ⟨ Output the code for the beginning of a new section 231 ⟩ Cited in section 19. Used in section 230.
- ⟨ Output the code for the end of a section 246 ⟩ Used in section 230.
- ⟨ Output the cross-references at *cur\_name* 263 ⟩ Used in section 261.
- ⟨ Output the name at *cur\_name* 262 ⟩ Used in section 261.
- ⟨ Output the text of the section name 223 ⟩ Used in section 222.
- ⟨ Predeclaration of procedures 4\*, 9\*, 12\*, 14\*, 25\*, 40, 45, 65, 69, 71, 83, 86, 90, 95, 98, 115, 118, 122, 181, 189, 194,  
201, 210, 214, 228, 235, 244, 248, 258, 267 ⟩ Used in section 1\*.
- ⟨ Print a snapshot of the scrap list if debugging 185 ⟩ Used in section 182.

- ⟨ Print error messages about unused or undefined section names 84 ⟩ Used in section 68.
- ⟨ Print token *r* in symbolic form 117 ⟩ Used in section 116.
- ⟨ Print warning message, break the line, **return** 94\* ⟩ Used in section 93.
- ⟨ Private variables 21, 23\*, 30\*, 37, 43, 46, 48, 67, 76, 81, 85, 106, 113, 119, 184, 208, 213, 229, 238, 250, 253, 255, 264 ⟩  
Used in section 1\*.
- ⟨ Process a format definition 78 ⟩ Used in section 77.
- ⟨ Process simple format in limbo 79\* ⟩ Used in section 41.
- ⟨ Put section name into *section\_text* 62\* ⟩ Used in section 60.
- ⟨ Raise preprocessor flag 47 ⟩ Used in section 44.
- ⟨ Reduce the scraps using the productions until no more rules apply 186\* ⟩ Used in section 188.
- ⟨ Replace ‘@@’ by ‘@’ 75 ⟩ Used in sections 72 and 74\*.
- ⟨ Rest of *trans\_plus* union 252 ⟩ Used in section 112.
- ⟨ Scan a verbatim string 66\* ⟩ Used in section 59\*.
- ⟨ Scan the section name and make *cur\_section* point to it 60 ⟩ Used in section 59\*.
- ⟨ Set initial values 24, 31, 38, 61, 92, 107, 114, 155, 204, 209, 254, 256, 271\*, 272\*, 277\* ⟩ Used in section 2\*.
- ⟨ Show cross-references to this section 242 ⟩ Used in section 230.
- ⟨ Skip next character, give error if not ‘@’ 224\* ⟩ Used in section 223.
- ⟨ Sort and output the index 259 ⟩ Used in section 247\*.
- ⟨ Special control codes for debugging 39 ⟩ Used in section 38.
- ⟨ Split the list at *sort\_ptr* into further lists 260 ⟩ Used in section 259.
- ⟨ Start T<sub>E</sub>X output 89\* ⟩ Used in section 2\*.
- ⟨ Start a format definition 237\* ⟩ Used in section 233.
- ⟨ Start a macro definition 236\* ⟩ Used in section 233.
- ⟨ Store all the reserved words 34 ⟩ Used in section 2\*.
- ⟨ Store cross-reference data for the current section 70\* ⟩ Used in section 68.
- ⟨ Store cross-references in the C part of a section 80 ⟩ Used in section 70\*.
- ⟨ Store cross-references in the T<sub>E</sub>X part of a section 74\* ⟩ Used in section 70\*.
- ⟨ Store cross-references in the definition part of a section 77 ⟩ Used in section 70\*.
- ⟨ Take appropriate action depending on the comparison 275\* ⟩ Used in section 273\*.
- ⟨ Tell about changed sections 249 ⟩ Used in section 247\*.
- ⟨ Translate the C part of the current section 239 ⟩ Used in section 230.
- ⟨ Translate the T<sub>E</sub>X part of the current section 232\* ⟩ Used in section 230.
- ⟨ Translate the current section 230 ⟩ Used in section 227\*.
- ⟨ Translate the definition part of the current section 233 ⟩ Used in section 230.
- ⟨ Typedef declarations 22, 29, 112, 207 ⟩ Used in section 1\*.
- ⟨ Update the result when it has changed 273\* ⟩ Used in section 247\*.